PCEP Extensions for Associated Bidirectional SR Paths

draft-ietf-pce-sr-bidir-path-02

```
Cheng Li (chengli13@huawei.com)
Mach(Guoyi) Chen (Mach.chen@huawei.com)
Weiqiang Cheng (chengweiqiang@chinamobile.com)
Rakesh Gandhi (<u>rgandhi@cisco.com</u>) - Presenter
Quan Xiong (xiong.quan@zte.com.cn)
```

Agenda

- Requirements and Scope
- Double-sided Associated Bidirectional with Reverse LSP
- PCEP Object Definitions
- Next Steps

Requirements and Scope

Requirements:

- Packet transport networks deploying bidirectional SR Paths
- Co-routed and non-co-routed forward and reverse SR Paths


Scope:

- Associated bidirectional SR Paths
- PCE-Initiated LSPs
- PCC-Initiated LSPs
- Stateless PCE (e.g. for co-routed path computation requests)


Not in Scope:

Associating a bidirectional SR Path with an RSVP LSP

Double-sided Associated Bidirectional with Reverse LSP



Double-sided Associated Bidirectional with Reverse LSP



PCEP Association Object

- Association Type (TBD1) = Double-sided Bidirectional with Reverse LSP Association Group
- The Association Object Populated using the procedure defined in [draft-ietf-pce-association-bidir]

Error Handling (PCErr Error-Type 26 - Association Error)

PCErr defined in [draft-ietf-pce-association-bidir] are applicable to SR Paths

Specifically –

- 1. Both forward and reverse LSPs MUST belong to the same bidirectional TE tunnel [RFC3209].
 - Error-Value = Bidirectional LSP Association Tunnel mismatch
- LSP (forward or reverse) cannot be part of more than one Bidirectional LSP Association Group.
 - Error-Value = Bidirectional LSP Association Group Mismatch
- 3. If a PCEP speaker receives a different PST value for Bidirectional LSP association group and it does not support.
 - Error-Value = Bidirectional LSP Association Path Setup Type Not Supported

Next Steps

- Welcome your review comments and suggestions
- Add in Queue for WG LC?

Thank you