

# Task 1 :

User permission and system misconfigurations ⚙️ :

```
(kali㉿kali)-[~/Desktop]
$ sudo useradd maddy
[sudo] password for kali:
```

First, we create a user named “**adenggappa**” using the `sudo useradd <username>` command.

```
(kali㉿kali)-[~/Desktop]
$ echo "maddy:12345678" | sudo chpasswd
```

2. We assign the password “**1234**” by using the `echo` command to write it into the password file `chpasswd`, with elevated privileges via `sudo`.

```
(kali㉿kali)-[~/Desktop]
$ ls -l /etc/shadow
-rw-rw-r-- 1 root shadow 1753 Mar 11 22:51 /etc/shadow
```

We examine the permissions of the password file to identify and exploit any misconfigurations.

```
(kali㉿kali) - [~/Desktop]
$ sudo chmod 777 /etc/shadow

(kali㉿kali) - [~/Desktop]
$ ls -l /etc/shadow
-rwxrwxrwx 1 root shadow 1753 Mar 11 22:51 /etc/shadow
```

☰☰☰ We modify the permissions of the shadow file using the `sudo chmod 777` command to grant full access. Then, we verify the updated permissions to confirm the ability to view the file.

```
(kali㉿kali) - [~/Desktop]
$ cat /etc/shadow
root:*:
daemon:*:
bin:*:
sys:*:
sync:*:
games:*:
```

☰☰☰ As observed, we can now view the contents of the `/etc/shadow` file, which contains hashed passwords, even with normal user privileges.

☰☰☰ We have successfully configured `/etc/shadow` to be accessible by normal users.

## Securing permissions 🔒 :

```
(kali㉿kali) - [~/Desktop]
$ sudo chmod 640 /etc/shadow

(kali㉿kali) - [~/Desktop]
$ sudo chown root:shadow /etc/shadow
```

1. We secure the password file by setting its permissions to `640` using the `chmod` command. This ensures that only the root user and members of the shadow group

can access it. The root user's password remains viewable only under superuser privileges.

```
(kali㉿kali) - [~/Desktop]
$ sudo chmod 644 /etc/passwd

(kali㉿kali) - [~/Desktop]
$ sudo chown root:root /etc/passwd
```

☰ We modify the permissions of the `/etc/passwd` file using `sudo chmod 644` and set its ownership to `root:root` with `sudo chown root:root` . This ensures that regular users can read the file but cannot modify it.

☰ Finally we use `sudo visudo` to check permissions.

## Summary of Steps

Step	Create Users	Command	Purpose
Set	Passwords	<code>sudo useradd user1</code>	Add new users
Break	Security	<code>`echo "user1:pass"</code>	<code>sudo chpasswd`</code>
Exploit	Fix	<code>sudo chmod 777 /etc/shadow</code>	Make shadow file world-readable ☰BAD☰
Permissions		<code>su user1 &amp;&amp; cat /etc/shadow</code>	Access passwords as normal user
Secure		<code>sudo chmod 640 /etc/shadow</code>	Secure shadow file
<code>/etc/passwd</code>	Fix	<code>sudo chmod 644 /etc/passwd</code>	Prevent unauthorized edits
<code>sudo</code>	Privileges	<code>sudo visudo</code>	Restrict <code>sudo</code> access