Unsupervised Neural Network for Multi-Genre Music Generation

1. Abstract

This project implements and evaluates four progressive deep learning architectures for unsupervised music generation using the MAESTRO v3.0.0 dataset (1,276 classical piano compositions, 200 hours). We progress from an LSTM Autoencoder (Task 1) through a Variational Autoencoder with KL annealing (Task 2), a Transformer decoder (Task 3), and policy gradient fine-tuning (Task 4). A critical technical finding is that piano-roll representations suffer from extreme class imbalance (97–98% silence), causing standard loss functions (MSE, BCE) to fail. We address this using Focal Loss as recommended by the Supplementary Implementation Guide. Task 3 (Transformer) achieves a validation perplexity of 7.8, representing a 7.95× improvement over a Markov chain baseline yet still exhibits repetitive generation patterns (0.845 repetition ratio). Token-based REMI representations dramatically outperform piano-rolls across all tasks, suggesting that discrete symbolic modeling is superior to continuous pixel-space approximations for structured sequential domains. Task 4 (RLHF) exposes fundamental challenges: without real human feedback, reward modeling provides zero optimization signal. This report emphasizes analytical depth, investigating why models succeed or fail, over score reporting, with detailed examination of architectural trade-offs, representation learning curves, and methodological limitations.

2. Introduction

2.1 Project Motivation

Music is a structured temporal signal containing complex patterns across multiple timescales: - **Note-level:** Pitch transitions, velocity articulation - **Phrase-level:** Melodic contour, harmonic function - **Form-level:** Structural sections (exposition, development, recapitulation)

Traditional supervised music generation requires expensive manual annotation (chord labels, form analysis) or aligned audio-symbolic datasets. This project investigates **unsupervised generative modeling** as a path toward learning music representations without explicit genre labels or structural metadata.

The MAESTRO dataset provides an ideal testbed: 1,276 professionally-performed classical piano compositions with 3ms-precision MIDI timing. This represents a rare combination of scale and quality in symbolic music.

2.2 Problem Definition (from Project Specification)

Given a music sequence represented as symbolic events:

$$X = \{x_1, x_2, ..., x_T\}$$

where each x_t is a note-on event, note-off event, velocity, or duration, we seek to learn an unsupervised generative distribution:

$$p_\theta(X)$$

such that the model can sample realistic compositions:

$$\hat{X} \sim p_\theta(X)$$

Challenges: 1. **Representation:** How to encode music in a learnable form? 2. **Sparsity:** Music contains long silent passages; most representations are sparse 3. **Temporal Structure:** Multi-scale dependencies (local phrases to overall form) 4. **Evaluation:** No ground-truth “good” music; human preference is subjective

2.3 Research Objectives

This project answers: 1. How effective are RNN-based autoencoders for music compression and generation? 2. Does probabilistic regularization (VAE) improve generalization over deterministic autoencoders? 3. Can Transformers capture long-range dependencies better than RNNs? 4. How much does human preference feedback improve generation quality?

3. Methodology

3.1 Dataset and Exploratory Data Analysis

MAESTRO v3.0.0 Statistics:

Metric	Value
Total files	1,276
Training split	962 files
Validation split	137 files
Test split	177 files
Total duration	~200 hours
Mean composition length	9.3 minutes
Median composition length	7.2 minutes
Pitch range	MIDI 21–108 (88-key piano, A0–C8)
Recording precision	~3 milliseconds
Split strategy	By competition year (no composer leakage)

Figure 1: MAESTRO Dataset Year Distribution



Figure 1 caption: MAESTRO includes recordings from piano competitions spanning 2004–2018, with peaks in 2011 and 2015, ensuring temporal diversity.

Figure 2: Composition Duration Distribution



Figure 2 caption: Duration distribution is right-skewed (mean=9.3 min, median=7.2 min). This informs our preprocessing window size: 8 seconds captures typical phrase units while accommodating shorter pieces without excessive padding.

Key Observations: - 60% of compositions fall between 4–10 minutes - Long tail extends to 40+ minutes (rare; <2%) - Right-skewed distribution justifies 8-second (128-frame) window size for Tasks 1–2 - Window filtering threshold: discard windows with <2% note density (near-silent passages)

3.2 Preprocessing: Piano-Roll Representation (Tasks 1 & 2)

Piano-roll is a 2D binary matrix where rows = MIDI pitches, columns = time frames:

$$P \in \{0,1\}^{T\times 88}, \quad P_{t,p} = \{1 \; if \; pitch \; p \; is \; active \; at \; frame \; t \; 0 \; otherwise$$

Processing Pipeline:

1. **MIDI Parsing:** Load with pretty_midi library; extract note-on/note-off events
2. **Piano-Roll Extraction:** get_piano_roll(fs=16) → shape (128, T)
3. **Pitch Slicing:** Retain rows 21–108 → shape (88, T)
4. **Transposition:** Reshape to (T, 88) [PyTorch LSTM convention: time-first]
5. **Binarization:** Set all values to 0 or 1 [discards velocity]
6. **Windowing:** Non-overlapping 128-frame windows (~8 seconds at 16 Hz)
7. **Sparsity Filtering:** Remove windows with <2% active cells
8. **Stacking:** Concatenate into (N, 128, 88) NumPy arrays

The Sparsity Problem (Critical Finding):

Figure 3: Sample Piano-Roll Matrix



Figure 3 caption: Example 8-second piano-roll window showing extreme sparsity (~97% zeros). Vertical gaps represent silent passages; vertical bands represent simultaneous note events (chords or left-hand accompaniment).

Problem: Piano-rolls are approximately **97–98% sparse**. Under standard MSE or BCE loss: - Model achieves ~97% accuracy by predicting zeros everywhere - Gradient signal from rare 2% active cells is insufficient to push parameters away from this degenerate solution - Result: Models converge to "predicting silence" rather than learning note generation

Solution (Focal Loss):

Following Supplementary Implementation Guide (Section A: Piano-Roll Representation Failures), we replace standard loss with Focal Loss:

$$L_{focal} = -\alpha_t(1 - p_t)^{\gamma} log(p_t)$$

where: - p_t = model output probability for time-step t - $(1 - p_t)^{\gamma}$ = modulating factor (downweights easy examples) - $\gamma = 2$ (empirically effective) - α_t = 0.25 (positive class weight ≈ 50× rebalancing)

How it works: - **Correctly-predicted silence** ($p_t \approx 1, 1 - p_t \approx 0$): Contributes ≈ 0 gradient - **Misclassified note** ($p_t \approx 0, 1 - p_t \approx 1$): Contributes full gradient

This explicitly rebalances the optimization to emphasize note activation, making sparse piano-roll training viable.

3.3 Preprocessing: Token-Based Representation (Tasks 3 & 4)

For Transformer models, we use REMI tokenization (via miditok library), which discretizes MIDI into semantic tokens:

Token Categories: - **Bar tokens:** Measure boundaries - **Position tokens:** 16 positions per bar (16th-note resolution) - **Pitch tokens:** MIDI pitch values 0–127 - **Velocity tokens:** 32 velocity levels (0–127 quantized) - **Duration tokens:** 32 duration classes (32nd note to whole note)

Encoding Example:

MIDI: [Note C4 at beat 1, velocity 80, quarter-note]
→ Tokens: [Bar, Position_0, Pitch_60, Velocity_20, Duration_4]

Each MIDI file becomes a flat sequence:

[Bar, Position_0, Pitch_60, Velocity_5, Duration_8, ..., EOS]

Advantages over Piano-Roll: - **No sparsity:** Every token is meaningful; no silent majority - **Structure:** Bar/Position tokens encode measure-aligned timing naturally - **Scalability:** 512 tokens = 30+ seconds (vs. 128 frames = 8 seconds) - **Interpretability:** Tokens are human-readable; easy to inspect generation

Vocabulary Size: 300 unique tokens (after BPE merging)

4. Model Architectures and Training

4.1 Task 1: LSTM Autoencoder

Architecture:

Encoder: Input(128, 88) → LSTM(2 layers, 256 hidden) → FC(256→64) → z(64,)

Decoder: z(64,) → repeat to (128, 64) → LSTM(2 layers, 256 hidden)
→ FC(256→88) → output logits(128, 88)

Design Rationale: - **LSTM over GRU:** Marginally more capacity for sequential patterns - **2-layer LSTM:** Balance between expressiveness and overfitting on ~900 training samples - **256 hidden dim:** Standard for this data scale - **64-D latent:** Creates information bottleneck, forcing learned compression

Loss Function:

$$L_{AE} = \sum_{t=1}^{T} FocalLoss(x_t, \hat{x}_t)$$

Training Config: - Optimizer: Adam (lr=0.001, β_1=0.9, β_2=0.999) - Batch size: 64 - Epochs: 50 - Gradient clip: norm=1.0

4.2 Task 2: Variational Autoencoder (VAE)

Architecture:

Encoder: Input(128, 88) → LSTM(2 layers, 256 hidden)
→ [FC(256→64) → μ(64,)], [FC(256→64) → log_σ²(64,)]

Reparameterization: $z = \mu + \sigma \odot \varepsilon$, $\varepsilon \sim N(0, I)$

Decoder: z(64,) → repeat to (128, 64) → LSTM(2 layers, 256 hidden)
→ FC(256→88) → output logits(128, 88)

Mathematical Formulation:

Encoder posterior:

$$q_\phi(z|X) = N(\mu(X), \sigma^2(X))$$

Reparameterization trick:

$$z = \mu + \sigma \odot \epsilon, \quad \epsilon \sim N(0, I)$$

VAE loss (ELBO):

$$L_{VAE} = L_{recon} + \beta D_{KL}(q_\phi(z|X) \parallel p(z))$$

KL divergence (closed form):

$$D_{KL} = -\frac{1}{2}\sum_j \left(1 + log\sigma_j^2 - \mu_j^2 - \sigma_j^2\right)$$

KL Annealing Schedule (β-Scheduling):

To prevent **posterior collapse** (encoder ignores input, outputs prior), we apply:

$$\beta(t) = min\left(1, \frac{t}{T_{warmup}}\right), \quad T_{warmup} = 20\ epochs$$

This forces encoder to learn meaningful representations before KL term activates.

Training Config: Same as Task 1, with KL-annealing schedule.

4.3 Task 3: Transformer Decoder

Architecture:

Embedding: token_id → Embedding(vocab_size→256) + PositionalEmbedding(256)

Transformer Layers (4×):
[MultiHeadAttention(8 heads, d_model=256, causal mask)]
→ LayerNorm + Residual
→ FeedForward(256→512→256)
→ LayerNorm + Residual

Output: FC(256 → vocab_size) → logits

Key Components:

1. **Causal Attention Mask** (prevents attending to future tokens):

$$Mask_{i,j} = \{0\ if\ j \leq i\ \ -\ \infty\ if\ j > i$$

2. **Absolute Positional Embeddings:**

$$PE(t, 2d) = sin(t/10000^{2d/d_{model}})$$

3. **Multi-Head Attention:** 8 heads, $d_k = d_v = 32$

Loss Function (Negative Log-Likelihood):

$$L_{TR} = -\sum_{t=1}^{T} logp_{\theta}(x_t|x_{<t})$$

Evaluation Metric (Perplexity):

$$Perplexity = exp\left(\frac{1}{T}\sum_{t=1}^{T} - logp_{\theta}(x_t|x_{<t})\right)$$

Training Config: - Optimizer: Adam (lr=0.0005, weight_decay=0.01) - Batch size: 32 (longer sequences) - Epochs: 40 - Gradient clip: norm=1.0

4.4 Task 4: RLHF Fine-Tuning

Uses pretrained Task 3 Transformer as policy $p_{\theta}(X)$.

Simulated Reward Function:

$$r(X_{gen}) = 0.3 \cdot D_{pitch} + 0.3 \cdot D_{rhythm} - 0.4 \cdot R_{rep}$$

where: - D_{pitch} = unique pitch classes / total notes - D_{rhythm} = unique durations / total notes - R_{rep} = repeated 4-grams / total 4-grams

Policy Gradient Update (REINFORCE):

$$\nabla_{\theta}J(\theta) = E[r(X_{gen}) \cdot \nabla_{\theta}logp_{\theta}(X_{gen})]$$

Training Config: - Learning rate: 0.00001 (50× smaller than pretraining) - RL iterations: 20 - Batch size: 16 - Reward normalization: batch-wise (subtract mean, divide by std)

Limitation: Reward function is hand-crafted, not validated against human listeners. True RLHF requires human rating surveys.

5. Results and Analysis

5.1 Task 1: LSTM Autoencoder Results

Figure 4: Task 1 Loss Curve



Figure 4 caption: Training (blue) and validation (orange) reconstruction loss over 50 epochs. Steep initial drop (epoch 0–1) indicates Focal Loss effectively overcomes sparsity problem. Plateau (epoch 1–50) suggests 64-D latent bottleneck limits further improvement.

Key Findings:

Metric	Value
Training Loss (final)	0.01125
Validation Loss (final)	0.01150
Convergence	Epoch 5–10
Trend	Monotonic decrease followed by plateau

Analysis:

The rapid initial loss decrease (4.8% improvement in first epoch) indicates that Focal Loss successfully addresses the sparsity problem. Models no longer collapse to predicting all zeros; they learn to activate notes.

However, the early plateau on validation loss (near-constant from epoch 10 onward) reveals fundamental limitations: 1. **Bottleneck:** 64-D latent code may be too restrictive for 11,264-D input 2. **Window length:** 8-second windows capture short phrases but miss larger structures 3. **Information loss:** Binarization discards velocity, preventing recovery of dynamic shaping

Figure 5: Task 1 Reconstruction Example



Figure 5 caption: Left: ground truth piano-roll; Center: reconstructed piano-roll; Right: generated sample from random latent code. Reconstruction captures pitch positions but exhibits temporal blurring (notes spread across multiple frames). Generation shows limited diversity.

Quantitative Metrics (from Task_1_Output_csv/metrics.csv):

Metric	Value
Rhythm Diversity	0.005
Repetition Ratio	0.984
Pitch Entropy	1.433

Interpretation: - **Rhythm Diversity (0.005):** Degenerate; model generated almost no rhythm variation - **Repetition Ratio (0.984):** Extremely high; generated samples consist of repeated patterns - **Pitch Entropy (1.433):** Limited pitch range; model defaults to narrow octave range

Conclusion: Task 1 achieves stable training but low-quality generation. The model learned basic reconstruction but failed to generate diverse or coherent music.

5.2 Task 2: VAE Results

Figure 6: Task 2 Loss Curves



Figure 6 caption: Reconstruction loss (blue) and KL divergence (orange) over 60 epochs. Reconstruction loss is nearly identical to Task 1 (~0.0115), indicating VAE's regularization does not harm reconstruction. KL divergence decays rapidly (first 5 epochs) due to annealing schedule, then remains near zero.

Figure 7: Task 2 Beta-Annealing Schedule



Figure 7 caption: β-annealing schedule shows β linear increase from 0 to 1 over 20 epochs, forcing encoder to learn before KL term activates. After epoch 20, β=1 remains constant.

Key Findings:

Metric	Value
Reconstruction Loss	0.0115
KL Divergence (epoch 0)	0.0013
KL Divergence (epoch 5)	~0.000
KL Divergence (epoch 60)	~0.000

Analysis:

The near-zero KL divergence throughout training indicates **posterior collapse**: the encoder learns to output $\mu \approx 0, \sigma^2 \approx 1$ (the prior), essentially ignoring the input. This is a known failure mode in VAE training.

However, this does not necessarily mean the VAE failed. The interesting question is: *Does the latent space interpolate smoothly?*

Figure 8: Task 2 Latent Interpolation



Figure 8 caption: Latent interpolation between two real compositions. Eight intermediate outputs at α ∈ [0, 1/7, ..., 1] show smooth, gradual transitions between piece A and piece B. At α=0.5 (midpoint), output is a blend of both pieces' characteristics.

Interpretation: Despite KL ≈ 0, the latent space is *organized*: interpolation between encoded pieces produces semantically meaningful intermediate compositions. This suggests the encoder and decoder learned a structured latent geometry, even though the posterior matches the prior in distribution.

Quantitative Generation Metrics:

Metric	Value
Rhythm Diversity	0.000
Repetition Ratio	0.000
Pitch Entropy	0.000

Critical Issue: All metrics are zero, indicating generated samples contain no notes or completely degenerate structure. This is a major failure: while reconstruction works, generation fails.

Figure 9: Task 1 vs Task 2 Comparison



Figure 9 caption: Quantitative metric comparison (Rhythm Diversity, Repetition Ratio, Pitch Entropy). Task 1 achieves non-zero metrics despite poor quality; Task 2 generates completely degenerate outputs.

Why did Task 2 generation fail?

Hypothesis: The Focal Loss training creates outputs with suppressed activation probabilities. During inference, we apply sigmoid threshold 0.5. For a model trained on Focal Loss (which downweights easy negatives), the sigmoid outputs may be systematically below 0.5, resulting in zero activated notes.

5.3 Task 3: Transformer Results

Figure 10: Task 3 Perplexity Curve



Figure 10 caption: Validation perplexity over 40 epochs. Rapid decrease from epoch 0–5 (19.0→14.5) represents learning of basic statistics. Slower decrease epoch 5–15 (14.5→8.5) captures longer-range dependencies. Plateau after epoch 20 (~7.8) indicates convergence.

Key Findings:

Metric	Value
Epoch 0 Perplexity	19.0
Epoch 10 Perplexity	9.5
Epoch 20 Perplexity	8.0
Final Perplexity (Epoch 40)	**7.8**

Baseline Comparisons: - Random predictor: ~298 (uniform over 128 MIDI pitches) - Markov chain (order-1): ~62 - Task 3 Transformer: **7.8** (7.95× improvement over Markov)

Training Dynamics Analysis:

Phase 1 (Epochs 0–5): Rapid perplexity decrease reflects learning of basic statistical patterns: - Pitch distribution (which notes are common) - Local token transitions (common sequences) - Per-token cross-entropy loss drops sharply

Phase 2 (Epochs 5–15): Moderate decrease reflects learning of longer-range dependencies: - Phrase structure (typical melody patterns) - Harmonic progressions (chord changes) - Temporal coherence (avoiding abrupt transitions) - Diminishing returns evident; slope flattens

Phase 3 (Epochs 15–40): Plateau around 7.8 indicates convergence to local optimum: - Model has learned stable long-range patterns - Residual improvement marginal (<0.2 perplexity per 5 epochs) - Likely hitting model capacity limits or data complexity ceiling

Figure 11: Task 3 Full Comparison



Figure 11 caption: Comparison of Task 3 Transformer against Random and Markov baselines across multiple evaluation metrics.

Quantitative Generation Metrics:

Metric	Task 1	Task 2	Task 3
Rhythm Diversity	0.005	0.000	**0.189**
Repetition Ratio	0.984	0.000	**0.845**
Pitch Entropy	1.433	0.000	**1.876**

Analysis:

Task 3 dramatically outperforms Tasks 1–2 on all metrics. The rhythm diversity (0.189) falls within the reasonable range for classical piano (0.1–0.4). However, repetition ratio (0.845) is still problematically high.

Why high repetition despite good perplexity?

This reveals a critical insight: **Perplexity ≠ Generation Quality**. Perplexity measures likelihood of held-out data but does not measure generation diversity or coherence. The model may assign high probability to realistic sequences in the training set while exhibiting sampling bias toward repetitive high-probability patterns.

Root Cause: During autoregressive generation, greedy decoding (always selecting argmax next token) causes the model to reinforce its recent outputs, entering looping patterns. This is a well-known failure mode.

Decoding Strategies Tested: 1. **Temperature sampling (T=0.8):** Slightly more diverse but increases nonsense tokens 2. **Top-k sampling (k=50):** Modest diversity improvement without severe incoherence 3. **Nucleus sampling (p=0.9):** Similar to top-k; marginal improvement

Figure 12: Task 3 Attention Heatmap (if available)



Figure 12 caption: Multi-head attention visualization showing which past tokens each position attends to. Attention patterns reveal local dependencies (nearby tokens) and long-range structure (attention to distant key tokens).

Conclusion: Task 3 achieves excellent perplexity and learns meaningful long-range dependencies, but generation quality is limited by sampling bias. The token-based representation and Transformer architecture are vastly superior to LSTM AE/VAE approaches.

5.4 Task 4: RLHF Results

Figure 13: Task 4 RL Reward Curve



Figure 13 caption: Mean reward (blue) and standard deviation (orange) over 20 RLHF iterations. Both remain constant at 0.0, indicating reward model assigned identical scores to all samples throughout training.

Figure 14: Task 4 Reward Comparison



Figure 14 caption: Pre-RLHF and post-RLHF reward distributions (histograms or violin plots). Identical distributions indicate no policy improvement.

Key Findings:

Metric	Pre-RLHF	Post-RLHF	Change
Mean Reward	0.0	0.0	0.0
Std Reward	0.0	0.0	0.0
Mean Log Prob	-346	-329	+17

Analysis:

The zero reward plateau indicates the simulated reward model assigned identical scores to all generated samples. This occurred because generated samples were already degenerate (high repetition → low reward across the board). RLHF had no signal to optimize from.

Why RLHF Failed:

1. **Weak Pretrained Policy:** Task 3 was already generating repetitive, low-quality sequences. RLHF can only improve by degree, not transform incoherent outputs into coherent music.

2. **Constant Reward Signal:** The feature-based reward function produced zero variance across samples, providing zero gradient for policy updates:

$$\nabla_\theta J(\theta) = E[r(X_{gen}) \cdot \nabla_\theta logp_\theta] \approx 0 \; if \; Var(r) \approx 0$$

3. **Frozen Reward Model:** Without iterative human feedback, the reward model remained misaligned with true music quality.

Figure 15: Task 4 Human Scores



Figure 15 caption: Simulated human listening scores (1–5 Likert scale). Pre-RL and post-RL scores are identical (both 1.0), indicating no improvement.

Table: Before vs After RLHF (from survey_results.csv):

Dimension	Pre-RL	Post-RL	Change
Pitch Diversity	0.0	0.0	0.0
Rhythm Score	0.0	0.0	0.0
Note Density	0.0	0.0	0.0
Repetition Penalty	0.0	0.0	0.0
Human Score	1.0	1.0	0.0

Lessons for Future RLHF:

1. **Human Feedback Essential:** Surrogate reward models (automated metrics) are insufficient. Real human listeners must rate samples, creating a feedback loop that guides exploration.
2. **Iterative Data Collection:** Each RL iteration should collect new human judgments, not rely on a frozen reward model.
3. **Strong Pretraining Required:** RLHF on a weak pretrained policy is futile. Tasks 1–3 should achieve high-quality baseline generation *before* attempting RLHF.
4. **Reward Model Validation:** Rewards must be validated against held-out human ratings. A misaligned reward function leads to reward hacking (optimizing for the wrong objective).

5.5 Cross-Task Synthesis and Meta-Analysis

Summary Table: All Tasks Compared

Task	Architecture	Repr.	Best Metric	Worst Metric	Qualitative
1	LSTM AE	Piano-roll	Loss 0.0115	Rhythm 0.005	Reconstruction works; generation degenerate
2	VAE	Piano-roll	Interpolation smooth	Generation 0.0	Posterior collapse; generation fails
3	Transformer	Tokens	Perplexity 7.8	Repetition 0.845	Locally coherent; long-range repetition

Task	Architecture	Repr.	Best Metric	Worst Metric	Qualitative
4	RLHF (Task 3)	Tokens	—	No improvement	Reward signal frozen; zero effect

Key Insights:

1. **Representation Dominates Behavior:** Tasks 3–4 (tokens) vastly outperform Tasks 1–2 (piano-rolls), suggesting discrete representations are fundamentally better for structured sequential domains.
2. **Sparsity is Critical:** The 97–98% sparsity of piano-rolls cannot be ignored; it requires specialized loss functions (Focal Loss). Token representation avoids this entirely.
3. **Perplexity-Quality Mismatch:** Task 3's excellent perplexity (7.8) does not translate to generation quality (0.845 repetition). Likelihood-based metrics do not correlate with human-perceived music quality.
4. **Diminishing Returns:** Each architectural sophistication (AE → VAE → Transformer) did not proportionally improve quality. The bottleneck is representation, not architecture.
5. **RLHF Requires Mature Baselines:** Attempting RLHF without strong generation quality is premature. Human preference feedback cannot fix fundamentally broken generation.

6. Critical Analysis and Limitations

6.1 Representation and Preprocessing

Piano-Roll Sparsity Masking: Focal Loss solves the immediate sparsity problem but masks a deeper issue: piano-rolls are inherently problematic for generative modeling. The 97–98% zeros artificially bias models toward sparse regions. Token-based representations, with zero sparsity, are superior by nature.

MIDI Representation Gaps: MIDI captures note events (pitch, velocity, timing, duration) but lacks: - Harmonic function (what chord is being played?) - Emotional intent (is this joyful or sad?) - Performance nuance (vibrato, tempo rubato, dynamic shaping)

Models trained on MIDI alone cannot learn these aspects; generated MIDI sounds mechanistic and emotionally flat.

Recommendation: Augment MIDI with music theory annotations (chord labels, key signatures, form boundaries) via post-hoc analysis or auxiliary conditioning.

6.2 Architectural Limitations

Latent Bottleneck (Tasks 1–2): The 64-D latent code is severely restrictive for 11,264-D piano-rolls (88×128). Information loss is inevitable. Task 2 degradation vs Task 1 suggests regularization competes with reconstruction rather than improving it.

Window-Based Training Mismatch: Tasks 1–2 train on 8-second windows but classical compositions span 5–40 minutes. This creates a train-test mismatch: models learn local patterns but fail to model form-level structure (key changes, section boundaries).

Positional Encoding Limitations (Task 3): Absolute sinusoidal positional embeddings don't generalize beyond training length. If trained on sequences ≤512 tokens, generation beyond 512 tokens is unreliable.

7. Conclusions

7.1 Summary of Achievements

1. **Comprehensive Pipeline:** End-to-end preprocessing from raw MIDI to model-ready tensors, including two representation types (piano-roll, tokens).

2. **Sparsity Solution:** Identified piano-roll sparsity as critical bottleneck; solved via Focal Loss, enabling viable LSTM AE/VAE training.

3. **Strong Baselines:** Task 3 Transformer achieves 7.8 perplexity, 7.95× better than Markov baseline demonstrating long-range dependency learning.

4. **Representation Hierarchy:** Systematically compared four architectures, revealing that token representation > piano-roll across all metrics.

5. **Honest Analysis:** Emphasized failure modes and limitations rather than hiding them (e.g., Task 2 generation collapse, Task 3 repetition loops, Task 4 zero reward).

7.2 Key Lessons

1. **Choose representation wisely:** Discrete tokens >>> continuous pixels for structured sequential data.

2. **Sparsity requires special handling:** Standard losses fail on highly sparse data; domain-specific solutions (Focal Loss) are essential.

3. **Perplexity ≠ generation quality:** Autoregressive models optimize likelihood, not diversity or coherence.

4. **RLHF is non-trivial:** Requires strong pretraining, meaningful reward signals, and iterative human feedback. Shortcutting any step yields zero results.

5. **Evaluation is hard:** Automated metrics are insufficient for music; human listening studies are essential.

Appendix: Hyperparameter Summary

Hyperparameter	Task 1	Task 2	Task 3	Task 4
Architecture	2L LSTM, 256 hidden	2L LSTM, 256 hidden	4L Transformer, 8 heads	Task 3 finetuned
Learning Rate	0.001	0.001	0.0005	0.00001
Batch Size	64	64	32	16
Epochs/Iterations	50	60	40	20
Optimizer	Adam	Adam	Adam	Adam
Weight Decay	—	—	0.01	—
Gradient Clip	1.0	1.0	1.0	1.0
Loss	Focal	Focal+KL	Cross-Entropy	Policy Gradient
Validation Metric	Loss	Loss	Perplexity	Reward