



United International University (UIU)

Dept. of Computer Science & Engineering (CSE)

Mid-term Exam: : Trimester: Spring 2024

Course Code: CSE 1111, Course Title: STRUCTURED PROGRAMMING LANGUAGE

Time: 1 hour 30 min Total Marks: 30

Answer all the questions.

"Any examinee found adopting unfair means will be expelled from the trimester / program as per UIU disciplinary rules."

1. (a) Identify and correct errors in the following code segment (below left). [3]
(b) Find output of the following code segment (below right). [3]

```
include <stdio>
Int main {
    int Num, a;
    Num = 20%3;
    a = Num+10
    printf("%d %f ", Num, a,);
    return 0;
}
```

C Code for 1(a)

```
int a=3, b=4, c=-5, result;
int mod;
result = a * b % c + b;
printf("result = %d\n",result);
if (result >= 0 && result < 10) {
    printf("a = %d\n", a);
}
else if (result >= 5) {
    printf("b = %d\n", b);
}
else printf("a = %d\n", a);
```

C Code for 1(b)

3.6

2. (a) Rewrite the code segment (below left) using "if ... else" without changing the logical meaning. [3]
(b) Manually trace the following code segment (below right) and show all the changes of the variables i, p, and x in each step. [3]

```
int num=5, sum=10, i=4, j=9;
switch(num) {
    case 1: sum *= 3;
    case 2:
    case 3: sum += --j * 2;
            i--; break;
    case 4: sum = ++i * j--;
            break;
    case 5: break;
            i += 10;
    default: sum *= i++ / j--;
            i=i % j; break;
}
```

C Code for 2(a)

```
#include <stdio.h>
int main() {
    int p=1;
    int x = 490;
    for(int i=1;i<=p;){
        printf("%d %d %d\n",i,p,x);
        if(x % 29 == 0){
            printf("Not a great number!");
            break;
        }
        else {
            x -= 13;
            p += x % 10;
            i += 3;
        }
    }
    return 0;
}
```

C Code for 2(b)

- (c) Draw a flow chart for the given code segment in Q.2(b) (above right). [3]

3. (a) Write a C program to print the following pattern of digit '2'. Take n as user input where n is odd and $n \geq 5$. [3]

Sample input	n=5
Sample output	<pre> * * * * * * * * * * * * * * * * *</pre>

- (b) Replace the "outer" while loop with "for" and the "nested" for loop with "while" loop in the following code without changing the logical meaning of the program. [3]

```

int i=0, count = 0;
int n = 12345;
while (n != 0) {
    printf ("%d", n % 10);
    count++;
    for(; i<count; i++) {
        printf("%d", n/= 10);
    }
    printf ("\n");
}
```

4. Manually trace the given code segment below. Show the changes of all the variables i , hi , hlw and array arr elements in each step. [3]

```

int hi = 0, hlw = 10;
int arr[4] = {10, 20, 30, 40};
for(int i=4; i<=hlw; i++) {
    arr[hi] = arr[hi+1] - 5;
    hlw -= 2;
}
```

5. Take an array as input of size N . Then take another number as input in K . Your task is to add this number to the even indexed elements, and subtract from the odd indexed elements. [6]

Sample Input	Sample Output
$N=5$ Array Elements: 10 20 30 40 50 $K=4$	14 16 34 36 54

OR

Write a program which will take input of $N \times N$ numbers in a 2D array A . Now swap all the elements in the first and last column within the array and finally print the array. [6]

Sample Input	Sample Output
3 1 4 7 2 8 3 5 6 0	7 4 1 3 8 2 0 6 5