Step 1 : Create a new Folder Inside the src named Component
Step 2 : Create a new file named Quiz.jsx and Quiz.css
Step 3: create one function component inside Quiz.jsx and call that inside App.jsx
Step 4 : Add the question List inside Quiz.jsx

```
App.jsx   Quiz.jsx ×   main.jsx   QuestionList.jsx   # Quiz.css
src > Component > Quiz.jsx > ...
import React, { useState } from 'react';
import './Quiz.css';

function Quiz() {
  const questions = [
    {
      question: "What is React ?",
      options: ['css Framework', 'React Library', 'React Framework', 'Testing tool'],
      answer: 'React Library'
    },
    {
      question: 'What is 1 + 2?',
      options: ['3', '1', '4', '5'],
      answer: '3'
    }
  ];
```

Step 5 : Create QuestionList.jsx inside the component : And Create a function inside QuestionList.jsx
And Call the QuestionList inside Quiz,jsx inside the return
And next Create a state `[currentQuestionIndex, setCurrentQuestionIndex]`

```
  ]
  const [currentQuestionIndex, setCurrentQuestionIndex] = useState(0);
return (
  <div>
      <div>
          <QuestionList />
      </div>
  </div>
)
}
```

Note : We are creating this State because we need to pass the question one by one through the index.
Step 5 : pass the props in Quiz.jsx file inside <QuestionList >

```
            answer: '4'
          }
    ]
    const [currentQuestionIndex, setCurrentQuestionIndex] = useState(0);
  return (
    <div>
        <div>
            <QuestionList question={questions[currentQuestionIndex].question}
            options={questions[currentQuestionIndex].options}/>
        </div>
    </div>
  )
}
```

Step 6 : Now Accept the props inside the QuestionList.jsx file inside the function created.And Display Questions and Answers

```
import React from 'react'

export default function QuestionList({question, options}) {
  return (
    <div>{question}{options}</div>
  )
}
```

Now the output will be in one single line including both Questions and Answers Which is wrong . As first we need to display the questions and the options in the form of list.

```
import React from 'react'

export default function QuestionList({question, options}) {
  return (
    <div>
        <h2>{question}</h2>
       <ul>
        {options.map((option, index)=> (
            <li key={index}>{option}</li>
        ))}
       </ul>
    </div>
  )
}
```

Step 7 : Create the button Next Question in Quiz.jsx file.
Now my my Next Question Button is enabled even when the option is not selected . so we need to disable the button till the option is selected

Step 8 : Create one more Variable [currentAnsewer, setCurrentAnsewer]

```
            }
      ]
      const [currentQuestionIndex, setCurrentQuestionIndex] = useState(0);
      const [currentAnswer, setCurrentAnswer] = useState(null);
    return (
      <div>
          <div>
              <QuestionList question={questions[currentQuestionIndex].question}
              options={questions[currentQuestionIndex].options}/>
              <button>Next Question</button>
          </div>
```

Step 9 : Now we need to make the select option by the user . for that we need to have the onClick function in the QuestionList.jsx file inside the option list

```
import React from 'react'

export default function QuestionList({question, options}) {
  return (
    <div>
        <h2>{question}</h2>
       <ul>
        {options.map((option, index)=> (
            <li key={index} onClick={()=>handleClick(option)}>{option} </li>
        ))}
       </ul>
    </div>
  )
}
```

Step 10 : Now we need to update the current answer but the currentAnswer is inside the Quiz.jsx but we have written the function in QuestionList.jsx i.e now we need to pass this function as a prop and create one more variable where the options is accepted
And the call the setCurrentAnswer and pass the option inside it

```
xport default function Quiz() {
  const [currentQuestionIndex, setCurrentQuestionIndex] = useState(0);
  const [currentAnswer, setCurrentAnswer] = useState(null);
  const handleClick= (option) => {
      setCurrentAnswer(option)
  }
return (
  <div>
      <div>
          <QuestionList question={questions[currentQuestionIndex].question}
          options={questions[currentQuestionIndex].options} handleClick={handleClick}/>
          <button>Next Question</button>
      </div>
  </div>
)
```

Step 11 : As now we have passed the handleClick function it should be now accepted in QuestionList.jsx file

```
import React from 'react'

export default function QuestionList({question, options, handleClick}) {
  return (
    <div>
        <h2>{question}</h2>
       <ul>
        {options.map((option, index)=> (
            <li key={index} onClick={()=>handleClick(option)}>{option} </li>
        ))}
       </ul>
    </div>
  )
}
```

Step 12 : As the user selects the option it should get highlighted . so now we need to add that functionality
So pass the currentAnswer as a prop

```
5   export default function Quiz() {
18      const [currentQuestionIndex, setCurrentQuestionIndex] = useState(0);
19      const [currentAnswer, setCurrentAnswer] = useState(null);
20      const handleClick = (option) => {
21          setCurrentAnswer(option)
22      }
23      return (
24          <div>
25              <div>
26                  <QuestionList question={questions[currentQuestionIndex].question}
27                      options={questions[currentQuestionIndex].options} handleClick=
                        {handleClick} currentAnswer={currentAnswer}/>
28                  <button>Next Question</button>
29              </div>
30          </div>
31      )
```

Step 13 : Accept the prop currentAnswer in QuestionList.jsx file and now add the css After the handleClick

```
import React from 'react'

export default function QuestionList({question, options, handleClick, currentAnswer}) {
  return (
    <div>
        <h2>{question}</h2>
       <ul>
        {options.map((option, index)=> (
            <li key={index} onClick={()=>handleClick(option)} className={currentAnswer ===
            option ? 'selected' : ''}>{option} </li>
        ))}
       </ul>
    </div>
  )
}
```

Step 14 : Now before selecting the option the Next Button should be disabled
Go to quiz.jsx and add disable

```
    <div>
        <div>
            <QuestionList question={questions[currentQuestionIndex].question}
                options={questions[currentQuestionIndex].options} handleClick=
                {handleClick} currentAnswer={currentAnswer}/>
            <button disabled={currentAnswer === null} className={currentAnswer ===
            null ? 'button-disable' : 'button'}>Next Question</button>
        </div>
    </div>
)
```

Step 15 : Next after selecting the option i need to move to the next question where the onClick Functionality should be added pass handleNextQuestion . then define the handleNextQuestion And convert it into the arrow function and make it as setCurrentQuestionIndex (currentQuestionIndex + 1)
Also add setCurrentAnswer(null);

```
return (
    <div>
        <div>
            <QuestionList question={questions[currentQuestionIndex].question}
                options={questions[currentQuestionIndex].options} handleClick=
                {handleClick} currentAnswer={currentAnswer}/>
            <button disabled={currentAnswer === null} className={currentAnswer ===
            null ? 'button-disable' : 'button'} onClick={handleNextQuestion}>Next
            Question</button>
        </div>
```

```
            options: ['3', '4', '5', '6'],
            answer: '4'
        }
    ]
    const [currentQuestionIndex, setCurrentQuestionIndex] = useState(0);
    const [currentAnswer, setCurrentAnswer] = useState(null);
    const handleClick = (option) => {
        setCurrentAnswer(option)
    }
    const handleNextQuestion = ()=>{
        setCurrentQuestionIndex(currentQuestionIndex + 1);
        setCurrentAnswer(null);
    }
    return (
```

Step 16 : now as i have only given 2 question after selecting the 2 nd question i dont need the Next Question Button . For that we need to add the conduction
Just add one conduction {currentQuestionIndex < questions.length : cut the below div and paste hear }

```
return (
    <div>
        {currentQuestionIndex < questions.length ?            <div>
            <QuestionList question={questions[currentQuestionIndex].question}
                options={questions[currentQuestionIndex].options} handleClick=
                {handleClick} currentAnswer={currentAnswer}/>
            <button disabled={currentAnswer === null} className={currentAnswer ===
            null ? 'button-disable' : 'button'} onClick={handleNextQuestion}>Next
            Question</button>
        </div> : ""}

    </div>
)
```

OUTPUT DEBUG CONSOLE TERMINAL PORTS node

Step 17 : Now we need to display the score
Create a new variable const [score , setScore] = useState(0);

```
const [currentAnswer, setCurrentAnswer] = useState(null);
const [score, setScore] = useState(0);
const handleClick = (option) => {
    setCurrentAnswer(option)
    if(option === questi setScore(value: React.SetStateAction<number>): void
        setScore(score+1)
    }
}
const handleNextQuestion = ()=>{
    setCurrentQuestionIndex(currentQuestionIndex + 1);
    setCurrentAnswer(null);
}
return (
    <div>
```

Step 18 (Last Step) : Display the Score .
Just create one div at last and pass the {score}

```
export default function Quiz() {
                    {handleClick} currentAnswer={currentAnswer}/>
                <button disabled={currentAnswer === null} className={currentAnswer ===
                null ? 'button-disable' : 'button'} onClick={handleNextQuestion}>Next
                Question</button>
            </div> : <div>You Score is {score}</div>}

        </div>
    )
}
```