

WARNING:

The password for this account is insecure. Password is currently set to the default value (pfsense).
Change the password as soon as possible.

Interfaces / WANuplink (le0)



The WANuplink configuration has been changed.
The changes must be applied to take effect.
Don't forget to adjust the DHCP Server range if needed after applying.

✓ Apply Changes

General Configuration

Enable	☒ Enable interface
Description	WANuplink Enter a description (name) for the interface here.
IPv4 Configuration Type	DHCP
IPv6 Configuration Type	DHCP6
MAC Address	xx:xx:xx:xx:xx:xx This field can be used to modify ("spoof") the MAC address of this interface. Enter a MAC address in the following format: xx:xx:xx:xx:xx:xx or leave blank.
MTU	

Description	LANcore
Enter a description (name) for the interface here.	
IPv4 Configuration Type	Static IPv4
IPv6 Configuration Type	DHCP6
MAC Address	xx:xx:xx:xx:xx:xx
This field can be used to modify ("spoof") the MAC address of this interface. Enter a MAC address in the following format: xx:xx:xx:xx:xx:xx or leave blank.	
MTU	
If this field is blank, the adapter's default MTU will be used. This is typically 1500 bytes but can vary in some circumstances.	
MSS	
If a value is entered in this field, then MSS clamping for TCP connections to the value entered above minus 40 for IPv4 (TCP/IPv4 header size) minus 60 for IPv6 (TCP/IPv6 header size) will be in effect.	
Speed and Duplex	Default (no preference, typically autoselect)
Explicitly set speed and duplex mode for this interface. WARNING: MUST be set to autoselect (automatically negotiate speed) unless the port this interface connects to has its speed and duplex	

Static IPv4 Configuration	
IPv4 Address	192.168.10.1
/ 25	
IPv4 Upstream gateway	None
+ Add a new gateway	
If this interface is an Internet connection, select an existing Gateway from the list or add a new one using the "Add" button. On local area network interfaces the upstream gateway should be "none".	

192.168.56.103/interfaces.php?if=lan

Enable ☒ Enable Interface

Description

LANcore

Enter a description (name) for the interface here.

IPv4 Configuration Type

Static IPv4

IPv6 Configuration Type

DHCP6

MAC Address

xxxxxxxxxxxx

This field can be used to modify ("spoof") the MAC address of this interface.
Enter a MAC address in the following format: xx:xx:xx:xx:xx:xx or leave blank.

MTU

If this field is blank, the adapter's default MTU will be used. This is typically 1500 bytes but can vary in some circumstances.

MSS

If a value is entered in this field, then MSS clamping for TCP connections to the value entered above minus 40 for IPv4 (TCP/IPv4 header size) and minus 60 for IPv6 (TCP/IPv6 header size) will be in effect.

Speed and Duplex

Default (no preference, typically autoselect)

Explicitly set speed and duplex mode for this interface.
WARNING: MUST be set to autoselect (automatically negotiate speed) unless the port this interface connects to has its speed and duplex forced.

Static IPv4 Configuration

IPv4 Address

192.168.10.1

/ 25

IPv4 Upstream gateway

None

+ Add a new gateway

If this interface is an Internet connection, select an existing Gateway from the list or add a new one using the "Add" button.
On local area network interfaces the upstream gateway should be "none".
Selecting an upstream gateway causes the firewall to treat this interface as a WAN type interface.
[Gateways can be managed by clicking here.](#)

18°C Sunny

Search

ENG IN

10:19 AM 12/13/2025

WARNING:

The password for this account is insecure. Password is currently set to the default value (pfsense).
[Change the password as soon as possible.](#)

Interfaces / **WANuplink (le0)**



The following input errors were detected:

- The settings have already been applied!

General Configuration

Enable ☒ Enable interface

Description

WANuplink

Enter a description (name) for the interface here.

IPv4 Configuration Type

DHCP ▾

IPv6 Configuration Type

DHCP6 ▾

MAC Address

xx:xx:xx:xx:xx:xx

This field can be used to modify ("spoof") the MAC address of this interface.
Enter a MAC address in the following format: xx:xx:xx:xx:xx:xx or leave blank.

MTU

SIGN IN

admin

.....|

SIGN IN