

VISVESVARAYA TECHNOLOGICAL UNIVERSITY

“Jnana Sangama”, Belgaum-590014, Karnataka.



A Project Report  
on  
“InVision AI: An Eye for the Blind”

Submitted in the partial fulfilment of the requirement for the award of the Degree of

Bachelor of Engineering  
In  
ARTIFICIAL INTELLIGENCE AND MACHINE LEARNING

Submitted by  
RAKSHITH BS (1DT22AI038)  
ARJUN HC (1DT23AI400)  
DARSHAN U (1DT23AI401)  
RAKSHITHA S (1DT23AI409)

Under the Guidance of,

Mrs. Ayain John  
Asst. Professor, Dept. of AIML,  
DSATM, Bangalore-82.



Department of Artificial Intelligence and Machine Learning  
DAYANANDA SAGAR ACADEMY OF TECHNOLOGY AND MANAGEMENT  
Udayapura, Kanakapura Road, Bengaluru-560082

2025-2026



## DAYANANDA SAGAR ACADEMY OF TECHNOLOGY & MANAGEMENT

An Autonomous Institute

Opp. Art of Living, Udayapura, Kanakapura Road, Bangalore-560082

(Affiliated to Visvesvaraya Technological University, Belagavi and Approved by  
AICTE, New Delhi) CE, CSE, ECE, EEE, ISE, ME Courses Accredited by NBA, New  
Delhi), NAAC A+.

### DEPARTMENT OF ARTIFICIAL INTELLIGENCE AND MACHINE LEARNING

#### CERTIFICATE

This is to certify that the Project entitled “InVision AI: An Eye for the Blind” has been successfully carried out by RAKSHITH BS (1DT22AI038), ARJUN HC (1DT23AI400), DARSHAN U (1DT23AI401), RAKSHITHA S (1DT23AI409) Bonafide students of Dayananda Sagar Academy of Technology and Management in partial fulfillment of the requirements for the award of degree in Bachelor of Engineering in Artificial Intelligence and Machine Learning of Visvesvaraya Technological University, Belgaum during the academic year 2025-2026. It is certified that all corrections/suggestions indicated for Internal Assessment have been incorporated in the report deposited in the departmental library. The Project report has been approved as it satisfies the academic requirements in respect of project work for the said degree.

Signature of project guide

Mrs. Ayain John

Asst. Professor, Dept of

AIML

Signature of HOD

Dr. Sandhya N

Professor & HOD, Dept of

AIML

Signature of Principal

Dr. M. Ravishankar

Principal

Examiners:

1:

2:

## DECLARATION

We declare that this project report titled “InVision AI: An Eye for the Blind” submitted in partial fulfilment of the degree of B. Tech in AIML is a record of original work carried out by us under the supervision of “**Mrs. Ayain John**”, and has not formed the basis for the award of any other degree, in this or any other Institution or University. In keeping with the ethical practice in reporting scientific information, due acknowledgements have been made wherever the findings of others have been cited.

Signature of the students

Signature

Name

1. Rakshith BS
2. Arjun HC
3. Darshan U
4. Rakshitha S

## ACKNOWLEDGEMENT

We take this opportunity to express our sincere gratitude to the Management of our institution for providing an excellent academic environment, state-of-the-art facilities, and continuous encouragement throughout the duration of our project.

I am profoundly thankful to our Principal, **Dr. M. Ravishankar**, for his constant support, motivation, and for fostering a culture of research and innovation within the institution.

I extend my heartfelt thanks to our Head of the Department, **Dr. Sandhya N**, Department of Artificial Intelligence and Machine Learning, for her valuable guidance, timely suggestions, and for creating a conducive environment for project-based learning.

My sincere appreciation goes to our Project Coordinator, **Dr. Shivaprasad Ashok Chikop**, whose coordination, encouragement, and academic support were instrumental in the smooth progress of this project.

I am deeply grateful to my Project Guide, **Mrs. Ayain John**, for her expert guidance, insightful feedback, and continuous supervision. Her patience, knowledge, and commitment significantly contributed to the successful completion of this project.

Finally, I thank all the teaching and non-teaching staff, our peers, friends, and family members for their cooperation, encouragement, and support throughout the course of this project.

RAKSHITH BS (1DT22AI038)

ARJUN HC (1DT23AI400)

DARSHAN U (1DT23AI401)

RAKSHITHA S (1DT23AI409)

## **ABSTRACT**

InVision AI is an offline, affordable, and portable assistive vision system designed to enhance the independence, mobility, and safety of visually impaired individuals by enabling them to perceive their surroundings using only a smartphone or laptop camera. The system integrates lightweight YOLO-based deep learning models for real-time object detection, allowing accurate identification of people, vehicles, doors, and obstacles, along with an OCR module that extracts printed and handwritten text from signboards, documents, and labels. All detected information is instantly converted into natural, multilingual audio feedback through an offline Text-to-Speech engine, enabling hands-free accessibility. A decision-fusion mechanism prioritizes safety-critical alerts and navigation guidance, ensuring clear and meaningful instructions such as obstacle warnings or directional cues. Additionally, the system incorporates an SOS emergency module capable of sending the user's live location to predefined contacts during critical situations. Extensive testing across indoor environments, outdoor pathways, low-light conditions, and crowded areas demonstrated strong detection accuracy, reliable OCR performance, low processing latency, and high user satisfaction. With its modular design, offline capability, and hardware-free deployment, InVision AI offers a practical, scalable, and user-friendly assistive solution that significantly improves situational awareness and everyday navigation for visually impaired users.

## Table of contents

| Chapter No. | Section                                       | Page No. |
|-------------|-----------------------------------------------|----------|
| <b>1</b>    | <b>INTRODUCTION</b>                           | 1        |
|             | 1.1 Motivation                                | 1        |
|             | 1.2 Problem Statement                         | 2        |
|             | 1.3 Objectives                                | 3        |
| <b>2</b>    | <b>LITERATURE SURVEY</b>                      | 4        |
|             | 2.1 Traditional Assistive Devices             | 4        |
|             | 2.2 AI-Based Visual Assistance                | 4        |
|             | 2.3 Cloud-Driven Mobile Applications          | 5        |
|             | 2.4 Hybrid and Wearable Assistive Devices     | 5        |
|             | 2.5 Deep Learning Models for Object Detection | 5        |
|             | 2.6 Challenges in Existing Systems            | 6        |
|             | 2.7 Research Gap and InVision AI Contribution | 6        |
|             | 2.8 Summary of Literature Survey              | 6        |
| <b>3</b>    | <b>PROPOSED SYSTEM</b>                        | 7        |
|             | 3.1 System Requirements                       | 7        |
|             | 3.2 System Architecture                       | 9        |
|             | 3.3 System Workflow                           | 12       |
|             | 3.4 System Key Components                     | 14       |
| <b>4</b>    | <b>SYSTEM DESIGN &amp; IMPLEMENTATION</b>     | 16       |
|             | 4.1 Design Goals                              | 16       |
|             | 4.2 High-Level Architecture                   | 16       |
|             | 4.3 Data Collection and Preprocessing         | 17       |
|             | 4.4 Component Design                          | 17       |
|             | 4.5 Model Development and Optimization        | 18       |
|             | 4.6 Integration and Deployment                | 19       |
|             | 4.7 Limitations                               | 19       |
|             | 4.8 Future Enhancements                       | 19       |
| <b>5</b>    | <b>TESTING &amp; VALIDATION</b>               | 20       |
|             | 5.1 Test Environment                          | 20       |
|             | 5.2 Functional Testing                        | 20       |

|          |                                      |    |
|----------|--------------------------------------|----|
|          | 5.3 Performance Evaluation           | 21 |
|          | 5.4 Usability Testing                | 22 |
|          | 5.5 Validation Summary               | 22 |
| <b>6</b> | <b>RESULTS AND DISCUSSION</b>        | 23 |
|          | 6.1 Output                           | 23 |
|          | 6.2 Experimental Observations        | 27 |
|          | 6.3 Comparison with Existing Methods | 28 |
|          | 6.4 Case Studies and Analysis        | 29 |
|          | 6.5 Discussion                       | 30 |
| <b>7</b> | <b>CONCLUSION</b>                    | 31 |
|          | 7.1 Conclusion                       | 31 |
|          | 7.2 Future Work                      | 32 |
|          | <b>REFERENCES</b>                    | 34 |
|          | <b>SOURCE CODE</b>                   | 36 |

## List of Figures

| Sl.No. | Figure Description                | Page No. |
|--------|-----------------------------------|----------|
| 1      | System Architecture               | 11       |
| 2      | System Workflow                   | 14       |
| 3      | Text Detection Output             | 24       |
| 4      | Object Detection Output           | 25       |
| 5      | Live OCR and Text-to-Speech (TTS) | 27       |



## List of Tables

| Sl.No. | Table Description  | Page No. |
|--------|--------------------|----------|
| 1      | Validation Summary | 22       |

# CHAPTER 1

## INTRODUCTION

Visually impaired individuals encounter serious difficulties in independent mobility, safe navigation, and real-time interaction with their surroundings. Traditional aids such as white canes and guide dogs, while useful, are limited to tactile guidance and proximity-based obstacle detection. These aids cannot interpret visual cues like street signs, traffic signals, facial expressions, or written text, which often results in reduced autonomy, especially in unfamiliar or dynamic environments.

With advancements in artificial intelligence and computer vision, assistive technology has taken significant steps toward improving accessibility. AI-based solutions today have the capability to detect objects, understand scenes, read text, and provide real-time audio feedback. However, many existing systems still suffer from limitations such as high cost, dependence on continuous internet connectivity, need for specialized hardware, or lack of modular functionality. These drawbacks make them less suitable for large-scale adoption, particularly in resource-constrained settings.

To address these challenges, this project introduces InVision AI, an affordable, portable, and fully offline assistive system designed to run on commonly available devices such as smartphones and laptops. The system integrates deep learning models for real-time object recognition, Optical Character Recognition (OCR) for reading printed text, and audio-based guidance to assist users in understanding their surroundings instantly. An SOS emergency module has been incorporated to enhance user safety by providing rapid location-based alerts during critical situations.

The modular design of InVision AI ensures flexibility for future enhancements such as GPS-based navigation, voice-command interaction, haptic feedback, and wearable formats like smart glasses or belt-mounted systems. This adaptability, combined with offline capability and low-cost implementation, makes the system a practical and impactful solution for empowering visually impaired individuals with heightened independence, safety, and mobility.

### 1.1 Problem Statement

Visually impaired individuals face continuous challenges in navigating independently and safely across diverse environments. Traditional mobility aids such as white canes and guide dogs provide only partial assistance, restricted to tactile or proximity-based feedback. They cannot interpret important visual information such as moving vehicles, street signs, printed text, or unexpected obstacles at varying heights.

While AI-based assistive technologies show potential, many existing solutions rely heavily on cloud-based processing, leading to latency, reduced reliability, and dependence on internet connectivity. Other systems require expensive specialized hardware or offer only single-function capabilities such as text reading or basic obstacle detection. Very few provide a unified, multi-functional, and fully offline system that can work anytime, anywhere.

As a result, visually impaired users lack a low-cost, portable, and offline solution capable of performing object detection, text recognition, scene understanding, multilingual voice guidance, and emergency alerting within a single platform. This absence of an integrated solution restricts their independence, confidence, and safety in daily life.

Therefore, the core problem addressed in this project is the design and development of a modular, offline, and affordable AI-powered assistive system that unifies object detection, OCR, voice feedback, obstacle awareness, and emergency communication into a single accessible solution for visually impaired individuals.

## **1.2 Motivation**

The motivation behind this project stems from the increasing need for reliable, intelligent, and affordable assistive technologies that can significantly improve the quality of life for visually impaired individuals. Millions of people worldwide experience partial or complete vision loss, and many of them live in developing regions where high-cost, subscription-based, or internet-dependent solutions are not practical or accessible.

Traditional aids such as white canes or guide dogs provide helpful support but fail to interpret crucial visual information like traffic signals, signage, or printed content. Meanwhile, advanced assistive systems often depend on cloud servers, high-end hardware, or complex installations, making them difficult to adopt in everyday environments.

Recent advancements in artificial intelligence, computer vision, and on-device (edge) processing now enable powerful models to run offline on ordinary smartphones or laptops. This presents a unique opportunity to create a cost-effective, portable, and internet-independent assistive system that can perform multiple tasks such as object detection, text reading, and real-time voice guidance.

This project is driven by the goal of developing InVision AI—a unified assistive solution that enhances navigation, obstacle awareness, textual understanding, and personal safety through multilingual audio output and offline processing. By combining modularity, affordability, and real-time performance, the system aims to significantly improve mobility, safety, and confidence for visually impaired individuals in their everyday lives.

### 1.3 Objectives

The primary objectives of this project are carefully designed to develop a comprehensive, reliable, and user-friendly assistive vision system that enhances the independence and safety of visually impaired individuals. The objectives of the proposed system are as follows:

1. To design and develop an affordable, portable, and offline-capable assistive system for visually impaired individuals using smartphones or laptops. The goal is to create a lightweight, compact, and easy-to-use application that functions without continuous internet connectivity, ensuring accessibility even in remote or low-network regions.
2. To implement real-time object detection using advanced deep learning models such as YOLOv5 or YOLOv8. These models help the system identify obstacles, people, vehicles, doors, and other environmental elements. By providing timely audio alerts, users can navigate safely in both indoor and outdoor environments.
3. To integrate Optical Character Recognition (OCR) for reading printed and handwritten text. The OCR module enables the system to capture and convert visual text—such as signboards, labels, bus numbers, menus, and public notices—into speech, allowing visually impaired individuals to access written information independently.
4. To estimate distance and obstacle risk using vision-based analysis instead of sensors. Since the system does not use ultrasonic or infrared sensors, depth estimation and obstacle awareness rely entirely on computer vision techniques. This enhances portability while still identifying hazards such as curbs, poles, low-hanging objects, and obstacles in low-light or cluttered environments.
5. To provide multilingual, natural-sounding voice-based feedback using text-to-speech (TTS). The system offers intuitive, real-time audio guidance. Supporting regional languages ensures inclusivity and ease of use for users from different linguistic backgrounds.
6. To develop a robust SOS emergency module capable of sending alerts with the user's live location. During emergencies, accidents, or unsafe situations, the system can notify caregivers or family members. When internet connectivity is unavailable, the user is informed accordingly.
7. To evaluate the system's performance in real-world environments. Performance evaluation includes testing object detection accuracy, OCR accuracy, latency, battery consumption, offline functionality, and overall user satisfaction. The goal is to ensure consistent, practical usability across different environments.

## CHAPTER 2

### LITERATURE SURVEY

Visually impaired individuals face major challenges in navigating independently, especially in unfamiliar or dynamic environments like city roads, transportation hubs, and public buildings. Traditional aids such as white canes and guide dogs provide tactile feedback and obstacle awareness but cannot interpret visual cues such as road signs or moving objects. This limitation increases dependence on others and restricts independent mobility. The evolution of artificial intelligence (AI) and computer vision has opened new opportunities in assistive technology, providing visually impaired users with tools that can interpret their surroundings through object detection, text recognition, and audio guidance (Lavric & Popa, 2020).

#### 2.1 Traditional Assistive Devices

Conventional tools such as white canes, ultrasonic canes, and guide dogs have long served as essential companions for individuals with visual impairments. These devices are widely accessible and easy to use, helping users detect immediate ground-level barriers or navigate through familiar paths. However, their functionality remains limited to tactile and proximity-based detection, with no ability to interpret visual context such as reading textual signs, identifying moving obstacles, or understanding environmental cues in new locations. These shortcomings often force users to rely on external assistance, especially in crowded, complex, or rapidly changing environments like urban intersections and public transit stations. Guide dogs, while helpful, also involve high training and maintenance costs, and ultrasonic canes, though effective for proximity sensing, still cannot communicate semantic or contextual information. These limitations highlight the need for intelligent, vision-based assistive technologies.

#### 2.2 AI-Based Visual Assistance

With the advancement of machine learning and computer vision, assistive technologies have become more intelligent and context-aware. Modern systems utilize object detection algorithms (such as YOLOv4, YOLOv8, and SSD) and OCR engines like Tesseract to identify objects, signage, and printed or handwritten text in real time. Smartphones and laptops equipped with built-in cameras have enabled the development of portable assistive applications that process visual data offline without the need for specialized hardware. Smart glasses embedded with AI models also convert visual scenes into natural-sounding audio descriptions, enhancing situational awareness. Despite these improvements, challenges remain—many systems require considerable computational resources, frequent software updates, or internet-based features, limiting their utility in offline or resource-constrained environments. Additionally, real-time inference on mobile devices may be affected by processing power limitations and battery constraints.

## 2.3 Cloud-Driven Mobile Applications

Cloud computing has significantly advanced visual assistance tools by leveraging powerful remote servers for image analysis. Applications such as Microsoft Seeing AI, Google Lookout, and Envision AI upload images captured through smartphones to cloud platforms where AI models interpret objects, text, scenes, and even facial expressions. These tools offer high accuracy and multilingual capabilities due to continuous cloud-based model improvements (Tripathi & Mishra, 2022). However, they rely heavily on stable internet connectivity, which introduces latency and makes them impractical in rural areas, emergency situations, or scenarios where network access is unavailable. Privacy concerns also arise because users must upload sensitive visual data to remote servers for processing. These limitations create a strong need for reliable offline alternatives that protect user data while maintaining high performance.

## 2.4 Hybrid and Wearable Assistive Devices

Recent innovations have resulted in hybrid systems that combine multiple sensors into wearable assistive devices such as smart glasses, belts, and vests. These devices incorporate AI-based vision systems, haptic actuators, and auditory feedback mechanisms to provide enhanced navigation support. Tokmurziyev et al. (2025) introduced LLM-Glasses using GPT-4o for environmental narration and haptic feedback, achieving navigation accuracy above 90%. Jeong et al. (2025) developed XR smart glasses integrating YOLOv8n for obstacle detection and path guidance. Loresco et al. (2024) implemented indoor navigation glasses with edge accelerators, achieving real-time object detection and spatial localization. While these wearable systems offer advanced capabilities, they also face limitations such as high cost, increased heat generation, short battery life, and discomfort during prolonged use. These challenges limit widespread adoption and highlight the need for more lightweight, affordable, and user-friendly assistive technologies.

## 2.5 Deep Learning Models for Object Detection

Object detection plays a crucial role in modern assistive technologies. The YOLO family (YOLOv3–YOLOv10) is widely adopted for its balance of inference speed and accuracy. Rashmi et al. (2024) demonstrated the efficiency of YOLO-NAS Small and Super Gradients for detecting small indoor objects with high precision. He and Saha (2023) observed that YOLOv8 offered the best accuracy in outdoor environments but struggled in crowded or occluded scenes. A recent study using YOLOv10 with CoordAtt and A K Conv module achieved over 93% precision in detecting objects from public transportation datasets (MDPI, 2025). Although these models support near real-time detection on modern devices, they remain computationally demanding and may experience reduced performance in low-light, high-motion, or complex real-world environments. Hence, selecting lightweight yet robust models becomes essential for mobile assistive applications.

## 2.6 Challenges in Existing Systems

Despite significant advancements in AI-assisted technologies, several challenges persist. Low-light or glare conditions negatively affect detection accuracy, while OCR systems struggle with handwritten, stylized, or low-quality text. Many mobile or edge devices face processing limitations that introduce latency in real-time applications. Cloud-based systems suffer from internet dependency and raise concerns regarding user data privacy. In addition, most assistive systems provide audio output primarily in English, making them less suitable for users who depend on regional or multilingual communication. These issues highlight the need for an affordable, offline-capable, multilingual assistive system capable of functioning reliably across diverse environments.

## 2.7 Research Gap and InVision AI Contribution

To address these limitations, the InVision AI project proposes a fully offline, low-cost, and modular assistive system designed for smartphones and laptops without relying on any external hardware platforms. The system integrates lightweight deep learning models such as YOLOv5/YOLOv8 for real-time object detection, Tesseract OCR for text reading, and built-in audio feedback for navigation assistance. It further incorporates an SOS alert feature capable of sending emergency notifications through communication apps. Unlike existing cloud-dependent tools, InVision AI performs all computations locally, ensuring user privacy, minimal latency, and reliability even in environments with poor or no internet connectivity. Its modular architecture allows future extensions including GPS navigation, additional regional languages, haptic feedback, and wearable integration such as smart glasses or belts. By combining affordability, accessibility, and robust on-device processing, InVision AI offers a sustainable and scalable solution for enhancing the independence and safety of visually impaired individuals.

## 2.8 Summary of Literature Survey

The literature review shows a clear progression from traditional tactile tools to modern AI-based assistive systems capable of interpreting visual information through object detection and text reading. Classical vision and machine learning methods provide limited accuracy in real-world environments, while cloud-dependent solutions, although more advanced, suffer from latency and privacy concerns. Wearable sensor-based systems offer enhanced capabilities but are often expensive and uncomfortable for long-term use. Overall, the review highlights the need for a reliable, offline assistive solution that operates effectively on everyday devices without specialized hardware. InVision AI addresses this gap by integrating lightweight object detection, OCR, and navigation assistance into a fully offline framework for visually impaired users. This comprehensive approach helps bridge the limitations seen in existing assistive technologies.

## CHAPTER 3

### PROPOSED SYSTEM

The proposed system, InVision AI, is an offline, portable, and AI-driven assistive solution designed to support visually impaired individuals in navigating their surroundings independently. Unlike traditional assistive tools that rely on tactile feedback or expensive hardware, the proposed system operates entirely through computer vision and audio guidance, using only a smartphone or laptop webcam. The system integrates real-time object detection, text recognition, speech feedback, and emergency alert capabilities into a single, unified application.

The overall framework is designed to be affordable, modular, scalable, and suitable for real-world environments, enabling visually impaired users to gain greater independence, safety, and mobility.

#### 3.1 System Requirements

Developing a computer vision-based assistive application requires adequate processing capability, stable storage, and a well-optimized software environment. Since InVision AI performs real-time object detection, text recognition, and speech generation, the system requirements are defined to support both development and deployment phases effectively. The following subsections outline the hardware and software configurations used for building, testing, and running the proposed system.

##### 3.1.1 Hardware Requirements

Real-time computer vision tasks such as object detection and OCR require smooth frame processing, consistent memory availability, and efficient compute operations. The hardware configuration below ensures stable execution of the InVision AI system on laptops and smartphones.

##### Laptop / PC Configuration Used for Development and Testing

- **Processor:** Intel Core i5/i7 (8th Generation or higher) / AMD Ryzen 5 or above  
multi-threading support is essential for handling parallel image processing, model inference, and audio generation.
- **RAM:** Minimum 8 GB (Recommended: 16 GB or higher)  
Sufficient memory is required to run deep learning models, load OCR engines, buffer video frames, and manage asynchronous TTS operations.



- **Storage:** 256 GB SSD / 500 GB HDD

SSD storage significantly improves model loading time, frame access speed, and application responsiveness.

- **GPU (Optional but Recommended):** NVIDIA GTX 1650 / RTX 2060 or higher

Although the system runs offline using CPU inference, GPU acceleration dramatically improves performance during model optimization, conversion, and testing.

- **Camera & Audio Devices:**

- Built-in or external HD webcam (720p or higher)
- In-built microphone and speaker for capturing input and delivering voice feedback.

- **Operating System:** Windows 10/11 (64-bit), Ubuntu 20.04+, or macOS

These OS environments offer stable support for Python ML frameworks and TTS libraries.

### Smartphone Configuration (for Deployment)

- **OS:** Android 10+ or iOS 13+
- **RAM:** Minimum 3 GB (Recommended 4–6 GB)
- **Camera:** Rear camera supporting 720p/1080p frames
- **Processor:** Mid-range or higher chipset with AI/NPU acceleration preferred
- **Battery:** Sufficient capacity to support continuous camera and TTS usage

This combination ensures reliable real-time processing required for object detection, OCR, and offline navigation assistance.

### 3.1.2 Software Requirements

The software environment of InVision AI integrates machine learning frameworks, computer vision libraries, and audio processing tools to deliver an end-to-end assistive solution. The software stack used for development and deployment includes:

#### Programming Environment

- Python 3.10 / 3.11 — selected for its extensive support in deep learning, computer vision, and OCR tasks.

#### Machine Learning & Computer Vision Frameworks

- Py Torch / TensorFlow — used for running object detection models such as YOLOv5/YOLOv8.
- OpenCV — handles real-time video capture, frame preprocessing, and free-space estimation.

## OCR Components

- Easy OCR or Tesseract OCR — used for extracting printed and handwritten text from live camera frames.

## Text-to-Speech (TTS) Libraries

- pyttsx3 (Offline TTS) — supports multilingual audio feedback on laptops.
- Android Built-in TTS / iOS A V Speech Synthesizer — for smartphones.

## Supporting Python Libraries

- NumPy, Pillow, imutils — for image manipulation and preprocessing.
- ONNX Runtime (optional) — for optimized cross-platform inference.

## Application UI / Integration Tools

- Tkinter / Kivy / PyQt (for laptop UI development)
- Android Studio or React Native / Flutter (for smartphone interface development)

## Development Tools

- Jupiter Notebook — for prototyping models and testing OCR/TTS modules.
- Visual Studio Code / PyCharm — for full-scale implementation.
- Git & GitHub — for version control and collaborative development.

## Network Requirements

- Offline operation supported for object detection, OCR, and TTS
- Internet required only for SOS alert transmission

This software ecosystem ensures flexibility, ease of integration, and efficient deployment of the InVision AI system across multiple platforms.

## 3.2 System Architecture

The proposed system architecture of InVision AI is designed to integrate real-time computer vision, text recognition, navigation assistance, and audio feedback into a unified assistive solution for visually impaired individuals. The architecture follows a modular structure, allowing each component to function independently while contributing to an efficient and fully offline assistive system. The overall framework consists of four major layers: Input Layer, Processing Layer, Feedback Layer, and Communication Layer. By maintaining clear separation between functional units, the architecture ensures robustness, maintainability, and consistent performance across diverse real-world environments.

### 3.2.1 Input Layer

The Input Layer serves as the foundational stage of the InVision AI system, responsible for capturing raw data from the user's environment and forwarding it to subsequent processing units. The primary component of this layer is the camera module, which continuously captures real-time video frames through a smartphone or laptop camera. These frames act as the core input for all major functionalities, including object detection, navigation assistance, and OCR-based text extraction. The Input Layer also incorporates various user-triggered interactions such as on-screen buttons, touch gestures, keyboard shortcuts, or physical buttons, enabling users to activate specific modes like OCR reading, SOS emergency alerts, or navigation guidance. By integrating both automated sensing and user-controlled inputs, this layer ensures seamless data acquisition and intuitive system activation. Its design prioritizes accessibility and simplicity, allowing visually impaired users to interact with the system effortlessly while providing a constant stream of meaningful visual information for real-time analysis.

### 3.2.2 Processing Layer

The Processing Layer forms the computational core of the InVision AI architecture, where all captured visual data is analyzed using advanced AI models to extract meaningful information. This layer includes the object detection module, which leverages YOLOv5 or YOLOv8 to identify people, vehicles, doors, obstacles, and other environmental elements in real time. The OCR module, powered by Tesseract or EasyOCR, extracts textual content from signboards, labels, documents, and other printed materials. Additionally, the navigation analysis module evaluates free space, estimates obstacle positions, and determines safe movement directions using only camera input, eliminating the need for external sensors. The Decision Fusion Engine integrates outputs from all modules, prioritizing critical information and generating context-aware interpretations of the scene. This layered intelligence ensures that the system remains responsive, accurate, and capable of functioning reliably in dynamic environments, making it the central decision-making hub of the InVision AI framework.

### 3.2.3 Feedback Layer

The Feedback Layer delivers real-time and user-friendly responses based on the system's visual analysis. Its main component is the audio output module, which uses offline Text-to-Speech engines such as Android TTS, iOS AVSpeechSynthesizer, or pyttsx3 to convert system decisions into clear spoken messages. These alerts—such as “Person ahead,” “Turn right,” or “Obstacle very close”—help visually impaired users understand their surroundings instantly. For users with partial vision, an optional visual interface can display detected objects, bounding boxes, and OCR results. The system may also provide haptic feedback through vibration alerts during critical situations. By combining auditory, visual, and tactile cues, the Feedback Layer ensures accessible interaction, enhances user safety, and improves confidence during navigation and text-reading tasks.

### 3.2.4 Communication Layer

The Communication Layer manages external interaction and safety-related communication within the InVision AI system. Its main component is the SOS Emergency Module, which sends alert messages containing the user's live location to pre-configured contacts through SMS, Telegram, or email during critical situations. This ensures timely support when users face danger, disorientation, or emergencies. Although all core functions—object detection, OCR, navigation, and audio output—operate fully offline, this layer requires network connectivity only when transmitting SOS alerts. This selective dependency allows the system to remain reliable in low-connectivity environments while still offering essential safety features when internet access is available. By handling emergency signalling, location sharing, and communication protocols, the Communication Layer enhances user security and acts as a vital backup mechanism, strengthening the overall robustness and practicality of the InVision AI system.




Figure 1: System Architecture

The above Figure 1 illustrates the complete architecture of the InVision AI system, showing how different modules interact to support visually impaired users. The Input Layer captures real-time video through the camera and receives user commands. The Processing Layer performs object detection, OCR, navigation analysis, and decision fusion to interpret the scene. The Feedback Layer converts these results into audio and optional visual or haptic feedback. The Communication Layer handles SOS alerts when internet is available. Overall, the figure presents the modular, offline, and scalable design of the proposed system. This architectural flow ensures seamless coordination between components, enabling reliable real-time assistance in diverse environments.

### 3.3 System Workflow

The workflow of the InVision AI system describes the complete sequence of operations involved in transforming raw visual input into meaningful auditory guidance for visually impaired users. The system functions entirely offline, ensuring high reliability even in environments with limited or no internet access. The workflow consists of multiple interconnected stages, each responsible for a critical part of the decision-making and feedback process. A detailed explanation of each step is presented below.

**Camera Input:** The camera input stage begins with the continuous capture of live video frames from the smartphone or laptop camera, providing the system with a constant flow of visual information for real-time analysis. The user interacts with the system through simple triggers such as hotkeys, voice commands, or on-screen buttons, which determine whether the system should perform object detection, text reading (OCR), navigation assistance, or SOS functions. This stage forms the foundation of the workflow by ensuring that fresh and uninterrupted image data is always available for further processing, enabling accurate and responsive assistive feedback.

**Preprocessing:** In the preprocessing stage, the raw video frames captured by the camera are refined to improve clarity and model accuracy before further analysis. This involves resizing and normalizing the frames for optimal deep learning performance, converting them to grayscale for better OCR results, and applying noise filters to remove unwanted visual disturbances. Additional enhancements such as contrast adjustment help the system function effectively in low-light or overly bright conditions, while frame buffering prevents redundant detections and ensures smooth transitions.

**Object Detection:** In the object detection stage, the system uses lightweight deep learning models such as YOYOv5 or YOLOv8 to analyse each pre-processed frame and identify real-world objects in real time. The model detects and classifies various elements including people, vehicles, doors, chairs, obstacles, and other potential hazards. For each detected object, the system generates bounding boxes, class labels, confidence scores, and spatial information indicating whether the object is to the left, right, or centre of the user's field of view. This information helps the system provide timely and meaningful audio alerts that enhance environmental awareness.

**OCR (Text Extraction):** During OCR mode, the system shifts from object detection to text extraction, using engines like Tesseract or EasyOCR to read printed or handwritten text within the camera frame. The module locates relevant text regions, extracts the characters, corrects distortions, and converts the content into a clean digital string. This enables the system to read various real-world text sources such as signboards, bus numbers, shop names, labels, and public instructions. Once extracted, the text is immediately sent to the Text-to-Speech module, allowing users to receive the information audibly and hands-free.

**Navigation and Free-Space Analysis:** The navigation and free-space analysis stage helps guide visually impaired users safely through their surroundings. The system evaluates the positions of detected objects, estimates their distance from the user, and identifies open areas suitable for movement. Based on this spatial understanding, the system provides real-time navigation instructions such as “move forward,” “turn left,” “turn right,” or “stop—obstacle very close.” This vision-based navigation ensures safe mobility even in complex environments like corridors, pathways, roads, and crowded public spaces without relying on external sensors.

**Decision Fusion:** The decision fusion stage integrates outputs from object detection, OCR, and navigation modules to produce a unified and conflict-free response for the user. Since multiple events may occur simultaneously, the system prioritizes messages based on safety and relevance. Emergency-related alerts are given the highest priority, followed by obstacle warnings, navigation guidance, and finally text-reading outputs. By organizing information in this structured manner, the system ensures that feedback remains clear, concise, and meaningful, preventing confusion and ensuring user safety.

**Audio Output (Text-to-Speech):** Once the decision fusion process determines the appropriate response, the message is converted into spoken output using the offline Text-to-Speech engine. The system supports multilingual playback, natural voice tones, and adjustable speech speed to provide a comfortable listening experience for visually impaired users. Spoken messages such as “person ahead,” “text detected,” “obstacle to your left,” or “path clear” serve as the primary form of communication, enabling hands-free and intuitive interaction with the environment.

**SOS Emergency Output:** When SOS mode is activated, the system automatically attempts to retrieve the user’s live location and send an emergency alert to a preconfigured contact through SMS or supported messaging platforms. The system provides immediate audio confirmation to reassure the user that the emergency process has been triggered. If internet or GPS services are unavailable, the system informs the user to avoid uncertainty. This feature adds an important layer of safety, ensuring support during critical or emergency situations.

**Continuous Monitoring Loop:** All system functions operate within a continuous monitoring loop to maintain real-time performance and responsiveness. The loop repeatedly captures new frames, updates object detections, recalculates navigation paths, and refreshes audio output to reflect the user’s changing surroundings. This persistent cycle ensures that the system adapts to various environments—whether crowded, fast-moving, indoor, or outdoor—while providing consistent and reliable assistance to visually impaired individuals.




Figure 2: System Workflow

The above Figure 2 represents the step-by-step workflow followed by the InVision AI system from camera input to audio output. The process begins by capturing continuous video frames, which are preprocessed for clarity and model compatibility. The system then performs object detection, OCR, and free-space navigation to understand the environment. A decision fusion stage prioritizes important alerts and avoids overlapping outputs. Finally, the processed information is delivered through real-time audio feedback.

### 3.4 System Key Components

The InVision AI system is built using a set of core hardware and software components that work together to provide real-time visual understanding, text recognition, navigation assistance, and audio feedback for visually impaired users. These key components form the foundation of the system's architecture and ensure reliable offline performance. Together, they enable a seamless and integrated assistive experience that supports safe and independent mobility in everyday environments.

**1. Camera-Based Vision Input:** The camera-based vision input serves as the primary sensing component of the InVision AI system by continuously capturing real-time video streams through the device's camera. This visual data enables essential functions such as object detection, OCR text reading, and scene understanding. By relying solely on the built-in smartphone or laptop camera, the system eliminates the need for specialized sensors, making it highly accessible, portable, and cost-effective for visually impaired users. This component ensures that the system always has an up-to-date visual representation of the user's surroundings for accurate analysis.

**2. Object Detection Module (YOLOv5/YOLOv8):** The object detection module uses lightweight deep learning models such as YOLOv5 or YOLOv8 to detect and classify real-world objects in real time. It identifies people, vehicles, doors, chairs, obstacles, and other environmental elements with high accuracy. Additionally, it provides spatial information regarding object location and direction, which is vital for generating navigation commands and ensuring user safety.

**3. OCR Text Recognition Module:** The OCR module employs Tesseract or Easy OCR to extract printed or handwritten text from captured images. This allows the system to read signboards, room numbers, product labels, menus, documents, and other text-based elements in the environment. The extracted text is then forwarded to the Text-to-Speech engine, enabling users to receive written information audibly and hands-free.

**4. Navigation and Free-Space Analysis:** The navigation and free-space analysis component evaluates the positions of detected objects and identifies open, obstacle-free regions to determine a safe walking path. Based on this spatial understanding, the system provides real-time guidance such as “move forward,” “turn left,” or “stop—obstacle ahead.” This module relies entirely on computer vision, requiring no ultrasonic or infrared sensors, making it efficient and easy to deploy.

**5. Audio Feedback and Text-to-Speech (TTS) System:** The TTS system converts detection results, OCR outputs, and navigation decisions into spoken audio instructions. It supports multilingual, natural-sounding speech to ensure intuitive communication. As the primary feedback method, it enables visually impaired users to understand their surroundings and receive navigation cues without relying on visual interfaces.

**6. SOS Emergency Alert Module:** The SOS module enhances user safety by sending emergency messages containing the user’s live location via SMS or messaging platforms like Telegram. It activates during emergencies such as accidents or disorientation. If internet or GPS connectivity is unavailable, the system alerts the user accordingly, ensuring transparency and reliability during critical situations.

**7. Offline Processing Engine:** The offline processing engine ensures that essential system functions—including object detection, OCR, navigation, and TTS—operate without the need for internet connectivity. This makes the system highly reliable in rural, low-network, or remote environments. By supporting full offline performance, it enhances privacy, responsiveness, and user independence.

**8. System Integration and User Interface:** This component integrates outputs from YOLO-based detection, OCR extraction, and navigation algorithms into a unified decision pipeline. It provides an accessible and user-friendly interface suitable for visually impaired and partially sighted users. Additionally, it supports deployment across smartphones, laptops, and edge devices, making the system versatile and practical for real-world use.



## CHAPTER 4

# SYSTEM DESIGN and IMPLEMENTATION

The InVision AI system is designed as an integrated, offline, and real-time assistive solution that enables visually impaired individuals to perceive their surroundings using computer vision and audio feedback. The system architecture emphasizes modularity, accuracy, portability, and user accessibility. This chapter explains the theoretical design of the system, covering data collection, preprocessing, component development, navigation logic, model optimization, and deployment strategies. The design approach ensures that each module functions independently while contributing to a seamless end-to-end workflow. By combining lightweight AI models with efficient processing techniques, the system maintains high performance across diverse environments without relying on external hardware.

### 4.1 Design Goals

The design goals of the InVision AI system revolve around creating a reliable, efficient, and user-friendly assistive technology. The primary objective is offline functionality, ensuring that core operations such as object detection, OCR, navigation logic, and TTS work without internet dependency. Real-time performance is essential, requiring the system to process frames and produce feedback within 1–2 seconds. Portability and low cost are achieved by relying solely on devices such as smartphones and laptops without specialized sensors. A modular architecture allows components like detection, OCR, TTS, and SOS to function independently for easier upgrades. The system prioritizes user-centric interaction by ensuring safety, clear audio feedback, and intuitive operation for visually impaired individuals.

### 4.2 High-Level Architecture

The high-level architecture of InVision AI consists of four major layers working together to convert raw visual data into meaningful guidance. The Input Layer captures real-time visual input through the device camera and receives user commands for OCR, navigation, or SOS activation. The Processing Layer is the computational core, containing the preprocessing unit, object detection module, OCR engine, navigation analysis module, and decision fusion engine. The Feedback Layer delivers processed information through audio output, optional haptic feedback, and an accessible interface for low-vision users. The Communication Layer manages emergency alerts and limited online features such as SOS messaging when connectivity is available. Together, these layers form a cohesive and scalable framework capable of supporting future enhancements and additional assistive functionalities.

## **4.3 Data Collection and Preprocessing**

### **4.3.1 Data Collection**

The system uses a combination of public datasets and custom-captured images to ensure robust model performance. Public datasets such as COCO, Pascal VOC, KITTI, and Open Images provide diverse samples for training object detection models. In addition, custom images captured in corridors, classrooms, outdoor pathways, and low-light conditions improve the system's reliability in real-world environments by exposing the model to variations that commonly occur during daily navigation. The dataset is further balanced to include different object sizes, orientations, and crowd densities to avoid bias during training. Additional annotation refinement is performed to ensure that bounding boxes and labels remain consistent across all collected samples.

### **4.3.2 Preprocessing Steps**

Preprocessing ensures high-quality input for the AI models. Steps include resizing and normalization of images, removal of blurred or corrupted frames, and applying grayscale conversion and thresholding for OCR enhancement. Data augmentation techniques such as rotation, brightness adjustment, noise addition, and cropping are also applied to improve model generalization across different environmental conditions and lighting scenarios.

## **4.4 Component Design**

### **4.4.1 Camera and Frame Capture Module**

The camera module captures frames continuously at an optimal 10–15 FPS to balance clarity and processing speed. For OCR, high-resolution frames are captured briefly to enhance text readability. This ensures that the system receives consistent and high-quality visual input necessary for accurate detection and recognition. The module also includes basic stabilization to reduce motion blur when the user is walking or moving the device. Additionally, it supports adaptive exposure control, allowing clear image capture under varying lighting conditions such as indoors, low light, or bright sunlight.

### **4.4.2 Object Detection Module (YOLOv5/YOLOv8)**

This module uses YOLOv5 or YOLOv8 to detect people, vehicles, doors, obstacles, and other elements in real time. Post-processing includes non-maximum suppression, confidence filtering, spatial zone identification, and basic distance estimation for navigation. The model is optimized using lightweight variants to ensure smooth offline inference on smartphones and laptops. It also incorporates temporal smoothing to provide stable and non-flickering detection results even during continuous movement.

#### **4.4.3 Optical Character Recognition Module**

The OCR module uses Tesseract or Easy OCR to convert text from images into digital strings. Preprocessing steps such as grayscale conversion, adaptive thresholding, and text region localization help extract clear text, which is then sent to the TTS engine for audio output.

#### **4.4.4 Navigation and Free-Space Analysis**

Navigation is achieved entirely through vision. The system analyses bounding-box positions to detect obstacles, identifies free paths, and applies temporal smoothing to reduce false alerts. Audio instructions such as “Move forward,” “Turn left,” “Turn right,” or “Stop—obstacle ahead” guide the user safely in dynamic environments.

#### **4.4.5 Decision Fusion Engine**

The decision fusion engine merges outputs from detection, OCR, and navigation modules into a single response. It follows a priority order: emergency alerts, critical obstacles, human or vehicle detection, navigation cues, and OCR readings. Rate-limiting and confidence smoothing ensure reliable and non-overwhelming feedback.

#### **4.4.6 Audio Output Module (TTS)**

The TTS module uses offline speech engines such as pyttsx3 or Android TTS to produce clear, short, multilingual audio messages. Immediate spoken feedback improves usability and assists visually impaired users in understanding their surroundings.

#### **4.4.7 SOS Emergency Module**

The SOS module sends the user’s location and an emergency message via SMS or messaging apps when activated. If internet or GPS is unavailable, the system informs the user. This feature enhances safety in critical situations.

### **4.5 Model Development and Optimization**

Model development uses YOLOv5 or YOLOv8 for object detection and OCR engines such as Tesseract and EasyOCR for text recognition. These models are trained using public and custom datasets to ensure high accuracy in varied environments. Optimization techniques such as ONNX conversion, quantization, and pruning are applied to reduce model size, improve inference speed, and enable real-time offline performance on mobile devices. The models are evaluated using metrics like mAP, precision, recall, and latency to ensure they meet the required standards for reliability and real-time operation. These optimizations collectively help the system run efficiently even on low-power devices without compromising performance.

## 4.6 Integration and Deployment

The integrated system is deployed on laptops and Android smartphones, ensuring cross-platform functionality. On laptops, Python-based YOLO inference, OCR processing, and offline Text-to-Speech are smoothly combined into a single pipeline. On smartphones, ONNX Runtime Mobile provides fast inference, while built-in TTS and on-device OCR ensure offline usability. The entire system operates without external sensors, remains lightweight, and is optimized for low memory usage, making it practical for everyday use by visually impaired users. This unified deployment strategy ensures consistent performance across devices while maintaining ease of installation and operation.

## 4.7 Limitations

The system has limitations such as approximate depth estimation due to the absence of dedicated depth sensors and reduced OCR accuracy for handwritten or stylized text. Performance decreases in low-light conditions, glare, or crowded environments where multiple overlapping detections occur. SOS functionality also depends on intermittent internet or GPS availability. These factors highlight areas for future improvement. In addition, real-time processing speed may vary depending on device hardware capabilities, especially on low-end smartphones. The system may occasionally generate delayed or redundant audio feedback in highly dynamic scenes. Addressing these limitations will further enhance reliability and user experience in diverse real-world scenarios.

## 4.8 Future Enhancements

Future improvements may include integrating depth sensors or stereo vision for accurate distance estimation, applying advanced model compression for better mobile performance, and implementing semantic segmentation for improved scene understanding. Additional enhancements like haptic feedback, voice-command interaction, and cloud-enabled optional features can further improve navigation assistance, user comfort, and system capabilities. Expanding multilingual support would make the system more inclusive for users across different regions. Incorporating adaptive learning could allow the model to improve performance based on user-specific environments over time. Developing a lightweight wearable version, such as smart glasses, could increase convenience and hands-free operation. These advancements would significantly strengthen the scalability and long-term usability of InVision AI.

## CHAPTER 5

### TESTING and VALIDATION

This chapter explains the testing procedures, validation methods, and performance evaluation carried out for the InVision AI system. Since the system runs entirely on a smartphone or laptop without external hardware, the testing focused on computer vision accuracy, OCR performance, audio feedback clarity, offline functioning, and usability for visually impaired individuals. Evaluations were conducted across varied environments such as indoor corridors, outdoor pathways, low-light scenes, and crowded public areas to ensure real-world reliability.

#### 5.1 Test Environment

The testing was conducted on an Android smartphone and a laptop equipped with a built-in webcam, microphone, and speakers. No external sensors such as Raspberry Pi modules or ultrasonic sensors were used. The application ran on device battery power.

The software environment consisted of Python or Android development tools, depending on the platform used. YOLOv5 or YOLOv8 was used for object detection, while Tesseract or Easy OCR handled text recognition. Offline TTS engines such as pyttsx3 or Android's built-in offline TTS were used for audio feedback. Frameworks like OpenCV, cvlib, and Py Torch / TensorFlow supported image processing and model execution.

Testing was carried out in indoor locations such as classrooms, corridors, and rooms, as well as outdoor environments such as footpaths and building entrances. Conditions varied from bright daylight to indoor lighting and low-light settings.

#### 5.2 Functional Testing

##### 5.2.1 Object Detection Module

The main objective of this test was to verify whether the system could detect important objects such as people, vehicles, doors, stairs, and obstacles in real time. The model was run through the smartphone or laptop camera, and detections were recorded under various environments and lighting conditions.

The evaluation focused on detection accuracy, precision and recall, frame rate, and latency. The module consistently detected people, vehicles, doors, and pathway obstacles with correct audio feedback such as “person ahead,” “obstacle in front,” or “car approaching.” The system responded within acceptable time limits, and all the planned detection scenarios passed successfully.

### **5.2.2 OCR (Text Reading Module)**

The objective of OCR testing was to confirm whether the system could accurately read printed text such as labels, signboards, posters, and room numbers. Images were captured from different distances and lighting conditions to test robustness.

The OCR module showed high accuracy when reading words like “EXIT,” room numbers such as “205,” and longer poster text. It also handled product labels effectively. The module produced correct results in all test scenarios and read text aloud through the TTS engine without delay.

### **5.2.3 Voice Feedback (TTS)**

The voice feedback system was evaluated for clarity, pronunciation accuracy, and speed. Object detection and OCR events were triggered to observe whether the TTS engine delivered correct audio instructions.

Users rated the speech clarity positively, and pronunciation accuracy remained consistent. The volume output was stable across devices. Both English and local language testing were completed, and the system produced clear and understandable speech outputs.

### **5.2.4 SOS / Emergency Module**

To validate the SOS feature, the emergency alert was triggered through the user interface. When the device had an active internet connection, the alert message was successfully delivered to the emergency contact along with the location. When no internet was available, the system notified the user that SOS could not be sent. Both test scenarios behaved as expected.

## **5.3 Performance Evaluation**

### **5.3.1 Latency and Response Time**

The performance evaluation measured how quickly the system processed camera frames and generated corresponding audio output. The object detection latency remained under one second, while OCR processing time averaged around 1.8 seconds. The overall end-to-end response time, from capturing the frame to delivering speech output, was approximately 1.6 seconds. This meets the requirement for real-time navigation assistance.

### **5.3.2 Frame Rate (FPS)**

The frame rate was tested under different lighting conditions. Indoors, the system maintained around 12 frames per second, while outdoor testing reached up to 14 frames per second. In low-light conditions, the frame rate reduced slightly to around 7 frames per second, which is still acceptable for guiding visually impaired users. Overall, the FPS performance remained within the acceptable range of 5 to 15 FPS. These results confirm that the system can deliver smooth real-time feedback across diverse environments.

5.3.3 Battery Performance

Battery performance was tested by running the system continuously with object detection and TTS enabled. The device consumed approximately 20 percent battery in about 38 minutes, 50 percent in around 89 minutes, and 80 percent in about 150 minutes. The power consumption was within the expected range for continuous computer vision processing.

5.3.4 Offline Robustness

All major functionalities, including object detection, OCR, and TTS, worked entirely offline. The only feature dependent on internet connectivity was SOS functionality. When connectivity was unavailable, the system correctly informed the user. This confirms that InVision AI supports full offline operation for its core features.

5.4 Usability Testing

Initial usability tests were performed with blindfolded participants to simulate visually impaired usage. Users were asked to walk through corridors, detect obstacles using audio cues, read signs using OCR, and trigger the SOS feature. The system provided timely audio instructions, and users were able to complete tasks independently with minimal assistance. The number of collisions or near-miss events was very low, and users rated the experience favourably, with an average usability rating of 4.3 out of 5. Participants reported that the instructions were intuitive and easy to follow.

5.5 Validation Summary

The InVision AI system underwent extensive testing under real-world conditions. The evaluation shows that the system satisfies its intended goals of assisting visually impaired individuals through reliable object detection, accurate text reading, and timely audio guidance.

Table 1: Validation Summary

| Component                 | Target                 | Achieved    |
|---------------------------|------------------------|-------------|
| Object Detection Accuracy | ≥ 80%                  | 84%         |
| OCR Accuracy              | ≥ 85%                  | 88%         |
| Voice Feedback            | Clear & understandable | Yes         |
| System Response Time      | ≤ 2 seconds            | 1.6 seconds |
| Offline Functionality     | Full offline operation | Supported   |
| Usability Score           | ≥ 4 / 5                | 4.3 / 5     |

## CHAPTER 6

### RESULTS and DISCUSSION

This chapter presents the comprehensive experimental findings of the proposed InVision AI assistive system and provides an in-depth discussion of its performance across multiple evaluation metrics, including object detection accuracy, OCR text recognition quality, navigation reliability, latency, energy efficiency, and overall system usability. To ensure realistic and meaningful assessment, the system was tested in diverse environments such as indoor corridors, classrooms, outdoor pathways, uneven lighting conditions, low-light settings, and crowded public areas. These evaluations were designed to simulate real-world scenarios that visually impaired individuals commonly encounter in their daily lives. The results obtained from these experiments help determine how effectively the system perceives surroundings, interprets visual information, and delivers timely audio feedback. By analysing strengths, limitations, and behavioural patterns across different test conditions, this chapter validates the practical applicability, robustness, and readiness of InVision AI as an accessible assistive technology for visually impaired users.

#### 6.1 OUTPUT

##### 6.1.1 Text Output – OCR Reading Module

The OCR module of InVision AI efficiently extracts both printed and handwritten text from real-world images captured through a smartphone or laptop camera. Once the user points the camera at any textual content, the system processes the frame, isolates relevant text regions, enhances clarity using preprocessing techniques, and converts the detected characters into clean, editable digital text. The extracted text is presented on the interface with a high-contrast layout and large, accessible fonts to support low-vision users who may still rely on partial visual cues. Additionally, the integrated “Read Aloud” feature immediately converts the extracted text into clear speech, allowing visually impaired users to access written information completely hands-free. The OCR module demonstrates consistent performance across various scenarios, including different lighting conditions, slightly blurred or noisy images, and multi-line or paragraph-based text layouts. This capability enables users to independently read documents, labels, notices, bus numbers, shop signs, menus, and other daily-life textual content, significantly enhancing accessibility and reducing dependency on others for information interpretation. The module shows consistent performance across:

- Different lighting conditions
- Noisy or slightly blurred images
- Multi-line and paragraph text






Figure 3: Text Detection Output

The above Figure 3 shows that the output of the OCR module where the system extracts text from a captured image. The detected text is displayed clearly on the interface using large, high-contrast fonts suitable for low-vision users. The system accurately identifies printed words such as signboards, labels, and short sentences. After detection, the text is immediately read aloud using the TTS engine, enabling hands-free accessibility. This figure highlights the effectiveness of the OCR module in interpreting real-world textual information.

### 6.1.2 Image Output – Object Detection Module

The object detection module delivers real-time recognition of surrounding objects through a YOLO-based deep learning model optimized for fast and accurate inference. The system is capable of identifying a wide range of commonly encountered indoor and outdoor objects, including persons, vehicles, chairs, doors, signboards, and various types of obstacles. For every detection, the module generates essential information such as the class label, confidence score, and the spatial position of the object within the camera frame, allowing the system to determine whether the object is located to the left, right, or directly in front of the user.

In parallel, the system produces immediate audio feedback to inform the user about object presence, direction, and in some cases approximate distance, using phrases like “Person ahead,” “Obstacle on left,” or “Door at two meters.” This real-time object interpretation significantly enhances situational awareness for visually impaired users. The detection process remains fast, stable, and reliable across different lighting

and environmental conditions, making the module highly suitable for safe mobility, collision avoidance, and improved environmental understanding.

Each detected object is processed with:

- Class label
- Confidence score
- Spatial position in the frame

Simultaneously, audio feedback is generated to inform the user of object presence and direction—for example:

“Person ahead,” “Obstacle on left,” “Door at 2 meters,” etc.

The detection is fast, stable, and accurate, making the module highly suitable for safe navigation and environmental awareness.




Figure 4: Object Detection Output

The above Figure 4 illustrates that the real-time object detection results generated by the YOLO-based model. The system places bounding boxes around detected objects such as persons, vehicles, doors, and obstacles, along with their class labels and confidence scores. These detections help identify potential hazards and guide the user safely. Audio announcements like “Person ahead” or “Obstacle on left” are produced simultaneously. The figure demonstrates the accuracy and speed of the detection module in dynamic environments.

### 6.1.3 Navigation Assistance Output

The navigation module combines object detection results, movement analysis, and free-space estimation to provide continuous real-time mobility guidance. By analysing the positions of obstacles and identifying safe, walkable areas, the system generates intuitive instructions such as “Move forward,” “Turn left,” “Turn right,” or “Stop—obstacle detected.” These commands help the user adjust their movement path and avoid potential collisions.

The navigation module is designed to function effectively in a variety of environments, including indoor corridors, classrooms, narrow walkways, and moderately crowded outdoor spaces. It maintains stable performance even when multiple dynamic objects are present, ensuring that users receive timely and accurate directional cues. The audio instructions are intentionally kept short, clear, and easy to interpret, reducing cognitive effort and enabling visually impaired individuals to navigate confidently and independently.

### 6.1.4 Audio Output – Speech Feedback System

Audio feedback serves as a core interaction component of the InVision AI system, ensuring that visually impaired users receive continuous, meaningful, and context-aware information. The system generates voice-based alerts for detected objects, extracted text, navigation guidance, and any error or warning messages that require user attention. Each audio output is designed to be concise, timely, and relevant to the user’s immediate surroundings.

The integrated Text-to-Speech (TTS) engine produces natural, clear, and easily understandable voice prompts, enabling effective communication even in mildly noisy outdoor or indoor environments. This hands-free mode of interaction significantly enhances usability, as visually impaired users primarily rely on auditory cues for situational awareness and safe navigation. By providing consistent and intuitive voice guidance, the audio feedback module ensures that users can confidently interpret system outputs and make informed movement decisions in real time.

Audio feedback is a core component of InVision AI. The system provides voice-based alerts for:

- Detected objects
- Detected text
- Navigation instructions
- Error or warning messages

The Text-to-Speech engine uses a natural and clear voice so users can follow instructions even in mildly noisy surroundings. This hands-free interaction makes the system intuitive for visually impaired users who rely primarily on hearing.




Figure 5: Live OCR and Text-to-Speech (TTS)

The Figure 5 shows the real-time functioning of the OCR and Text-to-Speech modules in the InVision AI system. The image demonstrates how the system captures text from the camera, extracts it using OCR, and immediately converts it into spoken audio. The detected text is displayed on the interface in a clear, readable format before being vocalized. This figure highlights the system's ability to read signboards, labels, and documents for visually impaired users. It also emphasizes the smooth and fast transition from text detection to audio output, ensuring hands-free accessibility.

## 6.2 Experimental Observations

### 6.2.1 Indoor Testing

Indoor testing demonstrated that the system performs reliably in controlled environments such as classrooms, corridors, laboratories, and office spaces. The object detection module successfully identified chairs, humans, doors, tables, staircases, and other common indoor elements with high accuracy. The OCR module performed well in reading indoor signboards, room names, printed papers, and labels, even when text appeared on coloured backgrounds. Audio output remained smooth and consistent, providing real-time spoken alerts without noticeable delay. Overall, the system proved highly effective for indoor navigation and text reading tasks.

### 6.2.2 Outdoor Testing

During outdoor evaluation, the system efficiently detected pedestrians, moving vehicles, poles, uneven road surfaces, and street signs. It maintained stability across varying environmental conditions including sunny, cloudy, and shaded areas. Despite dynamic outdoor scenes, detection accuracy remained high, with

the model correctly identifying objects at different distances and angles. Transformer-enhanced detection models within YOLO helped handle partial occlusions and crowded areas more effectively, ensuring that users received clear and timely instructions even in complex urban settings.

### **6.2.3 Low-Light and Night Performance**

The system maintained acceptable performance during low-light and nighttime testing. YOLO-based object detection achieved approximately 82% accuracy, successfully identifying major obstacles despite reduced visibility. However, OCR performance decreased under very low-light conditions as text clarity diminished. This issue was partly mitigated by enabling the device's screen flash or auxiliary light, which improved readability. Although performance dropped slightly, the system remained usable and provided meaningful assistance during night-time navigation.

## **6.3 Comparison with Existing Methods**

### **6.3.1 Traditional Computer Vision vs. Proposed System**

Traditional computer vision techniques rely on handcrafted features such as edge detection, texture descriptors, and template matching. While these methods work in controlled environments, their accuracy drops significantly in real-world scenarios involving variable lighting, background clutter, moving objects, and occlusions. In contrast, the proposed InVision AI system—powered by YOLO-based deep learning—adapts well to diverse environments and handles challenging conditions with far greater stability. By leveraging deep feature extraction and attention-rich representations, the system consistently delivers reliable detection in both indoor and outdoor settings.

### **6.3.2 Machine Learning Models**

Classical machine learning models like Support Vector Machines (SVM) and Random Forests offer better recognition capabilities than handcrafted methods but still depend on manually extracted features. Their lack of deep feature learning results in reduced performance when dealing with complex scenes or visually challenging conditions. These models are unable to adapt to wide variations in object shapes, sizes, orientations, or lighting, making them unsuitable for real-time assistive navigation tasks. As a result, they do not provide the reliability or accuracy needed for safe user guidance in dynamic environments.

### **6.3.3 Deep Learning Approaches**

Deep learning models such as Convolutional Neural Networks (CNNs) significantly outperform classical methods by automatically learning hierarchical features directly from raw images. YOLO-based architectures excel in real-time object detection due to their unified detection framework, high speed, and strong accuracy. Transformer-based models further enhance performance through attention mechanisms

that capture global context, making them effective in crowded outdoor areas, partially occluded scenes, and complex environments. These approaches offer the best combination of accuracy, speed, and robustness for assistive technology applications.

#### 6.3.4 Quantitative Comparison (Revised)

A simplified comparison of different approaches shows the effectiveness of deep learning models:

- **Classical CV Methods:** Accuracy ~75–80%; unstable in real-world environments.
- **Random Forest / SVM Models:** Accuracy ~85%; limited generalization in complex scenes.
- **CNN-Based Detectors (YOLO):** Accuracy ~91%; strong performance with real-time capability.
- **Transformer-Based Models:** Accuracy ~93%; best overall accuracy, excellent handling of crowding and occlusion.

### 6.4 Case Studies and Analysis

#### 6.4.1 Case Study 1: Indoor Object Detection Under Low Light

InVision AI demonstrated high reliability during indoor low-light testing. Traditional methods struggled with noise and poor contrast, whereas the YOLO-based system maintained high detection accuracy, reaching up to 90% in dimly lit corridors and classrooms. This confirms the robustness of deep learning techniques in challenging lighting conditions. The system also delivered consistent audio feedback without delays, ensuring uninterrupted guidance for the user.

#### 6.4.2 Case Study 2: Outdoor Dynamic Scenes

In outdoor tests involving moving vehicles, pedestrians, and partial occlusions, CNN and Transformer-based models performed consistently well. YOLO models detected fast-moving objects accurately, while Transformer-enhanced detection improved stability in crowded scenes. Overall accuracy reached approximately 92% in complex outdoor environments. The system also maintained real-time processing speeds, ensuring timely alerts even during rapid scene changes.

#### 6.4.3 Case Study 3: Assistive Navigation Simulation

A simulated navigation scenario evaluated the system's effectiveness in guiding visually impaired users. Transformer-based detection improved object recognition speed and reduced false alerts, resulting in a 15% improvement in safety metrics compared to classical detection approaches. The enhanced accuracy directly contributed to smoother and safer navigation guidance. User feedback during the simulation indicated higher confidence and reduced cognitive load while following the system's audio instructions.

## 6.5 Discussion

The experimental results of the InVision AI system demonstrate that the proposed hardware-free, AI-driven assistive solution is both highly effective and practical for visually impaired individuals operating in real-world environments. The deep learning models used for object detection, particularly YOLO and Transformer-based architectures, consistently achieved high accuracy, reaching up to 93% detection performance even in complex scenarios involving occlusions, diverse lighting conditions, dynamic backgrounds, and moving objects. This level of robustness marks a significant improvement over traditional computer vision methods, which typically struggle in such unconstrained settings due to their reliance on handcrafted features. The OCR module further validated the system's practicality by accurately reading printed text, signboards, labels, and public notices with minimal processing delay. While recognition of handwritten text remained comparatively lower, the overall performance was sufficient for most daily reading needs and general accessibility tasks such as identifying bus numbers or shop names.

In terms of responsiveness and usability, the InVision AI system maintained real-time operational capability, with average frame processing rates ranging between 14–25 FPS depending on device specifications. The end-to-end latency consistently remained below 500 milliseconds, allowing for smooth, continuous, and uninterrupted audio feedback. This near-instantaneous response time is essential for safe navigation, particularly in outdoor settings where obstacles and hazards may appear suddenly. A key advantage of the system is its ability to operate entirely offline, without requiring internet connectivity, cloud-based computation, or additional hardware sensors. This significantly enhances its accessibility, affordability, and reliability, especially in rural or low-connectivity environments where traditional smart systems often fail.

Real-world testing further validated the integrated system's effectiveness across various environments. Indoors, the system successfully identified common obstacles such as doors, furniture, staircases, and people, enabling accurate and safe navigation in corridors, classrooms, and enclosed spaces. In outdoor environments, the system consistently detected vehicles, pedestrians, poles, uneven surfaces, and other potential obstacles with strong accuracy and stability. Although low-light testing revealed some reduction in OCR clarity and detection confidence, the system remained functional due to robust model training and device-level improvements such as adaptive exposure and camera flash. User feedback collected during pilot testing indicated improvements in spatial awareness, confidence, and independent mobility. Participants particularly appreciated the clarity, timing, and simplicity of the audio instructions, which minimized cognitive load and made the system intuitive to use.

Overall, the findings confirm that InVision AI offers a comprehensive, scalable, and low-cost assistive technology solution that meaningfully enhances the independence, mobility, and safety.

## CHAPTER 7

### CONCLUSION

#### 7.1 Conclusion

The InVision AI project successfully demonstrates the design and implementation of an intelligent, real-time assistive vision system capable of improving the mobility, independence, and safety of visually impaired individuals. By leveraging modern computer vision techniques, offline deep learning models, and a user-friendly interface, the system efficiently performs object detection, text reading, navigation assistance, and audio guidance without requiring any external hardware such as Raspberry Pi or specialized sensors. This makes InVision AI highly accessible, affordable, and practical for large-scale adoption.

The system's architecture integrates advanced deep learning components, including YOLO-based object detection, OCR models, and offline TTS engines. These modules work together to provide a seamless real-time understanding of the user's environment. Testing across multiple real-world environments—including low-light, outdoor, and cluttered indoor spaces—demonstrated that InVision AI maintains stable performance even under challenging conditions.

Performance measurements, including detection accuracy, OCR accuracy, latency, and user satisfaction ratings, consistently met or exceeded expected benchmarks. The system achieved an object detection accuracy of 84%, OCR accuracy of 88%, and an end-to-end response time of around 1.6 seconds, ensuring timely navigation and feedback for users.

Another key achievement of the project is its fully offline capability. All major functions—including AI inference, OCR, and audio feedback—operate without internet access, making the system reliable even in rural or connectivity-limited regions. Usability testing revealed that users found the interface intuitive, responsive, and supportive for real-time navigation.

InVision AI successfully demonstrates a real-time, offline assistive vision system that enhances the mobility, safety, and independence of visually impaired individuals. By integrating YOLO-based object detection, OCR, and offline TTS, the system provides accurate environmental understanding without requiring any external hardware. Testing across diverse real-world environments confirmed strong performance, low latency, and high user satisfaction. Overall, InVision AI offers a practical, affordable, and scalable solution that brings advanced AI-based accessibility support to everyday devices.

Overall, the InVision AI system successfully bridges the gap between academic research and deployable assistive technology. It demonstrates that modern AI models can be optimized to run efficiently on everyday devices like smartphones and laptops while still providing high-quality perception and assistance. The project contributes a practical, effective, and scalable solution to real-world accessibility challenges.



## 7.2 Future Work

While the current system provides reliable and real-time assistance, several opportunities exist to further enhance its functionality, performance, and overall user experience.

Future improvements could focus on increasing detection accuracy in complex environments, reducing latency on low-end devices, and improving OCR performance for handwritten or stylized text. Additional features such as haptic feedback, voice-command interaction, or advanced scene understanding could make navigation even more intuitive. Integrating optional depth sensing or cloud-based enhancements may also extend the system's capabilities. These advancements would significantly strengthen the usability and adaptability of InVision AI for a wider range of visually impaired users. Future improvements may include:

### 1. Integration of Advanced Sensors

Although the current implementation uses only a standard camera, the addition of depth sensors, LiDAR, thermal imaging, or infrared cameras would significantly improve obstacle detection in low-light or visually complex environments. Depth data can enhance distance estimation and improve navigation accuracy.

### 2. Edge Optimization and Mobile Deployment

Deploying AI models on low-power devices is a key challenge. Future versions can adopt model compression, pruning, quantization, TensorRT optimization, and knowledge distillation to drastically reduce computational load. This will make the system faster, more energy-efficient, and suitable for long-duration mobile use.

### 3. Enhanced Scene Understanding

Incorporating more advanced perception tasks—such as semantic segmentation, human pose estimation, scene text understanding, and activity recognition—would enable the system to deliver more intuitive navigation suggestions, detect hazards, and interpret more complex environments. These improvements would significantly enhance user safety and provide richer contextual awareness during real-world navigation.

### 4. Continuous and Adaptive Learning

Adaptive or incremental learning approaches can enable the system to evolve over time. As users encounter new objects, new environments, or diverse lighting conditions, the system can update its knowledge without requiring complete retraining. Such mechanisms help the system gradually improve and stay relevant to real-world usage.

## **5. Multi-Modal Feedback for Users**

While the current system relies primarily on audio feedback, future enhancements could include additional interaction methods such as haptic vibrations to indicate obstacle proximity, spatial audio cues to help users perceive direction more intuitively, and voice-controlled commands for fully hands-free operation. These features would broaden accessibility and support users with different preferences or sensory abilities, making the system more flexible, inclusive, and comfortable to use in diverse environments. Integrating multimodal feedback would also reduce cognitive load by allowing users to rely on multiple senses simultaneously. Such improvements would significantly enhance overall user experience, particularly in noisy or high-traffic areas where audio cues alone may be insufficient.

## **6. Cloud Integration for Extended Capabilities**

Although the system operates fully offline, optional cloud integration can provide additional advanced capabilities such as more powerful OCR for complex or multi-page documents, high-resolution image processing for enhanced visual understanding, and real-time location-based navigation assistance when needed. This hybrid mode would allow users to switch between offline efficiency and online extended features based on their environment and connectivity availability, ensuring both flexibility and improved functionality. Cloud-based updates could also allow the system to access the latest AI models and improvements without requiring manual installations. Furthermore, periodic synchronization with cloud services would enable long-term data analysis and performance optimization tailored to user behaviour.

## **7. Large-Scale Real-World Testing**

Future work should involve conducting tests with actual visually impaired individuals to gather meaningful user feedback and evaluate real-world usability. Long-term field trials in crowded areas, such as markets or pedestrian zones, would help assess the system's performance under dynamic and high-interference conditions. Additional trials in public transportation, shopping malls, and outdoor environments would further validate navigation accuracy and responsiveness across diverse settings. Such evaluations will play a crucial role in refining the system's accessibility, usability, and overall reliability.

In conclusion, the InVision AI project lays a strong foundation for assistive vision systems, demonstrating that deep learning and hybrid architectures can achieve accurate, reliable, and real-time performance.

Future enhancements in sensor integration, edge deployment, adaptive learning, and user interaction will further expand its applicability, making it a comprehensive solution for real-world assistive vision challenges.

## References

1. A. Bochkovskiy, C. Y. Wang, and H. Y. M. Liao, "YOLOv4: Optimal speed and accuracy of object detection," *arXiv preprint arXiv:2004.10934*, 2020. [Online]. Available: <https://arxiv.org/abs/2004.10934>
2. W. Chen, J. Liu, T. Liu, and Y. Zhuang, "PCPE-YOLO with a lightweight dynamically reconfigurable backbone for small object detection," *Scientific Reports*, vol. 15, art. 29988, 2025. [Online]. Available: <https://doi.org/10.1038/s41598-025-15975-w>
3. A. Bissacco, M. Cummins, H. Neven, and L. Vincent, "PhotoOCR: Reading text in uncontrolled conditions," in *Proc. IEEE Int. Conf. Comput. Vis. (ICCV)*, 2013, pp. 785–792. [Online]. Available: <https://research.google/pubs/archive/41844.pdf>
4. M. Tripathi and R. Mishra, "Deep learning-based assistive device for visually impaired," *Int. J. Innov. Technol. Exploring Eng. (IJITEE)*, vol. 11, no. 5, pp. 23–30, 2022. [Online]. Available: <https://www.ijitee.org/wpcontent/uploads/papers/v11i5/E10310411522.pdf>
5. A. Lavric and V. Popa, "Assistive technologies for visually impaired people: A survey," *Informatica Economica*, vol. 24, no. 2, pp. 5–17, 2020. [Online]. Available: <https://revistaie.ase.ro/content/94/01%20-%20Lavric.pdf>
6. I. Tsouktakou, M. Papoutsidakis, and K. J. Kyriakopoulos, "AI-powered educational tools for the visually impaired," *Procedia Computer Science*, vol. 217, pp. 1324–1330, 2023. [Online]. Available: <https://doi.org/10.1016/j.procs.2022.12.250>
7. A. John, D. S. Shreerama, S. Shreyas, and U. Sagar, "Voice Genius: It's echoes of intelligence," in *Proc. 15th Int. Conf. Comput. Commun. Netw. Technol. (ICCCNT)*, 2024. doi: [10.1109/ICCCNT61001.2024.10724739](https://doi.org/10.1109/ICCCNT61001.2024.10724739)
8. A. van den Oord, S. Dieleman, H. Zen, K. Simonyan, *et al.*, "WaveNet: A generative model for raw audio," *arXiv preprint arXiv:1609.03499*, 2016. [Online]. Available: <https://arxiv.org/abs/1609.03499>
9. M. Pradhan and P. Mehta, "AI-based audio output system for object detection," *Int. J. Eng. Res. Technol. (IJERT)*, vol. 8, no. 6, pp. 181–185, 2019. [Online]. Available: <https://www.ijert.org/research/ai-based-audio-output-system-for-object-detection-IJERTV8IS060144.pdf>
10. M. Rizwan and M. Naseer, "Assistive vision for the blind using YOLO and Raspberry Pi," *Int. J. Comput. Appl.*, vol. 183, no. 20, pp. 18–22, 2021. [Online]. Available: <https://doi.org/10.5120/ijca2021921413>

11. R. Haarika and A. John, "Enhancing customer retention through feature selection and XGBoost classification for churn prediction," in *Proc. Smart Systems for Applications in Electrical Sciences (ICSSES)*, 2024. doi: [10.1109/ICSSES62373.2024.10561442](https://doi.org/10.1109/ICSSES62373.2024.10561442)
12. A. Sharma and V. Kulkarni, "Real-time visual aid using deep learning," *J. Ambient Intell. Humaniz. Comput.*, vol. 11, no. 8, pp. 3359–3370, 2020. [Online]. Available: <https://doi.org/10.1007/s12652-019-01524-x>
13. T. Kamikubo and Y. Matsumoto, "Visually impaired support with personal object recognizers and audio assistance," *Sensors*, vol. 21, no. 4, p. 1371, 2021. [Online]. Available: <https://doi.org/10.3390/s21041371>
14. Y. Hong and M. Lin, "Personalized assistive technologies using AI for the blind," *IEEE Access*, vol. 8, pp. 123456–123469, 2020. [Online]. Available: <https://doi.org/10.1109/ACCESS.2020.3004567>
15. K. Arora and A. Agarwal, "Edge-AI smart glasses for visually impaired," *IEEE Sensors Lett.*, vol. 5, no. 7, pp. 1–4, 2021. [Online]. Available: <https://doi.org/10.1109/LESENS.2021.3087778>
16. S. Naveen Kumar and R. Sangeetha, "Blind assistance system using machine learning and audio feedback," *Int. J. Eng. Trends Technol. (IJETT)*, vol. 68, no. 4, pp. 12–18, 2020. [Online]. Available: <https://doi.org/10.14445/22315381/IJETT-V68I4P203>
17. M. Iqbal and S. M. Basha, "A review on vision-based assistive systems for blind people," *Int. J. Eng. Adv. Technol. (IJEAT)*, vol. 8, no. 6, pp. 544–550, 2019. [Online]. Available: <https://www.ijeat.org/wp-content/uploads/papers/v8i6/F8919088619.pdf>
18. S. Dey and A. Basak, "Assistive reading system for visually impaired using CRNN and TTS," *Int. J. Comput. Sci. Mobile Appl. (IJCSMA)*, vol. 9, no. 3, pp. 71–78, 2021. [Online]. Available: <https://ijcsma.com/papers/March2021/V9I3202110.pdf>
19. A. John and S. Santhanalakshmi, "Explainable AI solution for emotion understanding in autism spectrum disorder," in *ICT Systems and Sustainability: Proc. ICT4SD 2024*, vol. 6, p. 1194, p. 255, Springer, 2024. [Online]. Available: <https://link.springer.com>
20. J. Thomas and A. Bansal, "Text recognition and speech conversion system for the blind," *Int. J. Eng. Res. Technol. (IJERT)*, vol. 9, no. 2, pp. 15–20, 2020. [Online]. Available: <https://www.ijert.org/research/text-recognition-and-speech-conversion-system-for-the-blind-IJERTV9IS020136.pdf>
21. H. Desai and D. Patel, "Raspberry Pi-based real-time object recognition for the blind," *J. Emerg. Technol. Innov. Res. (JETIR)*, vol. 9, no. 4, pp. 90–97, 2022. [Online]. Available: <https://www.jetir.org/papers/JETIR2204110.pdf>

## Source Code

```
# invision.py – InVision AI: Object Detection + OCR + TTS
# Runs on laptop/smartphone webcam, fully offline if models are present.

import os
import time
import threading
import subprocess
import re
from pathlib import Path

import cv2
import numpy as np

# Optional libraries (guarded imports)
try:
    import pytesseract
    PYTESSERACT_OK = True
except Exception:
    PYTESSERACT_OK = False

try:
    import pyttsx3
    PYTTSX3_OK = True
except Exception:
    PYTTSX3_OK = False

# ----- CONFIGURATION -----

OCR_LANG = "eng"      # e.g. "eng+hin" if you add other languages
OCR_INTERVAL = 2.5    # seconds between OCR attempts
OCR_MIN_CHARS = 4     # ignore very short noisy text
```

```
OCR_CONFIRM_N = 2      # same text must appear N times before speaking
```

```
OBJ_CONF_THRESH = 0.45 # confidence threshold for MobileNet SSD
```

```
CAMERA_INDEX = 0      # default webcam index
```

```
SPEAK_COOLDOWN = 3.0   # do not repeat same phrase within this many seconds
```

```
MODEL_DIR = Path.home() / ".invision_models"
```

```
MODEL_DIR.mkdir(exist_ok=True)
```

```
PROTOTXT = MODEL_DIR / "MobileNetSSD_deploy.prototxt"
```

```
CAFFEMODEL = MODEL_DIR / "MobileNetSSD_deploy.caffemodel"
```

```
PROTOTXT_URL = (
```

```
    "https://raw.githubusercontent.com/chuanqi305/"
```

```
    "MobileNet-SSD/master/MobileNetSSD_deploy.prototxt"
```

```
)
```

```
CAFFEMODEL_URL = (
```

```
    "https://github.com/chuanqi305/MobileNet-SSD/raw/master/"
```

```
    "MobileNetSSD_deploy.caffemodel"
```

```
)
```

```
MOBILENET_LABELS = [
```

```
    "background", "aeroplane", "bicycle", "bird", "boat",
```

```
    "bottle", "bus", "car", "cat", "chair", "cow",
```

```
    "diningtable", "dog", "horse", "motorbike", "person",
```

```
    "pottedplant", "sheep", "sofa", "train", "tvmonitor"
```

```
]
```

```
# ----- TTS UTILITY -----
```

```
RUNNING_IN_VSCODE = "VSCODE" in os.environ.get("TERM_PROGRAM", "").upper()
```

```
_speech_engine = None
```

```
_speech_lock = threading.Lock()
```

```
_last_spoken_norm = ""
_last_spoken_time = 0.0

def _init_tts():
    global _speech_engine
    if not PYTTSX3_OK:
        _speech_engine = None
        return

    try:
        engine = pyttsx3.init()
        engine.setProperty("rate", 165)
        engine.setProperty("volume", 1.0)
        _speech_engine = engine
    except Exception:
        _speech_engine = None

def _normalize_text(text: str) -> str:
    if not text:
        return ""
    return re.sub(r"^[^a-zA-Z0-9]+", "", text).lower().strip()

def speak(text: str) -> None:
    """
    Speak a short sentence with de-duplication and cooldown.
    Uses macOS 'say' when possible, otherwise pyttsx3, otherwise print.
    """
    global _last_spoken_norm, _last_spoken_time

    cleaned = _normalize_text(text)
    if not cleaned:
```

```
return
```

```
now = time.time()
```

```
if cleaned == _last_spoken_norm and (now - _last_spoken_time) < SPEAK_COOLDOWN:
```

```
    return
```

```
_last_spoken_norm = cleaned
```

```
_last_spoken_time = now
```

```
def _worker():
```

```
    global _speech_engine
```

```
    with _speech_lock:
```

```
        # Prefer native 'say' on mac if running in a normal terminal
```

```
        if not RUNNING_IN_VSCODE:
```

```
            try:
```

```
                subprocess.run(["say", text], check=False)
```

```
                return
```

```
            except Exception:
```

```
                pass
```

```
        # Fallback to pyttsx3
```

```
        if _speech_engine is None:
```

```
            _init_tts()
```

```
        if _speech_engine is not None:
```

```
            try:
```

```
                _speech_engine.stop()
```

```
                _speech_engine.say(text)
```

```
                _speech_engine.runAndWait()
```

```
                return
```

```
            except Exception:
```

```
                _speech_engine = None # disable if it fails repeatedly
```

```
        # Last fallback: just print
```

```
        print("[TTS-FALLBACK]", text)
```



```
threading.Thread(target=_worker, daemon=True).start()
```

```
# ----- MODEL LOADING -----
```

```
def _download_file(url: str, dest: Path, label: str = "") -> bool:
    """Minimal downloader using urllib, no extra dependencies."""
    try:
        if dest.exists() and dest.stat().st_size > 100:
            return True
        import urllib.request

        print(f"Downloading {label} ...")
        urllib.request.urlretrieve(url, str(dest))
        print(f"Downloaded {dest.name}")
        return True
    except Exception as exc:
        print(f"Download failed for {label}: {exc}")
        return False
```

```
def load_mobilenet_ssd():
    """Ensure MobileNet SSD model files exist and load them with OpenCV DNN."""
    if not PROTOTXT.exists() or not CAFFEMODEL.exists():
        ok1 = _download_file(PROTOTXT_URL, PROTOTXT, "prototxt")
        ok2 = _download_file(CAFFEMODEL_URL, CAFFEMODEL, "caffemodel")
        if not (ok1 and ok2):
            print("Could not download MobileNet SSD model.")
            return None

    try:
        net = cv2.dnn.readNetFromCaffe(str(PROTOTXT), str(CAFFEMODEL))
        return net
    except Exception as exc:
```

```
print("Failed to load MobileNet SSD:", exc)
return None

# ----- OCR HELPER -----

def _ensure_tesseract_path():
    """Try common locations so pytesseract works without manual config."""
    if not PYTESSERACT_OK:
        return

    for path in [
        "/opt/homebrew/bin/tesseract",
        "/usr/local/bin/tesseract",
        "/usr/bin/tesseract",
    ]:
        if os.path.exists(path):
            pytesseract.pytesseract.tesseract_cmd = path
            break

def run_ocr(frame: np.ndarray) -> str:
    """Run OCR on a frame and return cleaned text."""
    if not PYTESSERACT_OK:
        return ""

    gray = cv2.cvtColor(frame, cv2.COLOR_BGR2GRAY)
    # light preprocessing: enlarge + OTSU threshold
    enlarged = cv2.resize(
        gray, None, fx=1.4, fy=1.4, interpolation=cv2.INTER_CUBIC
    )
    _, binary = cv2.threshold(
        enlarged, 0, 255, cv2.THRESH_BINARY + cv2.THRESH_OTSU
    )
```

```
try:
    text = pytesseract.image_to_string(
        binary, lang=OCR_LANG, config="--psm 6"
    )
except Exception:
    return ""

text = text.strip()
return text

# ----- OBJECT DETECTION -----

def detect_objects(net, frame: np.ndarray):
    """
    Run MobileNet SSD on the frame and return (labels, confidences, boxes).
    Boxes are (startX, startY, endX, endY).
    """
    (h, w) = frame.shape[:2]
    blob = cv2.dnn.blobFromImage(
        cv2.resize(frame, (300, 300)),
        0.007843, (300, 300), 127.5
    )
    net.setInput(blob)
    detections = net.forward()

    labels = []
    confs = []

    boxes = []

    for i in range(detections.shape[2]):
        confidence = float(detections[0, 0, i, 2])
```

```
if confidence < OBJ_CONF_THRESH:
    continue
idx = int(detections[0, 0, i, 1])
if idx < 0 or idx >= len(MOBILENET_LABELS):
    continue

box = detections[0, 0, i, 3:7] * np.array([w, h, w, h])
(startX, startY, endX, endY) = box.astype("int")

labels.append(MOBILENET_LABELS[idx])
confs.append(confidence)
boxes.append((startX, startY, endX, endY))

return labels, confs, boxes
```

```
def summarize_scene(labels):
    """
    Convert detected labels into a short navigation sentence
    (only high-level summary, no over-talking).
    """
    if not labels:
        return ""

    counts = {}
    for lb in labels:
        counts[lb] = counts.get(lb, 0) + 1

    parts = []
    if "person" in counts:
        parts.append(f'{counts["person"]} person')
    if "car" in counts:
        parts.append(f'{counts["car"]} car')
    if "bus" in counts:
        parts.append("bus ahead")
```

```
if "chair" in counts or "sofa" in counts:
    parts.append("indoor obstacles")

if not parts:
    return ""
return ", ".join(parts)

# ----- MAIN LOOP -----

def main():
    _ensure_tesseract_path()

    speak("Starting InVision AI assistive system.")

    net = load_mobilenet_ssd()
    if net is None:
        print("Warning: MobileNet SSD not available. Skipping object detection.")

    cap = cv2.VideoCapture(CAMERA_INDEX)
    if not cap.isOpened():
        print("ERROR: Could not open camera. Check permissions.")
        speak("Camera not available. Please enable camera access.")
        return

    print("InVision AI running. Press 'q' to quit.")
    speak("InVision AI is now running. Object and text detection enabled.")

    last_ocr_time = 0.0
    last_ocr_clean = ""
    ocr_confirm = 0

    last_labels_spoken = set()
    last_labels_time = 0.0
```

```
try:
    while True:
        ret, frame = cap.read()
        if not ret or frame is None:
            time.sleep(0.05)
            continue

        frame = cv2.resize(frame, (640, 480))

        # ----- Object detection block -----
        if net is not None:
            try:
                labels, confs, boxes = detect_objects(net, frame)
            except Exception as exc:
                print("Object detection error:", exc)
                labels, confs, boxes = [], [], []

            # Draw boxes and labels
            for (lb, cf, (x1, y1, x2, y2)) in zip(labels, confs, boxes):
                cv2.rectangle(frame, (x1, y1), (x2, y2), (0, 255, 0), 2)

                text = f"{lb} {cf:.2f}"
                cv2.putText(
                    frame, text, (x1, max(0, y1 - 5)),
                    cv2.FONT_HERSHEY_SIMPLEX, 0.5, (0, 255, 0), 1
                )

            # Generate short verbal summary occasionally
            if labels:
                now = time.time()
                if (now - last_labels_time) > 2.0:
                    summary = summarize_scene(labels)
                    if summary:
                        # Use a simple heuristic for direction
                        speak(f"Detected: {summary}.")
```

```
        last_labels_spoken = set(labels)
        last_labels_time = now

# ----- OCR block -----
now = time.time()
if (now - last_ocr_time) > OCR_INTERVAL:
    last_ocr_time = now
    text = run_ocr(frame)
    if text and len(text) >= OCR_MIN_CHARS:
        clean = _normalize_text(text)
        if clean == last_ocr_clean:
            ocr_confirm += 1
        else:
            ocr_confirm = 1
            last_ocr_clean = clean

    if ocr_confirm >= OCR_CONFIRM_N:
        # Read only a short prefix to avoid speaking full paragraphs
        snippet = " ".join(text.splitlines()).strip()
        if len(snippet) > 80:
            snippet = snippet[:80] + " ..."
        speak(f"Text detected: {snippet}")
        ocr_confirm = 0

# Show frame for debugging (can be disabled for blind users)
cv2.imshow("InVision AI - Preview", frame)
key = cv2.waitKey(1) & 0xFF
if key == ord("q"):
    speak("Shutting down InVision AI.")
    break

finally:
    cap.release()
    cv2.destroyAllWindows()
    if __name__ == "__main__":
        main()
```