Status	Finished
Started	Thursday, 29 October 2026, 11:32 PM
Completed	Thursday, 29 October 2026, 11:53 PM
Duration	20 mins 34 secs
Grade	**14.00** out of 15.00 (**93.33**%)

Question **1**

Correct

Mark 1.00 out of 1.00

_____ function returns the value corresponding to the key passed as the argument.

a. get ✓
b. update
c. del
d. values

Question **2**

Correct

Mark 1.00 out of 1.00

Dictionary is a _____ data type.

a. None of the mentioned
b. Sequence
c. Ordered
d. Mapping ✓

Question **3**

Correct

Mark 1.00 out of 1.00

1,2,3 are the _____ in the following dictionary. D = {1 : "One", 2 : "Two", 3 : "Three"}

a. Keys ✓
b. None of the mentioned
c. Items
d. Values

Question **4**

Correct

Mark 1.00 out of 1.00

Choose the correct statement, in reference to the following code: D1.update(D2) #D1 and D2 are dictionaries

a. It will merge all the elements of dictionary 'D2' in dictionary 'D1'. ✓
b. None of the mentioned
c. It will merge all the elements of dictionary 'D1' in dictionary 'D2'.
d. It will create a new dictionary.

Question **5**

Correct

Mark 1.00 out of 1.00

Which of the following are immutable data type? A. String B. Tuple C. List D. Dictionary

a. b and d
b. c and d
c. a and b ✓
d. a and c

Question **6**

Correct

Mark 1.00 out of 1.00

Key – value concept is in _____.

a. String
b. List
c. Dictionary ✓
d. Tuple

Question **7**

Correct

Mark 1.00 out of 1.00

pop function delete and _____ the element of dictionary.

a. display
b. not return
c. add
d. return ✓

Question **8**

Incorrect

Mark 0.00 out of 1.00

What is the value of counter after the code is run?

```
phrase = "Cheese!!!! Cheese!!!! Python is a programming Language.Python!!"
counter = 0
letters = {}
for word in phrase.split():
    for letter in word:
        letter = letter.lower()
        if letter not in letters.keys():
            letters[letter] = 0
        letters[letter] += 1
for key in letters.keys():
    if letters[key] > 2:
        counter += 1
print(counter)
```

Answer: print('9') ✗

Question **9**

Correct

Mark 1.00 out of 1.00

In Python, Dictionaries are immutable

Select one:

- True
- False ✓

Question **10**

Correct

Mark 1.00 out of 1.00

Which function helps to merge dictionary 'D1' and 'D2'?

- a. merge
- b. update ✓
- c. get
- d. append

Question **11**

Correct

Mark 1.00 out of 1.00

Which function/statement delete the dictionary from the memory?

- a. pop
- b. clear
- c. delete
- d. del ✓

Question **12**

Correct

Mark 1.00 out of 1.00

Which of the following are true of Python dictionaries:

a) All the keys in a dictionary must be of the same type.

b) Items are accessed by their position in a dictionary.

c) A dictionary can contain any object type except another dictionary.

d) Dictionaries can be nested to any depth.

e) Dictionaries are mutable.

f) Dictionaries are accessed by key.

- a. d,e,f ✓
- b. b,c
- c. c,d,e
- d. a,b

Question **13**

Correct

Mark 1.00 out of 1.00

What does the following code print?

```
names = {'Janice': 5, 'Emily': 3, 'John': 7, 'Eleanor': 2}
list_o_names = []
names['Emily'] += 10
names['Erik'] = 22

for name in names:
    if names[name] > 5:
        list_o_names.append(name)
print(list_o_names)
```

a. ['Emily', 'John', 'Erik'] ✓

b. ['Janice', 'Emily', 'John', 'Eleanor']

c. ['Janice', 'John', 'Erik']

d. ['Janice', 'Emily', 'John']

Question **14**

Correct

Mark 1.00 out of 1.00

_____ function returns the number of key: value pairs of the dictionary.

a. length

b. len ✓

c. items

d. total

Question **15**

Correct

Mark 1.00 out of 1.00

Which of the following function create a dictionary from a sequence of key-value pairs

a. convert

b. dict ✓

c. dictionary

d. create