

Tibco BusinessWorks Project Analysis

customerOrder

Comprehensive analysis and documentation of Tibco BW 5.x project processes, connections, and resources

Generated: 2025-12-25 00:49:18 CST

Table of Contents

1 Project Information	3
1.1 Basic Information	3
1.2 Project Statistics	3
2 Tibco Services	5
2.1 Services Summary	5
2.2 On-Start Up Processes	5
2.2.1 Service/Initialization_onstartup.process	5
2.3 SOAP Services	6
2.3.1 Service/orderServiceSOAP.process	6
2.4 Service Agents	7
2.4.1 orderService	7
2.5 REST Services	9
2.5.1 Service/orderServiceREST.process	9
2.6 Adapter Services	9
2.6.1 TestService/Others/orderServiceFILEADAPTERSUBSCRIBER.process	9
2.6.2 TestService/Others/orderServiceFILEADAPTERSUBSCRIBER.process Integration	9
2.6.3 BusinessProcess/aereqresüRAKS.process	10
2.6.4 BusinessProcess/aereqresüRAKS.process Integration	10
2.7 File Pollers	11
2.7.1 Service/orderServiceFILE.process	11
2.7.3 TestService/Others/orderServiceFILEADAPTERPUBLISHER.process ..	13
2.8 JMS Queue Receivers	14
2.8.1 Service/orderServiceJMS.process	14
2.9 JavaEventSources	15
2.9.1 BusinessProcess/connector.process	15
2.10 Timers	16
2.10.1 Service/orderServiceSCHEDULER.process	16
3 Tibco Processes	18
3.1 Processes Summary	18
3.2 BusinessProcess/LogandErrorHandler.process	19
3.2.1 Flow Diagram	19
3.2.2 LogDEBUG (WriteToLogActivity)	20
3.2.3 LogINFO (WriteToLogActivity)	21
3.2.4 LogWARN (WriteToLogActivity)	21
3.2.5 LogERROR (WriteToLogActivity)	22
3.2.6 Map Data (MapperActivity)	22
3.2.7 insertProcessErrors (JDBCUpdateActivity)	23
3.2.8 insertFail (WriteToLogActivity)	24
3.3 BusinessProcess/LogandErrorHandlerDummy.process	24
3.3.1 Flow Diagram	24
3.3.2 LogDEBUG (WriteToLogActivity)	25
3.3.3 LogINFO (WriteToLogActivity)	26
3.3.4 LogWARN (WriteToLogActivity)	26
3.3.5 LogERROR (WriteToLogActivity)	27
3.3.6 Map Data (MapperActivity)	27
3.3.7 Send HTTP Request (HttpRequestActivity)	28
3.4 BusinessProcess/UpdatePayment.process	28

3.4.1 Flow Diagram	29
3.4.2 UpdateDiscountStatus (JDBCUpdateActivity)	31
3.4.3 Catch (CatchActivity)	32
3.4.4 LogandErrorHandler (CallProcessActivity)	32
3.4.5 Java Code (JavaActivity)	33
3.4.6 Engine Command (EngineCommandActivity)	35
3.4.7 Sleep (SleepActivity)	35
3.5 BusinessProcess/UpdatePaymentDummy.process	35
3.5.1 Flow Diagram	35
3.5.2 Catch (CatchActivity)	36
3.5.3 LogandErrorHandler (CallProcessActivity)	37
3.5.4 Log (WriteToLogActivity)	37
3.5.5 Read File (FileReadActivity)	38
3.5.6 createOrderService (CallProcessActivity)	38
3.6 BusinessProcess/aereqresüRAKS.process	38
3.6.1 Flow Diagram	38
3.6.2 Adapter Request-Response Server (AERPCServerActivity)	39
3.6.3 createOrder (CallProcessActivity)	40
3.7 BusinessProcess/connector.process	40
3.7.1 Flow Diagram	40
3.7.2 Java Event Source (JavaEventSource)	41
3.7.3 Java Method (JavaMethodActivity)	42
3.7.4 Java To XML (JavaToXmlActivity)	42
3.7.5 XML To Java (XmlToJavaActivity)	43
3.7.6 Java Code (JavaActivity)	43
3.8 BusinessProcess/createOrder.process	43
3.8.1 Flow Diagram	43
3.8.2 Group (TransactionGroup)	44
3.8.3 UpdateCustomerTable (JDBCUpdateActivity)	45
3.8.4 Map Data (MapperActivity)	46
3.8.5 GlobalCatch (CatchActivity)	47
3.8.6 ErrorHandler (CallProcessActivity)	47
3.8.7 UpdateOrderDetails (CallProcessActivity)	48
3.9 BusinessProcess/createOrderAdapterPublisher.process	49
3.9.1 Flow Diagram	49
3.9.2 Group (TransactionGroup)	50
3.9.3 Log (WriteToLogActivity)	50
3.9.4 Map Data (MapperActivity)	51
3.9.5 GlobalCatch (CatchActivity)	51
3.9.6 ErrorHandler (CallProcessActivity)	52
3.9.7 UpdateOrderDetails (CallProcessActivity)	52
3.9.8 Publish to Adapter (AEPublisherActivity)	53
3.9.9 Send HTTP Request (HttpRequestActivity)	55
3.9.10 Wait for HTTP Request (HTTPSignalInActivity)	55
3.10 BusinessProcess/createOrderDummy.process	56
3.10.1 Flow Diagram	56
3.10.2 Group (TransactionGroup)	57
3.10.3 Log (WriteToLogActivity)	57
3.10.4 Write File (FileWriteActivity)	58

3.10.5 Group (1) (TransactionGroup)	59
3.10.6 LogandErrorHandlerDummy (CallProcessActivity)	59
3.10.7 Group (2) (CriticalSectionGroup)	60
3.10.8 Errorhandler (CallProcessActivity)	60
3.10.9 Group (3) (LoopGroup)	61
3.10.10 LogandErrorHandler (CallProcessActivity)	61
3.10.11 Map Data (MapperActivity)	62
3.10.12 GlobalCatch (CatchActivity)	62
3.10.13 UpdateOrderDetails (CallProcessActivity)	63
3.10.14 JDBC Query (JDBCQueryActivity)	63
3.10.15 SOAPcreateOrderService (CallProcessActivity)	64
3.10.16 Java Method (JavaMethodActivity)	64
3.11 BusinessProcess/createOrderREST.process	64
3.11.1 Flow Diagram	64
3.11.2 Group (1) (LoopGroup)	66
3.11.3 Log (WriteToLogActivity)	66
3.11.4 Group (TransactionGroup)	67
3.11.5 Log (WriteToLogActivity)	67
3.11.6 Map Data (MapperActivity)	68
3.11.7 GlobalCatch (CatchActivity)	68
3.11.8 Errorhandler (CallProcessActivity)	69
3.11.9 UpdateOrderDetails (CallProcessActivity)	69
3.11.10 Render JSON (JSONRenderActivity)	70
3.12 Service/Initialization_onstartup.process	70
3.12.1 Flow Diagram	70
3.12.2 onStartup (OnStartupEventSource)	71
3.12.3 SetVariable_counter (SetSharedVariableActivity)	72
3.12.4 SetVariable_timestamp (SetSharedVariableActivity)	72
3.12.5 Log (WriteToLogActivity)	72
3.13 Service/orderServiceFILE.process	73
3.13.1 Flow Diagram	73
3.13.2 File Poller (FileEventSource)	75
3.13.3 Group (LoopGroup)	76
3.13.4 createOrder (CallProcessActivity)	76
3.13.5 Parse Data (ParseActivity)	77
3.13.6 Catch (CatchActivity)	78
3.13.7 LogandErrorHandler (CallProcessActivity)	78
3.13.8 Log (WriteToLogActivity)	78
3.13.9 Log-1 (WriteToLogActivity)	79
3.13.10 Copy File (FileCopyActivity)	79
3.13.11 Rename File (FileRenameActivity)	80
3.13.12 Remove File (FileRemoveActivity)	80
3.13.13 List Files (ListFilesActivity)	81
3.13.14 Write File (FileWriteActivity)	81
3.13.15 Null (NullActivity)	82
3.13.16 Sleep (SleepActivity)	82
3.13.17 GetVariable (GetSharedVariableActivity)	82
3.13.18 SetVariable (SetSharedVariableActivity)	82
3.14 Service/orderServiceJMS.process	83

3.14.1 Flow Diagram	84
3.14.2 JMS Queue Receiver (JMSQueueEventSource)	85
3.14.3 Group (CriticalSectionGroup)	85
3.14.4 createOrder (CallProcessActivity)	86
3.14.5 Catch (CatchActivity)	86
3.14.6 LogandErrorHandler (CallProcessActivity)	87
3.14.7 Log (WriteToLogActivity)	87
3.14.8 Log-1 (WriteToLogActivity)	88
3.14.9 Invoke REST API (class)	88
3.14.10 Log-1-1 (WriteToLogActivity)	89
3.14.11 Log-1-1-1 (WriteToLogActivity)	89
3.14.12 Null (NullActivity)	90
3.14.13 Log-1-1-2 (WriteToLogActivity)	90
3.14.14 Log-1-1-1-1 (WriteToLogActivity)	90
3.14.15 createOrderService (CallProcessActivity)	91
3.14.16 Map Data (MapperActivity)	91
3.14.17 Null-1 (NullActivity)	92
3.14.18 Reply to JMS Message (JMSReplyActivity)	92
3.14.19 Null-2 (NullActivity)	93
3.14.20 Write File (FileWriteActivity)	93
3.15 Service/orderServiceREST.process	93
3.15.1 Flow Diagram	93
3.15.2 HTTP Receiver (HTTPEventSource)	94
3.15.3 REST Dispatch and Reply (RestAdapterActivity)	95
3.15.4 Log (WriteToLogActivity)	95
3.15.5 Log-1 (WriteToLogActivity)	96
3.15.6 createOrderService (CallProcessActivity)	96
3.16 Service/orderServiceSCHEDULER.process	96
3.16.1 Flow Diagram	96
3.16.2 Timer (TimerEventSource)	98
3.16.3 Group (LoopGroup)	98
3.16.4 createOrder (CallProcessActivity)	99
3.16.5 Parse Data (ParseActivity)	99
3.16.6 Catch (CatchActivity)	100
3.16.7 LogandErrorHandler (CallProcessActivity)	100
3.16.8 Read File (FileReadActivity)	101
3.16.9 Log (WriteToLogActivity)	101
3.16.10 Log-1 (WriteToLogActivity)	101
3.17 Service/orderServiceSOAP.process	102
3.17.1 Flow Diagram	102
3.17.2 SOAPEventSource (SOAPEventSource)	103
3.18 Service/orderServiceWMQ-NotDoneYet.process	103
3.18.1 Flow Diagram	103
3.18.2 Group (LoopGroup)	105
3.18.3 createOrder (CallProcessActivity)	105
3.18.4 Catch (CatchActivity)	106
3.18.5 LogandErrorHandler (CallProcessActivity)	106
3.18.6 Log (WriteToLogActivity)	107
3.18.7 Log-1 (WriteToLogActivity)	107

3.18.8 Invoke REST API (RestActivity)	109
3.18.9 Log-1-1 (WriteToLogActivity)	110
3.18.10 Log-1-1-1 (WriteToLogActivity)	110
3.18.11 Null (NullActivity)	111
3.18.12 Log-1-1-2 (WriteToLogActivity)	111
3.18.13 Log-1-1-1-1 (WriteToLogActivity)	111
3.18.14 createOrderService (CallProcessActivity)	112
3.18.15 Map Data (MapperActivity)	112
3.18.16 Null-1 (NullActivity)	113
3.18.17 Reply to JMS Message (JMSReplyActivity)	113
3.18.18 Null-2 (NullActivity)	114
3.19 Service/poc_password.process	114
3.19.1 Flow Diagram	114
3.19.2 Java Code (JavaActivity)	115
3.20 TestService/JMS/JMSQReqRep.process	116
3.20.1 Flow Diagram	116
3.20.2 JMS Queue Requestor (JMSQueueRequestReplyActivity)	117
3.21 TestService/JMS/JMSQSender.process	118
3.21.1 Flow Diagram	118
3.21.2 JMS Queue Sender (JMSQueueSendActivity)	118
3.22 TestService/JMS/SOAPcreateOrderService.process	119
3.22.1 Flow Diagram	119
3.22.2 SOAPRequestReply (SOAPSendReceiveActivity)	120
3.23 TestService/Others/orderServiceFILEADAPTERPUBLISHER.process	121
3.23.1 Flow Diagram	121
3.23.2 File Poller (FileEventSource)	123
3.23.3 Group (LoopGroup)	123
3.23.4 createOrder (CallProcessActivity)	124
3.23.5 Parse Data (ParseActivity)	125
3.23.6 Catch (CatchActivity)	125
3.23.7 LogandErrorHandler (CallProcessActivity)	125
3.23.8 Log (WriteToLogActivity)	126
3.23.9 Log-1 (WriteToLogActivity)	126
3.23.10 Write File (FileWriteActivity)	127
3.24 TestService/Others/orderServiceFILEADAPTERSUBSCRIBER.process	127
3.24.1 Flow Diagram	127
3.24.2 Adapter Subscriber (AESubscriberActivity)	128
3.24.3 Group (LoopGroup)	129
3.24.4 createOrder (CallProcessActivity)	130
3.24.5 Catch (CatchActivity)	131
3.24.6 LogandErrorHandler (CallProcessActivity)	131
3.24.7 Log (WriteToLogActivity)	131
3.24.8 Log-1 (WriteToLogActivity)	132
3.25 TestService/REST/Process Definition.process	132
3.25.1 Flow Diagram	132
3.25.2 Invoke REST API (RestActivity)	133
3.26 TestService/createOrderService.process	135
3.26.1 Flow Diagram	135
3.26.2 SOAPRequestReply (SOAPSendReceiveActivity)	135

4 Connections & Configurations	138
4.1 Archive Info	138
4.2 HTTP Connection	138
4.3 JDBC Connection	139
4.4 JMS Connection	140
4.5 Job Shared Variable	141
4.6 Service Agent Config	141
4.7 Shared Variable	143
4.8 WADL Resource	143
4.9 WSDL	144
4.10 WebSphere MQ Connection	145
4.11 XSD Schema	146
5 Adapters & Plugins	148
5.1 File Adapter Configuration	148
6 Global Variables	151
6.1 Connections (Count: 1)	151
6.2 Connections/FILE (Count: 6)	151
6.3 Connections/SCHEDULER (Count: 1)	151
6.4 Flags (Count: 2)	151
6.5 JDBCCConnection (Count: 6)	151
6.6 LogLevels (Count: 6)	152
6.7 defaultVars (Count: 17)	152
6.8 httpConnection (Count: 3)	153
7 Files Inventory	154
7.1 File Types Count	154
7.2 Files List	154
8 Archives	156
8.1 customerOrder.archive	156
9 References	157

1 Project Information

1.1 Basic Information

Attribute	Value
Project Name	customerOrder
Project Type	Tibco BusinessWorks 5.x
Project Path	C:\raks\apiguard\raksanalyzer\testdata\customerOrder
TIBCO Version	5.x

1.2 Project Statistics

Metric	Count
Total Processes	25
- Starter Processes	10
• AERPCServerActivity	1
• AESubscriberActivity	1
• FileEventSource	2
• JMSQueueEventSource	1
• JavaEventSource	1
• RestAdapterActivity	1
• SOAPEventSource	1
• TimerEventSource	1
- Non-Starter Processes	15
Total Activities	164
Shared Variable	1
JMS Connection	1
XSD Schema	3
WebSphere MQ Connection	1
JDBC Connection	1
Archive Info	1
HTTP Connection	2
WSDL	2
Job Shared Variable	1
Service Agent Config	1
WADL Resource	1
Global Variables Files	8
Total Global Variables	42

2 Tibco Services

2.1 Services Summary

Service/Process Name	Type
BusinessProcess/aereqresüRAKS.process	Adapter Service
TestService/Others/orderServiceFILEADAPTERSUBSCRIBER.process	Adapter Subscriber
Service/orderServiceFILE.process	File Poller
TestService/Others/orderServiceFILEADAPTERPUBLISHER.process	File Poller
Service/orderServiceJMS.process	JMS Queue Receiver
BusinessProcess/connector.process	JavaEventSource
Service/Initialization_onstartup.process	On-Start Up
Service/orderServiceREST.process	REST Service
Service/orderServiceSOAP.process	SOAP Service
orderService	Service Agent
Service/orderServiceSCHEDULER.process	Timer

2.2 On-Start Up Processes

2.2.1 Service/Initialization_onstartup.process

(No configuration detected)

2.2.2 Service/Initialization_onstartup.process Integration

PlantUML 1.2023.13

**This version of PlantUML is 744 days old, so you should
consider upgrading from <https://plantuml.com/download>**

[From string (line 18)]

```
@startuml
skinparam shadowing false
skinparam activity {
  BackgroundColor #E6E6FA
  BorderColor #6A5ACD
  ArrowColor #483D8B
  FontSize 11
}
skinparam partition {
  BackgroundColor #F0F0F0
  BorderColor #999999
  FontSize 11
  BorderThickness 2
}
skinparam dpi 300
!pragma maxwidth 600
start #4CAF50
state OnStartupEventSource state;
Syntax Error?
```

2.3 SOAP Services

2.3.1 Service/orderServiceSOAP.process

Service Process	Operation	Service Address	SOAP Action
Service/orderServiceSOA-P.process	Operation	soapOrderServicePath	/Service/Process%2-0Definition

2.3.2 Service/orderServiceSOAP.process Integration

PlantUML 1.2023.13

**This version of PlantUML is 744 days old, so you should
consider upgrading from <https://plantuml.com/download>**

[From string (line 18)]

```
@startuml
skinparam shadowing false
skinparam activity {
  BackgroundColor #E6E6FA
  BorderColor #6A5ACD
  ArrowColor #483D8B
  FontSize 11
}
skinparam partition {
  BackgroundColor #F0F0F0
  BorderColor #999999
  FontSize 11
  BorderThickness 2
}
skinparam dpi 300
!pragma maxwidth 600
start #4CAF50
..SOAPEventSource..
Syntax Error?
```

2.4 Service Agents

2.4.1 orderService

Path: Service/orderService.serviceagent

WSDL Source: /WSDL/customerorder.wsdl

Address: /Service/orderService.serviceagent/createOrderEndpoint1

Operation	Implementation Process	SOAP Action
Operation	/BusinessProcess/createOrderDummy.process	/Service/orderService. serviceagent/create- OrderEndpoint1/Op- eration

2.4.1.1 Operation Integration

PlantUML 1.2023.13

**This version of PlantUML is 744 days old, so you should
consider upgrading from <https://plantuml.com/download>**

[From string (line 18)]

```

@startuml
skinparam shadowing false
skinparam activity {
  BackgroundColor #E6E6FA
  BorderColor #6A5ACD
  ArrowColor #483D8B
  FontSize 11
}
skinparam partition {
  BackgroundColor #F0F0F0
  BorderColor #999999
  FontSize 11
  BorderThickness 2
}
skinparam dpi 300
!pragma maxwidth 600
start #4CAF50
fork
Syntax error: fork

```

2.5 REST Services

2.5.1 Service/orderServiceREST.process

Process Path: testdata/customerOrder/Service/orderServiceREST.process

WADL Source: /WADL/OrderService.wadl

Method	Resource Path	Implementation Process
POST	http://localhost:8085/orderCreateAPI/customerDetails	/BusinessProcess/createOrderREST.process

2.6 Adapter Services

2.6.1 TestService/Others/orderServiceFILEADAPTERSUBSCRIBER.process

Adapter Service: /Adapters/File/FileAdapterConfiguration.adfiles#adapterService.PublicationService

Transport	Subject / Destination	Provider Url
Adapter Service Default		PublicationServiceEndPoint

2.6.2 TestService/Others/orderServiceFILEADAPTERSUBSCRIBER.process Integration

2.6.2 TestService/Others/orderServiceFILEADAPTERSUBSCRIBER.process Integration

PlantUML 1.2023.13

**This version of PlantUML is 744 days old, so you should
consider upgrading from <https://plantuml.com/download>**

[From string (line 18)]

```
@startuml
skinparam shadowing false
skinparam activity {
  BackgroundColor #E6E6FA
  BorderColor #6A5ACD
  ArrowColor #483D8B
  FontSize 11
}
skinparam partition {
  BackgroundColor #F0F0F0
  BorderColor #999999
  FontSize 11
  BorderThickness 2
}
skinparam dpi 300
!pragma maxwidth 600
start #4CAF50
state AESubscriberActivity;
Syntax Error?
```

2.6.3 BusinessProcess/aereqresüRAKS.process

Adapter Service: N/A

Transport	Subject / Destination	Provider Url
Adapter Service Default		

2.6.4 BusinessProcess/aereqresüRAKS.process Integration

2.6.4 BusinessProcess/aereqresüRAKS.process Integration

PlantUML 1.2023.13

**This version of PlantUML is 744 days old, so you should
consider upgrading from <https://plantuml.com/download>**

[From string (line 18)]

```
@startuml
skinparam shadowing false
skinparam activity {
  BackgroundColor #E6E6FA
  BorderColor #6A5ACD
  ArrowColor #483D8B
  FontSize 11
}
skinparam partition {
  BackgroundColor #F0F0F0
  BorderColor #999999
  FontSize 11
  BorderThickness 2
}
skinparam dpi 300
!pragma maxwidth 600
start #4CAF50
state AERPCServerActivity
Syntax Error?
```

2.7 File Pollers

2.7.1 Service/orderServiceFILE.process

Property	Value
encoding	text
fileName	C:\tibco510\raks\in\orderServiceFILE.txt
includeCurrent	true
mode	files-and-directories
pollInterval	5
sortBy	File Name

2.7.2 Service/orderServiceFILE.process Integration

PlantUML 1.2023.13

**This version of PlantUML is 744 days old, so you should
consider upgrading from <https://plantuml.com/download>**

[From string (line 18)]

```

@startuml
skinparam shadowing false
skinparam activity {
  BackgroundColor #E6E6FA
  BorderColor #6A5ACD
  ArrowColor #483D8B
  FontSize 11
}
skinparam partition {
  BackgroundColor #F0F0F0
  BorderColor #999999
  FontSize 11
  BorderThickness 2
}
skinparam dpi 300
!pragma maxwidth 600
start #4CAF50
FileEventSource;
Syntax Error?

```

2.7.3 TestService/Others/orderServiceFILEADAPTERPUBLISHER.process

Property	Value
encoding	text
fileName	C:\tibco510\raks\in\orderServiceFILE.txt
includeCurrent	true
mode	files-and-directories
pollInterval	5
sortBy	File Name

2.7.4 TestService/Others/orderServiceFILEADAPTERPUBLISHER.process Integration

PlantUML 1.2023.13

**This version of PlantUML is 744 days old, so you should
consider upgrading from <https://plantuml.com/download>**

[From string (line 18)]

```
@startuml
skinparam shadowing false
skinparam activity {
  BackgroundColor #E6E6FA
  BorderColor #6A5ACD
  ArrowColor #483D8B
  FontSize 11
}
skinparam partition {
  BackgroundColor #F0F0F0
  BorderColor #999999
  FontSize 11
  BorderThickness 2
}
skinparam dpi 300
!pragma maxwidth 600
start #4CAF50
..FileEventSource..
Syntax Error?
```

2.8 JMS Queue Receivers

2.8.1 Service/orderServiceJMS.process

Property	Value
ApplicationProperties	/Connections/JMS Application Properties.sharedjmsapp
JMSDeliveryMode	PERSISTENT
ConnectionReference	/Connections/JMS Connection.sharedjmscon
acknowledgeMode	1
destination	temp

2.8.2 Service/orderServiceJMS.process Integration

PlantUML 1.2023.13

**This version of PlantUML is 744 days old, so you should
consider upgrading from <https://plantuml.com/download>**

[From string (line 18)]

```
@startuml
skinparam shadowing false
skinparam activity {
  BackgroundColor #E6E6FA
  BorderColor #6A5ACD
  ArrowColor #483D8B
  FontSize 11
}
skinparam partition {
  BackgroundColor #F0F0F0
  BorderColor #999999
  FontSize 11
  BorderThickness 2
}
skinparam dpi 300
!pragma maxwidth 600
start #4CAF50
:~JMSQueueEventSource~:
Syntax Error?
```

2.9 JavaEventSources

2.9.1 BusinessProcess/connector.process

Property	Value
fileName	connectorJavaEventSource
fullsource	
packageName	BusinessProcess.connector

2.9.2 BusinessProcess/connector.process Integration

PlantUML 1.2023.13

**This version of PlantUML is 744 days old, so you should
consider upgrading from <https://plantuml.com/download>**

[From string (line 18)]

```
@startuml
skinparam shadowing false
skinparam activity {
  BackgroundColor #E6E6FA
  BorderColor #6A5ACD
  ArrowColor #483D8B
  FontSize 11
}
skinparam partition {
  BackgroundColor #F0F0F0
  BorderColor #999999
  FontSize 11
  BorderThickness 2
}
skinparam dpi 300
!pragma maxwidth 600
start #4CAF50
*JavaEventSource*;
Syntax Error?
```

2.10 Timers

2.10.1 Service/orderServiceSCHEDULER.process

Property	Value
Frequency	false
FrequencyIndex	Minute
StartTime	1742409227000
TimeInterval	1

2.10.2 Service/orderServiceSCHEDULER.process Integration

PlantUML 1.2023.13

**This version of PlantUML is 744 days old, so you should
consider upgrading from <https://plantuml.com/download>**

[From string (line 18)]

```
@startuml
skinparam shadowing false
skinparam activity {
  BackgroundColor #E6E6FA
  BorderColor #6A5ACD
  ArrowColor #483D8B
  FontSize 11
}
skinparam partition {
  BackgroundColor #F0F0F0
  BorderColor #999999
  FontSize 11
  BorderThickness 2
}
skinparam dpi 300
!pragma maxwidth 600
start #4CAF50
:TimerEventSource:
Syntax Error?
```


3 Tibco Processes

Process Statistics

Property	Value
Total Process Count	25
Starter Process Count	10
Normal Process Count	15

3.1 Processes Summary

Process Name	Starter	Type
BusinessProcess/LogandErrorHandler.process	N/A	Normal Process
BusinessProcess/LogandErrorHandlerDummy.process	N/A	Normal Process
BusinessProcess/UpdatePayment.process	N/A	Normal Process
BusinessProcess/UpdatePaymentDummy.process	N/A	Normal Process
BusinessProcess/aereqresüRAKS.process	Adapter Request-Response Server	AERPCServerActivity
BusinessProcess/connector.process	Java Event Source	JavaEventSource
BusinessProcess/createOrder.process	N/A	Normal Process
BusinessProcess/createOrderAdapterPublisher.process	N/A	Normal Process
BusinessProcess/createOrderDummy.process	N/A	Normal Process
BusinessProcess/createOrderREST.process	N/A	Normal Process
Service/Initialization_onstartup.process	onStartup	OnStartupEventSource
Service/orderServiceFILE.process	File Poller	FileEventSource
Service/orderServiceJMS.process	JMS Queue Receiver	JMSQueueEventSource
Service/orderServiceREST.process	HTTP Receiver	RestAdapterActivity
Service/orderServiceSCHEDULER.process	Timer	TimerEventSource
Service/orderServiceSOAP.process	SOAPEventSource	SOAPEventSource
Service/orderServiceWMQ-NotDoneYet.process	N/A	Normal Process
Service/poc_password.process	N/A	Normal Process
TestService/JMS/JMSQReqRep.process	N/A	Normal Process
TestService/JMS/JMSQSender.process	N/A	Normal Process
TestService/JMS/SOAPcreateOrderService.process	N/A	Normal Process
TestService/Others/orderServiceFILEADAPTERPUBLISHER.process	File Poller	FileEventSource
TestService/Others/orderServiceFILEADAPTERSUBSCRIBER.process	Adapter Subscriber	AESubscriberActivity
TestService/REST/Process Definition.process	N/A	Normal Process
TestService/createOrderService.process	N/A	Normal Process

3.2 BusinessProcess/LogandErrorHandler.process

3.2.1 Flow Diagram

PlantUML 1.2023.13

**This version of PlantUML is 744 days old, so you should
consider upgrading from <https://plantuml.com/download>**

[From string (line 18)]

```
@startuml
skinparam shadowing false
skinparam activity {
  BackgroundColor #E6E6FA
  BorderColor #6A5ACD
  ArrowColor #483D8B
  FontSize 11
}
skinparam partition {
  BackgroundColor #F0F0F0
  BorderColor #999999
  FontSize 11
  BorderThickness 2
}
skinparam dpi 300
!pragma maxwidth 600
start #4CAF50
switch (Start)
Syntax Error?
```

Property	Value
Total Activity Count	7
JDBCUpdateActivity type count	1
MapperActivity type count	1
WriteToLogActivity type count	5

3.2.2 LogDEBUG (WriteToLogActivity)

Name: LogDEBUG

Type: WriteToLogActivity

3.2.2.1 Configurations

Attribute Name	Attribute Value
role	DEBUG
suppressHeader	true

3.2.2.2 Mappings

Attribute Name	Attribute Value
ns:ActivityInput.message.xsl:value-of	\$Map-Data/log/msg
ns:ActivityInput.msgCode.xsl:value-of	\$Map-Data/log/msgCode

3.2.3 LogINFO (WriteToLogActivity)

Name: LogINFO

Type: WriteToLogActivity

3.2.3.1 Configurations

Attribute Name	Attribute Value
role	INFO
suppressHeader	true

3.2.3.2 Mappings

Attribute Name	Attribute Value
ns:ActivityInput.message.xsl:value-of	\$Map-Data/log/msg
ns:ActivityInput.msgCode.xsl:value-of	\$Map-Data/log/msgCode

3.2.4 LogWARN (WriteToLogActivity)

Name: LogWARN

Type: WriteToLogActivity

3.2.4.1 Configurations

Attribute Name	Attribute Value
role	WARN
suppressHeader	true

3.2.4.2 Mappings

Attribute Name	Attribute Value
ns:ActivityInput.message.xsl:value-of	\$Map-Data/log/msg
ns:ActivityInput.msgCode.xsl:value-of	\$Map-Data/log/msgCode

3.2.5 LogERROR (WriteToLogActivity)

Name: LogERROR

Type: WriteToLogActivity

3.2.5.1 Configurations

Attribute Name	Attribute Value
role	ERROR
suppressHeader	true

3.2.5.2 Mappings

Attribute Name	Attribute Value
ns:ActivityInput.message.xsl:value-of	\$Map-Data/log/msg
ns:ActivityInput.msgCode.xsl:value-of	\$Map-Data/log/msgCode

3.2.6 Map Data (MapperActivity)

Name: Map Data

Type: MapperActivity

3.2.6.1 Configurations

Attribute Name	Attribute Value
element	

3.2.6.2 Mappings

Attribute Name	Attribute Value
log.msg.xsl:value-of	concat(tib:tokenize("DEBUG INFO WARN ERROR", " \$var ", " ", \$Start/root/pfx4:processCtx/pfx4:projectName, " ", \$Start/root/pfx4:...
log.msgCode.xsl:value-of	""
log.xsl:variable	number(\$Start/root/pfx4:logLevel)
log.xsl:variable/@name	var

3.2.7 insertProcessErrors (JDBCUpdateActivity)

Name: insertProcessErrors

Type: JDBCUpdateActivity

3.2.7.1 Configurations

Attribute Name	Attribute Value
Prepared_Param_DataType	process_id VARCHAR process_name VARCHAR ...
commit	false
emptyStrAsNil	false
jdbcSharedConfig	/Connections/JDBC Connection.sharedjdbc
statement	insert into process_errors (processid , process_name , ERROR_DESCRIPTION ,errortime) values (?, ?, ?, ?)
timeout	10

3.2.7.2 Mappings

Attribute Name	Attribute Value
jdbcUpdateActivityInput.error_description.xml:choose.xml:otherwise.xml:attribute	true
jdbcUpdateActivityInput.error_description.xml:choose.xml:otherwise.xml:attribute/@name	xsi:nil
jdbcUpdateActivityInput.error_description.xml:choose.xml:when.xml:value-of	\$Start/root/pfx4:ExceptionData/pfx4:Message
jdbcUpdateActivityInput.errortime.xml:value-of	current-dateTime()
jdbcUpdateActivityInput.process_id.xml:value-of	\$Start/root/pfx4:processCtx/pfx4:processId
jdbcUpdateActivityInput.process_name.xml:value-of	\$Start/root/pfx4:processCtx/pfx4:projectName

3.2.8 insertFail (WriteToLogActivity)

Name: insertFail

Type: WriteToLogActivity

3.2.8.1 Configurations

Attribute Name	Attribute Value
role	User

3.2.8.2 Mappings

Attribute Name	Attribute Value
ns:ActivityInput.message.xml:value-of	concat('ERROR *****', \$Start/root/pfx4:processCtx/pfx4:ProcessName, " -- ", \$Start/root/pfx4:ExceptionData/pfx4:Message)

3.3 BusinessProcess/LogandErrorHandlerDummy.process

3.3.1 Flow Diagram

PlantUML 1.2023.13

**This version of PlantUML is 744 days old, so you should
consider upgrading from <https://plantuml.com/download>**

[From string (line 18)]

```
@startuml
skinparam shadowing false
skinparam activity {
  BackgroundColor #E6E6FA
  BorderColor #6A5ACD
  ArrowColor #483D8B
  FontSize 11
}
skinparam partition {
  BackgroundColor #F0F0F0
  BorderColor #999999
  FontSize 11
  BorderThickness 2
}
skinparam dpi 300
!pragma maxwidth 600
start #4CAF50
switch (Start)
Syntax Error?
```

Property	Value
Total Activity Count	6
HttpRequestActivity type count	1
MapperActivity type count	1
WriteToLogActivity type count	4

3.3.2 LogDEBUG (WriteToLogActivity)

Name: LogDEBUG

Type: WriteToLogActivity

3.3.2.1 Configurations

Attribute Name	Attribute Value
role	DEBUG
suppressHeader	true

3.3.2.2 Mappings

Attribute Name	Attribute Value
ns:ActivityInput.message.xsl:value-of	\$Map-Data/log/msg
ns:ActivityInput.msgCode.xsl:value-of	\$Map-Data/log/msgCode

3.3.3 LogINFO (WriteToLogActivity)

Name: LogINFO

Type: WriteToLogActivity

3.3.3.1 Configurations

Attribute Name	Attribute Value
role	INFO
suppressHeader	true

3.3.3.2 Mappings

Attribute Name	Attribute Value
ns:ActivityInput.message.xsl:value-of	\$Map-Data/log/msg
ns:ActivityInput.msgCode.xsl:value-of	\$Map-Data/log/msgCode

3.3.4 LogWARN (WriteToLogActivity)

Name: LogWARN

Type: WriteToLogActivity

3.3.4.1 Configurations

Attribute Name	Attribute Value
role	WARN
suppressHeader	true

3.3.4.2 Mappings

Attribute Name	Attribute Value
ns:ActivityInput.message.xsl:value-of	\$Map-Data/log/msg
ns:ActivityInput.msgCode.xsl:value-of	\$Map-Data/log/msgCode

3.3.5 LogERROR (WriteToLogActivity)

Name: LogERROR

Type: WriteToLogActivity

3.3.5.1 Configurations

Attribute Name	Attribute Value
role	ERROR
suppressHeader	true

3.3.5.2 Mappings

Attribute Name	Attribute Value
ns:ActivityInput.message.xsl:value-of	\$Map-Data/log/msg
ns:ActivityInput.msgCode.xsl:value-of	\$Map-Data/log/msgCode

3.3.6 Map Data (MapperActivity)

Name: Map Data

Type: MapperActivity

3.3.6.1 Configurations

Attribute Name	Attribute Value
element	

3.3.6.2 Mappings

Attribute Name	Attribute Value
log.msg.xsl:value-of	concat(tib:tokenize("DEBUG INFO WARN ERROR", " \$var ", " ", \$Start/root/pfx4:processCtx/pfx4:projectName, " ", \$Start/root/pfx4:...
log.msgCode.xsl:value-of	""
log.xsl:variable	number(\$Start/root/pfx4:logLevel)
log.xsl:variable/@name	var

3.3.7 Send HTTP Request (HttpRequestActivity)

Name: Send HTTP Request

Type: HttpRequestActivity

3.3.7.1 Configurations

Attribute Name	Attribute Value
InputHeaders	
OutputHeaders	
inputOutputVersion	5.3.0
newMimeSupport	true

3.4 BusinessProcess/UpdatePayment.process

3.4.1 Flow Diagram

Flow Diagram: BusinessProcess/UpdatePayment.process

PlantUML 1.2023.13

**This version of PlantUML is 744 days old, so you should
consider upgrading from <https://plantuml.com/download>**

[From string (line 18)]

```
@startuml
skinparam shadowing false
skinparam activity {
  BackgroundColor #E6E6FA
  BorderColor #6A5ACD
  ArrowColor #483D8B
  FontSize 11
}
skinparam partition {
  BackgroundColor #F0F0F0
  BorderColor #999999
  FontSize 11
  BorderThickness 2
}
skinparam dpi 300
!pragma maxwidth 600
start #4CAF50
:<&code> ***Java Code***\njava;
Syntax Error?
```

Property	Value
Total Activity Count	6
CallProcessActivity type count	1
CatchActivity type count	1
EngineCommandActivity type count	1
JDBCUpdateActivity type count	1
JavaActivity type count	1
SleepActivity type count	1

3.4.2 UpdateDiscountStatus (JDBCUpdateActivity)

Name: UpdateDiscountStatus

Type: JDBCUpdateActivity

3.4.2.1 Configurations

Attribute Name	Attribute Value
Prepared_Param_DataType	orderid VARCHAR customerid VARCHAR ...
commit	false
emptyStrAsNil	false
jdbcSharedConfig	/Connections/JDBC Connection.sharedjdbc
statement	insert into orderdetails (orderid ,customerid, firstname , lastname , productcode , price , discountstatus, orderDatetime) values(?,?,?,?,?,?,?)
timeout	10

3.4.2.2 Mappings

Attribute Name	Attribute Value
jdbcUpdateActivityInput.customerid.xsl:value-of	\$Start/pfx:order/pfx:customerid
jdbcUpdateActivityInput.discountstatus.xsl:value-of	\$Start/pfx:order/pfx:discountstatus
jdbcUpdateActivityInput.firstname.xsl:value-of	\$Start/pfx:order/pfx:firstname
jdbcUpdateActivityInput.lastname.xsl:value-of	\$Start/pfx:order/pfx:lastname
jdbcUpdateActivityInput.orderDatetime.xsl:value-of	current-dateTime()
jdbcUpdateActivityInput.orderid.xsl:choose. xsl:otherwise.xsl:attribute	true
jdbcUpdateActivityInput.orderid.xsl:choose. xsl:otherwise.xsl:attribute/@name	xsi:nil
jdbcUpdateActivityInput.orderid.xsl:choose.xsl:when. xsl:value-of	\$Java-Code/javaCodeActivityOutput/orderid
jdbcUpdateActivityInput.price.xsl:value-of	\$Start/pfx:order/pfx:price
jdbcUpdateActivityInput.productcode.xsl:value-of	\$Start/pfx:order/pfx:productcode

3.4.3 Catch (CatchActivity)

Name: Catch

Type: CatchActivity

3.4.3.1 Configurations

Attribute Name	Attribute Value
catchAll	true

3.4.4 LogandErrorHandler (CallProcessActivity)

Name: LogandErrorHandler

Type: CallProcessActivity

3.4.4.1 Configurations

Attribute Name	Attribute Value
processName	/BusinessProcess/LogandErrorHandler.process

3.4.4.2 Mappings

Attribute Name	Attribute Value
root.pfx:ExceptionData.pfx:ErrorData.xsl:value-of	\$Catch/exceptiondata/*
root.pfx:ExceptionData.pfx:Message.xsl:value-of	\$_error/ns:ErrorReport/Msg
root.pfx:ExceptionData.pfx:StackTrace.xsl:value-of	\$_error/ns:ErrorReport/StackTrace
root.pfx:description.xsl:value-of	'Error in RetryProcess to update records'
root.pfx:logLevel.xsl:value-of	\$_globalVariables/ns1:GlobalVariables/LogLevels/LOG- _ERROR
root.pfx:processCtx.pfx:ProcessName.xsl:value-of	'/Common/RetryProcessErrors'
root.pfx:processCtx.pfx:processId.xsl:value-of	\$_processContext/ns:ProcessContext/ProcessId
root.pfx:processCtx.pfx:projectName.xsl:value-of	\$_processContext/ns:ProcessContext/ProjectName

3.4.5 Java Code (JavaActivity)

Name: Java Code

Type: JavaActivity

3.4.5.1 Configurations

Attribute Name	Attribute Value
byteCode	UpdatePaymentJavaCode yv66vgAAADMANwkADAAjCQAMACQJAAwAJQoAD- QAmCAAnCgAoACkHACoKAAcAJggAKwoABwAsCg- AHAC0HAC4HAC8BAApjdXN0b21lcmlkA...
fileName	UpdatePaymentJavaCode
fullsource	
inputData	customerid string optional firstname ...
outputData	orderid string optional
packageName	BusinessProcess.UpdatePayment

3.4.5.2 Mappings

Attribute Name	Attribute Value
javaCodeActivityInput.customerid.xsl:value-of	\$Start/pfx:order/pfx:customerid
javaCodeActivityInput.firstname.xsl:value-of	\$Start/pfx:order/pfx:firstname

3.4.6 Engine Command (EngineCommandActivity)

Name: Engine Command

Type: EngineCommandActivity

3.4.6.1 Configurations

Attribute Name	Attribute Value
command	Shutdown

3.4.7 Sleep (SleepActivity)

Name: Sleep

Type: SleepActivity

3.5 BusinessProcess/UpdatePaymentDummy.process

3.5.1 Flow Diagram

Flow Diagram: BusinessProcess/UpdatePaymentDummy.process

PlantUML 1.2023.13

**This version of PlantUML is 744 days old, so you should
consider upgrading from <https://plantuml.com/download>**

[From string (line 18)]

```
@startuml
skinparam shadowing false
skinparam activity {
  BackgroundColor #E6E6FA
  BorderColor #6A5ACD
  ArrowColor #483D8B
  FontSize 11
}
skinparam partition {
  BackgroundColor #F0F0F0
  BorderColor #999999
  FontSize 11
  BorderThickness 2
}
skinparam dpi 300
!pragma maxwidth 600
start #4CAF50
fork
Syntax error: fork
```

Property	Value
Total Activity Count	5
CallProcessActivity type count	2
CatchActivity type count	1
FileReadActivity type count	1
WriteToLogActivity type count	1

3.5.2 Catch (CatchActivity)

Name: Catch

Type: CatchActivity

3.5.2.1 Configurations

Attribute Name	Attribute Value
catchAll	true

3.5.3 LogandErrorHandler (CallProcessActivity)

Name: LogandErrorHandler

Type: CallProcessActivity

3.5.3.1 Configurations

Attribute Name	Attribute Value
processName	/BusinessProcess/LogandErrorHandlerDummy.process

3.5.3.2 Mappings

Attribute Name	Attribute Value
root.pfx:ExceptionData.pfx:ErrorData.xsl:value-of	\$Catch/exceptiondata/*
root.pfx:ExceptionData.pfx:Message.xsl:value-of	\$_error/ns:ErrorReport/Msg
root.pfx:ExceptionData.pfx:StackTrace.xsl:value-of	\$_error/ns:ErrorReport/StackTrace
root.pfx:description.xsl:value-of	'Error in RetryProcess to update records'
root.pfx:logLevel.xsl:value-of	\$_globalVariables/ns1:GlobalVariables/LogLevels/LOG-ERROR
root.pfx:processCtx.pfx:ProcessName.xsl:value-of	'/Common/RetryProcessErrors'
root.pfx:processCtx.pfx:processId.xsl:value-of	\$_processContext/ns:ProcessContext/ProcessId
root.pfx:processCtx.pfx:projectName.xsl:value-of	\$_processContext/ns:ProcessContext/ProjectName

3.5.4 Log (WriteToLogActivity)

Name: Log

Type: WriteToLogActivity

3.5.4.1 Configurations

Attribute Name	Attribute Value
role	User

3.5.4.2 Mappings

Attribute Name	Attribute Value
ns2:ActivityInput.message.xsl:value-of	concat("Order Updated: ", \$Start/pfx:order/pfx:orderid, "-", \$Start/pfx:order/pfx:firstname, "-ProcessId-", \$_processContext/ns:ProcessContext/Proc...
ns2:ActivityInput.xsl:if.msgCode.xsl:value-of	\$Start/pfx:order/pfx:orderid

3.5.5 Read File (FileReadActivity)

Name: Read File

Type: FileReadActivity

3.5.5.1 Configurations

Attribute Name	Attribute Value
encoding	text

3.5.5.2 Mappings

Attribute Name	Attribute Value
ns3:ReadActivityInputClass.fileName.xsl:value-of	"C:\temp.txt"

3.5.6 createOrderService (CallProcessActivity)

Name: createOrderService

Type: CallProcessActivity

3.5.6.1 Configurations

Attribute Name	Attribute Value
processName	/TestService/createOrderService.process

3.6 BusinessProcess/aereqresüRAKS.process

3.6.1 Flow Diagram

PlantUML 1.2023.13

**This version of PlantUML is 744 days old, so you should
consider upgrading from <https://plantuml.com/download>**

[From string (line 18)]

```
@startuml
skinparam shadowing false
skinparam activity {
  BackgroundColor #E6E6FA
  BorderColor #6A5ACD
  ArrowColor #483D8B
  FontSize 11
}
skinparam partition {
  BackgroundColor #F0F0F0
  BorderColor #999999
  FontSize 11
  BorderThickness 2
}
skinparam dpi 300
!pragma maxwidth 600
start #4CAF50
:<&transfer> ~Adapter Request-Response Server~\naeRRServer;
Syntax Error?
```

Property	Value
Total Activity Count	2
AERPCServerActivity type count	1
CallProcessActivity type count	1

3.6.2 Adapter Request-Response Server (AERPCServerActivity)

Name: Adapter Request-Response Server

Type: AERPCServerActivity

3.6.2.1 Configurations

Attribute Name	Attribute Value
ae.aepalette.sharedProperties.transportChoice	default
ae.aepalette.sharedProperties.useRequestReply	false

3.6.3 createOrder (CallProcessActivity)

Name: createOrder

Type: CallProcessActivity

3.6.3.1 Configurations

Attribute Name	Attribute Value
processName	/BusinessProcess/createOrder.process

3.7 BusinessProcess/connector.process

3.7.1 Flow Diagram

Flow Diagram: BusinessProcess/connector.process

PlantUML 1.2023.13

**This version of PlantUML is 744 days old, so you should
consider upgrading from <https://plantuml.com/download>**

[From string (line 18)]

```
@startuml
skinparam shadowing false
skinparam activity {
  BackgroundColor #E6E6FA
  BorderColor #6A5ACD
  ArrowColor #483D8B
  FontSize 11
}
skinparam partition {
  BackgroundColor #F0F0F0
  BorderColor #999999
  FontSize 11
  BorderThickness 2
}
skinparam dpi 300
!pragma maxwidth 600
start #4CAF50
:<&code> Java Event Source\nJavaEventSource;
Syntax Error?
```

Property	Value
Total Activity Count	5
JavaActivity type count	1
JavaEventSource type count	1
JavaMethodActivity type count	1
JavaToXmlActivity type count	1
XmlToJavaActivity type count	1

3.7.2 Java Event Source (JavaEventSource)

Name: Java Event Source

Type: JavaEventSource

3.7.2.1 Configurations

Attribute Name	Attribute Value
fileName	connectorJavaEventSource
fullsource	
packageName	BusinessProcess.connector

3.7.3 Java Method (JavaMethodActivity)

Name: Java Method

Type: JavaMethodActivity

3.7.3.1 Configurations

Attribute Name	Attribute Value
CacheConstructedClass	false
ConstructDeclaredClass	false
InvokeCleanupMethod	false

3.7.4 Java To XML (JavaToXmlActivity)

Name: Java To XML

Type: JavaToXmlActivity

3.7.4.1 Configurations

Attribute Name	Attribute Value
CacheConstructedClass	false
ConstructDeclaredClass	false
Repeatable	false
UseJavaSchema	false

3.7.5 XML To Java (XmlToJavaActivity)

Name: XML To Java

Type: XmlToJavaActivity

3.7.5.1 Configurations

Attribute Name	Attribute Value
Repeatable	false
UseJavaSchema	false

3.7.6 Java Code (JavaActivity)

Name: Java Code

Type: JavaActivity

3.8 BusinessProcess/createOrder.process

3.8.1 Flow Diagram

Flow Diagram: BusinessProcess/createOrder.process

PlantUML 1.2023.13

**This version of PlantUML is 744 days old, so you should
consider upgrading from <https://plantuml.com/download>**

[From string (line 18)]

```
@startuml
skinparam shadowing false
skinparam activity {
  BackgroundColor #E6E6FA
  BorderColor #6A5ACD
  ArrowColor #483D8B
  FontSize 11
}
skinparam partition {
  BackgroundColor #F0F0F0
  BorderColor #999999
  FontSize 11
  BorderThickness 2
}
skinparam dpi 300
!pragma maxwidth 600
start #4CAF50
partition "group: Group (transactionGroup)" {
Syntax Error?
```

Property	Value
Total Activity Count	6
CallProcessActivity type count	2
CatchActivity type count	1
JDBCUpdateActivity type count	1
MapperActivity type count	1
TransactionGroup type count	1

3.8.2 Group (TransactionGroup)

Name: Group

Type: TransactionGroup

3.8.2.1 Configurations

Attribute Name	Attribute Value
pd:groupType	transactionGroup
pd:includeCheckpoint	false
pd:serializable	false
pd:transactionType	JDBCTransaction

3.8.3 UpdateCustomerTable (JDBCUpdateActivity)

Name: UpdateCustomerTable

Type: JDBCUpdateActivity

3.8.3.1 Configurations

Attribute Name	Attribute Value
Prepared_Param_DataType	customerid VARCHAR firstname VARC. ..
commit	false
emptyStrAsNil	false
jdbcSharedConfig	/Connections/JDBC Connection.sharedjdbc
statement	insert into customer (customerid , firstname , lastname , age , email , city , zip , transactionstatus) values(?,?,? ?,?,?,?)
timeout	10

3.8.3.2 Mappings

Attribute Name	Attribute Value
jdbcUpdateActivityInput.age.xsl:value-of	\$Start/pfx:orderRequest/order/ns:customer/ns:age
jdbcUpdateActivityInput.city.xsl:value-of	\$Start/pfx:orderRequest/order/ns:customer/ns:city
jdbcUpdateActivityInput.customerid.xsl:value-of	\$Start/pfx:orderRequest/order/ns:customer/ns:customerid
jdbcUpdateActivityInput.email.xsl:value-of	\$Start/pfx:orderRequest/order/ns:customer/ns:email
jdbcUpdateActivityInput.firstname.xsl:value-of	\$Start/pfx:orderRequest/order/ns:customer/ns:firstname
jdbcUpdateActivityInput.lastname.xsl:value-of	\$Start/pfx:orderRequest/order/ns:customer/ns:lastname
jdbcUpdateActivityInput.transactionstatus.xsl:value-of	\$Start/pfx:orderRequest/order/ns:customer/ns:transactionstatus
jdbcUpdateActivityInput.zipcode.xsl:value-of	\$Start/pfx:orderRequest/order/ns:customer/ns:zipcode

3.8.4 Map Data (MapperActivity)

Name: Map Data

Type: MapperActivity

3.8.4.1 Configurations

Attribute Name	Attribute Value
element	

3.8.4.2 Mappings

Attribute Name	Attribute Value
ns:order.ns:customerid.xsl:value-of	\$Start/pfx:orderRequest/order/ns:customer/ns:customerid
ns:order.ns:discountstatus.xsl:value-of	if (\$Start/pfx:orderRequest/order/ns:customer/ns:age>40) then "Discount applied" else "Discount not eligible"
ns:order.ns:firstname.xsl:value-of	\$Start/pfx:orderRequest/order/ns:customer/ns:firstname
ns:order.ns:lastname.xsl:value-of	\$Start/pfx:orderRequest/order/ns:customer/ns:lastname
ns:order.ns:orderdatetime.xsl:value-of	current-dateTime()
ns:order.ns:orderid.xsl:value-of	""
ns:order.ns:price.xsl:value-of	"1000"
ns:order.ns:productcode.xsl:value-of	"UPS00"

3.8.5 GlobalCatch (CatchActivity)

Name: GlobalCatch

Type: CatchActivity

3.8.5.1 Configurations

Attribute Name	Attribute Value
catchAll	true

3.8.6 Errorhandler (CallProcessActivity)

Name: Errorhandler

Type: CallProcessActivity

3.8.6.1 Configurations

Attribute Name	Attribute Value
processName	/BusinessProcess/LogandErrorHandler.process

3.8.6.2 Mappings

Attribute Name	Attribute Value
root.ns:ExceptionData.ns:ErrorData.xsl:value-of	\$GlobalCatch/exceptiondata/*
root.ns:ExceptionData.ns:Message.xsl:value-of	\$_error/ns3:ErrorReport/Msg
root.ns:ExceptionData.ns:StackTrace.xsl:value-of	\$_error/ns3:ErrorReport/StackTrace
root.ns:description.xsl:value-of	'Error in Retyrprocess to update records'
root.ns:logLevel.xsl:value-of	\$_globalVariables/ns5:GlobalVariables/LogLevels/LOG- _ERROR
root.ns:processCtx.ns:ProcessName.xsl:value-of	'/Common/RetryProcessErrors'
root.ns:processCtx.ns:processId.xsl:value-of	\$_processContext/ns3:ProcessContext/ProcessId
root.ns:processCtx.ns:projectName.xsl:value-of	\$_processContext/ns3:ProcessContext/ProjectName

3.8.7 UpdateOrderDetails (CallProcessActivity)

Name: UpdateOrderDetails

Type: CallProcessActivity

3.8.7.1 Configurations

Attribute Name	Attribute Value
processName	/BusinessProcess/UpdatePayment.process

3.8.7.2 Mappings

Attribute Name	Attribute Value
ns:order.ns:customerid.xsl:value-of	\$Map-Data/ns:order/ns:customerid
ns:order.ns:discountstatus.xsl:value-of	\$Map-Data/ns:order/ns:discountstatus
ns:order.ns:firstname.xsl:value-of	\$Map-Data/ns:order/ns:firstname
ns:order.ns:lastname.xsl:value-of	\$Map-Data/ns:order/ns:lastname
ns:order.ns:orderdatetime.xsl:value-of	\$Map-Data/ns:order/ns:orderdatetime
ns:order.ns:orderid.xsl:value-of	\$Map-Data/ns:order/ns:orderid
ns:order.ns:price.xsl:value-of	\$Map-Data/ns:order/ns:price
ns:order.ns:productcode.xsl:value-of	\$Map-Data/ns:order/ns:productcode

3.9 BusinessProcess/createOrderAdapterPublisher.process

3.9.1 Flow Diagram

Flow Diagram: BusinessProcess/createOrderAdapterPublisher.process

PlantUML 1.2023.13

**This version of PlantUML is 744 days old, so you should
consider upgrading from <https://plantuml.com/download>**

[From string (line 18)]

```
@startuml
skinparam shadowing false
skinparam activity {
  BackgroundColor #E6E6FA
  BorderColor #6A5ACD
  ArrowColor #483D8B
  FontSize 11
}
skinparam partition {
  BackgroundColor #F0F0F0
  BorderColor #999999
  FontSize 11
  BorderThickness 2
}
skinparam dpi 300
!pragma maxwidth 600
start #4CAF50
partition "group: Group (transactionGroup)" {
Syntax Error?
```

Property	Value
Total Activity Count	9
AEPublisherActivity type count	1
CallProcessActivity type count	2
CatchActivity type count	1
HTTPSignalInActivity type count	1
HttpRequestActivity type count	1
MapperActivity type count	1
TransactionGroup type count	1
WriteToLogActivity type count	1

3.9.2 Group (TransactionGroup)

Name: Group

Type: TransactionGroup

3.9.2.1 Configurations

Attribute Name	Attribute Value
pd:groupType	transactionGroup
pd:includeCheckpoint	false
pd:serializable	false
pd:transactionType	JDBCTransaction

3.9.3 Log (WriteToLogActivity)

Name: Log

Type: WriteToLogActivity

3.9.3.1 Configurations

Attribute Name	Attribute Value
role	User

3.9.3.2 Mappings

Attribute Name	Attribute Value
ns0:ActivityInput.message.xsl:value-of	concat("Order created by AdapterPublisher: ", \$Start/pfx:orderRequest/order/ns:customer/ns:custome- rid,"-", \$Start/pfx:orderRequest/order/ns:custome...
ns0:ActivityInput.msgCode.xsl:value-of	\$Start/pfx:orderRequest/order/ns:customer/ns:custome- rid

3.9.4 Map Data (MapperActivity)

Name: Map Data

Type: MapperActivity

3.9.4.1 Configurations

Attribute Name	Attribute Value
element	

3.9.4.2 Mappings

Attribute Name	Attribute Value
ns:order.ns:customerid.xsl:value-of	\$Start/pfx:orderRequest/order/ns:customer/ns:custome- rid
ns:order.ns:discountstatus.xsl:value-of	if (\$Start/pfx:orderRequest/order/ns:customer/ns:age>40-) then "Discount applied" else "Discount not eligible"
ns:order.ns:firstname.xsl:value-of	\$Start/pfx:orderRequest/order/ns:customer/ns:firstname
ns:order.ns:lastname.xsl:value-of	\$Start/pfx:orderRequest/order/ns:customer/ns:lastname
ns:order.ns:orderdatetime.xsl:value-of	current-dateTime()
ns:order.ns:orderid.xsl:value-of	""
ns:order.ns:price.xsl:value-of	"1000"
ns:order.ns:productcode.xsl:value-of	"UPS00"

3.9.5 GlobalCatch (CatchActivity)

Name: GlobalCatch

Type: CatchActivity

3.9.5.1 Configurations

Attribute Name	Attribute Value
catchAll	true

3.9.6 Errorhandler (CallProcessActivity)

Name: Errorhandler

Type: CallProcessActivity

3.9.6.1 Configurations

Attribute Name	Attribute Value
processName	/BusinessProcess/LogandErrorHandlerDummy.process

3.9.6.2 Mappings

Attribute Name	Attribute Value
root.ns:ExceptionData.ns:ErrorData.xsl:value-of	\$GlobalCatch/exceptiondata/*
root.ns:ExceptionData.ns:Message.xsl:value-of	\$_error/ns3:ErrorReport/Msg
root.ns:ExceptionData.ns:StackTrace.xsl:value-of	\$_error/ns3:ErrorReport/StackTrace
root.ns:description.xsl:value-of	'Error in Retyrprocess to update records'
root.ns:logLevel.xsl:value-of	\$_globalVariables/ns5:GlobalVariables/LogLevels/LOG- _ERROR
root.ns:processCtx.ns:ProcessName.xsl:value-of	'/Common/RetryProcessErrors'
root.ns:processCtx.ns:processId.xsl:value-of	\$_processContext/ns3:ProcessContext/ProcessId
root.ns:processCtx.ns:projectName.xsl:value-of	\$_processContext/ns3:ProcessContext/ProjectName

3.9.7 UpdateOrderDetails (CallProcessActivity)

Name: UpdateOrderDetails

Type: CallProcessActivity

3.9.7.1 Configurations

Attribute Name	Attribute Value
processName	/BusinessProcess/UpdatePaymentDummy.process

3.9.7.2 Mappings

Attribute Name	Attribute Value
ns:order.ns:customerid.xsl:value-of	\$Map-Data/ns:order/ns:customerid
ns:order.ns:discountstatus.xsl:value-of	\$Map-Data/ns:order/ns:discountstatus
ns:order.ns:firstname.xsl:value-of	\$Map-Data/ns:order/ns:firstname
ns:order.ns:lastname.xsl:value-of	\$Map-Data/ns:order/ns:lastname
ns:order.ns:orderdatetime.xsl:value-of	\$Map-Data/ns:order/ns:orderdatetime
ns:order.ns:orderid.xsl:value-of	\$Map-Data/ns:order/ns:orderid
ns:order.ns:price.xsl:value-of	\$Map-Data/ns:order/ns:price
ns:order.ns:productcode.xsl:value-of	\$Map-Data/ns:order/ns:productcode

3.9.8 Publish to Adapter (AEPublisherActivity)

Name: Publish to Adapter

Type: AEPublisherActivity

3.9.8.1 Configurations

Attribute Name	Attribute Value
ae.aepalette.sharedProperties.adapterService	/Adapters/File/FileAdapterConfiguration. adfiles#adapterService.SubscriptionService
ae.aepalette.sharedProperties.msgFormat	aeRvMsg
ae.aepalette.sharedProperties.outputMeta	/AESchemas/ae/FileAdapter/wire/FileAdapterConfigura- tion.aeschema#class.WriterFileRecord
ae.aepalette.sharedProperties. rvCmSessionDefaultTimeLimit	0
ae.aepalette.sharedProperties.rvCmSessionLedgerFile	./bwdomain.customerOrder-1.%%AppName%%. %%Instanceld%%.ldg
ae.aepalette.sharedProperties.rvCmSessionName	bwdomain.customerOrder-1.%%AppName%%. %%Instanceld%%.CM
ae.aepalette.sharedProperties.rvCmSessionRelayAgent	
ae.aepalette.sharedProperties. rvCmSessionRequireOldMessages	true
ae.aepalette.sharedProperties. rvCmSessionSyncLedger	true
ae.aepalette.sharedProperties.rvSessionDaemon	tcp:7500
ae.aepalette.sharedProperties.rvSessionNetwork	
ae.aepalette.sharedProperties.rvSessionService	7500
ae.aepalette.sharedProperties.rvSubject	domain.customerOrder-1.FileAdapter. FileAdapterConfiguration.SubscriptionService
ae.aepalette.sharedProperties.transportChoice	default
ae.aepalette.sharedProperties.transportType	rvcm
ae.aepalette.sharedProperties.useRequestReply	false
tpPluginEndpointName	SubscriptionServiceEndPoint

3.9.8.2 Mappings

Attribute Name	Attribute Value
aePubInputType.body.xsl:for-each. ns6:WriterFileRecord.age.xsl:value-of	'99'
aePubInputType.body.xsl:for-each. ns6:WriterFileRecord.city.xsl:value-of	'default'
aePubInputType.body.xsl:for-each. ns6:WriterFileRecord.customerid_verbar_.xsl:value-of	ns:customerid
aePubInputType.body.xsl:for-each. ns6:WriterFileRecord.email.xsl:value-of	'dummy@test.com'
aePubInputType.body.xsl:for-each. ns6:WriterFileRecord.firstname.xsl:value-of	ns:firstname
aePubInputType.body.xsl:for-each. ns6:WriterFileRecord.lastname.xsl:value-of	ns:lastname
aePubInputType.body.xsl:for-each. ns6:WriterFileRecord.transactionstatus.xsl:value-of	'Processed'
aePubInputType.body.xsl:for-each. ns6:WriterFileRecord.zipcode.xsl:value-of	'12345'

3.9.9 Send HTTP Request (HttpRequestActivity)

Name: Send HTTP Request

Type: HttpRequestActivity

3.9.9.1 Configurations

Attribute Name	Attribute Value
InputHeaders	
OutputHeaders	
authScheme	NONE
inputOutputVersion	5.3.0
newMimeSupport	true

3.9.10 Wait for HTTP Request (HTTPSignalInActivity)

Name: Wait for HTTP Request

Type: HTTPSignalInActivity

3.9.10.1 Configurations

Attribute Name	Attribute Value
Headers	
_eventTimeout	60000
defaultEncoding	ISO8859_1
inputOutputVersion	5.3.0
newMimeSupport	true
outputMode	String

3.10 BusinessProcess/createOrderDummy.process

3.10.1 Flow Diagram

Flow Diagram: BusinessProcess/createOrderDummy.process

PlantUML 1.2023.13

**This version of PlantUML is 744 days old, so you should
consider upgrading from <https://plantuml.com/download>**

[From string (line 18)]

```
@startuml
skinparam shadowing false
skinparam activity {
  BackgroundColor #E6E6FA
  BorderColor #6A5ACD
  ArrowColor #483D8B
  FontSize 11
}
skinparam partition {
  BackgroundColor #F0F0F0
  BorderColor #999999
  FontSize 11
  BorderThickness 2
}
skinparam dpi 300
!pragma maxwidth 600
start #4CAF50
fork
Syntax error: fork
```

Property	Value
Total Activity Count	15
CallProcessActivity type count	5
CatchActivity type count	1
CriticalSectionGroup type count	1
FileWriteActivity type count	1
JDBCQueryActivity type count	1
JavaMethodActivity type count	1
LoopGroup type count	1
MapperActivity type count	1
TransactionGroup type count	2
WriteToLogActivity type count	1

3.10.2 Group (TransactionGroup)

Name: Group

Type: TransactionGroup

3.10.2.1 Configurations

Attribute Name	Attribute Value
pd:groupType	transactionGroup
pd:includeCheckpoint	false
pd:serializable	false
pd:transactionType	JDBCTransaction

3.10.3 Log (WriteToLogActivity)

Name: Log

Type: WriteToLogActivity

3.10.3.1 Configurations

Attribute Name	Attribute Value
role	User

3.10.3.2 Mappings

Attribute Name	Attribute Value
ns0:ActivityInput.message.xsl:value-of	concat("Order created: ", \$Start/pfx:orderRequest/order/ns:customer/ns:customer- rid,"-", \$Start/pfx:orderRequest/order/ns:customer/ns:firstnam- e,"-Pr...
ns0:ActivityInput.msgCode.xsl:value-of	\$Start/pfx:orderRequest/order/ns:customer/ns:customer- rid

3.10.4 Write File (FileWriteActivity)

Name: Write File

Type: FileWriteActivity

3.10.4.1 Configurations

Attribute Name	Attribute Value
compressFile	None
encoding	text

3.10.5 Group (1) (TransactionGroup)

Name: Group (1)

Type: TransactionGroup

3.10.5.1 Configurations

Attribute Name	Attribute Value
pd:groupType	transactionGroup
pd:includeCheckpoint	false
pd:serializable	false
pd:transactionType	JDBCTransaction

3.10.6 LogandErrorHandlerDummy (CallProcessActivity)

Name: LogandErrorHandlerDummy

Type: CallProcessActivity

3.10.6.1 Configurations

Attribute Name	Attribute Value
processName	/BusinessProcess/LogandErrorHandler.process
processNameXPath	if(\$_globalVariables/ns5:GlobalVariables/Flags/Invoke-SOAPService='yes') then "/BusinessProcess/UpdatePaymentDummy.process" else "/BusinessProcess/...
spawn	true

3.10.7 Group (2) (CriticalSectionGroup)

Name: Group (2)

Type: CriticalSectionGroup

3.10.7.1 Configurations

Attribute Name	Attribute Value
pd:groupType	criticalSection
pd:scope	single
pd:serializable	false

3.10.8 Errorhandler (CallProcessActivity)

Name: Errorhandler

Type: CallProcessActivity

3.10.8.1 Configurations

Attribute Name	Attribute Value
processName	/BusinessProcess/LogandErrorHandlerDummy.process

3.10.8.2 Mappings

Attribute Name	Attribute Value
root.ns:ExceptionData.ns:ErrorData.xsl:value-of	\$GlobalCatch/exceptiondata/*
root.ns:ExceptionData.ns:Message.xsl:value-of	\$_error/ns3:ErrorReport/Msg
root.ns:ExceptionData.ns:StackTrace.xsl:value-of	\$_error/ns3:ErrorReport/StackTrace
root.ns:description.xsl:value-of	'Error in Retyrprocess to update records'
root.ns:logLevel.xsl:value-of	\$_globalVariables/ns5:GlobalVariables/LogLevels/LOG- _ERROR
root.ns:processCtx.ns:ProcessName.xsl:value-of	'/Common/RetryProcessErrors'
root.ns:processCtx.ns:processId.xsl:value-of	\$_processContext/ns3:ProcessContext/ProcessId
root.ns:processCtx.ns:projectName.xsl:value-of	\$_processContext/ns3:ProcessContext/ProjectName

3.10.9 Group (3) (LoopGroup)

Name: Group (3)

Type: LoopGroup

3.10.9.1 Configurations

Attribute Name	Attribute Value
pd:accumulateOutput	false
pd:activityOutputName	
pd:groupType	inputLoop
pd:indexSlot	i
pd:over	"test"
pd:serializable	false

3.10.10 LogandErrorHandler (CallProcessActivity)

Name: LogandErrorHandler

Type: CallProcessActivity

3.10.10.1 Configurations

Attribute Name	Attribute Value
processName	/BusinessProcess/LogandErrorHandler.process
spawn	true

3.10.11 Map Data (MapperActivity)

Name: Map Data

Type: MapperActivity

3.10.11.1 Configurations

Attribute Name	Attribute Value
element	

3.10.11.2 Mappings

Attribute Name	Attribute Value
ns:order.ns:customerid.xsl:value-of	\$Start/pfx:orderRequest/order/ns:customer/ns:customerid
ns:order.ns:discountstatus.xsl:value-of	if (\$Start/pfx:orderRequest/order/ns:customer/ns:age>40-) then "Discount applied" else "Discount not eligible"
ns:order.ns:firstname.xsl:value-of	\$Start/pfx:orderRequest/order/ns:customer/ns:firstname
ns:order.ns:lastname.xsl:value-of	\$Start/pfx:orderRequest/order/ns:customer/ns:lastname
ns:order.ns:orderdatetime.xsl:value-of	current-dateTime()
ns:order.ns:orderid.xsl:value-of	""
ns:order.ns:price.xsl:value-of	"1000"
ns:order.ns:productcode.xsl:value-of	"UPS00"

3.10.12 GlobalCatch (CatchActivity)

Name: GlobalCatch

Type: CatchActivity

3.10.12.1 Configurations

Attribute Name	Attribute Value
catchAll	true

3.10.13 UpdateOrderDetails (CallProcessActivity)

Name: UpdateOrderDetails

Type: CallProcessActivity

3.10.13.1 Configurations

Attribute Name	Attribute Value
processName	/BusinessProcess/UpdatePaymentDummy.process
processNameXPath	if(\$_globalVariables/ns5:GlobalVariables/Flags/Invoke-SOAPService='yes') then "/BusinessProcess/UpdatePaymentDummy.process" else "/BusinessProcess/...

3.10.13.2 Mappings

Attribute Name	Attribute Value
ns:order.ns:customerid.xsl:value-of	\$Map-Data/ns:order/ns:customerid
ns:order.ns:discountstatus.xsl:value-of	\$Map-Data/ns:order/ns:discountstatus
ns:order.ns:firstname.xsl:value-of	\$Map-Data/ns:order/ns:firstname
ns:order.ns:lastname.xsl:value-of	\$Map-Data/ns:order/ns:lastname
ns:order.ns:orderdatetime.xsl:value-of	\$Map-Data/ns:order/ns:orderdatetime
ns:order.ns:orderid.xsl:value-of	\$Map-Data/ns:order/ns:orderid
ns:order.ns:price.xsl:value-of	\$Map-Data/ns:order/ns:price
ns:order.ns:productcode.xsl:value-of	\$Map-Data/ns:order/ns:productcode

3.10.14 JDBC Query (JDBCQueryActivity)

Name: JDBC Query

Type: JDBCQueryActivity

3.10.14.1 Configurations

Attribute Name	Attribute Value
commit	false
emptyStrAsNil	false
jdbcSharedConfig	/Connections/JDBC Connection.sharedjdbc
maxRows	100
statement	select * from temptable
timeout	10

3.10.15 SOAPcreateOrderService (CallProcessActivity)

Name: SOAPcreateOrderService

Type: CallProcessActivity

3.10.15.1 Configurations

Attribute Name	Attribute Value
processName	/TestService/JMS/SOAPcreateOrderService.process

3.10.16 Java Method (JavaMethodActivity)

Name: Java Method

Type: JavaMethodActivity

3.10.16.1 Configurations

Attribute Name	Attribute Value
CacheConstructedClass	false
ConstructDeclaredClass	false
InvokeCleanupMethod	false

3.11 BusinessProcess/createOrderREST.process

3.11.1 Flow Diagram

PlantUML 1.2023.13

**This version of PlantUML is 744 days old, so you should
consider upgrading from <https://plantuml.com/download>**

[From string (line 18)]

```
@startuml
skinparam shadowing false
skinparam activity {
  BackgroundColor #E6E6FA
  BorderColor #6A5ACD
  ArrowColor #483D8B
  FontSize 11
}
skinparam partition {
  BackgroundColor #F0F0F0
  BorderColor #999999
  FontSize 11
  BorderThickness 2
}
skinparam dpi 300
!pragma maxwidth 600
start #4CAF50
partition "group: Group (1) (simpleGroup)" {
  Syntax Error?
```

Property	Value
Total Activity Count	9
CallProcessActivity type count	2
CatchActivity type count	1
JSONRenderActivity type count	1
LoopGroup type count	1
MapperActivity type count	1
TransactionGroup type count	1
WriteToLogActivity type count	2

3.11.2 Group (1) (LoopGroup)

Name: Group (1)

Type: LoopGroup

3.11.2.1 Configurations

Attribute Name	Attribute Value
pd:groupType	simpleGroup
pd:serializable	false

3.11.3 Log (WriteToLogActivity)

Name: Log

Type: WriteToLogActivity

3.11.3.1 Configurations

Attribute Name	Attribute Value
role	User

3.11.3.2 Mappings

Attribute Name	Attribute Value
ns0:ActivityInput.message.xsl:value-of	concat("Order created: ", \$Start/pfx:orderRequest/order/ns:customer/ns:customer- rid,"-", \$Start/pfx:orderRequest/order/ns:customer/ns:firstname- e,"-Pr...
ns0:ActivityInput.msgCode.xsl:value-of	\$Start/pfx:orderRequest/order/ns:customer/ns:customer- rid

3.11.4 Group (TransactionGroup)

Name: Group

Type: TransactionGroup

3.11.4.1 Configurations

Attribute Name	Attribute Value
pd:groupType	transactionGroup
pd:includeCheckpoint	false
pd:serializable	false
pd:transactionType	JDBCTransaction

3.11.5 Log (WriteToLogActivity)

Name: Log

Type: WriteToLogActivity

3.11.5.1 Configurations

Attribute Name	Attribute Value
role	User

3.11.5.2 Mappings

Attribute Name	Attribute Value
ns0:ActivityInput.message.xsl:value-of	concat("Order created: ", \$Start/pfx:orderRequest/order/ns:customer/ns:customerid,"-", \$Start/pfx:orderRequest/order/ns:customer/ns:firstname,"-Pr...
ns0:ActivityInput.msgCode.xsl:value-of	\$Start/pfx:orderRequest/order/ns:customer/ns:customerid

3.11.6 Map Data (MapperActivity)

Name: Map Data

Type: MapperActivity

3.11.6.1 Configurations

Attribute Name	Attribute Value
element	

3.11.6.2 Mappings

Attribute Name	Attribute Value
ns:order.ns:customerid.xsl:value-of	\$Start/pfx:orderRequest/order/ns:customer/ns:customerid
ns:order.ns:discountstatus.xsl:value-of	if (\$Start/pfx:orderRequest/order/ns:customer/ns:age>40-) then "Discount applied" else "Discount not eligible"
ns:order.ns:firstname.xsl:value-of	\$Start/pfx:orderRequest/order/ns:customer/ns:firstname
ns:order.ns:lastname.xsl:value-of	\$Start/pfx:orderRequest/order/ns:customer/ns:lastname
ns:order.ns:orderdatetime.xsl:value-of	current-dateTime()
ns:order.ns:orderid.xsl:value-of	""
ns:order.ns:price.xsl:value-of	"1000"
ns:order.ns:productcode.xsl:value-of	"UPS00"

3.11.7 GlobalCatch (CatchActivity)

Name: GlobalCatch

Type: CatchActivity

3.11.7.1 Configurations

Attribute Name	Attribute Value
catchAll	true

3.11.8 Errorhandler (CallProcessActivity)

Name: Errorhandler

Type: CallProcessActivity

3.11.8.1 Configurations

Attribute Name	Attribute Value
processName	/BusinessProcess/LogandErrorHandlerDummy.process

3.11.8.2 Mappings

Attribute Name	Attribute Value
root.ns:ExceptionData.ns:ErrorData.xsl:value-of	\$GlobalCatch/exceptiondata/*
root.ns:ExceptionData.ns:Message.xsl:value-of	\$_error/ns3:ErrorReport/Msg
root.ns:ExceptionData.ns:StackTrace.xsl:value-of	\$_error/ns3:ErrorReport/StackTrace
root.ns:description.xsl:value-of	'Error in Retyrprocess to update records'
root.ns:logLevel.xsl:value-of	\$_globalVariables/ns5:GlobalVariables/LogLevels/LOG- _ERROR
root.ns:processCtx.ns:ProcessName.xsl:value-of	'/Common/RetryProcessErrors'
root.ns:processCtx.ns:processId.xsl:value-of	\$_processContext/ns3:ProcessContext/ProcessId
root.ns:processCtx.ns:projectName.xsl:value-of	\$_processContext/ns3:ProcessContext/ProjectName

3.11.9 UpdateOrderDetails (CallProcessActivity)

Name: UpdateOrderDetails

Type: CallProcessActivity

3.11.9.1 Configurations

Attribute Name	Attribute Value
processName	/BusinessProcess/UpdatePaymentDummy.process

3.11.9.2 Mappings

Attribute Name	Attribute Value
ns:order.ns:customerid.xsl:value-of	\$Map-Data/ns:order/ns:customerid
ns:order.ns:discountstatus.xsl:value-of	\$Map-Data/ns:order/ns:discountstatus
ns:order.ns:firstname.xsl:value-of	\$Map-Data/ns:order/ns:firstname
ns:order.ns:lastname.xsl:value-of	\$Map-Data/ns:order/ns:lastname
ns:order.ns:orderdatetime.xsl:value-of	\$Map-Data/ns:order/ns:orderdatetime
ns:order.ns:orderid.xsl:value-of	\$Map-Data/ns:order/ns:orderid
ns:order.ns:price.xsl:value-of	\$Map-Data/ns:order/ns:price
ns:order.ns:productcode.xsl:value-of	\$Map-Data/ns:order/ns:productcode

3.11.10 Render JSON (JSONRenderActivity)

Name: Render JSON

Type: JSONRenderActivity

3.11.10.1 Configurations

Attribute Name	Attribute Value
ActivityInputEditor	
BadgerfishCheck	false
SchemaType	xsdType

3.11.10.2 Mappings

Attribute Name	Attribute Value
ns6:ActivityInputClass.Status.Code.xsl:value-of	000
ns6:ActivityInputClass.Status.Message.xsl:value-of	"Update Received"

3.12 Service/Initialization_onstartup.process

3.12.1 Flow Diagram

PlantUML 1.2023.13

**This version of PlantUML is 744 days old, so you should
consider upgrading from <https://plantuml.com/download>**

[From string (line 18)]

```
@startuml
skinparam shadowing false
skinparam activity {
  BackgroundColor #E6E6FA
  BorderColor #6A5ACD
  ArrowColor #483D8B
  FontSize 11
}
skinparam partition {
  BackgroundColor #F0F0F0
  BorderColor #999999
  FontSize 11
  BorderThickness 2
}
skinparam dpi 300
!pragma maxwidth 600
start #4CAF50
:<&puzzle-piece> onStartup \nonStartup;
Syntax Error?
```

Property	Value
Total Activity Count	4
OnStartupEventSource type count	1
SetSharedVariableActivity type count	2
WriteToLogActivity type count	1

3.12.2 onStartup (OnStartupEventSource)

Name: onStartup

Type: OnStartupEventSource

3.12.3 SetVariable_counter (SetSharedVariableActivity)

Name: SetVariable_counter

Type: SetSharedVariableActivity

3.12.3.1 Configurations

Attribute Name	Attribute Value
showResult	true
variableConfig	/SharedVariables/SharedVariable_counter. sharedvariable

3.12.3.2 Mappings

Attribute Name	Attribute Value
root.counter.xsl:value-of	1

3.12.4 SetVariable_timestamp (SetSharedVariableActivity)

Name: SetVariable_timestamp

Type: SetSharedVariableActivity

3.12.4.1 Configurations

Attribute Name	Attribute Value
showResult	true
variableConfig	/SharedVariables/JobSharedVariable_timestamp. jobsharedvariable

3.12.4.2 Mappings

Attribute Name	Attribute Value
root.timestamp.xsl:value-of	current-dateTime()

3.12.5 Log (WriteToLogActivity)

Name: Log

Type: WriteToLogActivity

3.12.5.1 Configurations

Attribute Name	Attribute Value
role	User

3.12.5.2 Mappings

Attribute Name	Attribute Value
ns:ActivityInput.message.xsl:value-of	"Counter shared variable and Timestamp job shared variable are initialized on start up of the service."
ns:ActivityInput.msgCode.xsl:value-of	000

3.13 Service/orderServiceFILE.process

3.13.1 Flow Diagram

Flow Diagram: Service/orderServiceFILE.process

PlantUML 1.2023.13

**This version of PlantUML is 744 days old, so you should
consider upgrading from <https://plantuml.com/download>**

[From string (line 18)]

```
@startuml
skinparam shadowing false
skinparam activity {
  BackgroundColor #E6E6FA
  BorderColor #6A5ACD
  ArrowColor #483D8B
  FontSize 11
}
skinparam partition {
  BackgroundColor #F0F0F0
  BorderColor #999999
  FontSize 11
  BorderThickness 2
}
skinparam dpi 300
!pragma maxwidth 600
start #4CAF50
:<&file> $$$File Poller$$$\nFileEventSourceResource;
Syntax Error?
```

Property	Value
Total Activity Count	17
CallProcessActivity type count	2
CatchActivity type count	1
FileCopyActivity type count	1
FileEventSource type count	1
FileRemoveActivity type count	1
FileRenameActivity type count	1
FileWriteActivity type count	1
GetSharedVariableActivity type count	1
ListFilesActivity type count	1
LoopGroup type count	1
NullActivity type count	1
ParseActivity type count	1
SetSharedVariableActivity type count	1
SleepActivity type count	1
WriteToLogActivity type count	2

3.13.2 File Poller (FileEventSource)

Name: File Poller

Type: FileEventSource

3.13.2.1 Configurations

Attribute Name	Attribute Value
createEvent	true
deleteEvent	true
encoding	text
fileName	C:\tibco510\raks\in\orderServiceFILE.txt
includeCurrent	true
mode	files-and-directories
modifyEvent	true
pollInterval	5
sortby	File Name
sortorder	descending

3.13.3 Group (LoopGroup)

Name: Group

Type: LoopGroup

3.13.3.1 Configurations

Attribute Name	Attribute Value
pd:accumulateOutput	false
pd:activityOutputName	
pd:groupType	inputLoop
pd:indexSlot	i
pd:iterationElementSlot	customers
pd:over	\$Parse-Data/Output/Rows/root
pd:serializable	false

3.13.4 createOrder (CallProcessActivity)

Name: createOrder

Type: CallProcessActivity

3.13.4.1 Configurations

Attribute Name	Attribute Value
processName	/BusinessProcess/createOrderDummy.process

3.13.4.2 Mappings

Attribute Name	Attribute Value
ns:orderRequest.order.ns2:customer.ns2:age.xsl:value-of	\$customers/root/age
ns:orderRequest.order.ns2:customer.ns2:city.xsl:value-of	\$customers/root/city
ns:orderRequest.order.ns2:customer.ns2:customerid.xsl:value-of	\$customers/root/customerid
ns:orderRequest.order.ns2:customer.ns2:email.xsl:value-of	\$customers/root/email
ns:orderRequest.order.ns2:customer.ns2:firstname.xsl:value-of	\$customers/root/firstname
ns:orderRequest.order.ns2:customer.ns2:lastname.xsl:value-of	\$customers/root/lastname
ns:orderRequest.order.ns2:customer.ns2:transactionstatus.xsl:value-of	\$customers/root/transactionstatus
ns:orderRequest.order.ns2:customer.ns2:zipcode.xsl:value-of	\$customers/root/zipcode

3.13.5 Parse Data (ParseActivity)

Name: Parse Data

Type: ParseActivity

3.13.5.1 Configurations

Attribute Name	Attribute Value
Encoding	ASCII
InputType	String
ParseSharedConfig	/DataFormat/OrderServiceDataFormat.sharedparse

3.13.5.2 Mappings

Attribute Name	Attribute Value
Input.noOfRecords.xsl:value-of	-1
Input.text.xsl:value-of	\$File-Poller/ns1:EventSourceOutputTextClass/fileContent/textContent

3.13.6 Catch (CatchActivity)

Name: Catch

Type: CatchActivity

3.13.6.1 Configurations

Attribute Name	Attribute Value
catchAll	true

3.13.7 LogandErrorHandler (CallProcessActivity)

Name: LogandErrorHandler

Type: CallProcessActivity

3.13.7.1 Configurations

Attribute Name	Attribute Value
processName	/BusinessProcess/LogandErrorHandlerDummy.process

3.13.7.2 Mappings

Attribute Name	Attribute Value
root.ns2:ExceptionData.ns2:ErrorData.xsl:value-of	\$_error/ns4:ErrorReport/Data/*
root.ns2:ExceptionData.ns2:Message.xsl:value-of	\$_error/ns4:ErrorReport/Msg
root.ns2:ExceptionData.ns2:StackTrace.xsl:value-of	\$_error/ns4:ErrorReport/ProcessStack
root.ns2:description.xsl:value-of	'exception handling activated'
root.ns2:logLevel.xsl:value-of	\$_globalVariables/ns3:GlobalVariables/LogLevels/LOG-ERROR
root.ns2:processCtx.ns2:ProcessName.xsl:value-of	'/Common/RetryProcessErrors'
root.ns2:processCtx.ns2:processId.xsl:value-of	\$_processContext/ns4:ProcessContext/ProcessId
root.ns2:processCtx.ns2:projectName.xsl:value-of	\$_processContext/ns4:ProcessContext/ProjectName

3.13.8 Log (WriteToLogActivity)

Name: Log

Type: WriteToLogActivity

3.13.8.1 Configurations

Attribute Name	Attribute Value
role	User

3.13.8.2 Mappings

Attribute Name	Attribute Value
ns5:ActivityInput.message.xsl:value-of	concat("File Poller Order Service Started with counter value =", \$SetVariable/root/counter)

3.13.9 Log-1 (WriteToLogActivity)

Name: Log-1

Type: WriteToLogActivity

3.13.9.1 Configurations

Attribute Name	Attribute Value
role	User

3.13.9.2 Mappings

Attribute Name	Attribute Value
ns5:ActivityInput.message.xsl:value-of	"File Poller Order Service Terminated"

3.13.10 Copy File (FileCopyActivity)

Name: Copy File

Type: FileCopyActivity

3.13.10.1 Configurations

Attribute Name	Attribute Value
createMissingDirectories	true
overwrite	true

3.13.10.2 Mappings

Attribute Name	Attribute Value
ns1:CopyActivityConfig.fromFileName.xsl:value-of	\$File-Poller/ns1:EventSourceOutputTextClass/fileInfo/fullName
ns1:CopyActivityConfig.toFileName.xsl:value-of	concat(\$_globalVariables/ns3:GlobalVariables/Connections/FILE/outDir, \$_globalVariables/ns3:GlobalVariables/Connections/FILE/fileName)

3.13.11 Rename File (FileRenameActivity)

Name: Rename File

Type: FileRenameActivity

3.13.11.1 Configurations

Attribute Name	Attribute Value
createMissingDirectories	true

3.13.11.2 Mappings

Attribute Name	Attribute Value
ns1:RenameActivityConfig.fromFileName.xsl:value-of	concat(\$_globalVariables/ns3:GlobalVariables/Connections/FILE/outDir, \$_globalVariables/ns3:GlobalVariables/Connections/FILE/fileName)
ns1:RenameActivityConfig.toFileName.xsl:value-of	concat(\$_globalVariables/ns3:GlobalVariables/Connections/FILE/outDir, \$_globalVariables/ns3:GlobalVariables/Connections/FILE/fileName,"-",tib:format...

3.13.12 Remove File (FileRemoveActivity)

Name: Remove File

Type: FileRemoveActivity

3.13.12.2 Mappings

Attribute Name	Attribute Value
ns1:RemoveActivityInputClass.fileName.xsl:value-of	concat(\$_globalVariables/ns3:GlobalVariables/Connections/FILE/inDir, \$_globalVariables/ns3:GlobalVariables/Connections/FILE/fileName)

3.13.13 List Files (ListFilesActivity)

Name: List Files

Type: ListFilesActivity

3.13.13.1 Configurations

Attribute Name	Attribute Value
mode	files-and-directories

3.13.13.2 Mappings

Attribute Name	Attribute Value
ns1:ListFilesActivityConfig.fileName.xsl:value-of	\$_globalVariables/ns3:GlobalVariables/Connections/FILE/outDir

3.13.14 Write File (FileWriteActivity)

Name: Write File

Type: FileWriteActivity

3.13.14.1 Configurations

Attribute Name	Attribute Value
append	true
compressFile	None
createMissingDirectories	true
encoding	text

3.13.14.2 Mappings

Attribute Name	Attribute Value
ns1:WriteActivityInputTextClass.fileName.xsl:value-of	concat(\$_globalVariables/ns3:GlobalVariables/Connections/FILE/outDir, "Log.txt")
ns1:WriteActivityInputTextClass.textContent.xsl:value-of	concat("log file updated at ", current-dateTime(), " ")

3.13.15 Null (NullActivity)

Name: Null

Type: NullActivity

3.13.16 Sleep (SleepActivity)

Name: Sleep

Type: SleepActivity

3.13.16.2 Mappings

Attribute Name	Attribute Value
ns6:SleepInputSchema.IntervalInMillisec.xsl:value-of	1000

3.13.17 GetVariable (GetSharedVariableActivity)

Name: GetVariable

Type: GetSharedVariableActivity

3.13.17.1 Configurations

Attribute Name	Attribute Value
variableConfig	/SharedVariables/SharedVariable_counter. sharedvariable

3.13.18 SetVariable (SetSharedVariableActivity)

Name: SetVariable

Type: SetSharedVariableActivity

3.13.18.1 Configurations

Attribute Name	Attribute Value
showResult	true
variableConfig	/SharedVariables/SharedVariable_counter. sharedvariable

3.13.18.2 Mappings

Attribute Name	Attribute Value
root.counter.xsl:value-of	\$GetVariable/root/counter +1

3.14 Service/orderServiceJMS.process

3.14.1 Flow Diagram

Flow Diagram: Service/orderServiceJMS.process

PlantUML 1.2023.13

**This version of PlantUML is 744 days old, so you should
consider upgrading from <https://plantuml.com/download>**

[From string (line 18)]

```
@startuml
skinparam shadowing false
skinparam activity {
  BackgroundColor #E6E6FA
  BorderColor #6A5ACD
  ArrowColor #483D8B
  FontSize 11
}
skinparam partition {
  BackgroundColor #F0F0F0
  BorderColor #999999
  FontSize 11
  BorderThickness 2
}
skinparam dpi 300
!pragma maxwidth 600
start #4CAF50
:<&envelope-closed> **JMS Queue Receiver**\nJMSQueueEventSource;
Syntax Error?
```

Property	Value
Total Activity Count	19
CallProcessActivity type count	3
CatchActivity type count	1
CriticalSectionGroup type count	1
FileWriteActivity type count	1
JMSQueueEventSource type count	1
JMSReplyActivity type count	1
MapperActivity type count	1
NullActivity type count	3
WriteToLogActivity type count	6
class type count	1

3.14.2 JMS Queue Receiver (JMSQueueEventSource)

Name: JMS Queue Receiver

Type: JMSQueueEventSource

3.14.2.1 Configurations

Attribute Name	Attribute Value
ApplicationProperties	/Connections/JMS Application Properties.sharedjmsapp
ConfigurableHeaders	PERSISTENT 0 4
ConnectionReference	/Connections/JMS Connection.sharedjmscon
PermittedMessageType	Text
SessionAttributes	false 1 1 temp

3.14.3 Group (CriticalSectionGroup)

Name: Group

Type: CriticalSectionGroup

3.14.3.1 Configurations

Attribute Name	Attribute Value
pd:groupType	criticalSection
pd:scope	single
pd:serializable	false

3.14.4 createOrder (CallProcessActivity)

Name: createOrder

Type: CallProcessActivity

3.14.4.1 Configurations

Attribute Name	Attribute Value
processName	/BusinessProcess/createOrderDummy.process

3.14.4.2 Mappings

Attribute Name	Attribute Value
ns:orderRequest.order.ns2:customer.ns2:age.xsl:value-of	\$Map-Data/ns2:customer/ns2:age
ns:orderRequest.order.ns2:customer.ns2:city.xsl:value-of	\$Map-Data/ns2:customer/ns2:city
ns:orderRequest.order.ns2:customer.ns2:customerid.xsl:value-of	\$Map-Data/ns2:customer/ns2:customerid
ns:orderRequest.order.ns2:customer.ns2:email.xsl:value-of	\$Map-Data/ns2:customer/ns2:email
ns:orderRequest.order.ns2:customer.ns2:firstname.xsl:value-of	\$Map-Data/ns2:customer/ns2:firstname
ns:orderRequest.order.ns2:customer.ns2:lastname.xsl:value-of	\$Map-Data/ns2:customer/ns2:lastname
ns:orderRequest.order.ns2:customer.ns2:transactionstatus.xsl:value-of	\$Map-Data/ns2:customer/ns2:transactionstatus
ns:orderRequest.order.ns2:customer.ns2:zipcode.xsl:value-of	\$Map-Data/ns2:customer/ns2:zipcode

3.14.5 Catch (CatchActivity)

Name: Catch

Type: CatchActivity

3.14.5.1 Configurations

Attribute Name	Attribute Value
catchAll	true

3.14.6 LogandErrorHandler (CallProcessActivity)

Name: LogandErrorHandler

Type: CallProcessActivity

3.14.6.1 Configurations

Attribute Name	Attribute Value
processName	/BusinessProcess/LogandErrorHandlerDummy.process

3.14.6.2 Mappings

Attribute Name	Attribute Value
root.ns2:ExceptionData.ns2:ErrorData.xsl:value-of	\$_error/ns4:ErrorReport/Data/*
root.ns2:ExceptionData.ns2:Message.xsl:value-of	\$_error/ns4:ErrorReport/Msg
root.ns2:ExceptionData.ns2:StackTrace.xsl:value-of	\$_error/ns4:ErrorReport/ProcessStack
root.ns2:description.xsl:value-of	'exception handling activated'
root.ns2:logLevel.xsl:value-of	\$_globalVariables/ns3:GlobalVariables/LogLevels/LOG- _ERROR
root.ns2:processCtx.ns2:ProcessName.xsl:value-of	'/Common/RetryProcessErrors'
root.ns2:processCtx.ns2:processId.xsl:value-of	\$_processContext/ns4:ProcessContext/ProcessId
root.ns2:processCtx.ns2:projectName.xsl:value-of	\$_processContext/ns4:ProcessContext/ProjectName

3.14.7 Log (WriteToLogActivity)

Name: Log

Type: WriteToLogActivity

3.14.7.1 Configurations

Attribute Name	Attribute Value
role	User

3.14.7.2 Mappings

Attribute Name	Attribute Value
ns5:ActivityInput.message.xsl:value-of	"JMS Order Service Started"

3.14.8 Log-1 (WriteToLogActivity)

Name: Log-1

Type: WriteToLogActivity

3.14.8.1 Configurations

Attribute Name	Attribute Value
role	User

3.14.8.2 Mappings

Attribute Name	Attribute Value
ns5:ActivityInput.message.xsl:value-of	"JMS Order Service Terminated"

3.14.9 Invoke REST API (class)

Name: Invoke REST API

Type: class

3.14.9.1 Configurations

Attribute Name	Attribute Value
WADLBaseURL	http://localhost:8085/orderCreateAPI
WADLContent	
WADLPaths	customerDetails
WADLReference	/WADL/OrderService.wadl
authChoiceUI	No Authentication
enableProtocolUI	WADL
restInputReferNode	
restMethodIDUI	POST_CreateCustomer
restMethodUI	POST
restOutputReferNode	
restResponseType	JSON
restURI	/orderCreateAPI/customerDetails

3.14.9.2 Mappings

Attribute Name	Attribute Value
ns12:ActivityInput.Parameters.Header.age.xsl:value-of	\$Map-Data/ns2:customer/ns2:age
ns12:ActivityInput.Parameters.Header.city.xsl:value-of	\$Map-Data/ns2:customer/ns2:city
ns12:ActivityInput.Parameters.Header.customerid.xsl:value-of	\$Map-Data/ns2:customer/ns2:customerid
ns12:ActivityInput.Parameters.Header.email.xsl:value-of	\$Map-Data/ns2:customer/ns2:email
ns12:ActivityInput.Parameters.Header.firstname.xsl:value-of	\$Map-Data/ns2:customer/ns2:firstname
ns12:ActivityInput.Parameters.Header.lastname.xsl:value-of	\$Map-Data/ns2:customer/ns2:lastname
ns12:ActivityInput.Parameters.Header.transactionstatus.xsl:value-of	\$Map-Data/ns2:customer/ns2:transactionstatus
ns12:ActivityInput.Parameters.Header.zipcode.xsl:value-of	\$Map-Data/ns2:customer/ns2:zipcode

3.14.10 Log-1-1 (WriteToLogActivity)

Name: Log-1-1

Type: WriteToLogActivity

3.14.10.1 Configurations

Attribute Name	Attribute Value
role	User

3.14.10.2 Mappings

Attribute Name	Attribute Value
ns5:ActivityInput.message.xsl:value-of	"Order Handling REST API Invocation begins"

3.14.11 Log-1-1-1 (WriteToLogActivity)

Name: Log-1-1-1

Type: WriteToLogActivity

3.14.11.1 Configurations

Attribute Name	Attribute Value
role	User

3.14.11.2 Mappings

Attribute Name	Attribute Value
ns5:ActivityInput.message.xsl:value-of	"Order Handling REST API Invocation Completed"

3.14.12 Null (NullActivity)

Name: Null

Type: NullActivity

3.14.13 Log-1-1-2 (WriteToLogActivity)

Name: Log-1-1-2

Type: WriteToLogActivity

3.14.13.1 Configurations

Attribute Name	Attribute Value
role	User

3.14.13.2 Mappings

Attribute Name	Attribute Value
ns5:ActivityInput.message.xsl:value-of	"Order Handling SOAP Service Invocation begins"

3.14.14 Log-1-1-1-1 (WriteToLogActivity)

Name: Log-1-1-1-1

Type: WriteToLogActivity

3.14.14.1 Configurations

Attribute Name	Attribute Value
role	User

3.14.14.2 Mappings

Attribute Name	Attribute Value
ns5:ActivityInput.message.xsl:value-of	"Order Handling SOAP Service Invocation Completed"

3.14.15 createOrderService (CallProcessActivity)

Name: createOrderService

Type: CallProcessActivity

3.14.15.1 Configurations

Attribute Name	Attribute Value
processName	/TestService/JMS/SOAPcreateOrderService.process

3.14.15.2 Mappings

Attribute Name	Attribute Value
xsl:copy-of	\$Map-Data/ns2:customer

3.14.16 Map Data (MapperActivity)

Name: Map Data

Type: MapperActivity

3.14.16.1 Configurations

Attribute Name	Attribute Value
element	

3.14.16.2 Mappings

Attribute Name	Attribute Value
xsl:for-each.ns2:customer.ns2:age.xsl:value-of	age
xsl:for-each.ns2:customer.ns2:city.xsl:value-of	city
xsl:for-each.ns2:customer.ns2:customerid.xsl:value-of	customerid
xsl:for-each.ns2:customer.ns2:email.xsl:value-of	email
xsl:for-each.ns2:customer.ns2:firstname.xsl:value-of	firstname
xsl:for-each.ns2:customer.ns2:lastname.xsl:value-of	lastname
xsl:for-each.ns2:customer.ns2:transactionstatus.xsl:value-of	transactionstatus
xsl:for-each.ns2:customer.ns2:zipcode.xsl:value-of	zipcode

3.14.17 Null-1 (NullActivity)

Name: Null-1

Type: NullActivity

3.14.18 Reply to JMS Message (JMSReplyActivity)

Name: Reply to JMS Message

Type: JMSReplyActivity

3.14.18.1 Configurations

Attribute Name	Attribute Value
ApplicationProperties	/Connections/JMS Application Properties.sharedjmsapp
ConfigurableHeaders	PERSISTENT 0 4 JMS Queue Receiver
PermittedMessageType	Text
SessionAttributes	false 1 1

3.14.18.2 Mappings

Attribute Name	Attribute Value
ns6:ActivityInput.Body.xsl:value-of	"Order Processed by OrderServiceJMS"
ns6:ActivityInput.xsl:copy-of	\$JMS-Queue-Receiver/ns6:ActivityOutput/OtherProperties

3.14.19 Null-2 (NullActivity)

Name: Null-2

Type: NullActivity

3.14.20 Write File (FileWriteActivity)

Name: Write File

Type: FileWriteActivity

3.14.20.1 Configurations

Attribute Name	Attribute Value
append	true
compressFile	None
createMissingDirectories	true
encoding	text

3.14.20.2 Mappings

Attribute Name	Attribute Value
ns1:WriteActivityInputTextClass.fileName.xml:value-of	concat(\$_globalVariables/ns3:GlobalVariables/Connections/FILE/outDir, "Log.txt")
ns1:WriteActivityInputTextClass.textContent.xml:value-of	concat("log file updated at ", current-dateTime(), " ")

3.15 Service/orderServiceREST.process

3.15.1 Flow Diagram

Flow Diagram: Service/orderServiceREST.process

PlantUML 1.2023.13

**This version of PlantUML is 744 days old, so you should
consider upgrading from <https://plantuml.com/download>**

[From string (line 18)]

```
@startuml
skinparam shadowing false
skinparam activity {
  BackgroundColor #E6E6FA
  BorderColor #6A5ACD
  ArrowColor #483D8B
  FontSize 11
}
skinparam partition {
  BackgroundColor #F0F0F0
  BorderColor #999999
  FontSize 11
  BorderThickness 2
}
skinparam dpi 300
!pragma maxwidth 600
start #4CAF50
switch (HTTP Receiver)
Syntax Error?
```

Property	Value
Total Activity Count	5
CallProcessActivity type count	1
HTTPEventSource type count	1
RestAdapterActivity type count	1
WriteToLogActivity type count	2

3.15.2 HTTP Receiver (HTTPEventSource)

Name: HTTP Receiver

Type: HTTPEventSource

3.15.2.1 Configurations

Attribute Name	Attribute Value
Headers	
defaultEncoding	ISO8859_1
inputOutputVersion	5.3.0
newMimeSupport	true
outputMode	String
sharedChannel	/Connections/HTTP-Connection-REST.sharedhttp

3.15.3 REST Dispatch and Reply (RestAdapterActivity)

Name: REST Dispatch and Reply

Type: RestAdapterActivity

3.15.3.1 Configurations

Attribute Name	Attribute Value
EnableWADLReference	true
RestService	
WADLReference	/WADL/OrderService.wadl
eventSource	HTTP Receiver

3.15.3.2 Mappings

Attribute Name	Attribute Value
ns0:ActivityInputClass.tmp.xsl:value-of	\$HTTP-Receiver/ProcessStarterOutput/Method

3.15.4 Log (WriteToLogActivity)

Name: Log

Type: WriteToLogActivity

3.15.4.1 Configurations

Attribute Name	Attribute Value
role	User

3.15.4.2 Mappings

Attribute Name	Attribute Value
ns1:ActivityInput.message.xsl:value-of	"REST API for Order Service Started"

3.15.5 Log-1 (WriteToLogActivity)

Name: Log-1

Type: WriteToLogActivity

3.15.5.1 Configurations

Attribute Name	Attribute Value
role	User

3.15.5.2 Mappings

Attribute Name	Attribute Value
ns1:ActivityInput.message.xsl:value-of	"REST API for Order Service Terminated"

3.15.6 createOrderService (CallProcessActivity)

Name: createOrderService

Type: CallProcessActivity

3.15.6.1 Configurations

Attribute Name	Attribute Value
processName	/TestService/createOrderService.process

3.16 Service/orderServiceSCHEDULER.process

3.16.1 Flow Diagram

PlantUML 1.2023.13

**This version of PlantUML is 744 days old, so you should
consider upgrading from <https://plantuml.com/download>**

[From string (line 18)]

```
@startuml
skinparam shadowing false
skinparam activity {
  BackgroundColor #E6E6FA
  BorderColor #6A5ACD
  ArrowColor #483D8B
  FontSize 11
}
skinparam partition {
  BackgroundColor #F0F0F0
  BorderColor #999999
  FontSize 11
  BorderThickness 2
}
skinparam dpi 300
!pragma maxwidth 600
start #4CAF50
:<&clock> Timer \ntimer;
Syntax Error?
```

Property	Value
Total Activity Count	9
CallProcessActivity type count	2
CatchActivity type count	1
FileReadActivity type count	1
LoopGroup type count	1
ParseActivity type count	1
TimerEventSource type count	1
WriteToLogActivity type count	2

3.16.2 Timer (TimerEventSource)

Name: Timer

Type: TimerEventSource

3.16.2.1 Configurations

Attribute Name	Attribute Value
Frequency	false
FrequencyIndex	Minute
StartTime	1742409227000
TimeInterval	1

3.16.3 Group (LoopGroup)

Name: Group

Type: LoopGroup

3.16.3.1 Configurations

Attribute Name	Attribute Value
pd:accumulateOutput	false
pd:activityOutputName	
pd:groupType	inputLoop
pd:indexSlot	i
pd:iterationElementSlot	customers
pd:over	\$Parse-Data/Output/Rows/root
pd:serializable	false

3.16.4 createOrder (CallProcessActivity)

Name: createOrder

Type: CallProcessActivity

3.16.4.1 Configurations

Attribute Name	Attribute Value
processName	/BusinessProcess/createOrderDummy.process

3.16.4.2 Mappings

Attribute Name	Attribute Value
ns:orderRequest.order.ns2:customer.ns2:age.xsl:value-of	\$customers/root/age
ns:orderRequest.order.ns2:customer.ns2:city.xsl:value-of	\$customers/root/city
ns:orderRequest.order.ns2:customer.ns2:customerid.xsl:value-of	\$customers/root/customerid
ns:orderRequest.order.ns2:customer.ns2:email.xsl:value-of	\$customers/root/email
ns:orderRequest.order.ns2:customer.ns2:firstname.xsl:value-of	\$customers/root/firstname
ns:orderRequest.order.ns2:customer.ns2:lastname.xsl:value-of	\$customers/root/lastname
ns:orderRequest.order.ns2:customer.ns2:transactionstatus.xsl:value-of	\$customers/root/transactionstatus
ns:orderRequest.order.ns2:customer.ns2:zipcode.xsl:value-of	\$customers/root/zipcode

3.16.5 Parse Data (ParseActivity)

Name: Parse Data

Type: ParseActivity

3.16.5.1 Configurations

Attribute Name	Attribute Value
Encoding	ASCII
InputType	String
ParseSharedConfig	/DataFormat/OrderServiceDataFormat.sharedparse

3.16.5.2 Mappings

Attribute Name	Attribute Value
Input.noOfRecords.xml:value-of	-1
Input.text.xml:value-of	\$Read-File/ns1:ReadActivityOutputTextClass/fileContent/textContent

3.16.6 Catch (CatchActivity)

Name: Catch

Type: CatchActivity

3.16.6.1 Configurations

Attribute Name	Attribute Value
catchAll	true

3.16.7 LogandErrorHandler (CallProcessActivity)

Name: LogandErrorHandler

Type: CallProcessActivity

3.16.7.1 Configurations

Attribute Name	Attribute Value
processName	/BusinessProcess/LogandErrorHandlerDummy.process

3.16.7.2 Mappings

Attribute Name	Attribute Value
root.ns2:ExceptionData.ns2:ErrorData.xml:value-of	\$_error/ns4:ErrorReport/Data/*
root.ns2:ExceptionData.ns2:Message.xml:value-of	\$_error/ns4:ErrorReport/Msg
root.ns2:ExceptionData.ns2:StackTrace.xml:value-of	\$_error/ns4:ErrorReport/ProcessStack
root.ns2:description.xml:value-of	'exception handling activated'
root.ns2:logLevel.xml:value-of	\$_globalVariables/ns3:GlobalVariables/LogLevels/LOG_ERROR
root.ns2:processCtx.ns2:ProcessName.xml:value-of	'/Common/RetryProcessErrors'
root.ns2:processCtx.ns2:processId.xml:value-of	\$_processContext/ns4:ProcessContext/ProcessId
root.ns2:processCtx.ns2:projectName.xml:value-of	\$_processContext/ns4:ProcessContext/ProjectName

3.16.8 Read File (FileReadActivity)

Name: Read File

Type: FileReadActivity

3.16.8.1 Configurations

Attribute Name	Attribute Value
encoding	text

3.16.8.2 Mappings

Attribute Name	Attribute Value
ns5:ReadActivityInputClass.fileName.xsl:value-of	\$_globalVariables/ns3:GlobalVariables/Connections/FI-LE/inputFileName

3.16.9 Log (WriteToLogActivity)

Name: Log

Type: WriteToLogActivity

3.16.9.1 Configurations

Attribute Name	Attribute Value
role	User

3.16.9.2 Mappings

Attribute Name	Attribute Value
ns12:ActivityInput.message.xsl:value-of	"Scheduled Order Service Started"

3.16.10 Log-1 (WriteToLogActivity)

Name: Log-1

Type: WriteToLogActivity

3.16.10.1 Configurations

Attribute Name	Attribute Value
role	User

3.16.10.2 Mappings

Attribute Name	Attribute Value
ns12:ActivityInput.message.xsl:value-of	"Scheduled Order Service Terminated"

3.17 Service/orderServiceSOAP.process

3.17.1 Flow Diagram

Flow Diagram: Service/orderServiceSOAP.process

PlantUML 1.2023.13

*This version of PlantUML is 744 days old, so you should
consider upgrading from <https://plantuml.com/download>*

[From string (line 18)]

```
@startuml
skinparam shadowing false
skinparam activity {
  BackgroundColor #E6E6FA
  BorderColor #6A5ACD
  ArrowColor #483D8B
  FontSize 11
}
skinparam partition {
  BackgroundColor #F0F0F0
  BorderColor #999999
  FontSize 11
  BorderThickness 2
}
skinparam dpi 300
!pragma maxwidth 600
start #4CAF50
:<&cloud> **SOAPEventSource**\nSOAPEventSourceUI;
```

Syntax Error?

Property	Value
Total Activity Count	1
SOAPEventSource type count	1

3.17.2 SOAPEventSource (SOAPEventSource)

Name: SOAPEventSource

Type: SOAPEventSource

3.17.2.1 Configurations

Attribute Name	Attribute Value
embedSchemaComponents	true
embedWsdIComponents	true
httpURI	soapOrderServicePath
operation	Operation
operationStyle	document
portAddressPrefix	
service	pfx:createOrder
sharedChannel	/Connections/HTTP Connection.sharedhttp
soapAction	/Service/Process%20Definition
soapUse	literal
soapVersion	SOAP 1.1
wsdINamespaceRoot	http://xmlns.example. com/1628143989205/OperationImpl

3.18 Service/orderServiceWMQ-NotDoneYet.process

3.18.1 Flow Diagram

PlantUML 1.2023.13

**This version of PlantUML is 744 days old, so you should
consider upgrading from <https://plantuml.com/download>**

[From string (line 18)]

```
@startuml
skinparam shadowing false
skinparam activity {
  BackgroundColor #E6E6FA
  BorderColor #6A5ACD
  ArrowColor #483D8B
  FontSize 11
}
skinparam partition {
  BackgroundColor #F0F0F0
  BorderColor #999999
  FontSize 11
  BorderThickness 2
}
skinparam dpi 300
!pragma maxwidth 600
start #4CAF50
:<&file> stackLogstack\nlog;
Syntax Error?
```

Property	Value
Total Activity Count	17
CallProcessActivity type count	3
CatchActivity type count	1
JMSReplyActivity type count	1
LoopGroup type count	1
MapperActivity type count	1
NullActivity type count	3
RestActivity type count	1
WriteToLogActivity type count	6

3.18.2 Group (LoopGroup)

Name: Group

Type: LoopGroup

3.18.2.1 Configurations

Attribute Name	Attribute Value
pd:accumulateOutput	false
pd:activityOutputName	
pd:groupType	inputLoop
pd:indexSlot	i
pd:iterationElementSlot	customers
pd:over	\$Map-Data/ns2:customer
pd:serializable	false

3.18.3 createOrder (CallProcessActivity)

Name: createOrder

Type: CallProcessActivity

3.18.3.1 Configurations

Attribute Name	Attribute Value
processName	/BusinessProcess/createOrderDummy.process

3.18.3.2 Mappings

Attribute Name	Attribute Value
ns:orderRequest.order.ns2:customer.ns2:age.xsl:value-of	\$Map-Data/ns2:customer/ns2:age
ns:orderRequest.order.ns2:customer.ns2:city.xsl:value-of	\$Map-Data/ns2:customer/ns2:city
ns:orderRequest.order.ns2:customer.ns2:customerid.xsl:value-of	\$Map-Data/ns2:customer/ns2:customerid
ns:orderRequest.order.ns2:customer.ns2:email.xsl:value-of	\$Map-Data/ns2:customer/ns2:email
ns:orderRequest.order.ns2:customer.ns2:firstname.xsl:value-of	\$Map-Data/ns2:customer/ns2:firstname
ns:orderRequest.order.ns2:customer.ns2:lastname.xsl:value-of	\$Map-Data/ns2:customer/ns2:lastname
ns:orderRequest.order.ns2:customer.ns2:transactionstatus.xsl:value-of	\$Map-Data/ns2:customer/ns2:transactionstatus
ns:orderRequest.order.ns2:customer.ns2:zipcode.xsl:value-of	\$Map-Data/ns2:customer/ns2:zipcode

3.18.4 Catch (CatchActivity)

Name: Catch

Type: CatchActivity

3.18.4.1 Configurations

Attribute Name	Attribute Value
catchAll	true

3.18.5 LogandErrorHandler (CallProcessActivity)

Name: LogandErrorHandler

Type: CallProcessActivity

3.18.5.1 Configurations

Attribute Name	Attribute Value
processName	/BusinessProcess/LogandErrorHandlerDummy.process

3.18.5.2 Mappings

Attribute Name	Attribute Value
root.ns2:ExceptionData.ns2:ErrorData.xsl:value-of	\$_error/ns4:ErrorReport/Data/*
root.ns2:ExceptionData.ns2:Message.xsl:value-of	\$_error/ns4:ErrorReport/Msg
root.ns2:ExceptionData.ns2:StackTrace.xsl:value-of	\$_error/ns4:ErrorReport/ProcessStack
root.ns2:description.xsl:value-of	'exception handling activated'
root.ns2:logLevel.xsl:value-of	\$_globalVariables/ns3:GlobalVariables/LogLevels/LOG- _ERROR
root.ns2:processCtx.ns2:ProcessName.xsl:value-of	'/Common/RetryProcessErrors'
root.ns2:processCtx.ns2:processId.xsl:value-of	\$_processContext/ns4:ProcessContext/ProcessId
root.ns2:processCtx.ns2:projectName.xsl:value-of	\$_processContext/ns4:ProcessContext/ProjectName

3.18.6 Log (WriteToLogActivity)

Name: Log

Type: WriteToLogActivity

3.18.6.1 Configurations

Attribute Name	Attribute Value
role	User

3.18.6.2 Mappings

Attribute Name	Attribute Value
ns5:ActivityInput.message.xsl:value-of	"JMS Order Service Started"

3.18.7 Log-1 (WriteToLogActivity)

Name: Log-1

Type: WriteToLogActivity

3.18.7.1 Configurations

Attribute Name	Attribute Value
role	User

3.18.7.2 Mappings

Attribute Name	Attribute Value
ns5:ActivityInput.message.xsl:value-of	"JMS Order Service Terminated"

3.18.8 Invoke REST API (RestActivity)

Name: Invoke REST API

Type: RestActivity

3.18.8.1 Configurations

Attribute Name	Attribute Value
WADLBaseURL	http://localhost:8085/orderCreateAPI
WADLContent	
WADLPaths	customerDetails
WADLReference	/WADL/OrderService.wadl
authChoiceUI	No Authentication
enableProtocolUI	WADL
restInputReferNode	
restMethodIDUI	POST_CreateCustomer
restMethodUI	POST
restOutputReferNode	
restResponseType	JSON
restURI	/orderCreateAPI/customerDetails

3.18.8.2 Mappings

Attribute Name	Attribute Value
ns12:ActivityInput.Parameters.Header.age.xsl:value-of	\$Map-Data/ns2:customer/ns2:age
ns12:ActivityInput.Parameters.Header.city.xsl:value-of	\$Map-Data/ns2:customer/ns2:city
ns12:ActivityInput.Parameters.Header.customerid.xsl:value-of	\$Map-Data/ns2:customer/ns2:customerid
ns12:ActivityInput.Parameters.Header.email.xsl:value-of	\$Map-Data/ns2:customer/ns2:email
ns12:ActivityInput.Parameters.Header.firstname.xsl:value-of	\$Map-Data/ns2:customer/ns2:firstname
ns12:ActivityInput.Parameters.Header.lastname.xsl:value-of	\$Map-Data/ns2:customer/ns2:lastname
ns12:ActivityInput.Parameters.Header.transactionstatus.xsl:value-of	\$Map-Data/ns2:customer/ns2:transactionstatus
ns12:ActivityInput.Parameters.Header.zipcode.xsl:value-of	\$Map-Data/ns2:customer/ns2:zipcode

3.18.9 Log-1-1 (WriteToLogActivity)

Name: Log-1-1

Type: WriteToLogActivity

3.18.9.1 Configurations

Attribute Name	Attribute Value
role	User

3.18.9.2 Mappings

Attribute Name	Attribute Value
ns5:ActivityInput.message.xsl:value-of	"Order Handling REST API Invocation begins"

3.18.10 Log-1-1-1 (WriteToLogActivity)

Name: Log-1-1-1

Type: WriteToLogActivity

3.18.10.1 Configurations

Attribute Name	Attribute Value
role	User

3.18.10.2 Mappings

Attribute Name	Attribute Value
ns5:ActivityInput.message.xsl:value-of	"Order Handling REST API Invocation Completed"

3.18.11 Null (NullActivity)

Name: Null

Type: NullActivity

3.18.12 Log-1-1-2 (WriteToLogActivity)

Name: Log-1-1-2

Type: WriteToLogActivity

3.18.12.1 Configurations

Attribute Name	Attribute Value
role	User

3.18.12.2 Mappings

Attribute Name	Attribute Value
ns5:ActivityInput.message.xsl:value-of	"Order Handling SOAP Service Invocation begins"

3.18.13 Log-1-1-1-1 (WriteToLogActivity)

Name: Log-1-1-1-1

Type: WriteToLogActivity

3.18.13.1 Configurations

Attribute Name	Attribute Value
role	User

3.18.13.2 Mappings

Attribute Name	Attribute Value
ns5:ActivityInput.message.xsl:value-of	"Order Handling SOAP Service Invocation Completed"

3.18.14 createOrderService (CallProcessActivity)

Name: createOrderService

Type: CallProcessActivity

3.18.14.1 Configurations

Attribute Name	Attribute Value
processName	/TestService/JMS/SOAPcreateOrderService.process

3.18.14.2 Mappings

Attribute Name	Attribute Value
xsl:copy-of	\$Map-Data/ns2:customer

3.18.15 Map Data (MapperActivity)

Name: Map Data

Type: MapperActivity

3.18.15.1 Configurations

Attribute Name	Attribute Value
element	

3.18.15.2 Mappings

Attribute Name	Attribute Value
xsl:for-each.ns2:customer.ns2:age.xsl:value-of	age
xsl:for-each.ns2:customer.ns2:city.xsl:value-of	city
xsl:for-each.ns2:customer.ns2:customerid.xsl:value-of	customerid
xsl:for-each.ns2:customer.ns2:email.xsl:value-of	email
xsl:for-each.ns2:customer.ns2:firstname.xsl:value-of	firstname
xsl:for-each.ns2:customer.ns2:lastname.xsl:value-of	lastname
xsl:for-each.ns2:customer.ns2:transactionstatus.xsl:value-of	transactionstatus
xsl:for-each.ns2:customer.ns2:zipcode.xsl:value-of	zipcode

3.18.16 Null-1 (NullActivity)

Name: Null-1

Type: NullActivity

3.18.17 Reply to JMS Message (JMSReplyActivity)

Name: Reply to JMS Message

Type: JMSReplyActivity

3.18.17.1 Configurations

Attribute Name	Attribute Value
ApplicationProperties	/Connections/JMS Application Properties.sharedjmsapp
ConfigurableHeaders	PERSISTENT 0 4 JMS Queue Receiver
PermittedMessageType	Text
SessionAttributes	false 1 1

3.18.17.2 Mappings

Attribute Name	Attribute Value
ns6:ActivityInput.Body.xsl:value-of	"Order Processed by OrderServiceJMS"
ns6:ActivityInput.xsl:copy-of	\$JMS-Queue-Receiver/ns6:ActivityOutput/OtherProperties

3.18.18 Null-2 (NullActivity)

Name: Null-2

Type: NullActivity

3.19 Service/poc_password.process

3.19.1 Flow Diagram

Flow Diagram: Service/poc_password.process

PlantUML 1.2023.13

**This version of PlantUML is 744 days old, so you should
consider upgrading from <https://plantuml.com/download>**

[From string (line 18)]

```
@startuml
skinparam shadowing false
skinparam activity {
  BackgroundColor #E6E6FA
  BorderColor #6A5ACD
  ArrowColor #483D8B
  FontSize 11
}
skinparam partition {
  BackgroundColor #F0F0F0
  BorderColor #999999
  FontSize 11
  BorderThickness 2
}
skinparam dpi 300
!pragma maxwidth 600
start #4CAF50
:<&code> **Java Code**\njava;
```

Syntax Error?

Property	Value
Total Activity Count	1
JavaActivity type count	1

3.19.2 Java Code (JavaActivity)

Name: Java Code

Type: JavaActivity

3.19.2.1 Configurations

Attribute Name	Attribute Value
byteCode	poc_passwordJavaCode yv66vgAAADcAKwkACAAcCQAIAB0KAAkAHggAHwc- AlAoAlQAIcGAFACMHACQHACUBAAJpbgEAEkxqYX- ZhL2xhbmcvU3RyaW5nOwEAA291dA...
fileName	poc_passwordJavaCode
fullsource	
inputData	in string optional
outputData	out string optional
packageName	Service.poc_password

3.19.2.2 Mappings

Attribute Name	Attribute Value
javaCodeActivityInput.in.xml:value-of	""

3.20 TestService/JMS/JMSQReqRep.process

3.20.1 Flow Diagram

Flow Diagram: TestService/JMS/JMSQReqRep.process

PlantUML 1.2023.13

**This version of PlantUML is 744 days old, so you should
consider upgrading from <https://plantuml.com/download>**

[From string (line 18)]

```
@startuml
skinparam shadowing false
skinparam activity {
  BackgroundColor #E6E6FA
  BorderColor #6A5ACD
  ArrowColor #483D8B
  FontSize 11
}
skinparam partition {
  BackgroundColor #F0F0F0
  BorderColor #999999
  FontSize 11
  BorderThickness 2
}
skinparam dpi 300
!pragma maxwidth 600
start #4CAF50
:<&envelope-closed> JMS Queue Requestor \n JMS Queue RequestReply;
Syntax Error?
```

Property	Value
Total Activity Count	1
JMSQueueRequestReplyActivity type count	1

3.20.2 JMS Queue Requestor (JMSQueueRequestReplyActivity)

Name: JMS Queue Requestor

Type: JMSQueueRequestReplyActivity

3.20.2.1 Configurations

Attribute Name	Attribute Value
ApplicationProperties	/Connections/JMS Application Properties.sharedjmsapp
ConfigurableHeaders	PERSISTENT 0 4
ConnectionReference	/Connections/JMS Connection.sharedjmscon
PermittedMessageType	Text
SessionAttributes	false 1 1 temp

3.20.2.2 Mappings

Attribute Name	Attribute Value
ns:ActivityInput.Body.xml:value-of	"EMS Message payload for Queue Request Reply"
ns:ActivityInput.OtherProperties.age.xml:value-of	'40'
ns:ActivityInput.OtherProperties.city.xml:value-of	'Super City'
ns:ActivityInput.OtherProperties.customerid.xml:value-of	12345
ns:ActivityInput.OtherProperties.email.xml:value-of	'test@test.com'
ns:ActivityInput.OtherProperties.firstname.xml:value-of	'Rakesh'
ns:ActivityInput.OtherProperties.lastname.xml:value-of	'Kumar'
ns:ActivityInput.OtherProperties.transactionstatus.xml:value-of	'Open'
ns:ActivityInput.OtherProperties.zipcode.xml:value-of	12345

3.21 TestService/JMS/JMSQSender.process

3.21.1 Flow Diagram

Flow Diagram: TestService/JMS/JMSQSender.process

PlantUML 1.2023.13

**This version of PlantUML is 744 days old, so you should
consider upgrading from <https://plantuml.com/download>**

[From string (line 18)]

```
@startuml
skinparam shadowing false
skinparam activity {
  BackgroundColor #E6E6FA
  BorderColor #6A5ACD
  ArrowColor #483D8B
  FontSize 11
}
skinparam partition {
  BackgroundColor #F0F0F0
  BorderColor #999999
  FontSize 11
  BorderThickness 2
}
skinparam dpi 300
!pragma maxwidth 600
start #4CAF50
:<&envelope-closed> **JMS Queue Sender**\nJMSQueueSend;
Syntax Error?
```

Property	Value
Total Activity Count	1
JMSQueueSendActivity type count	1

3.21.2 JMS Queue Sender (JMSQueueSendActivity)

Name: JMS Queue Sender

Type: JMSQueueSendActivity

3.21.2.1 Configurations

Attribute Name	Attribute Value
ApplicationProperties	/Connections/JMS Application Properties.sharedjmsapp
ConfigurableHeaders	PERSISTENT 0 4
ConnectionReference	/Connections/JMS Connection.sharedjmscon
PermittedMessageType	Text
SessionAttributes	false 1 1 temp

3.21.2.2 Mappings

Attribute Name	Attribute Value
ns:ActivityInput.Body.xml:value-of	"EMS Message payload"
ns:ActivityInput.OtherProperties.age.xml:value-of	'40'
ns:ActivityInput.OtherProperties.city.xml:value-of	'Super City'
ns:ActivityInput.OtherProperties.customerid.xml:value-of	12345
ns:ActivityInput.OtherProperties.email.xml:value-of	'test@test.com'
ns:ActivityInput.OtherProperties.firstname.xml:value-of	'Rakesh'
ns:ActivityInput.OtherProperties.lastname.xml:value-of	'Kumar'
ns:ActivityInput.OtherProperties.transactionstatus.xml:value-of	'Open'
ns:ActivityInput.OtherProperties.zipcode.xml:value-of	12345

3.22 TestService/JMS/SOAPcreateOrderService.process

3.22.1 Flow Diagram

PlantUML 1.2023.13

**This version of PlantUML is 744 days old, so you should
consider upgrading from <https://plantuml.com/download>**

[From string (line 18)]

```
@startuml
skinparam shadowing false
skinparam activity {
  BackgroundColor #E6E6FA
  BorderColor #6A5ACD
  ArrowColor #483D8B
  FontSize 11
}
skinparam partition {
  BackgroundColor #F0F0F0
  BorderColor #999999
  FontSize 11
  BorderThickness 2
}
skinparam dpi 300
!pragma maxwidth 600
start #4CAF50
:<&cloud> SOAPRequestReply\nSOAPSndReceiveUI;
Syntax Error?
```

Property	Value
Total Activity Count	1
SOAPSndReceiveActivity type count	1

3.22.2 SOAPRequestReply (SOAPSndReceiveActivity)

Name: SOAPRequestReply

Type: SOAPSndReceiveActivity

3.22.2.1 Configurations

Attribute Name	Attribute Value
authScheme	NONE
endpointURL	http://localhost:9090/Service/orderService.serviceagent/createOrderEndpoint1
operation	Operation
service	pfx:orderService
servicePort	createOrderEndpoint1
soapAction	/Service/orderService.serviceagent/createOrderEndpoint1/Operation
soapAttachmentStyle	SwA
timeout	0
timeoutType	Seconds

3.22.2.2 Mappings

Attribute Name	Attribute Value
inputMessage.xsl:copy-of	\$Start/ns:customer

3.23 TestService/Others/orderServiceFILEADAPTERPUBLISHER.process

3.23.1 Flow Diagram

Flow Diagram: TestService/Others/orderServiceFILEADAPTERPUBLISHER.process

PlantUML 1.2023.13

**This version of PlantUML is 744 days old, so you should
consider upgrading from <https://plantuml.com/download>**

[From string (line 18)]

```
@startuml
skinparam shadowing false
skinparam activity {
  BackgroundColor #E6E6FA
  BorderColor #6A5ACD
  ArrowColor #483D8B
  FontSize 11
}
skinparam partition {
  BackgroundColor #F0F0F0
  BorderColor #999999
  FontSize 11
  BorderThickness 2
}
skinparam dpi 300
!pragma maxwidth 600
start #4CAF50
:<&file> File PollernFileEventSourceResource;
Syntax Error?
```

Property	Value
Total Activity Count	9
CallProcessActivity type count	2
CatchActivity type count	1
FileEventSource type count	1
FileWriteActivity type count	1
LoopGroup type count	1
ParseActivity type count	1
WriteToLogActivity type count	2

3.23.2 File Poller (FileEventSource)

Name: File Poller

Type: FileEventSource

3.23.2.1 Configurations

Attribute Name	Attribute Value
createEvent	true
deleteEvent	true
encoding	text
fileName	C:\tibco510\raks\in\orderServiceFILE.txt
includeCurrent	true
mode	files-and-directories
modifyEvent	true
pollInterval	5
sortby	File Name
sortorder	descending

3.23.3 Group (LoopGroup)

Name: Group

Type: LoopGroup

3.23.3.1 Configurations

Attribute Name	Attribute Value
pd:accumulateOutput	false
pd:activityOutputName	
pd:groupType	inputLoop
pd:indexSlot	i
pd:iterationElementSlot	customers
pd:over	\$Parse-Data/Output/Rows/root
pd:serializable	false

3.23.4 createOrder (CallProcessActivity)

Name: createOrder

Type: CallProcessActivity

3.23.4.1 Configurations

Attribute Name	Attribute Value
processName	/BusinessProcess/createOrderAdapterPublisher. process

3.23.4.2 Mappings

Attribute Name	Attribute Value
ns:orderRequest.order.ns2:customer.ns2:age.xsl:value-of	\$customers/root/age
ns:orderRequest.order.ns2:customer.ns2:city.xsl:value-of	\$customers/root/city
ns:orderRequest.order.ns2:customer.ns2:customerid.xsl:value-of	\$customers/root/customerid
ns:orderRequest.order.ns2:customer.ns2:email.xsl:value-of	\$customers/root/email
ns:orderRequest.order.ns2:customer.ns2:firstname.xsl:value-of	\$customers/root/firstname
ns:orderRequest.order.ns2:customer.ns2:lastname.xsl:value-of	\$customers/root/lastname
ns:orderRequest.order.ns2:customer.ns2:transactionstatus.xsl:value-of	\$customers/root/transactionstatus
ns:orderRequest.order.ns2:customer.ns2:zipcode.xsl:value-of	\$customers/root/zipcode

3.23.5 Parse Data (ParseActivity)

Name: Parse Data

Type: ParseActivity

3.23.5.1 Configurations

Attribute Name	Attribute Value
Encoding	ASCII
InputType	String
ParseSharedConfig	/DataFormat/OrderServiceDataFormat.sharedparse

3.23.5.2 Mappings

Attribute Name	Attribute Value
Input.noOfRecords.xsl:value-of	-1
Input.text.xsl:value-of	\$File-Poller/ns1:EventSourceOuputTextClass/fileContent/textContent

3.23.6 Catch (CatchActivity)

Name: Catch

Type: CatchActivity

3.23.6.1 Configurations

Attribute Name	Attribute Value
catchAll	true

3.23.7 LogandErrorHandler (CallProcessActivity)

Name: LogandErrorHandler

Type: CallProcessActivity

3.23.7.1 Configurations

Attribute Name	Attribute Value
processName	/BusinessProcess/LogandErrorHandlerDummy.process

3.23.7.2 Mappings

Attribute Name	Attribute Value
root.ns2:ExceptionData.ns2:ErrorData.xsl:value-of	\$_error/ns4:ErrorReport/Data/*
root.ns2:ExceptionData.ns2:Message.xsl:value-of	\$_error/ns4:ErrorReport/Msg
root.ns2:ExceptionData.ns2:StackTrace.xsl:value-of	\$_error/ns4:ErrorReport/ProcessStack
root.ns2:description.xsl:value-of	'exception handling activated'
root.ns2:logLevel.xsl:value-of	\$_globalVariables/ns3:GlobalVariables/LogLevels/LOG- _ERROR
root.ns2:processCtx.ns2:ProcessName.xsl:value-of	'/Common/RetryProcessErrors'
root.ns2:processCtx.ns2:processId.xsl:value-of	\$_processContext/ns4:ProcessContext/ProcessId
root.ns2:processCtx.ns2:projectName.xsl:value-of	\$_processContext/ns4:ProcessContext/ProjectName

3.23.8 Log (WriteToLogActivity)

Name: Log

Type: WriteToLogActivity

3.23.8.1 Configurations

Attribute Name	Attribute Value
role	User

3.23.8.2 Mappings

Attribute Name	Attribute Value
ns5:ActivityInput.message.xsl:value-of	"File Poller Order Service Started"

3.23.9 Log-1 (WriteToLogActivity)

Name: Log-1

Type: WriteToLogActivity

3.23.9.1 Configurations

Attribute Name	Attribute Value
role	User

3.23.9.2 Mappings

Attribute Name	Attribute Value
ns5:ActivityInput.message.xsl:value-of	"File Poller Order Service Terminated"

3.23.10 Write File (FileWriteActivity)

Name: Write File

Type: FileWriteActivity

3.23.10.1 Configurations

Attribute Name	Attribute Value
append	true
compressFile	None
createMissingDirectories	true
encoding	text

3.23.10.2 Mappings

Attribute Name	Attribute Value
ns1:WriteActivityInputTextClass.fileName.xsl:value-of	concat(\$_globalVariables/ns3:GlobalVariables/Connections/FILE/outDir, "Log.txt")
ns1:WriteActivityInputTextClass.textContent.xsl:value-of	concat("log file updated at ", current-dateTime(), " ")

3.24 TestService/Others/orderServiceFILEADAPTERSUBSCRIBER.process

3.24.1 Flow Diagram

Flow Diagram: TestService/Others/orderServiceFILEADAPTERSUBSCRIBER.process

PlantUML 1.2023.13

**This version of PlantUML is 744 days old, so you should
consider upgrading from <https://plantuml.com/download>**

[From string (line 18)]

```
@startuml
skinparam shadowing false
skinparam activity {
  BackgroundColor #E6E6FA
  BorderColor #6A5ACD
  ArrowColor #483D8B
  FontSize 11
}
skinparam partition {
  BackgroundColor #F0F0F0
  BorderColor #999999
  FontSize 11
  BorderThickness 2
}
skinparam dpi 300
!pragma maxwidth 600
start #4CAF50
:<&transfer> **Adapter Subscriber<del>naeSubscription;
Syntax Error?
```

Property	Value
Total Activity Count	7
AESubscriberActivity type count	1
CallProcessActivity type count	2
CatchActivity type count	1
LoopGroup type count	1
WriteToLogActivity type count	2

3.24.2 Adapter Subscriber (AESubscriberActivity)

Name: Adapter Subscriber

Type: AESubscriberActivity

3.24.2.1 Configurations

Attribute Name	Attribute Value
ae.aepalette.sharedProperties.adapterService	/Adapters/File/FileAdapterConfiguration. adfiles#adapterService.PublicationService
ae.aepalette.sharedProperties.msgFormat	aeRvMsg
ae.aepalette.sharedProperties.outputMeta	/AESchemas/ae/FileAdapter/wire/FileAdapterConfigura- tion.aeschema#class.DelimitedFileRecord
ae.aepalette.sharedProperties. rvCmSessionDefaultTimeLimit	0
ae.aepalette.sharedProperties.rvCmSessionLedgerFile	./bwdomain.customerOrder-1.%%AppName%%. %%InstanceId%%.ldg
ae.aepalette.sharedProperties.rvCmSessionName	bwdomain.customerOrder-1.%%AppName%%. %%InstanceId%%.CM
ae.aepalette.sharedProperties.rvCmSessionRelayAgent	
ae.aepalette.sharedProperties. rvCmSessionRequireOldMessages	true
ae.aepalette.sharedProperties. rvCmSessionSyncLedger	true
ae.aepalette.sharedProperties.rvSessionDaemon	tcp:7500
ae.aepalette.sharedProperties.rvSessionNetwork	
ae.aepalette.sharedProperties.rvSessionService	7500
ae.aepalette.sharedProperties.rvSubject	domain.customerOrder-1.FileAdapter. FileAdapterConfiguration.PublicationService
ae.aepalette.sharedProperties.transportChoice	default
ae.aepalette.sharedProperties.transportType	rvcm
ae.aepalette.sharedProperties.useRequestReply	false
tpPluginEndpointName	PublicationServiceEndPoint

3.24.3 Group (LoopGroup)

Name: Group

Type: LoopGroup

3.24.3.1 Configurations

Attribute Name	Attribute Value
pd:accumulateOutput	false
pd:activityOutputName	
pd:groupType	inputLoop
pd:indexSlot	i
pd:iterationElementSlot	customers
pd:over	\$Adapter-Subscriber/ProcessStarterOutput/body/pfx:DelimitedFileRecord
pd:serializable	false

3.24.4 createOrder (CallProcessActivity)

Name: createOrder

Type: CallProcessActivity

3.24.4.1 Configurations

Attribute Name	Attribute Value
processName	/BusinessProcess/createOrderDummy.process

3.24.4.2 Mappings

Attribute Name	Attribute Value
ns:orderRequest.order.xsl:for-each.ns2:customer.ns2:age.xsl:value-of	age
ns:orderRequest.order.xsl:for-each.ns2:customer.ns2:city.xsl:value-of	city
ns:orderRequest.order.xsl:for-each.ns2:customer.ns2:customerid.xsl:value-of	customerid
ns:orderRequest.order.xsl:for-each.ns2:customer.ns2:email.xsl:value-of	email
ns:orderRequest.order.xsl:for-each.ns2:customer.ns2:firstname.xsl:value-of	firstname
ns:orderRequest.order.xsl:for-each.ns2:customer.ns2:lastname.xsl:value-of	lastname
ns:orderRequest.order.xsl:for-each.ns2:customer.ns2:transactionstatus.xsl:value-of	transactionstatus
ns:orderRequest.order.xsl:for-each.ns2:customer.ns2:zipcode.xsl:value-of	zipcode

3.24.5 Catch (CatchActivity)

Name: Catch

Type: CatchActivity

3.24.5.1 Configurations

Attribute Name	Attribute Value
catchAll	true

3.24.6 LogandErrorHandler (CallProcessActivity)

Name: LogandErrorHandler

Type: CallProcessActivity

3.24.6.1 Configurations

Attribute Name	Attribute Value
processName	/BusinessProcess/LogandErrorHandlerDummy.process

3.24.6.2 Mappings

Attribute Name	Attribute Value
root.ns2:ExceptionData.ns2:ErrorData.xsl:value-of	\$_error/ns4:ErrorReport/Data/*
root.ns2:ExceptionData.ns2:Message.xsl:value-of	\$_error/ns4:ErrorReport/Msg
root.ns2:ExceptionData.ns2:StackTrace.xsl:value-of	\$_error/ns4:ErrorReport/ProcessStack
root.ns2:description.xsl:value-of	'exception handling activated'
root.ns2:logLevel.xsl:value-of	\$_globalVariables/ns3:GlobalVariables/LogLevels/LOG- _ERROR
root.ns2:processCtx.ns2:ProcessName.xsl:value-of	'/Common/RetryProcessErrors'
root.ns2:processCtx.ns2:processId.xsl:value-of	\$_processContext/ns4:ProcessContext/ProcessId
root.ns2:processCtx.ns2:projectName.xsl:value-of	\$_processContext/ns4:ProcessContext/ProjectName

3.24.7 Log (WriteToLogActivity)

Name: Log

Type: WriteToLogActivity

3.24.7.1 Configurations

Attribute Name	Attribute Value
role	User

3.24.7.2 Mappings

Attribute Name	Attribute Value
ns5:ActivityInput.message.xsl:value-of	"File Adapter Subscriber Order Service Started"

3.24.8 Log-1 (WriteToLogActivity)

Name: Log-1

Type: WriteToLogActivity

3.24.8.1 Configurations

Attribute Name	Attribute Value
role	User

3.24.8.2 Mappings

Attribute Name	Attribute Value
ns5:ActivityInput.message.xsl:value-of	"File Adapter Subscriber Order Service Terminated"

3.25 TestService/REST/Process Definition.process

3.25.1 Flow Diagram

Flow Diagram: TestService/REST/Process Definition.process

PlantUML 1.2023.13

**This version of PlantUML is 744 days old, so you should
consider upgrading from <https://plantuml.com/download>**

[From string (line 18)]

```
@startuml
skinparam shadowing false
skinparam activity {
  BackgroundColor #E6E6FA
  BorderColor #6A5ACD
  ArrowColor #483D8B
  FontSize 11
}
skinparam partition {
  BackgroundColor #F0F0F0
  BorderColor #999999
  FontSize 11
  BorderThickness 2
}
skinparam dpi 300
!pragma maxwidth 600
start #4CAF50
:<&cloud> Invoke REST API REST Activity;
Syntax Error?
```

Property	Value
Total Activity Count	1
RestActivity type count	1

3.25.2 Invoke REST API (RestActivity)

Name: Invoke REST API

Type: RestActivity

3.25.2.1 Configurations

Attribute Name	Attribute Value
WADLBaseURL	http://localhost:8085/orderCreateAPI
WADLContent	
WADLPaths	customerDetails
WADLReference	/WADL/OrderService.wadl
authChoiceUI	No Authentication
enableProtocolUI	WADL
restInputReferNode	
restMethodIDUI	POST_CreateCustomer
restMethodUI	POST
restOutputReferNode	
restResponseType	JSON
restURI	/orderCreateAPI/customerDetails

3.25.2.2 Mappings

Attribute Name	Attribute Value
ns:ActivityInput.Parameters.Header.age.xsl:value-of	"40"
ns:ActivityInput.Parameters.Header.city.xsl:value-of	"SuperCity"
ns:ActivityInput.Parameters.Header.customerid.xsl:value-of	12345
ns:ActivityInput.Parameters.Header.email.xsl:value-of	"test@test.com"
ns:ActivityInput.Parameters.Header.firstname.xsl:value-of	"Rakesh"
ns:ActivityInput.Parameters.Header.lastname.xsl:value-of	"Kumar"
ns:ActivityInput.Parameters.Header.transactionstatus.xsl:value-of	"Completed"
ns:ActivityInput.Parameters.Header.zipcode.xsl:value-of	"12345"

3.26 TestService/createOrderService.process

3.26.1 Flow Diagram

Flow Diagram: TestService/createOrderService.process

PlantUML 1.2023.13

**This version of PlantUML is 744 days old, so you should
consider upgrading from <https://plantuml.com/download>**

[From string (line 18)]

```
@startuml
skinparam shadowing false
skinparam activity {
  BackgroundColor #E6E6FA
  BorderColor #6A5ACD
  ArrowColor #483D8B
  FontSize 11
}
skinparam partition {
  BackgroundColor #F0F0F0
  BorderColor #999999
  FontSize 11
  BorderThickness 2
}
skinparam dpi 300
!pragma maxwidth 600
start #4CAF50
:<&cloud> **SOAPRequestReply<sup>ack</sup>\nSOAPSendReceiveUI;
Syntax Error?
```

Property	Value
Total Activity Count	1
SOAPSendReceiveActivity type count	1

3.26.2 SOAPRequestReply (SOAPSendReceiveActivity)

Name: SOAPRequestReply

Type: SOAPSendReceiveActivity

3.26.2.1 Configurations

Attribute Name	Attribute Value
authScheme	NONE
endpointURL	http://localhost:9090/Service/orderService.serviceagent/createOrderEndpoint1
operation	Operation
service	pfx:orderService
servicePort	createOrderEndpoint1
soapAction	/Service/orderService.serviceagent/createOrderEndpoint1/Operation
soapAttachmentStyle	SwA
timeout	0
timeoutType	Seconds

3.26.2.2 Mappings

Attribute Name	Attribute Value
inputMessage.ns:customer.ns:age.xsl:value-of	36
inputMessage.ns:customer.ns:city.xsl:value-of	"Bangalore"
inputMessage.ns:customer.ns:customerid.xsl:value-of	"XYZ133"
inputMessage.ns:customer.ns:email.xsl:value-of	"test@ibm.com"
inputMessage.ns:customer.ns:firstname.xsl:value-of	"Michael"
inputMessage.ns:customer.ns:lastname.xsl:value-of	"Smith"
inputMessage.ns:customer.ns:transactionstatus.xsl:value-of	"order placed"
inputMessage.ns:customer.ns:zipcode.xsl:value-of	"500600"

4 Connections & Configurations

4.1 Archive Info

4.1.1 customerOrder.archive

Path: customerOrder.archive

Property	Value
enterpriseArchive.addServiceSettableGvars	true
enterpriseArchive.authorProperty	Rakesh.Kumar@ibm.com
enterpriseArchive.fileLocationProperty	C:\Users\raksj\Documents\IBM\tmp\customerOrder.ear
enterpriseArchive.name	customerOrder
enterpriseArchive.processArchive. authorProperty	Rakesh.Kumar@ibm.com
enterpriseArchive.processArchive. processProperty	/Service/orderService.serviceagent,/Service/orderServiceFILE. process,/Service/orderServiceJMS.process, /Service/orderServiceREST.process,/Service/or...
enterpriseArchive.processArchive. resourceType	process.archive.resource
enterpriseArchive.sharedArchive. authorProperty	0016SR744
enterpriseArchive.sharedArchive. resourceType	shared.archive.resource
enterpriseArchive.versionProperty	4

4.2 HTTP Connection

4.2.1 HTTP Connection.sharedhttp

Path: Connections/HTTP Connection.sharedhttp

Property	Value
config.Host	localhost
config.HttpConnectionProperties.row. PropertyDefaultValue	60000
config.HttpConnectionProperties.row. PropertyName	connectionTimeOut (ms)
config.Port	9090
config.serverType	Tomcat

4.2.2 HTTP-Connection-REST.sharedhttp

Path: Connections/HTTP-Connection-REST.sharedhttp

Property	Value
config.Host	localhost
config.HttpConnectionProperties.row. PropertyDefaultValue	60000
config.HttpConnectionProperties.row. PropertyName	connectionTimeOut (ms)
config.Port	8085
config.serverType	Tomcat

4.3 JDBC Connection

4.3.1 JDBC Connection.sharedjdbc

Path: Connections/JDBC Connection.sharedjdbc

Property	Value
config.UseSharedJndiConfig	false
config.connectionType	JDBC
config.driver	com.mysql.jdbc.Driver
config.location	jdbc:mysql://localhost:3306/mydb
config.loginTimeout	10
config.maxConnections	10
config.password	my_pass
config.user	myuser
name	JDBC Connection
resourceType	ae.shared.JDBCSharedResource

4.4 JMS Connection

4.4.1 JMS Connection.sharedjmscon

Path: Connections/JMS Connection.sharedjmscon

Property	Value
config.ConnectionAttributes. autoGenClientID	true
config.NamingEnvironment. NamingInitialContextFactory	com.tibco.tibjms.naming.TibjmsInitialContextFactory
config.NamingEnvironment.NamingURL	tibjmsnaming://localhost:7222
config.NamingEnvironment.ProviderURL	tcp://localhost:7222
config.NamingEnvironment. QueueFactoryName	QueueConnectionFactory
config.NamingEnvironment. TopicFactoryName	TopicConnectionFactory
config.NamingEnvironment.UseJNDI	false
config.UseXACF	false
name	JMS Connection
resourceType	ae.shared.JMSConnectionKey

4.5 Job Shared Variable

4.5.1 JobSharedVariable_timestamp.jobsharedvariable

Path: SharedVariables/JobSharedVariable_timestamp.jobsharedvariable

Property	Value
config.initialValue	none
config.xsdString.xsd:element. xsd:complexType.xsd:sequence. xsd:element/@minOccurs	0
config.xsdString.xsd:element. xsd:complexType.xsd:sequence. xsd:element/@name	timestamp
config.xsdString.xsd:element. xsd:complexType.xsd:sequence. xsd:element/@type	xsd:string
name	JobSharedVariable_timestamp
resourceType	ae.shared.jobSharedVariable

4.6 Service Agent Config

4.6.1 orderService.serviceagent

Path: Service/orderService.serviceagent

Property	Value
config.class	com.tibco.bw.service.serviceAgent.ServiceServiceAgent
config.groups.row/@groupName	Default
config.groups.row/@isDefault	true
config.implType	bw
config.interfaceImpl.tab.config.detail.tab. config.epBindings.row.config.epDetail.tab. config.operationStyle	document
config.interfaceImpl.tab.config.detail.tab. config.epBindings.row.config.epDetail.tab. config.sharedChannel	/Connections/HTTP Connection.sharedhttp
config.interfaceImpl.tab.config.detail.tab. config.epBindings.row.config.epDetail.tab. config.soap.operation.general.config. soapAction	/Service/orderService. serviceagent/createOrderEndpoint1/Operation
config.interfaceImpl.tab.config.detail.tab. config.epBindings.row.config.epDetail.tab. config.soap.operation.general.config. soapUse	literal
config.interfaceImpl.tab.config.detail.tab. config.epBindings.row.config.epDetail.tab. config.soapVersion	SOAP 1.1
config.interfaceImpl.tab.config.detail.tab. config.epBindings.row.config.epDetail.tab. config.transport.config.httpURI	/Service/orderService.serviceagent/createOrderEndpoint1
config.interfaceImpl.tab.config.detail.tab. config.epBindings.row.config.epDetail.tab. config.transport.config. useBasicAuthentication	false
config.interfaceImpl.tab.config.detail.tab. config.epBindings.row.config.epDetail.tab. tabName	soap.service.transport.ui.details.tab.label
config.interfaceImpl.tab.config.detail.tab. config.epBindings.row.config.epDetail.tab. tabType	details
config.interfaceImpl.tab.config.detail.tab. config.operations.row/@opImpl	/BusinessProcess/createOrderDummy.process
config.interfaceImpl.tab.config.detail.tab. config.operations.row/@opName	Operation
config.interfaceImpl.tab.config.detail.tab. tabName	service.definition.ep.tab.label
config.interfaceImpl.tab.config.detail.tab. tabType	ep
config.interfaceImpl.tab.config. wsdlDetail/@location	/WSDL/customerorder.wsdl
config.interfaceImpl.tab.config. wsdlDetail/@ns	http://xmlns.example.com/1628143989205
config.interfaceImpl.tab.config. wsdlDetail/@portType	createOrder
config.interfaceImpl.tab.tabName	createOrder

4.7 Shared Variable

4.7.1 SharedVariable_counter.sharedvariable

Path: SharedVariables/SharedVariable_counter.sharedvariable

Property	Value
config.initialValue	byData
config.initialValueData	<?xml version="1.0" encoding="UTF-8"?> <root> <counter>1</counter> </root>
config.multi-engine	false
config.persistent	false
config.xsdString.xsd:element. xsd:complexType.xsd:sequence. xsd:element/@minOccurs	0
config.xsdString.xsd:element. xsd:complexType.xsd:sequence. xsd:element/@name	counter
config.xsdString.xsd:element. xsd:complexType.xsd:sequence. xsd:element/@type	xsd:string
name	SharedVariable_counter
resourceType	ae.shared.sharedVariable

4.8 WADL Resource

4.8.1 OrderService.wadl

Path: WADL/OrderService.wadl

Property	Value
resources.resource.method.request. representation/@mediaType	application/json
resources.resource.method.response. representation/@mediaType	application/json

4.9 WSDL

4.9.1 ConcreteOrderService.wsdl

Path: TestService/ConcreteOrderService.wsdl

Property	Value
wsdl:binding.soap:binding/@style	document
wsdl:binding.soap:binding/@transport	http://schemas.xmlsoap.org/soap/http
wsdl:binding.wsdl:operation. soap:operation/@soapAction	/Service/orderService. serviceagent/createOrderEndpoint1/Operation
wsdl:binding.wsdl:operation. soap:operation/@style	document
wsdl:binding.wsdl:operation.wsdl:input. soap:body/@parts	order
wsdl:binding.wsdl:operation.wsdl:input. soap:body/@use	literal
wsdl:binding.wsdl:operation.wsdl:output. soap:body/@parts	order
wsdl:binding.wsdl:operation.wsdl:output. soap:body/@use	literal
wsdl:message.wsdl:part/@element	ns0:customer
wsdl:message.wsdl:part/@name	order
wsdl:portType.wsdl:operation. wsdl:input/@message	tns:orderRequest
wsdl:portType.wsdl:operation. wsdl:output/@message	tns:orderResponse
wsdl:service.wsdl:port. soap:address/@location	http://localhost:9090/Service/orderService. serviceagent/createOrderEndpoint1
wsdl:types.xsd:schema.xsd:element. xsd:complexType.xsd:sequence. xsd:element/@name	transactionstatus
wsdl:types.xsd:schema.xsd:element. xsd:complexType.xsd:sequence. xsd:element/@type	xsd:string

4.9.2 customerorder.wsdl

Path: WSDL/customerorder.wsdl

Property	Value
import/@location	../Schema/CustomerOrder.xsd
import/@namespace	http://xmlns.example.com/unique/default/namespace/1134438639123
message.part/@element	ns:customer
message.part/@name	order
portType.operation.input/@message	tns:orderRequest
portType.operation.output/@message	tns:orderResponse

4.10 WebSphere MQ Connection

4.10.1 WebSphere MQ Connection.mqcon

Path: Connections/WebSphere MQ Connection.mqcon

Property	Value
config.PASSWORD	test
config.hdrcomp	false
config.host	localhost
config.keyorident	Keystore
config.msgcomp	msgcomp_none
config.pooled	false
config.qmanageractive	9
config.qmanagerbindingmode	remote
config.qmanagerport	1414
config.qmanagertimeout	100
config.qmanagerunused	3
config.serverchannel	CITI.POC.CHANNEL
config.tls	false
config.userid	test
config.version	7.05.00
name	WebSphere MQ Connection
resourceType	plugin.bwmq.ConnectionResource

4.11 XSD Schema

4.11.1 CustomerOrder.xsd

Path: Schema/CustomerOrder.xsd

Property	Value
xsd:element.xsd:complexType. xsd:sequence.xsd:element/@name	transactionstatus
xsd:element.xsd:complexType. xsd:sequence.xsd:element/@type	xsd:string

4.11.2 LogError.xsd

Path: Schema/LogError.xsd

Property	Value
xs:complexType.xs:sequence. xs:element/@minOccurs	0
xs:complexType.xs:sequence. xs:element/@name	projectName
xs:complexType.xs:sequence. xs:element/@ref	ProcessName
xs:complexType.xs:sequence. xs:element/@type	xs:string
xs:element.xs:complexType.xs:sequence. xs:element/@ref	ErrorData
xs:element/@name	TransactionData
xs:element/@type	xs:string
xs:simpleType.xs:restriction. xs:enumeration/@id	FATAL
xs:simpleType.xs:restriction. xs:enumeration/@value	5

4.11.3 OrderStatus.xsd

Path: Schema/OrderStatus.xsd

Property	Value
xsd:element.xsd:complexType. xsd:sequence.xsd:element/@name	orderdatetime
xsd:element.xsd:complexType. xsd:sequence.xsd:element/@type	xsd:string

5 Adapters & Plugins

5.1 File Adapter Configuration

5.1.1 FileAdapterConfiguration.adfiles

Path: Adapters/File/FileAdapterConfiguration.adfiles

Property	Value
AEService:client.AEService:class	/AESchemas/ae/FileAdapter/operation.aeschema#rpcClass. Operation
AEService:client.AEService:class/@isRef	true
AEService:client. AEService:invocationTimeout	60
AEService:client.AEService:session	#rvSession.DefaultRVRPCSession
AEService:client.AEService:session/@isRef	true
AEService:client.AEService:subject	domain.customerOrder-1.adfiles.%%InstanceId%%.userExit
AEService:client.AEService:wireFormat	rvMsg
AEService:consumer.AEService:session	#rvCmSession.DefaultRVCMSession
AEService:consumer. AEService:session/@isRef	true
AEService:consumer.AEService:subject	domain.customerOrder-1.FileAdapter.FileAdapterConfiguration. SubscriptionService
AEService:consumer.AEService:wireFormat	aeRvMsg
AEService:producer.AEService:session	#rvCmSession.DefaultRVCMSession
AEService:producer. AEService:session/@isRef	true
AEService:producer.AEService:subject	domain.customerOrder-1.FileAdapter.FileAdapterConfiguration. PublicationService
AEService:producer.AEService:wireFormat	aeRvMsg
AEService:rvCmSession. AEService:cmName	domain.customerOrder-1.%%AppName%%.%%InstanceId%%.CM
AEService:rvCmSession. AEService:daemon	tcp:7500
AEService:rvCmSession. AEService:defaultTimeLimit	0
AEService:rvCmSession. AEService:ledgerFile	./domain.customerOrder-1.%%AppName%%.%%InstanceId%%. ldg
AEService:rvCmSession.AEService:network	
AEService:rvCmSession. AEService:requireOldMessages	true
AEService:rvCmSession.AEService:service	7500
AEService:rvCmSession. AEService:syncLedger	true
AEService:rvSession.AEService:daemon	tcp:7474
AEService:rvSession.AEService:network	
AEService:rvSession.AEService:service	7474
fa:adapter.AESDK:deployment. AESDK:advisories.AESDK:advisory. AESDK:name	advisory.sdk.info
fa:adapter.AESDK:deployment. AESDK:advisories.AESDK:advisory. AESDK:subject	_SDK.INFO.>
fa:adapter.AESDK:deployment. AESDK:clients.AESDK:rvRpcClient	#client.UserExitClient
fa:adapter.AESDK:deployment. AESDK:clients.AESDK:rvRpcClient/@isRef	true
fa:adapter.AESDK:deployment.	#consumer.SubscriptionServiceEndPoint

6 Global Variables

Total Global Variables Count: 42

6.1 Connections (Count: 1)

Name	Value	Type
NewItem	no value	Str

6.2 Connections/FILE (Count: 6)

Name	Value	Type
errDir	C:\tibco510\raks\err\	Str
fileName	orderServiceFILE.txt	Str
inDir	C:\tibco510\raks\in\	Str
inputFileName	C:\tibco510\raks\in\orderServiceFILE.txt	Str
outDir	C:\tibco510\raks\out\	Str
prcDir	C:\tibco510\raks\prc\	Str

6.3 Connections/SCHEDULER (Count: 1)

Name	Value	Type
TimeInterval	1	Str

6.4 Flags (Count: 2)

Name	Value	Type
InvokeRESTService	Yes	Str
InvokeSOAPService	Yes	Str

6.5 JDBCConnection (Count: 6)

Name	Value	Type
Timeout	10	Str
dbname	mydb	Str
hostname	localhost	Str
password	my_pass	Str
port	3306	Str
username	myuser	Str

6.6 LogLevels (Count: 6)

Name	Value	Type
LOG_DEBUG	0	Str
LOG_ERROR	3	Str
LOG_INFO	1	Str
LOG_LEVEL	0	Str
LOG_WARNING	2	Str
LoggingEnabled	true	Str

6.7 defaultVars (Count: 17)

Name	Value	Type
Deployment	customerOrder-1	Str
DirLedger	.	Str
DirTrace	.	Str
Domain	domain	Str
HawkEnabled	false	Str
JmsProviderUrl	tcp://localhost:7222	Str
JmsSslProviderUrl	ssl://localhost:7243	Str
MyUniqueVar	DefaultValue	Str
RemoteRvDaemon		Str
RvDaemon	tcp:7500	Str
RvNetwork		Str
RvService	7500	Str
RvaHost	localhost	Str
RvaPort	7600	Str
TIBHawkDaemon	tcp:7474	Str
TIBHawkNetwork		Str
TIBHawkService	7474	Str

6.8 httpConnection (Count: 3)

Name	Value	Type
httphost	localhost	Str
httpport	9090	Str
soapPath	soapOrderServicePath	Str

7 Files Inventory

7.1 File Types Count

File Type	Count	Total Size (KB)
adfiles	1	36
archive	1	1
dat	1	0
jobsharedvariable	1	0
mqcon	1	0
process	24	293
serviceagent	1	5
sharedhttp	2	3
sharedjdbc	1	0
sharedjmsapp	1	1
sharedjmscon	1	0
sharedparse	1	1
sharedvariable	1	0
substvar	9	12
txt	1	0
wadl	1	1
wsdl	2	3
xsd	3	3

7.2 Files List

Complete list of all project files:

File Name	Relative Path
FileAdapterConfiguration.adfiles	Adapters/File/FileAdapterConfiguration.adfiles
LogandErrorHandler.process	BusinessProcess/LogandErrorHandler.process
LogandErrorHandlerDummy. process	BusinessProcess/LogandErrorHandlerDummy.process
UpdatePayment.process	BusinessProcess/UpdatePayment.process
UpdatePaymentDummy.process	BusinessProcess/UpdatePaymentDummy.process
connector.process	BusinessProcess/connector.process
createOrder.process	BusinessProcess/createOrder.process
createOrderAdapterPublisher. process	BusinessProcess/createOrderAdapterPublisher.process
createOrderDummy.process	BusinessProcess/createOrderDummy.process
createOrderREST.process	BusinessProcess/createOrderREST.process
HTTP Connection.sharedhttp	Connections/HTTP Connection.sharedhttp
HTTP-Connection-REST. sharedhttp	Connections/HTTP-Connection-REST.sharedhttp
JDBC Connection.sharedjdbc	Connections/JDBC Connection.sharedjdbc
JMS Application Properties. sharedjmsapp	Connections/JMS Application Properties.sharedjmsapp
JMS Connection.sharedjmscon	Connections/JMS Connection.sharedjmscon
WebSphere MQ Connection. mqcon	Connections/WebSphere MQ Connection.mqcon
OrderServiceDataFormat. sharedparse	DataFormat/OrderServiceDataFormat.sharedparse
CustomerOrder.xsd	Schema/CustomerOrder.xsd
LogError.xsd	Schema/LogError.xsd
OrderStatus.xsd	Schema/OrderStatus.xsd
Initialization_onstartup.process	Service/Initialization_onstartup.process
orderService.serviceagent	Service/orderService.serviceagent
orderServiceFILE.process	Service/orderServiceFILE.process
orderServiceJMS.process	Service/orderServiceJMS.process
orderServiceREST.process	Service/orderServiceREST.process
orderServiceSCHEDULER. process	Service/orderServiceSCHEDULER.process
orderServiceSOAP.process	Service/orderServiceSOAP.process
orderServiceWMQ-NotDoneYet. process	Service/orderServiceWMQ-NotDoneYet.process
poc_password.process	Service/poc_password.process
JobSharedVariable_timestamp. jobsharedvariable	SharedVariables/JobSharedVariable_timestamp.jobsharedvariable
SharedVariable_counter. sharedvariable	SharedVariables/SharedVariable_counter.sharedvariable
ConcreteOrderService.wsdl	TestService/ConcreteOrderService.wsdl
orderServiceFILE.txt	TestService/FILE/orderServiceFILE.txt
JMSQReqRep.process	TestService/JMS/JMSQReqRep.process
JMSQSender.process	TestService/JMS/JMSQSender.process
SOAPcreateOrderService. process	TestService/JMS/SOAPcreateOrderService.process
orderServiceFILEADAPTERPU- BLISHER.process	TestService/Others/orderServiceFILEADAPTERPUBLISHER.process

8 Archives

8.1 customerOrder.archive

Type: Enterprise Archive

Path: C:\raks\apiguard\raksanalyzer\testdata\customerOrder\customerOrder.archive

Author: 0016SR744

Version: 4

Child Archive: Process Archive (PROCESS)

Included Processes:

Process Path
/Service/orderService.serviceagent
/Service/orderServiceFILE.process
/Service/orderServiceJMS.process
/Service/orderServiceREST.process
/Service/orderServiceSCHEDULER.process
/Service/Initialization_onstartup.process

Child Archive: Shared Archive (SHARED)

9 References

References section is placeholder for any reference details team requires.

- TIBCO ActiveMatrix BusinessWorks 5.x Documentation
- TIBCO Designer User Guide
- TIBCO Administrator Guide