Symbolic synthesis: global minimum certificates and an objective obstruction

Computational proof ledger

7 November 2026

The certificates below distinguish exact circuit identities, global entangler minima, and global minima of the parameter-sensitive objective. These are separate statements. They do not establish optimality throughout all 327×32 target/basis cells.

1 An obstruction in the unrestricted historical objective

For an operation with k wires and parameters p_j, the historical score is

$$2^k + \frac{1}{5} \sum_j \left(\log_2 |\operatorname{den}(p_j)| + \frac{1}{100} \right),$$

where numerator and denominator are taken after symbolic simplification. This expression need not be nonnegative for unrestricted real expressions. Let $d = \log(2049/2048)$ and $a = 1/d$. The native one-qubit word

$$U_3(-a, 0, 0) U_3(a, 0, 0) = I$$

is an exact matrix identity, not merely equality up to scalar. Its score is

$$C = \frac{1003}{250} + \frac{2}{5} \log_2 d < -\frac{97}{250} < 0.$$

Indeed $0 < \log(1 + x) < x$ for $x > 0$, since $[\log(1 + x) - x]' = -x/(1 + x) < 0$, and here $x = 2^{-11}$. Appending arbitrarily many copies of the word preserves the target, phase, and entangler count, while its score tends to $-\infty$. Consequently there is *no unrestricted global minimum* of the secondary historical score in bases admitting these U3 words. No amount of additional search proves a minimum that does not exist.

One concrete repair is to replace the denominator term by $\log_2 \max(1, |\operatorname{den}(p_j)|)$. An exact compatibility audit of the 1,339 distinct retained parameter expressions in the pre-refinement archive found no changed scores and no undecided denominator comparisons. The user approved this repair and the compiler now uses objective version 2. The expanded audit covered 1,390 distinct retained expressions, with zero changed or undecided scores. The archive was migrated after this check; historical source snapshots retain their original contracts. Alternatively the admissible expression language can be explicitly restricted; any resulting minimum claim must name that restriction. Under version 2 every local costs at least two and every entangler at least four. An incumbent score C at fixed entangler count E therefore bounds every potentially cheaper word to at most $\lfloor (C - 4E)/2 \rfloor$ locals. This bounds word length; continuous angle optimality still needs a separate proof. The historical obstruction does not affect entangler-count lower bounds or the finite alphabet proof in the next section.

2 Global phase-resolved Clifford minima in Clifford+T

The supplied alphabet is exactly $\{H, S, T, T^\dagger\}$. Each fixed gate has historical score two, so minimum score is equivalent to minimum word length. Every matrix is stored exactly in $\mathbb{Z}[\sqrt{2}, i]/2^k$, with common powers of two removed from its integer representation. Thus hashing and equality use integer arithmetic; floating comparisons play no role.

Breadth-first search through radius seven reaches 628 distinct matrices, including non-Clifford intermediate states. For each of the 192 exact-phase Clifford targets G, enumerate each first half A in that ball and look up GA^{-1} in the same ball. The resulting witnesses have maximum length 14. Every shorter word can be split into two halves of length at most seven; therefore the lookup excludes every cheaper word in the supplied alphabet. The proof covers all 192 literal phases, and taking the minimum over the eight phases of each representative proves the corresponding projective minima. It extends the H/S proof without assuming that intermediate gates are Clifford.

For projective completeness, every H/S/T/Tdg matrix has entries in $K = \mathbb{Q}(\sqrt{2}, i) = \mathbb{Q}(\zeta_8)$, of degree four. The determinant of any word is an eighth root; the determinant of a Clifford target is a fourth root. If a word is λC, then $\lambda \in K$ and λ^2 is an eighth root. An odd sixteenth root has degree eight, so cannot lie in K. Thus λ is one of the eight phases already enumerated. This excludes additional scalar phases from the projective search, including words with non-Clifford intermediates.

The canonical ball SHA256 is

```
e7c7e0492f5ee55d0b80adacc65331c9dc0c2230cd04e2b1b53c58441e7462af.
```

The implementation replays all target witnesses and checks their distances against the Clifford shortest-path certificate. Altered proof radii, distances, alphabets, and missing global certificates are rejected. Continuous alphabets remain outside this finite-word proof.

3 Two B gates for the full Cartan family

Use the convention

$$A(x, y, z) = \exp\{i(xXX + yYY + zZZ)\}, \qquad B = A(\pi/4, \pi/8, 0).$$

The two-B upper bound is established in the literature [1]. The new implementation supplies explicit symbolic outer frames, all real-angle branches, native U3 lowering, and physical scalar absorption. Fold y, z into $[-\pi/4, \pi/4)$ using $\pi/2$ shifts. Put

$$u = \sqrt{2}\sin y \cos z, \quad v = \sqrt{2}\cos y \sin z, \quad w = \sqrt{\cos 2y \cos 2z}.$$

Then $u^2 + v^2 + w^2 = 1$. On the regular chart choose

$$2p_- = \operatorname{atan2}(-w, \sin(y - z)), \quad 2p_+ = \operatorname{atan2}(-w, \sin(y + z)),$$

$$\beta = \operatorname{atan2}(w, u), \qquad a = 2\operatorname{atan2}(v, \sqrt{u^2 + w^2}), \quad \chi = -p_- - p_+ - \pi.$$

The circuit in time order has local layers

	q_0	q_1
before first B	$U_3(\pi/2, \chi, 0)$	$U_3(\pi + p_- - p_+, -\pi/2, -\pi/2)$
between B gates	$U_3(-2x, 0, 0)$	$U_3(-a, -\beta, -\beta)$
after second B	$U_3(-\pi/2, 0, \chi - \pi)$	$U_3(\pi - p_- + p_+, -\pi/2, \pi/2)$

and scalar $\exp\{i(\beta+p_-+p_+)\}$ on the folded chart. An extra native U3 absorbs this scalar for literal equality. No GP primitive is introduced. Local Y/Z frames restore the folds; the implementation also absorbs the input/output Z gauges of PhasedFSim and its scalar.

The full matrix identity reduces six nonzero Pauli coefficients modulo $c_y^2 + s_y^2 = 1$, $c_z^2 + s_z^2 = 1$ and $w^2 = (c_y^2 - s_y^2)(c_z^2 - s_z^2)$. The four chart corners and the zero-radius branch are treated explicitly. Arbitrary x follows from exact Pauli transport through B. Parameter substitutions are regression checks, not family proofs.

For the lower bound, the phase-normalized spin-flip invariants [2] are

$$I_1 = 16(\cos 2x \cos 2y \cos 2z + i \sin 2x \sin 2y \sin 2z)^2,$$
$$I_2 = 4(\cos 4x \cos 4y \cos 4z + i \sin 4x \sin 4y \sin 4z).$$

Local products have $I_1 = 16$; one B pulse has $I_1 = I_2 = 0$. Consequently the construction is globally minimum in entangler count whenever

$$I_1 \neq 16 \quad \text{and} \quad (I_1 \neq 0 \text{ or } I_2 \neq 0).$$

The certificate records this condition rather than claiming every specialization needs two pulses. Scalar relaxation in the lower bound makes it valid for both phase policies. No minimum local score is claimed for these charts.

4 Additional analytic score floors and local transfers

At zero entanglers, each wire on which the target acts nontrivially requires at least one one-wire gate. An exact nonzero commutator with an embedded X or Z proves such support. For a family, a nonzero exact specialization is a witness that the entire family cannot omit that wire; cheaper exceptional specializations remain possible. Literal nonidentity scalar targets also need at least one physical operation. Combining these support bounds with the nonnegative primitive floors certifies a secondary minimum whenever the constructed score meets the bound. Optional default parameters are excluded from the minimum mandatory-arity surcharge.

The current archive records 372 literal and 1,144 projective global lexicographic minimum certificates from this floor argument. There are also 24 literal and 31 projective matches of the secondary floor at a fixed entangler count whose entangler minimum is not established by this argument. These counts can overlap existing Clifford and entangler certificates.

The C4X native-CZ transfer first proves the complete 36-CZ, 46-U3 parent, then proves every distinct local replacement as a two-by-two identity. The free-angle identity that Rz commutes with CZ on either wire justifies collecting diagonal phases across interactions. This yields 69 locals in the CZ/Rz/Rx basis, compared with the stored SDK's 72, and 130 locals in the IBM CZ basis, compared with 143. The IBM construction searches exact native Euler variants while carrying diagonal phases through CZ gates; each variant and every removed full turn have their own exact identity. Both transfers preserve 36 entanglers and a recorded projective scalar; these are constructive improvements, not minimum-count proofs for C4X.

5 Exact local polar fusion

For a constant one-qubit unitary $M = \left(\begin{smallmatrix} A & B \\ C & D \end{smallmatrix}\right)$, put $r = |A|$, $s = |C|$. If $A, C \neq 0$, define

$$\delta = \arg A, \quad \vartheta = 2\,\mathrm{atan2}(s, r), \quad \varphi = \arg C - \delta, \quad \lambda = \arg(-B) - \delta.$$

Then $M = e^{i\delta}U_3(\vartheta, \varphi, \lambda)$. Unitarity gives $r^2 + s^2 = 1$, $|B| = s$, and $\bar{A}B + \bar{C}D = 0$. The defining polar identities reproduce the first three entries; the last is fixed by column orthogonality. If $A = 0$, use $\vartheta = \pi$, $\varphi = \arg C$, $\lambda = \arg(-B)$ and $\delta = 0$. If $C = 0$, use $\vartheta = \varphi = 0$ and $\lambda = \arg D - \arg A$. Scalar blocks need no physical local operation. These explicit charts avoid undefined arguments at zero.

The implementation proves primitive unitarity for arbitrary real arguments, then uses closure under multiplication for every source block. Exact zero predicates and algebraic minimal polynomials select the constant charts. The complete parent circuit is proved separately. The local proof therefore does not rely on numerical fidelities or a general simplifier rediscovering polar branch identities. Rz/Ry lowering and literal U3 phase absorption have independent free-angle matrix identities.

This reduces C3SX/iSWAP to 40 locals projectively and 41 literally, compared with the SDK's projective 56. C4X/iSWAP uses 78 and 79, compared with SDK 113. Their entangler counts remain 26 and 54. Peres/Rxx/Rz/Ry now matches the SDK's 35 locals at five entanglers. These are upper bounds, not unrestricted local-minimum claims. Only C3X/Rzz/U3 retains a higher local count in the matched SDK audit: 28 locals score 115.594, whereas its available proved 24-local alternative scores 116.37. This establishes a tradeoff between those two witnesses, not the impossibility of a better unknown circuit.

6 Reproduction

Run `pytesttests/symbolic/test_b_cartan.py` and `pytesttests/symbolic/test_clifford_t_global.py`. The counterexample is regenerated by `symbolic_cost_proof.negative_identity_certificate()`. Raw source-pinned archive refinements retain their exact implementation hashes and separate phase policies. A verified circuit is an upper bound until its matching lower bound and assumptions are recorded.

References

[1] J. Zhang, J. Vala, S. Sastry, K. B. Whaley, Minimum construction of two-qubit quantum operations, Phys. Rev. Lett. 93, 020502 (2004), `https://arxiv.org/abs/quant-ph/0312193`.

[2] Y. Makhlin, Nonlocal properties of two-qubit gates and mixed states and optimization of quantum computations, Quantum Information Processing 1, 243–252 (2002), `https://arxiv.org/abs/quant-ph/0002045`.