

spec · Figma
critical user flow
JTBD · staging URL

Take stock

Is the critical user flow complete · are the JTBD written · do they carry outcomes

Incomplete

Complete the flow, derive the JTBD; anything AI filled in is marked

Already there

Validate and fill the gaps only, nothing redone

Round 2

Reuse the frozen JTBD, no re-deriving

IN PARALLEL One file per rule, with what failing and passing look like plus a weight: the agent judges by it, the script scores by it

Flow Integrity

4 rules

flow-visible-entry-point

Entry is findable; a first-timer knows where to start

flow-prerequisites-met

Whatever a step needs was collected earlier

flow-all-states-designed

Success, failure, loading, empty; all four drawn

flow-system-status-visible

A click gets a response; a long wait says what is happening

Control & Transparency

4 rules

control-pause-stop-undo

Every screen has an exit; work in progress can be stopped

control-confirm-irreversible

Anything unrecoverable confirms first, or offers undo

control-explain-behaviour

The system explains its own changes and what unlocks a disabled control

control-action-history

What was done is still findable, not just a toast that vanished

Trust & Copy

4 rules

trust-actionable-errors

Errors say what went wrong and what to do now

trust-plain- language

The user's words, not internal jargon

trust-explain-recommendations

Recommendations and scores come with a reason

trust-specific-ctas

Buttons say what happens, not "Submit"

Edge Cases

5 rules

edge-missing-data

Missing data is stated, not left blank or faked into a score

edge-network-failure

Offline, timeout and server error each have a screen

edge-duplicate-actions

A double click does not send two

edge-interruption-recovery

Close it and come back: what was typed is still there

edge-first-vs-returning

A first visit and a hundredth look different

Usability Heuristics

9 checks

ux-no-dark-patterns

Cancelling is as easy as subscribing; no guilt copy or hidden fees

ux-consistency-standards

Components behave and are named consistently

ux-error-prevention

Pickers and defaults prevent errors, rather than scolding afterwards

ux-recognition-over-recall

Nothing to memorise from the previous screen

ux-minimalist-hierarchy

One primary action per screen

ux-orientation-trunk-test

Land on any page and you know where you are

ux-scannable-not-thinkable

Scannable; nothing makes you stop and think

ux-flexibility-efficiency

Shortcuts and bulk actions for repeat users

ux-contextual-help

Help sits where it is needed, not on another site

Accessibility

9 checks

a11y-keyboard-operable

The whole flow works on a keyboard alone

a11y-names-and-labels

Every control has a name, icon-only buttons included

a11y-form-errors

Errors point at the right field and input is preserved

a11y-focus-visible

You can see where focus is

a11y-contrast-aa

Contrast measured not eyeballed: text 4.5:1, components 3:1

a11y-status-announced

Async results are announced, not only shown

a11y-not-colour-alone

Nothing is distinguished by colour alone

a11y-target-size

Targets at least 24px

a11y-motion-and-timing

Motion can be turned off, timeouts extended

Usability Test

one task per JTBD

task-<jtbd-slug>

Walk each user goal end to end and see whether it completes

score_audit.py

Verdict from the Critical count,
score from the weighted pass rate

EXAMPLE OUTPUT

Do not ship

24/100

80% coverage

2

2

0

Critical / Major / Nice to have

Repeating loop · fix, rerun against the same frozen JTBD · it never completes, it produces comparable rounds