# ONTAP Select 9.5 performance: Premium HA direct-attached SSD storage

**ONTAP Select** 

Barb Einarsen November 19, 2019

This PDF was generated from https://docs.netapp.com/us-en/ontap-select/concept\_perf\_premium\_ha\_direct\_ssd\_95.html on December 11, 2020. Always check docs.netapp.com for the latest.



## **Table of Contents**

ONTAP Select 9.5 performance: Premium HA direct-attached SSD storage	 1
Reference platform	 1

# ONTAP Select 9.5 performance: Premium HA direct-attached SSD storage

ONTAP Select 9.5 performance with premium HA direct-attached SSD storage.

### Reference platform

ONTAP Select 9.5 (Premium) hardware (per node):

- Cisco UCS C240 M4SX:
  - Intel Xeon CPU E5-2620 at 2.1GHz
  - 2 x sockets; 16 x CPUs per socket
  - 128GB RAM
  - VMware ESXi 6.5
  - Drives per host: 24 900GB SSD

#### Client hardware:

• 5 x NFSv3 IBM 3550m4 clients

#### Configuration information:

- 1,500 MTU for data path between clients and Select cluster
- No storage efficiency features in use (compression, deduplication, Snapshot copies, SnapMirror, and so on)

The following table lists the throughput measured against read/write workloads on an HA pair of ONTAP Select Premium nodes using both software RAID and hardware RAID. Performance measurements were taken using the SIO load-generating tool.

Performance results for a single node (part of a four-node medium instance) ONTAP Select 9.5 cluster on DAS (SSD) with software RAID and hardware RAID

Description	Sequential	Sequential	Random Read	Random Write	Random WR/
	Read 64KiB	Write 64KiB	8KiB	8KiB	RD (50/50) 8KiB
ONTAP 9.5 Select Medium instance with DAS (SSD) hardware RAID	1,714MiBps	412MiBps	391MiBps	1251MiBps	309MiBps

Description	Sequential	Sequential	Random Read	Random Write	Random WR/
	Read 64KiB	Write 64KiB	8KiB	8KiB	RD (50/50) 8KiB
ONTAP 9.5 Select Medium instance with DAS (SSD) software RAID	1,674MiBps	360MiBps	451MiBps	223MiBps	293MiBps

#### 64K sequential read

#### Details:

- SIO direct I/O enabled
- 2 nodes
- 2 x data NIC per node
- 1 x data aggregate per node (2TB hardware RAID), (8TB software RAID)
- 64 SIO procs, 1 thread per proc
- 32 volumes per node
- 1 x files per proc; files are 12000MB each

### 64K sequential write

#### Details:

- SIO direct I/O enabled
- 2 nodes
- 2 x data NIC per node
- 1 x data aggregate per node (2TB hardware RAID), (4TB software RAID)
- 128 SIO procs, 1 thread per proc
- volumes per node 32 (hardware RAID), 16 (software RAID)
- 1 x files per proc; files are 30720MB each

#### 8K random read

#### Details:

- SIO direct I/O enabled
- 2 nodes
- 2 x data NIC per node

- 1 x data aggregate per node (2TB hardware RAID), (4TB software RAID)
- 64 SIO procs, 8 threads per proc
- volumes per node 32
- 1 file per proc; files are 12228MB each

#### 8K random write

#### Details:

- SIO direct I/O enabled
- 2 nodes
- 2 x data NIC per node
- 1 x data aggregate per node (2TB hardware RAID), (4TB software RAID)
- 64 SIO procs, 8 threads per proc
- volumes per node 32
- 1 file per proc; files are 8192MB each

#### 8K random 50% write 50% read

#### Details:

- SIO direct I/O enabled
- 2 nodes
- 2 x data NIC per node
- 1 x data aggregate per node (2TB hardware RAID), (4TB software RAID)
- 64 SIO procs, 20 threads per proc
- volumes per node 32
- 1 file per proc; files are 12228MB each

#### **Copyright Information**

Copyright © 2020 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval systemwithout prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

#### **Trademark Information**

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.