■ NetApp

Common support module

ONTAP Select

David Peterson November 21, 2019

This PDF was generated from https://docs.netapp.com/us-en/ontap-select/reference_api_script_common.html on December 17, 2020. Always check docs.netapp.com for the latest.

Table of Contents

Common	support modu	ام											-
COMMISSION	Support modu	10	 										

Common support module

All of the Python scripts use a common Python class in a single module.

```
1 #!/usr/bin/env python
 2 ##-----
4 # File: deploy requests.py
6 # (C) Copyright 2019 NetApp, Inc.
8 # This sample code is provided AS IS, with no support or warranties of
9 # any kind, including but not limited for warranties of
 merchantability
10 # or fitness of any kind, expressed or implied. Permission to use,
11 # reproduce, modify and create derivatives of the sample code is
  granted
12 # solely for the purpose of researching, designing, developing and
13 # testing a software application product for use with NetApp products,
14 # provided that the above copyright notice appears in all copies and
15 # that the software application product is distributed pursuant to
16 # no less restrictive than those set forth herein.
18 ##----
19
20 import json
21 import logging
22 import requests
23
24 requests.packages.urllib3.disable warnings()
25
26 class DeployRequests (object):
     1.1.1
27
28
      Wrapper class for requests that simplifies the ONTAP Select Deploy
29
      path creation and header manipulations for simpler code.
      1.1.1
30
31
      def init (self, ip, admin password):
32
          self.base url = 'https://{}/api'.format(ip)
33
          self.auth = ('admin', admin password)
34
          self.headers = {'Accept': 'application/json'}
          self.logger = logging.getLogger('deploy')
36
37
      def post(self, path, data, files=None, wait_for_job=False):
38
```

```
39
           if files:
40
               self.logger.debug('POST FILES:')
41
               response = requests.post(self.base url + path,
                                         auth=self.auth, verify=False,
42
                                         files=files)
43
44
           else:
               self.logger.debug('POST DATA: %s', data)
45
               response = requests.post(self.base url + path,
46
47
                                         auth=self.auth, verify=False,
48
                                         json=data,
49
                                         headers=self.headers)
50
51
           self.logger.debug('HEADERS: %s\nBODY: %s', self.
   filter headers(response), response.text)
52
           self.exit on errors(response)
53
54
           if wait for job and response.status code == 202:
               self.wait for job(response.json())
55
56
           return response
57
       def patch(self, path, data, wait for job=False):
58
59
           self.logger.debug('PATCH DATA: %s', data)
           response = requests.patch(self.base url + path,
60
                                      auth=self.auth, verify=False,
61
62
                                      json=data,
63
                                      headers=self.headers)
           self.logger.debug('HEADERS: %s\nBODY: %s', self.
64
   filter headers(response), response.text)
           self.exit on errors(response)
65
66
67
           if wait for job and response.status code == 202:
68
               self.wait for job(response.json())
69
           return response
70
       def put(self, path, data, files=None, wait for job=False):
71
72
           if files:
               print('PUT FILES: {}'.format(data))
73
               response = requests.put(self.base url + path,
74
                                        auth=self.auth, verify=False,
75
76
                                        data=data,
                                        files=files)
77
78
           else:
               self.logger.debug('PUT DATA:')
79
               response = requests.put(self.base url + path,
80
                                        auth=self.auth, verify=False,
81
82
                                        json=data,
```

```
83
                                         headers=self.headers)
 84
 85
            self.logger.debug('HEADERS: %s\nBODY: %s', self.
    filter headers(response), response.text)
            self.exit on errors(response)
 86
 87
            if wait for job and response.status code == 202:
 88
 89
                self.wait for job(response.json())
            return response
 90
 91
 92
        def get(self, path):
            """ Get a resource object from the specified path """
 93
 94
            response = requests.get(self.base url + path, auth=self.auth,
    verify=False)
 95
            self.logger.debug('HEADERS: %s\nBODY: %s', self.
    filter headers(response), response.text)
            self.exit on errors(response)
            return response
 97
 98
        def delete(self, path, wait for job=False):
 99
            """ Delete's a resource from the specified path """
100
            response = requests.delete(self.base url + path, auth=self
    .auth, verify=False)
            self.logger.debug('HEADERS: %s\nBODY: %s', self.
102
    filter headers (response), response.text)
103
            self.exit on errors(response)
104
            if wait for job and response.status code == 202:
105
                self.wait for job(response.json())
106
107
            return response
108
109
        def find resource(self, path, name, value):
110
            ''' Returns the 'id' of the resource if it exists, otherwise
   None '''
111
            resource = None
            response = self.get('{path}?{field}={value}'.format(
112
113
                                 path=path, field=name, value=value))
            if response.status code == 200 and response.json().get
    ('num records') >= 1:
115
                resource = response.json().get('records')[0].get('id')
116
            return resource
117
        def get num records(self, path, query=None):
118
            ''' Returns the number of records found in a container, or
119
    None on error '''
120
            resource = None
```

```
121
            query opt = '?{}'.format(query) if query else ''
122
            response = self.get('{path}{query}'.format(path=path, query
    =query opt))
            if response.status code == 200 :
123
                return response.json().get('num records')
124
125
            return None
126
127
        def resource exists(self, path, name, value):
128
            return self.find resource(path, name, value) is not None
129
        def wait for job(self, response, poll timeout=120):
130
            last modified = response['job']['last modified']
131
132
            job id = response['job']['id']
133
134
            self.logger.info('Event: ' + response['job']['message'])
135
136
            while True:
137
                response = self.get('/jobs/{}?fields=state,message&'
                                     'poll timeout={}&last modified=>={}'
138
    .format(
139
                                         job id, poll timeout,
    last modified))
140
141
                job body = response.json().get('record', {})
142
143
                # Show interesting message updates
                message = job body.get('message', '')
144
                self.logger.info('Event: ' + message)
145
146
147
                # Refresh the last modified time for the poll loop
                last modified = job body.get('last modified')
148
149
150
                # Look for the final states
151
                state = job body.get('state', 'unknown')
                if state in ['success', 'failure']:
152
153
                    if state == 'failure':
154
                        self.logger.error('FAILED background job.\nJOB:
    %s', job body)
155
                        exit(1) # End the script if a failure occurs
156
                    break
157
        def exit on errors(self, response):
158
            if response.status code >= 400:
159
                self.logger.error('FAILED request to URL: %s\nHEADERS:
160
    %s\nRESPONSE BODY: %s',
161
                                  response.request.url,
```

```
self.filter headers (response),
162
163
                               response.text)
164
     response.raise for status() # Displays the response error,
and exits the script
165
166
     @staticmethod
     def filter headers(response):
167
          ''' Returns a filtered set of the response headers '''
168
169
          return {key: response.headers[key] for key in ['Location',
'request-id'] if key in response.headers}
```

Copyright Information

Copyright © 2020 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.