

RS-COLORS

A Color Data Type for Common Lisp

Ralph Schleicher

This is edition 1, last updated 2020-02-09, of RS-COLORS – *A Color Data Type for Common Lisp*, for RS-COLORS version 1.0.1.

Copyright © 2014 Ralph Schleicher

Permission is granted to make and distribute verbatim copies of this manual, provided the copyright notice and this permission notice are preserved on all copies.

Please report any errors in this manual to `rs@ralph-schleicher.de`.

Table of Contents

1	Introduction	3
2	Installation	5
3	User's Guide	7
3.1	The Color Data Type	7
3.2	Creating Color Objects	8
3.3	Color Coordinates	9
3.4	White Point	9
3.5	Color Conversion	9
3.6	External Representations	11
3.7	Color Dictionaries	11
4	Reference Manual	13
4.1	Color Predicates	13
4.2	Abstract Color Classes	13
4.3	Generic Color Spaces (Color Models)	14
4.3.1	Generic RGB Color Space	15
4.3.2	Generic HSV Color Space	16
4.3.3	Generic HSL Color Space	17
4.3.4	Generic CMY Color Space	18
4.3.5	Generic CMYK Color Space	19
4.4	CIE Color Spaces	20
4.4.1	CIE RGB Color Space	20
4.4.2	CIE XYZ Color Space	21
4.4.3	CIE xyY Color Space	21
4.4.4	CIE L*u*v* Color Space	23
4.4.5	CIE L*a*b* Color Space	23
4.4.6	CIE L*C*h Color Space	24
4.4.7	CIE Standard Observers	25
4.4.8	CIE Standard Illuminants	26
4.5	RGB Color Spaces	27
4.5.1	sRGB Color Space	27
4.5.2	Adobe RGB Color Space	28
4.6	Color Properties	29
4.7	Color Conversions	29
4.8	Color Differences	30
4.9	Input and Output	30
4.9.1	Xcms Formats	30
4.9.2	HTML Format	32
4.9.3	CSS3 Formats	33
4.10	Miscellaneous	34
	Symbol Index	35
	Concept Index	37

References

- [sRGB] <http://www.w3.org/Graphics/Color/sRGB.html>
 <http://www.color.org/chardata/rgb/srgb.xalter>
- [Adobe RGB] Adobe RGB (1998) Color Image Encoding, Version 2005-05
 <http://www.color.org/chardata/rgb/adobergb.xalter>
- [Xcms] Valerie Quercia, Tim O'Reilly: X Window System User's Guide, for X11
 Release 5
- [HTML] <http://www.w3.org/TR/1999/REC-html401-19991224>
- [CSS3] <https://www.w3.org/TR/css-color-3>

1 Introduction

By using the RS-COLORS library you can create and manipulate colors, or better color objects, in Common Lisp. A color is either associated with a color model or a color space. The implemented color models and color spaces are:

- generic RGB
- generic HSV/HSB
- generic HSL
- generic CMY
- generic CMYK

and

- CIE RGB
- CIE XYZ
- CIE xyY
- CIE $L^*u^*v^*$
- CIE $L^*a^*b^*$
- CIE L^*C^*h
- sRGB
- Adobe RGB

In Chapter 3 User's Guide, we demonstrate the most important concepts provided by the RS-COLORS library. The details are documented in Chapter 4 Reference Manual.

2 Installation

The RS-COLORS library is available in Quicklisp (<https://www.quicklisp.org>). Thus,

```
(ql:quickload :rs-colors)  
(use-package :rs-colors)
```

should do it.

3 User's Guide

3.1 The Color Data Type

First of all, there is not *one* color data type. Instead, every color is an instance of a particular color class. All color classes are sub-classes of the abstract `color-object` class. The built-in color classes are listed in the following tables.

Color Classes for Color Models

`generic-rgb-color`

Mathematical description of the RGB color model.

`generic-hsv-color`

Mathematical description of the HSV color space. The HSV color space is a different representation of the RGB color model.

`generic-hsl-color`

Mathematical description of the HSL color space. The HSL color space is a different representation of the RGB color model.

`generic-cmy-color`

Mathematical description of the CMY color model.

`generic-cmyk-color`

Mathematical description of the CMYK color model.

Color Classes for Absolute Color Spaces

`ciernb-color`

The CIE RGB color space.

`ciexyz-color`

The CIE XYZ color space.

`ciexyy-color`

The CIE xyY color space.

`cieluv-color`

The CIE $L^*u^*v^*$ color space.

`cielab-color`

The CIE $L^*a^*b^*$ color space.

`cielch-color`

The CIE L^*C^*h color space.

Color Classes for Device Dependent Color Spaces

`srgb-color`

The sRGB color space.

`adobe-rgb-color`

The Adobe RGB color space.

3.2 Creating Color Objects

Colors are instantiated by calling a constructor function. Constructor arguments are usually the color coordinates in the respective color space. To create, for example, a color in the sRGB color space, say

```
(make-srgb-color 252/255 175/255 62/255)
⇒ #<SRGB-COLOR (84/85 35/51 62/255)>
```

Many color coordinates have to be expressed as intensity values, that is values in the range from zero to one inclusive. That's the reason why the sRGB color coordinates in the above example are specified as rational numbers.

Some constructors accept a `:byte-size` keyword argument. This is useful if the scale factor is equal for all color coordinates. With that we can rewrite the above example as

```
(make-srgb-color 252 175 62 :byte-size 8)
⇒ #<SRGB-COLOR (84/85 35/51 62/255)>
```

As you can see, the resulting color coordinates are equal. Another common case is to encode the color coordinates in a single integral number. Again, the `:byte-size` keyword argument specifies how many bits are used to encode a single color coordinate. Thus,

```
(make-srgb-color-from-number #XFCFAF3E :byte-size 8)
⇒ #<SRGB-COLOR (84/85 35/51 62/255)>
```

results in the same color as before.

The built-in constructors are listed in the following table.

<code>make-generic-rgb-color</code>	
<code>make-generic-rgb-color-from-number</code>	Create a generic RGB color object.
<code>make-generic-hsv-color</code>	Create a generic HSV color object.
<code>make-generic-hsl-color</code>	Create a generic HSL color object.
<code>make-generic-cmy-color</code>	
<code>make-generic-cmy-color-from-number</code>	Create a generic CMY color object.
<code>make-generic-cmyk-color</code>	
<code>make-generic-cmyk-color-from-number</code>	Create a generic CMYK color object.
<code>make-ciergb-color</code>	Create a CIE RGB color object.
<code>make-ciexyz-color</code>	Create a CIE XYZ color object.
<code>make-ciexyy-color</code>	Create a CIE xyY color object.
<code>make-luv-color</code>	Create a CIE L*u*v* color object.
<code>make-lab-color</code>	Create a CIE L*a*b* color object.
<code>make-lch-color</code>	Create a CIE L*C*h color object.

```
make-srgb-color
make-srgb-color-from-number
    Create a sRGB color object.

make-adobe-rgb-color
make-adobe-rgb-color-from-number
    Create an Adobe RGB color object.
```

3.3 Color Coordinates

Use the `color-coordinates` function to get the color coordinates of a color.

```
(let ((color (make-srgb-color 252 175 62 :byte-size 8)))
  ;; We know that color is an RGB color.
  (multiple-value-bind (r g b)
    (color-coordinates color)
    (list r g b)))
⇒ (84/85 35/51 62/255)
```

A more practical way to get the color coordinates of a color is described in Section 3.5 Color Conversion.

3.4 White Point

A device dependent color space usually has a *white point*. If so, the `white-point` function returns a color object of this white point.

3.5 Color Conversion




Figure 3.1: Color Conversions

Figure 3.1 depicts the implemented color conversions. The nice thing about RS-COLORS is that all these color conversions can be performed with the `change-class` function.

```
(let ((color (make-srgb-color 252 175 62 :byte-size 8)))
  (values (change-class color 'generic-cmyk-color) color))
⇒ #<GENERIC-CMYK-COLOR (0 11/36 95/126 1/85)>
⇒ #<GENERIC-CMYK-COLOR (0 11/36 95/126 1/85)>
```

If you wish to keep the original color object unchanged, use the `coerce-color` function.

```
(let ((color (make-srgb-color 252 175 62 :byte-size 8)))
  (values (coerce-color color 'generic-cmyk-color) color))
⇒ #<GENERIC-CMYK-COLOR (0 11/36 95/126 1/85)>
⇒ #<SRGB-COLOR (84/85 35/51 62/255)>
```

The `coerce-color` function only creates a copy of the color if the color object is not already of the correct type.

If you only need the color coordinates, then you can call one of the following functions to get them.

generic-rgb-color-coordinates

Return the generic RGB color space coordinates of a color.

generic-hsv-color-coordinates

Return the generic HSV color space coordinates of a color.

generic-hsl-color-coordinates

Return the generic HSL color space coordinates of a color.

generic-cmy-color-coordinates

Return the generic CMY color space coordinates of a color.

generic-cmyk-color-coordinates

Return the generic CMYK color space coordinates of a color.

ciergb-color-coordinates

Return the CIE RGB color space coordinates of a color.

ciexyz-color-coordinates

Return the CIE XYZ color space coordinates of a color.

ciexyy-color-coordinates

Return the CIE xyY color space coordinates of a color.

cieluv-color-coordinates

Return the CIE $L^*u^*v^*$ color space coordinates of a color.

cielab-color-coordinates

Return the CIE $L^*a^*b^*$ color space coordinates of a color.

cielch-color-coordinates

Return the CIE L^*C^*h color space coordinates of a color.

srgb-color-coordinates

Return the sRGB color space coordinates of a color.

adobe-rgb-color-coordinates

Return the Adobe RGB color space coordinates of a color.

Let's repeat our example:

```
(let ((color (make-srgb-color 252 175 62 :byte-size 8)))
  (multiple-value-bind (c m y k)
    (generic-cmyk-color-coordinates color)
    (values (list c m y k) color)))
⇒ (0 11/36 95/126 1/85)
⇒ #<SRGB-COLOR (84/85 35/51 62/255)>
```

All these color conversions only work if the color conversion path is unambiguous. The crux is the conversion from the CIE XYZ color space to the generic RGB color space and

vice versa. If you want to go that way, then you have to specify the intermediate color space.

```
(let ((color (make-generic-hsl-color 30 1 1/2)))
  (multiple-value-bind (L* C* h)
    (cielch-color-coordinates
     (if (typep color 'generic-color-object)
         (coerce-color color 'srgb-color)
         color)))
    (values (list L* C* h) color)))
⇒ (66.95426618791458d0 85.58632577011882d0 59.7885844150978d0)
⇒ #<GENERIC-HSL-COLOR (30 1 1/2)>
```

Or destructively:

```
(let ((color (make-generic-hsl-color 30 1 1/2)))
  (change-class (change-class color 'srgb-color) 'cielch-color))
⇒ #<CIELCH-COLOR (66.95426... 85.58632... 59.78858...)>
```

3.6 External Representations

There are some functions for reading and printing colors in different formats. The RS-COLORS library supports Xcms notation, numerical HTML notation, and CSS3 functional notation.

All functions adhere to the standards set forth by the `read`, `print`, and `format` functions. Thus, they interoperate well with the stream concepts of Common Lisp.

```
(with-input-from-string (input "RGB:4e/9a/06")
  (with-output-to-string (output)
    (print-color-html (read-color-xcms-rgb input) output)))
⇒ "#4E9A06"

(let ((color (make-srgb-color 78 154 6 :byte-size 8)))
  (format nil "background: ~?;" color-formatter-css3-rgb (list color)))
⇒ "background: rgb(78, 154, 6);"
```

See Section 4.9 Input and Output, for more details about the supported formats.

3.7 Color Dictionaries

The RS-COLORS library provides several packages with predefined named colors. The recommended way to use these packages is to load it, for example, with QuickLisp. Then you should refer to the named colors via the package prefix to avoid name clashes.

```
;; Load a color dictionary.
(ql:quickload :rs-colors-html)

;; Use a named color.
(format nil color-formatter-css3-rgb html-color:green)
⇒ "rgb(0, 128, 0)"
```

Below is a list of all package prefixes together with their meaning.

```
rs-colors-x11, x11-color
  X11 color names, '(ql:quickload :rs-colors-x11)'.
  See https://en.wikipedia.org/wiki/X11\_color\_names.

rs-colors-html, html-color
  HTML basic colors, '(ql:quickload :rs-colors-html)'.
  See https://www.w3.org/TR/css3-color/#html4.
```

`rs-colors-svg`, `svg-color`

SVG color names, `'(ql:quickload :rs-colors-svg)'`.

See <https://www.w3.org/TR/css3-color/#svg-color>.

`rs-colors-ral`, `ral-color`

RAL Classic color names, `'(ql:quickload :rs-colors-ral)'`.

See <https://www.ral-farben.de>.

`rs-colors-ral-design`, `ral-design-color`

RAL Design color names, `'(ql:quickload :rs-colors-ral-design)'`.

See <https://www.ral-farben.de>.

`rs-colors-tango`, `tango-color`

Tango desktop project colors, `'(ql:quickload :rs-colors-tango)'`.

See http://tango.freedesktop.org/Tango_Icon_Theme_Guidelines.

`rs-colors-material-io`, `material-io-color`

Material design color palette, `'(ql:quickload :rs-colors-material-io)'`.

See <https://material.io/guidelines/style/color.html>.

4 Reference Manual

4.1 Color Predicates

Use the `colorp` function to check whether or not an object is a color. This covers all color classes documented in this manual.

`colorp` *object* [Function]
 Return true if *object* is a color object.

4.2 Abstract Color Classes

The color classes documented in this section are merely used as superclasses.

`color-object` [Class]
 Base class for a color.

Class Precedence List

`color-object`, `standard-object`, `t`.

`rgb-color-object` [Class]
 Color class for a RGB color space.

Color coordinates are the normalized intensities of the red, green, and blue primary. Values are real numbers in the closed interval $[0, 1]$.

Class Precedence List

`rgb-color-object`, `color-object`, ...

`hsv-color-object` [Class]
 Color class for a HSV/HSB color space.

Color coordinates are hue, saturation, and value (brightness). Hue is a real number in the half-closed interval $[0, 360)$. Saturation and value are real numbers in the closed interval $[0, 1]$.

Class Precedence List

`hsv-color-object`, `color-object`, ...

`hsl-color-object` [Class]
 Color class for a HSL color space.

Color coordinates are hue, saturation, and lightness. Hue is a real number in the half-closed interval $[0, 360)$. Saturation and lightness are real numbers in the closed interval $[0, 1]$.

Class Precedence List

`hsl-color-object`, `color-object`, ...

`cmy-color-object` [Class]
 Color class for a CMY color space.

Color coordinates are the normalized intensities of the cyan, magenta, and yellow primary. Values are real numbers in the closed interval $[0, 1]$.

Class Precedence List

`cmy-color-object`, `color-object`, ...

cmk-color-object [Class]

Color class for a CMYK color space.

Color coordinates are the normalized intensities of the cyan, magenta, yellow, and black (key) primary. Values are real numbers in the closed interval $[0, 1]$.

Class Precedence List

cmk-color-object, color-object, ...

generic-color-object [Class]

Color class for the mathematical model of a color space.

Class Precedence List

generic-color-object, color-object, ...

4.3 Generic Color Spaces (Color Models)

A generic color space implements a color model. Two color models are in widespread use with computers:

- The additive RGB color model with the primary colors red, green, and blue.
- The subtractive CMY color model with the primary colors cyan, magenta, and yellow.

The RGB color model is the usual color model for computer displays. If the color intensity of all primary colors is zero, that means “off”, the display appears “black”. Otherwise, if the color intensity of all primary colors is one, that means “on”, the display appears “white”.

The CMY color model is the usual color model for paper printers. If the color intensity of all primary colors is zero, that means “off”, the paper appears “white”. Otherwise, if the color intensity of all primary colors is one, that means “on”, the paper appears “black”.

Theoretically, a RGB tuple (R, G, B) and a CMY tuple (C, M, Y) are related to each other via the simple equations

$$C = 1 - R$$

$$M = 1 - G$$

$$Y = 1 - B$$

and

$$R = 1 - C$$

$$G = 1 - M$$

$$B = 1 - Y$$

The CMYK color model is an extension of the CMY color model to save ink. Theoretically, a CMY tuple (C, M, Y) and a CMYK quadruple (c, m, y, k) can be related to each other via the equations

$$k = \min(C, M, Y)$$

$$c = \frac{C - k}{1 - k}$$

$$m = \frac{M - k}{1 - k}$$

$$y = \frac{Y - k}{1 - k}$$

and

$$\begin{aligned}C &= \min(1, c \cdot (1 - k) + k) \\M &= \min(1, m \cdot (1 - k) + k) \\Y &= \min(1, y \cdot (1 - k) + k)\end{aligned}$$

4.3.1 Generic RGB Color Space

The generic RGB color space is a mathematical description of the RGB color model. It is not associated with a particular device.

Color coordinates are the normalized intensities of the red, green, and blue primary. Values are real numbers in the closed interval $[0, 1]$. There is no white point.




Figure 4.1: RGB Color Space with sRGB Colors

generic-rgb-color [Class]

Color class for the generic RGB color space.

Class Precedence List

generic-rgb-color, rgb-color-object, generic-color-object, color-object,
...

make-generic-rgb-color *red green blue* &key *byte-size* [Function]

Create a new color in the generic RGB color space.

- First argument *red* is the normalized intensity of the red primary.
- Second argument *green* is the normalized intensity of the green primary.
- Third argument *blue* is the normalized intensity of the blue primary.

Arguments *red*, *green*, and *blue* have to be real numbers in the closed interval $[0, 1]$.

Keyword argument *byte-size* is the number of bits used to represent a primary. If specified, arguments *red*, *green*, and *blue* have to be integral numbers in the range from 0 to $2^n - 1$ where n is the number of bits. If so, arguments *red*, *green*, and *blue* are scaled accordingly.

Example:

```
(make-generic-rgb-color 252/255 175/255 62/255)
⇒ #<GENERIC-RGB-COLOR (84/85 35/51 62/255)>
```

```
(make-generic-rgb-color 252 175 62 :byte-size 8)
⇒ #<GENERIC-RGB-COLOR (84/85 35/51 62/255)>
```

make-generic-rgb-color-from-number *value* &key *byte-size* [Function]
 Create a new color in the generic RGB color space.

- Argument *value* is the numerical value of the encoded RGB color coordinates.

Keyword argument *byte-size* is the number of bits used to represent a primary. Default is eight bit (one byte). Argument *value* has to be an integral number in the range from 0 to $2^{3n} - 1$ where n is the number of bits per primary. The most significant bits denote the intensity of the red primary.

Example:

```
(make-generic-rgb-color-from-number #XFCAF3E)
⇒ #<GENERIC-RGB-COLOR (84/85 35/51 62/255)>
```

generic-rgb-color-coordinates *color* [Generic Function]
 Return the generic RGB color space coordinates of the color.

- Argument *color* is a color object.

Values are the normalized intensities of the red, green, and blue primary.

4.3.2 Generic HSV Color Space

The HSV color space is a different representation of the RGB color model. The HSV color space is also called HSB color space. The generic HSV color space is not associated with a particular device.

Color coordinates are hue, saturation, and value (brightness). Hue is measured in degree angle and it is a real number in the half-closed interval $[0, 360)$. Saturation and value are real numbers in the closed interval $[0, 1]$. There is no white point.

The HSV color space is a cylindrical coordinate system but it is usually visualized as a cone as depicted in Figure 4.2. $H = 0^\circ$ is red, $H = 120^\circ$ is green, and $H = 240^\circ$ is blue. $S = 0$ is the centerline of the cone with the gray levels from black ($V = 0$) to white ($V = 1$). $S = 1$ defines the surface of the cone.




Figure 4.2: HSV Color Space with sRGB Colors

generic-hsv-color [Class]
 Color class for the generic HSV color space.

Class Precedence List

generic-hsv-color, hsv-color-object, generic-color-object, color-object,
 ...

make-generic-hsv-color *hue saturation value* [Function]

Create a new color in the generic HSV color space.

- First argument *hue* is the angle of the RGB color wheel in degree.
- Second argument *saturation* is the saturation.
- Third argument *value* is the brightness.

Argument *hue* has to be a real number. It's value is reduced to the half-closed interval $[0, 360)$. Arguments *saturation* and *value* have to be real numbers in the closed interval $[0, 1]$.

generic-hsv-color-coordinates *color* [Generic Function]

Return the generic HSV color space coordinates of the color.

- Argument *color* is a color object.

Values are the hue, saturation, and value (brightness).

4.3.3 Generic HSL Color Space

The HSL color space is a different representation of the RGB color model. The generic HSL color space is not associated with a particular device.

Color coordinates are hue, saturation, and lightness. Hue is measured in degree angle and it is a real number in the half-closed interval $[0, 360)$. Saturation and lightness are real numbers in the closed interval $[0, 1]$. There is no white point.

The HSL color space is a cylindrical coordinate system but it is usually visualized as a bicone as depicted in Figure 4.3. $H = 0^\circ$ is red, $H = 120^\circ$ is green, and $H = 240^\circ$ is blue. $S = 0$ is the centerline of the bicone with the gray levels from black ($L = 0$) to white ($L = 1$). $S = 1$ defines the surface of the bicone.




Figure 4.3: HSL Color Space with sRGB Colors

generic-hsl-color [Class]

Color class for the generic HSL color space.

Class Precedence List

`generic-hsl-color`, `hsl-color-object`, `generic-color-object`, `color-object`,
...

make-generic-hsl-color *hue saturation lightness* [Function]

Create a new color in the generic HSL color space.

- First argument *hue* is the angle of the RGB color wheel in degree.
- Second argument *saturation* is the saturation.

- Third argument *lightness* is the lightness.

Argument *hue* has to be a real number. It's value is reduced to the half-closed interval $[0, 360)$. Arguments *saturation* and *lightness* have to be real numbers in the closed interval $[0, 1]$.

generic-hsl-color-coordinates *color* [Generic Function]

Return the generic HSL color space coordinates of the color.

- Argument *color* is a color object.

Values are the hue, saturation, and lightness.

4.3.4 Generic CMY Color Space

The generic CMY color space is a mathematical description of the CMY color model. It is not associated with a particular device.

Color coordinates are the normalized intensities of the cyan, magenta, and yellow primary. Values are real numbers in the closed interval $[0, 1]$. There is no white point.

generic-cmy-color [Class]

Color class for the generic CMY color space.

Class Precedence List

generic-cmy-color, **cmy-color-object**, **generic-color-object**, **color-object**, ...

make-generic-cmy-color *cyan magenta yellow* &key *byte-size* [Function]

Create a new color in the generic CMY color space.

- First argument *cyan* is the normalized intensity of the cyan primary.
- Second argument *magenta* is the normalized intensity of the magenta primary.
- Third argument *yellow* is the normalized intensity of the yellow primary.

Arguments *cyan*, *magenta*, and *yellow* have to be real numbers in the closed interval $[0, 1]$.

Keyword argument *byte-size* is the number of bits used to represent a primary. If specified, arguments *cyan*, *magenta*, and *yellow* have to be integral numbers in the range from 0 to $2^n - 1$ where n is the number of bits. If so, arguments *cyan*, *magenta*, and *yellow* are scaled accordingly.

Example:

```
(make-generic-cmy-color 3/255 80/255 193/255)
⇒ #<GENERIC-CMY-COLOR (1/85 16/51 193/255)>
```

```
(make-generic-cmy-color 3 80 193 :byte-size 8)
⇒ #<GENERIC-CMY-COLOR (1/85 16/51 193/255)>
```

make-generic-cmy-color-from-number *value* &key *byte-size* [Function]

Create a new color in the generic CMY color space.

- Argument *value* is the numerical value of the encoded CMY color coordinates.

Keyword argument *byte-size* is the number of bits used to represent a primary. Default is eight bit (one byte). Argument *value* has to be an integral number in the range from 0 to $2^{3n} - 1$ where n is the number of bits per primary. The most significant bits denote the intensity of the cyan primary.

Example:

```
(make-generic-cmy-color-from-number #X0350C1)
⇒ #<GENERIC-CMY-COLOR (1/85 16/51 193/255)>
```

generic-cmy-color-coordinates *color* [Generic Function]

Return the generic CMY color space coordinates of the color.

- Argument *color* is a color object.

Values are the normalized intensities of the cyan, magenta, and yellow primary.

4.3.5 Generic CMYK Color Space

The generic CMYK color space is a mathematical description of the CMYK color model. It is not associated with a particular device.

Color coordinates are the normalized intensities of the cyan, magenta, yellow, and black (key) primary. Values are real numbers in the closed interval $[0, 1]$. There is no white point.

generic-cmyk-color [Class]

Color class for the generic CMYK color space.

Class Precedence List

generic-cmyk-color, **cmyk-color-object**, **generic-color-object**, **color-object**,
...

make-generic-cmyk-color *cyan magenta yellow black &key* *byte-size* [Function]

Create a new color in the generic CMYK color space.

- First argument *cyan* is the normalized intensity of the cyan primary.
- Second argument *magenta* is the normalized intensity of the magenta primary.
- Third argument *yellow* is the normalized intensity of the yellow primary.
- Fourth argument *black* is the normalized intensity of the black primary.

Arguments *cyan*, *magenta*, *yellow*, and *black* have to be real numbers in the closed interval $[0, 1]$. If *black* is zero, *cyan*, *magenta*, and *yellow* are converted from CMY color coordinates to CMYK color coordinates.

Keyword argument *byte-size* is the number of bits used to represent a primary. If specified, arguments *cyan*, *magenta*, *yellow*, and *black* have to be integral numbers in the range from 0 to $2^n - 1$ where n is the number of bits. If so, arguments *cyan*, *magenta*, *yellow*, and *black* are scaled accordingly.

Example:

```
(make-generic-cmyk-color 3/255 80/255 193/255 0)
⇒ #<GENERIC-CMYK-COLOR (0 11/36 95/126 1/85)>
```

```
(make-generic-cmyk-color 3 80 193 :byte-size 8)
⇒ #<GENERIC-CMYK-COLOR (0 11/36 95/126 1/85)>
```

make-generic-cmyk-color-from-number *value &key byte-size* [Function]

Create a new color in the generic CMYK color space.

- Argument *value* is the numerical value of the encoded CMYK color coordinates.

Keyword argument *byte-size* is the number of bits used to represent a primary. Default is eight bit (one byte). Argument *value* has to be an integral number in the range from 0 to $2^{4n} - 1$ where n is the number of bits per primary. The most significant bits denote the intensity of the cyan primary.

Example:

```
(make-generic-cmyk-color-from-number #X0350C100)
⇒ #<GENERIC-CMYK-COLOR (0 11/36 95/126 1/85)>
```

generic-cmyk-color-coordinates *color* [Generic Function]

Return the generic CMYK color space coordinates of the color.

- Argument *color* is a color object.

Values are the normalized intensities of the cyan, magenta, yellow, and black primary.

4.4 CIE Color Spaces

All CIE color spaces are absolute color spaces, that means they are device independent.

4.4.1 CIE RGB Color Space

The CIE RGB color space is the origin of all CIE color spaces.

Color coordinates are the normalized intensities of the red, green, and blue primary. Values are real numbers in the closed interval $[0, 1]$. The white point of the CIE RGB color space is the CIE standard illuminant E^1 .




Figure 4.4: CIE RGB Color Space with sRGB Colors

ciergb-color [Class]

Color class for the CIE RGB color space.

Class Precedence List

ciergb-color, rgb-color-object, color-object, ...

make-ciergb-color *red green blue* [Function]

Create a new color in the CIE RGB color space.

- First argument *red* is the normalized intensity of the red primary.
- Second argument *green* is the normalized intensity of the green primary.
- Third argument *blue* is the normalized intensity of the blue primary.

Arguments *red*, *green*, and *blue* have to be real numbers in the closed interval $[0, 1]$.

ciergb-color-coordinates *color* [Generic Function]

Return the CIE RGB color space coordinates of the color.

- Argument *color* is a color object.

Values are the normalized intensities of the red, green, and blue primary.

¹ You can easily check this if you convert CIE RGB white into the CIE xyY color space:

```
(change-class (make-ciergb-color 1 1 1) 'ciexyy-color)
⇒ #<CIEXYY-COLOR (1/3 1/3 1)>
```


4.4.2 CIE XYZ Color Space

The CIE XYZ color space is a linear transformation of the CIE RGB color space. The CIE XYZ color space covers all colors an average person can experience. Many other color spaces are defined against the CIE XYZ color space.

Color coordinates are the X , Y , and Z tristimulus values. The CIE XYZ color space has no explicit white point.




Figure 4.5: CIE XYZ Color Space with sRGB Colors

ciexyz-color [Class]

Color class for the CIE XYZ color space.

Class Precedence List

ciexyz-color, color-object, ...

make-ciexyz-color x y z [Function]

Create a new color in the CIE XYZ color space.

- First argument x is the X tristimulus value.
- Second argument y is the Y tristimulus value.
- Third argument z is the Z tristimulus value.

Arguments x , y , and z have to be non-negative real numbers.

ciexyz-color-coordinates *color* [Generic Function]

Return the CIE XYZ color space coordinates of the color.

- Argument *color* is a color object.

Values are the X , Y , and Z tristimulus values.

Objects of the **ciexyz-color** class can be instantiated with absolute and normalized color coordinates. However, if you want to convert colors from CIE XYZ color space to CIE RGB color space (or any other RGB color space), the CIE XYZ color coordinates have to be normalized color coordinates. See the **normalize-color** and **absolute-color**, for how to convert from absolute color coordinates to normalized color coordinates and vice versa.

4.4.3 CIE xyY Color Space

The CIE xyY color space uses the x and y chromaticity coordinates of the CIE XYZ color space. That is,

$$x = \frac{X}{X + Y + Z}$$

$$y = \frac{Y}{X + Y + Z}$$

$$z = \frac{Z}{X + Y + Z}$$

Simple arithmetic results in the following relations:

$$\frac{Y}{y} = X + Y + Z$$

$$1 = x + y + z$$

Therefore, the inverse transformation is

$$X = x \cdot \frac{Y}{y}$$

$$Y = y \cdot \frac{Y}{y} = Y$$

$$Z = z \cdot \frac{Y}{y} = (1 - x - y) \cdot \frac{Y}{y}$$




Figure 4.6: CIE xyY Color Space with sRGB Colors

ciexyy-color [Class]

Color class for the CIE xyY color space.

Class Precedence List

ciexyy-color, color-object, ...

make-ciexyy-color x^* y^* y [Function]

Create a new color in the CIE xyY color space.

- Arguments x^* and y^* are the x and y chromaticity coordinates of the CIE XYZ color space.
- Third argument y is the luminance, that is the Y tristimulus value of the CIE XYZ color space.

ciexyy-color-coordinates *color* [Generic Function]

Return the CIE xyY color space coordinates of the color.

- Argument *color* is a color object.

Values are the x and y chromaticity coordinates and the luminance.

4.4.4 CIE $L^*u^*v^*$ Color Space

The CIE $L^*u^*v^*$ color space is a non-linear transformation of the CIE XYZ color space. The CIE $L^*u^*v^*$ color space is more perceptually uniform than the CIE XYZ color space.

Color coordinates are lightness and two chromaticity coordinates. Lightness L^* is in the range from 0 to 100. However, values greater than 100 are accepted, too. The two chromaticity coordinates u^* and v^* are usually in the range from -100 to $+100$.

CIE $L^*u^*v^*$ color coordinates are always relative to a white point. This is either the white point of the color space you are converting from or CIE standard illuminant D50.




Figure 4.7: CIE $L^*u^*v^*$ Color Space with sRGB Colors

cieluv-default-white-point [Variable]

The default white point for colors in the CIE $L^*u^*v^*$ color space. Default value is the CIE 1931 D50 standard illuminant.

cieluv-color [Class]

Color class for the CIE $L^*u^*v^*$ color space.

Class Precedence List

cieluv-color, color-object, ...

make-cieluv-color $L^* u^* v^*$ &optional *white-point* [Function]

Create a new color in the CIE $L^*u^*v^*$ color space.

- First argument L^* is the lightness.
- Second argument u^* is the first chromaticity coordinate.
- Third argument v^* is the second chromaticity coordinate.
- Optional fourth argument *white-point* is the white point. Default is the value of ***cieluv-default-white-point***.

cieluv-color-coordinates *color* [Generic Function]

Return the CIE $L^*u^*v^*$ color space coordinates of the color.

- Argument *color* is a color object.

Values are the lightness and the two chromaticity coordinates.

4.4.5 CIE $L^*a^*b^*$ Color Space

The CIE $L^*a^*b^*$ color space is a non-linear transformation of the CIE XYZ color space. The CIE $L^*a^*b^*$ color space is more perceptually uniform than the CIE XYZ color space.

Color coordinates are lightness and two chromaticity coordinates. Lightness L^* is in the range from 0 to 100. However, values greater than 100 are accepted, too. The two

chromaticity coordinates a^* and b^* are usually in the range from -250 to $+250$ and from -100 to $+100$ respectively.

CIE $L^*a^*b^*$ color coordinates are always relative to a white point. This is either the white point of the color space you are converting from or CIE standard illuminant D50.




Figure 4.8: CIE $L^*a^*b^*$ Color Space with sRGB Colors

cielab-default-white-point [Variable]
The default white point for colors in the CIE $L^*a^*b^*$ color space. Default value is the CIE 1931 D50 standard illuminant.

cielab-color [Class]
Color class for the CIE $L^*a^*b^*$ color space.
Class Precedence List
cielab-color, color-object, ...

make-cielab-color $L^* a^* b^*$ &optional *white-point* [Function]
Create a new color in the CIE $L^*a^*b^*$ color space.

- First argument L^* is the lightness.
- Second argument a^* is the first chromaticity coordinate.
- Third argument b^* is the second chromaticity coordinate.
- Optional fourth argument *white-point* is the white point. Default is the value of ***cielab-default-white-point***.

cielab-color-coordinates *color* [Generic Function]
Return the CIE $L^*a^*b^*$ color space coordinates of the color.

- Argument *color* is a color object.

Values are the lightness and the two chromaticity coordinates.

4.4.6 CIE L^*C^*h Color Space

The CIE L^*C^*h color space is the transformation of the CIE $L^*a^*b^*$ color space from a Cartesian coordinate system into a cylindrical coordinate system.

Color coordinates are lightness, chroma, and hue. Lightness L^* is equal to the lightness of the CIE $L^*a^*b^*$ color space. Chroma C^* and hue h are the polar coordinates, i.e. radius and angle, of a color in the (a^*, b^*) plane.

Hue is measured in degree angle; $h = 0^\circ$ is the positive a^* -axis (red), $h = 90^\circ$ is the positive b^* -axis (yellow), $h = 180^\circ$ is the negative a^* -axis (green), and $h = 270^\circ$ is the negative b^* -axis (blue).

CIE L^*C^*h color coordinates are always relative to a white point. This is either the white point of the color space you are converting from or CIE standard illuminant D50.

cielch-default-white-point [Variable]
The default white point for colors in the CIE L^*C^*h color space. Default value is the CIE 1931 D50 standard illuminant.

cielch-color [Class]
Color class for the CIE L^*C^*h color space.
Class Precedence List
cielch-color, **color-object**, ...

make-cielch-color $L^* C^* h$ & optional *white-point* [Function]
Create a new color in the CIE L^*C^*h color space.

- First argument L^* is the lightness.
- Second argument C^* is the chroma.
- Third argument h is the hue.
- Optional fourth argument *white-point* is the white point. Default is the value of ***cielch-default-white-point***.

Arguments L^* and C^* have to be non-negative real numbers. Argument h has to be a real number. It's value is reduced to the half-closed interval $[0, 360)$.

cielch-color-coordinates *color* [Generic Function]
Return the CIE L^*C^*h color space coordinates of the color.

- Argument *color* is a color object.

Values are the lightness, chroma, and hue.

4.4.7 CIE Standard Observers

cie-1931-standard-observer [Constant]
CIE standard observer for a 2° field of view.
Value are the color matching functions $\bar{x}(\lambda)$, $\bar{y}(\lambda)$, and $\bar{z}(\lambda)$. The wavelength λ ranges from 380 nm to 780 nm in steps of 5 nm.
See the ***color-matching-functions*** special variable for more details.

cie-1964-standard-observer [Constant]
CIE standard observer for a 10° field of view.
Value are the color matching functions $\bar{x}(\lambda)$, $\bar{y}(\lambda)$, and $\bar{z}(\lambda)$. The wavelength λ ranges from 380 nm to 780 nm in steps of 5 nm.
See the ***color-matching-functions*** special variable for more details.

color-matching-functions *wavelength* [Function]
Evaluate the color matching functions.
The binding of the ***color-matching-functions*** special variable defines the color matching functions $\bar{x}(\lambda)$, $\bar{y}(\lambda)$, and $\bar{z}(\lambda)$.

- Argument *wavelength* is the wavelength λ in nanometer.

Return values are the values of the color matching functions $\bar{x}(\lambda)$, $\bar{y}(\lambda)$, and $\bar{z}(\lambda)$ for the wavelength λ .

color-matching-functions [Variable]

A list of three color matching functions. Default is the CIE 1931 standard observer.

Value is an alist of cons cells of the form `(l . (x y z))`. Key *l* is the wavelength λ in nanometer and values *x*, *y*, and *z* are the discrete values of the color matching functions $\bar{x}(\lambda)$, $\bar{y}(\lambda)$, and $\bar{z}(\lambda)$ respectively. The list elements have to be sorted in strictly increasing order of the wavelength.

Value can also be a list of three functions, i.e. `(x y z)`. where *x*, *y*, and *z* are the color matching functions $\bar{x}(\lambda)$, $\bar{y}(\lambda)$, and $\bar{z}(\lambda)$ respectively.

Use the `color-matching-functions` function to evaluate the color matching functions.

cie-xy-chromaticity-of-light *wavelength* [Function]

Calculate the chromaticity coordinates of a single color of light. These chromaticity coordinates define the border of the chromaticity space in a chromaticity diagram.

- Argument *wavelength* is the wavelength λ of the light in nanometer.

Return values are the CIE xyY color space chromaticity coordinates *x* and *y* as multiple values.

The three color matching functions $\bar{x}(\lambda)$, $\bar{y}(\lambda)$, and $\bar{z}(\lambda)$ are evaluated by calling the `color-matching-functions` function.

cie-xy-chromaticity-of-black-body *temperature* &key *from to* *by* [Function]

Calculate the chromaticity coordinates of a Planckian radiator. These chromaticity coordinates define the Planckian locus in a chromaticity diagram.

- Argument *temperature* is the temperature of the black body in kelvin.
- Keyword arguments *from*, *to*, and *by* define the boundaries and step size for the wavelength λ of the light in nanometer. Default is 380 nm, 780 nm, and 5 nm respectively.

Return values are the CIE xyY color space chromaticity coordinates *x* and *y* as multiple values.

The three color matching functions $\bar{x}(\lambda)$, $\bar{y}(\lambda)$, and $\bar{z}(\lambda)$ are evaluated by calling the `color-matching-functions` function. The second radiation constant for calculating the spectral radiant exitance of the black body is defined by the binding of the `*second-radiation-constant*` special variable.

second-radiation-constant [Variable]

Second radiation constant. Default is `codata-2018-second-radiation-constant`.

cie-1931-second-radiation-constant [Constant]

Second radiation constant.

Value used by the CIE when defining the CIE 1931 color space.

codata-2018-second-radiation-constant [Constant]

Second radiation constant.

2018 CODATA recommended value.

4.4.8 CIE Standard Illuminants

cie-1931-white-point-a [Constant]

cie-1931-white-point-b [Constant]

cie-1931-white-point-c [Constant]

cie-1931-white-point-d50 [Constant]

<code>cie-1931-white-point-d55</code>	[Constant]
<code>cie-1931-white-point-d65</code>	[Constant]
<code>cie-1931-white-point-d75</code>	[Constant]
<code>cie-1931-white-point-e</code>	[Constant]
<code>cie-1931-white-point-f1</code>	[Constant]
<code>cie-1931-white-point-f2</code>	[Constant]
<code>cie-1931-white-point-f3</code>	[Constant]
<code>cie-1931-white-point-f4</code>	[Constant]
<code>cie-1931-white-point-f5</code>	[Constant]
<code>cie-1931-white-point-f6</code>	[Constant]
<code>cie-1931-white-point-f7</code>	[Constant]
<code>cie-1931-white-point-f8</code>	[Constant]
<code>cie-1931-white-point-f9</code>	[Constant]
<code>cie-1931-white-point-f10</code>	[Constant]
<code>cie-1931-white-point-f11</code>	[Constant]
<code>cie-1931-white-point-f12</code>	[Constant]

White points of the CIE standard illuminants for a 2° field of view (2° standard observer).

<code>cie-1964-white-point-a</code>	[Constant]
<code>cie-1964-white-point-b</code>	[Constant]
<code>cie-1964-white-point-c</code>	[Constant]
<code>cie-1964-white-point-d50</code>	[Constant]
<code>cie-1964-white-point-d55</code>	[Constant]
<code>cie-1964-white-point-d65</code>	[Constant]
<code>cie-1964-white-point-d75</code>	[Constant]
<code>cie-1964-white-point-e</code>	[Constant]
<code>cie-1964-white-point-f1</code>	[Constant]
<code>cie-1964-white-point-f2</code>	[Constant]
<code>cie-1964-white-point-f3</code>	[Constant]
<code>cie-1964-white-point-f4</code>	[Constant]
<code>cie-1964-white-point-f5</code>	[Constant]
<code>cie-1964-white-point-f6</code>	[Constant]
<code>cie-1964-white-point-f7</code>	[Constant]
<code>cie-1964-white-point-f8</code>	[Constant]
<code>cie-1964-white-point-f9</code>	[Constant]
<code>cie-1964-white-point-f10</code>	[Constant]
<code>cie-1964-white-point-f11</code>	[Constant]
<code>cie-1964-white-point-f12</code>	[Constant]

White points of the CIE standard illuminants for a 10° field of view (10° standard observer).

4.5 RGB Color Spaces

4.5.1 sRGB Color Space

<code>srgb-color</code>	[Class]
-------------------------	---------

Color class for the sRGB color space.

Class Precedence List

`srgb-color`, `rgb-color-object`, `color-object`, ...

<code>make-srgb-color</code> <i>red green blue &key byte-size</i>	[Function]
---	------------

Create a new color in the sRGB color space.

- First argument *red* is the normalized intensity of the red primary.
- Second argument *green* is the normalized intensity of the green primary.
- Third argument *blue* is the normalized intensity of the blue primary.

Arguments *red*, *green*, and *blue* have to be normalized intensity values in the closed interval $[0, 1]$.

Keyword argument *byte-size* is the number of bits used to represent a primary. If specified, arguments *red*, *green*, and *blue* have to be integral numbers in the range from 0 to $2^n - 1$ where n is the number of bits. If so, arguments *red*, *green*, and *blue* are scaled accordingly.

Example:

```
(make-srgb-color 252/255 175/255 62/255)
⇒ #<SRGB-COLOR (84/85 35/51 62/255)>
```

```
(make-srgb-color 252 175 62 :byte-size 8)
⇒ #<SRGB-COLOR (84/85 35/51 62/255)>
```

make-srgb-color-from-number *value* &key *byte-size* [Function]

Create a new color in the sRGB color space.

- Argument *value* is the numerical value of the encoded RGB color coordinates.

Keyword argument *byte-size* is the number of bits used to represent a primary. Default is eight bit (one byte). Argument *value* has to be an integral number in the range from 0 to $2^{3n} - 1$ where n is the number of bits per primary. The most significant bits denote the intensity of the red primary.

Example:

```
(make-srgb-color-from-number #XFCFA3E)
⇒ #<SRGB-COLOR (84/85 35/51 62/255)>
```

srgb-color-coordinates *color* [Generic Function]

Return the sRGB color space coordinates of the color.

- Argument *color* is a color object.

Values are the normalized intensities of the red, green, and blue primary.

4.5.2 Adobe RGB Color Space

adobe-rgb-color [Class]

Color class for the Adobe RGB color space.

Class Precedence List

adobe-rgb-color, rgb-color-object, color-object, ...

make-adobe-rgb-color *red green blue* &key *byte-size* [Function]

Create a new color in the Adobe RGB color space.

- First argument *red* is the normalized intensity of the red primary.
- Second argument *green* is the normalized intensity of the green primary.
- Third argument *blue* is the normalized intensity of the blue primary.

Arguments *red*, *green*, and *blue* have to be normalized intensity values in the closed interval $[0, 1]$.

Keyword argument *byte-size* is the number of bits used to represent a primary. If specified, arguments *red*, *green*, and *blue* have to be integral numbers in the range

from 0 to $2^n - 1$ where n is the number of bits. If so, arguments *red*, *green*, and *blue* are scaled accordingly.

Example:

```
(make-adobe-rgb-color 252/255 175/255 62/255)
⇒ #<ADOBE-RGB-COLOR (84/85 35/51 62/255)>
```

```
(make-adobe-rgb-color 252 175 62 :byte-size 8)
⇒ #<ADOBE-RGB-COLOR (84/85 35/51 62/255)>
```

make-adobe-rgb-color-from-number *value* &key *byte-size* [Function]

Create a new color in the Adobe RGB color space.

- Argument *value* is the numerical value of the encoded RGB color coordinates.

Keyword argument *byte-size* is the number of bits used to represent a primary. Default is eight bit (one byte). Argument *value* has to be an integral number in the range from 0 to $2^{3n} - 1$ where n is the number of bits per primary. The most significant bits denote the intensity of the red primary.

Example:

```
(make-adobe-rgb-color-from-number #XFCAF3E)
⇒ #<ADOBE-RGB-COLOR (84/85 35/51 62/255)>
```

adobe-rgb-color-coordinates *color* [Generic Function]

Return the Adobe RGB color space coordinates of the color.

- Argument *color* is a color object.

Values are the normalized intensities of the red, green, and blue primary.

4.6 Color Properties

color-coordinates *color* [Generic Function]

Return the color space coordinates of the color as multiple values.

- Argument *color* is a color object.

white-point *color* [Generic Function]

Return the white point of the color.

- Argument *color* is a color object.

Value is the color object of the color's white point, or nil if the white point is not defined or if multiple white points exist.

4.7 Color Conversions

change-class *color color-type* [Generic Function]

Change the class of the color object.

- First argument *color* is a color object.
- Second argument *color-type* is a color data type.

The **change-class** function destructively modifies *color* by converting it's color coordinates into the color space denoted by *color-type*.

Example:

```
(let ((red (make-srgb-color 1 0 0)))
  (change-class red 'ciexyy-color)
  red)
⇒ #<CIEXYY-COLOR (0.64d0 0.33d0 ...)>
```

coerce-color *color color-type* [Function]

Coerce the color object into the specified color type.

- First argument *color* is a color object.
- Second argument *color-type* is a color data type.

If argument *color* is already a color of the requested color data type, return *color* as is (no conversion). Otherwise, return a new color with the color coordinates of *color* converted into the color space denoted by *color-type*.

copy-color *color* [Generic Function]

Return a shallow copy of the color.

- Argument *color* is a color object.

Value is a color object with the same color coordinates as *color*.

4.8 Color Differences

cie76 *first-color second-color* [Function]

Calculate the CIE76 color difference between two colors.

Value is the Euclidean distance between the two colors in the CIE L*a*b* color space. The CIE76 color difference is symmetric, i.e. CIE76(a,b) is equal to CIE76(b,a).

cie94 *reference other* &optional *textile lightness chroma hue* [Function]

Calculate the CIE94 color difference between two colors.

- First argument *reference* is the reference color.
- Second argument *other* is the other color.
- If optional third argument *textile* is non-null, use parameters for calculating the color difference for textiles. Default is to calculate the color difference for graphic arts.
- Optional fourth to sixth argument *lightness*, *chroma*, and *HUE* are the weighting factors for differences in lightness, chroma, and hue respectively. Higher value means less weight. Default is one for all weighting factors (if *textile* is true, the default for *lightness* is two).

The CIE94 color difference is asymmetric, i.e. CIE94(a,b) is not equal to CIE94(b,a).

4.9 Input and Output

4.9.1 Xcms Formats

The syntax of a Xcms (X Color Management System) color is

prefix:first/second/third

The *prefix* part specifies the color space or format and *first*, *second*, and *third* are the color coordinates. Below is a table with all color spaces and corresponding Xcms prefix.

Color Space	Prefix	R5
CIE RGB	CIERGB	
CIE XYZ	CIEXYZ	•
CIE xyY	CIExyY	•
CIE L*u*v*	CIELuv	•
CIE L*a*b*	CIELab	•
CIE L*C*h	CIELCh	

generic RGB	RGBi	•
generic RGB	RGB	•

The Xcms prefix is case insensitive.

<code>print-color-xcms-ciergb</code>	<i>color</i> &optional <i>stream</i>	[Function]
<code>print-color-xcms-ciexyz</code>	<i>color</i> &optional <i>stream</i>	[Function]
<code>print-color-xcms-ciexyy</code>	<i>color</i> &optional <i>stream</i>	[Function]
<code>print-color-xcms-cieluv</code>	<i>color</i> &optional <i>stream</i>	[Function]
<code>print-color-xcms-cielab</code>	<i>color</i> &optional <i>stream</i>	[Function]
<code>print-color-xcms-cielch</code>	<i>color</i> &optional <i>stream</i>	[Function]
<code>print-color-xcms-rgbi</code>	<i>color</i> &optional <i>stream</i>	[Function]
<code>print-color-xcms-rgb</code>	<i>color</i> &optional <i>stream</i>	[Function]

Print a color in Xcms notation.

- First argument *color* is a color object.
- Optional second argument *stream* is an output stream. Default is to print to `*standard-output*`.

Value is the color object.

The RGBi and RGB formats are device dependent. Thus, you can only print colors in these formats if the color conversion path to the generic RGB color space is unambiguous.

The RGB format prints the color coordinates as hexadecimal numbers. If all RGB color intensities are multiples of 1/255, it uses two digits. Otherwise, it uses four digits with a precision of 1/65535.

Example:

```
(let ((color (make-srgb-color 78 154 6 :byte-size 8)))
  (with-output-to-string (stream)
    (print-color-xcms-ciexyz color stream)))
⇒ "CIEXYZ:0.14729778/0.24743336/0.04172078"

(let ((color (make-srgb-color-from-number #X4E9A06)))
  (with-output-to-string (stream)
    (print-color-xcms-rgb color stream)))
⇒ "RGB:4e/9a/06"
```

<code>color-formatter-xcms-ciergb</code>	[Constant]
<code>color-formatter-xcms-ciexyz</code>	[Constant]
<code>color-formatter-xcms-ciexyy</code>	[Constant]
<code>color-formatter-xcms-cieluv</code>	[Constant]
<code>color-formatter-xcms-cielab</code>	[Constant]
<code>color-formatter-xcms-cielch</code>	[Constant]
<code>color-formatter-xcms-rgbi</code>	[Constant]
<code>color-formatter-xcms-rgb</code>	[Constant]

A format function for printing a color in Xcms notation.

Value is a function which has a behavior equivalent to a function returned by the `formatter` macro.

Example:

```
(let ((color (make-srgb-color 78 154 6 :byte-size 8)))
  (format nil color-formatter-xcms-ciexyz color))
⇒ "CIEXYZ:0.14729778/0.24743336/0.04172078"
```

<code>read-color-xcms-ciergb</code>	<code>&optional stream</code>	[Function]
<code>read-color-xcms-ciexyz</code>	<code>&optional stream</code>	[Function]
<code>read-color-xcms-ciexyy</code>	<code>&optional stream</code>	[Function]
<code>read-color-xcms-cieluv</code>	<code>&optional stream</code>	[Function]
<code>read-color-xcms-cielab</code>	<code>&optional stream</code>	[Function]
<code>read-color-xcms-cielch</code>	<code>&optional stream</code>	[Function]
<code>read-color-xcms-rgbi</code>	<code>&optional stream</code>	[Function]
<code>read-color-xcms-rgb</code>	<code>&optional stream</code>	[Function]
<code>read-color-xcms</code>	<code>&optional stream</code>	[Function]

Read a color in Xcms notation.

- Optional argument *stream* is an input stream. Default is to read from `*standard-input*`.

Value is a color object in the respective color space.

The functions expect the respective Xcms prefix followed by a colon and the three color coordinates separated by a slash character. Leading or trailing whitespace is not ignored. Reading stops immediately after the last color coordinate. An error is signaled if a parse error occurs or if the file ends prematurely.

The `read-color-xcms` function is slightly different since it first reads the Xcms prefix and then dispatches on it.

Example:

```
(with-input-from-string (stream "RGB:4e/9a/06 junk")
  (change-class (read-color-xcms stream) 'srgb-color))
⇒ #<SRGB-COLOR (26/85 154/255 2/85)>
```

4.9.2 HTML Format

A HTML color value is either a hexadecimal number prefixed by a hash mark or a keyword. This section only covers numerical color values.

<code>print-color-html</code>	<code>color &optional stream</code>	[Function]
-------------------------------	---	------------

Print a numerical HTML color value, that is a hexadecimal number prefixed by a hash mark.

- First argument *color* is a color object.
- Optional second argument *stream* is an output stream. Default is to print to `*standard-output*`.

Value is the color object.

Example:

```
(let ((color (make-srgb-color-from-number #X4E9A06)))
  (with-output-to-string (stream)
    (print-color-html color stream)))
⇒ "#4E9A06"
```

<code>color-formatter-html</code>	[Constant]
-----------------------------------	------------

A format function for printing a numerical HTML color value.

Value is a function which has a behavior equivalent to a function returned by the `formatter` macro.

Example:

```
(let ((color (make-srgb-color-from-number #X4E9A06)))
  (format nil color-formatter-html color))
⇒ "#4E9A06"
```

read-color-html &optional *stream* [Function]

Read a numerical HTML color value, that is a hexadecimal number prefixed by a hash mark.

- Optional argument *stream* is an input stream. Default is to read from **standard-input**.

Value is a color object in the sRGB color space.

The function expects a hash mark followed by a sequence of hexadecimal digits. The number of hexadecimal digits has to be a multiple of three. Leading or trailing white-space is not ignored. Reading stops at the first non-hexadecimal digit character. An error is signaled if a parse error occurs or if the file ends prematurely.

Example:

```
(with-input-from-string (stream "#4E9A06 junk")
  (read-color-html stream))
⇒ #<SRGB-COLOR (26/85 154/255 2/85)>
```

4.9.3 CSS3 Formats

A CSS3 (cascading style sheets, level 3) color is either a HTML color value or a color value in functional notation. The later has the form

rgb(*red*, *green*, *blue*)

where *red*, *green*, and *blue* are either integers in the range from 0 to 255 or percentage values in the range from 0 % to 100 %. CSS3 also supports a functional notation for RGB colors represented in the HSL color space. The format is

hsl(*hue*, *saturation*, *lightness*)

where *hue* is the angle in degree and *saturation* and *lightness* are percentage values in the range from 0 % to 100 %.

print-color-css3-rgb *color* &optional *stream* [Function]

print-color-css3-hsl *color* &optional *stream* [Function]

Print a color in CSS3 functional notation.

- First argument *color* is a color object.
- Optional second argument *stream* is an output stream. Default is to print to **standard-output**.

Value is the color object.

If all sRGB color intensities are multiples of 1/255, the *red*, *green*, and *blue* color intensities are printed as integers. Otherwise, they are printed as percentage values.

Example:

```
(let ((color (make-srgb-color-from-number #X4E9A06)))
  (with-output-to-string (stream)
    (print-color-css3-rgb color stream)))
⇒ "rgb(78, 154, 6)"

(let ((color (make-srgb-color 0.3D0 0.6D0 0.1D0)))
  (with-output-to-string (stream)
    (print-color-css3-rgb color stream)))
⇒ "rgb(30.0%, 60.0%, 10.0%)"
```

color-formatter-css3-rgb [Constant]

color-formatter-css3-hsl [Constant]

A format function for printing a color in CSS3 functional notation.

Value is a function which has a behavior equivalent to a function returned by the `formatter` macro.

Example:

```
(let ((color (make-srgb-color-from-number #X4E9A06)))
  (format nil color-formatter-css3-rgb color))
⇒ "rgb(78, 154, 6)"
```

`read-color-css3-rgb` &optional *stream* [Function]

`read-color-css3-hsl` &optional *stream* [Function]

Read a color in CSS3 functional notation.

- Optional argument *stream* is an input stream. Default is to read from `*standard-input*`.

Value is a color object in the sRGB color space.

The functions expect a character sequence of the form `rgb(red,green,blue)` or `hsl(hue,saturation,lightness)` respectively. Leading or trailing whitespace is not ignored but whitespace characters are allowed around the numerical values. Reading stops after the closing parenthesis. An error is signaled if a parse error occurs or if the file ends prematurely.

Example:

```
(with-input-from-string (stream "rgb(78, 154, 6) junk")
  (read-color-css3-rgb stream))
⇒ #<SRGB-COLOR (26/85 154/255 2/85)>

(with-input-from-string (stream "rgb(30%, 60%, 10%) junk")
  (read-color-css3-rgb stream))
⇒ #<SRGB-COLOR (0.3d0 0.6d0 0.1d0)>
```

`read-color-css3` &optional *stream* [Function]

Read a CSS3 color value, i.e. either a numerical HTML color value or a color in RGB or HSL functional notation.

- Optional argument *stream* is an input stream. Default is to read from `*standard-input*`.

Value is a color object in the sRGB color space.

See the `read-color-html`, `read-color-css3-rgb`, and `read-color-css3-hsl` function for more details.

4.10 Miscellaneous

`normalize-color` *color* &key *black white* [Generic Function]

Convert from absolute color coordinates to normalized color coordinates.

`absolute-color` *color* &key *black white* [Generic Function]

Convert from normalized color coordinates to absolute color coordinates.

Symbol Index

*

cielab-default-white-point	24
cielch-default-white-point	25
cielv-default-white-point	23
color-matching-functions	26
second-radiation-constant	26

A

absolute-color	34
adobe-rgb-color	28
adobe-rgb-color-coordinates	29

C

change-class	29
cie-1931-second-radiation-constant	26
cie-1931-standard-observer	25
cie-1931-white-point-a	26
cie-1931-white-point-b	26
cie-1931-white-point-c	26
cie-1931-white-point-d50	26
cie-1931-white-point-d55	26
cie-1931-white-point-d65	27
cie-1931-white-point-d75	27
cie-1931-white-point-e	27
cie-1931-white-point-f1	27
cie-1931-white-point-f10	27
cie-1931-white-point-f11	27
cie-1931-white-point-f12	27
cie-1931-white-point-f2	27
cie-1931-white-point-f3	27
cie-1931-white-point-f4	27
cie-1931-white-point-f5	27
cie-1931-white-point-f6	27
cie-1931-white-point-f7	27
cie-1931-white-point-f8	27
cie-1931-white-point-f9	27
cie-1964-standard-observer	25
cie-1964-white-point-a	27
cie-1964-white-point-b	27
cie-1964-white-point-c	27
cie-1964-white-point-d50	27
cie-1964-white-point-d55	27
cie-1964-white-point-d65	27
cie-1964-white-point-d75	27
cie-1964-white-point-e	27
cie-1964-white-point-f1	27
cie-1964-white-point-f10	27
cie-1964-white-point-f11	27
cie-1964-white-point-f12	27
cie-1964-white-point-f2	27
cie-1964-white-point-f3	27
cie-1964-white-point-f4	27
cie-1964-white-point-f5	27
cie-1964-white-point-f6	27
cie-1964-white-point-f7	27
cie-1964-white-point-f8	27
cie-1964-white-point-f9	27
cie-xy-chromaticity-of-black-body	26

cie-xy-chromaticity-of-light	26
cie76	30
cie94	30
cielab-color	24
cielab-color-coordinates	24
cielch-color	25
cielch-color-coordinates	25
cielv-color	23
cielv-color-coordinates	23
ciergb-color	20
ciergb-color-coordinates	20
ciexy-color	22
ciexy-color-coordinates	22
ciexyz-color	21
ciexyz-color-coordinates	21
cmv-color-object	13
cmv-color-object	14
codata-2018-second-radiation-constant	26
coerce-color	30
color-coordinates	29
color-formatter-css3-hsl	33
color-formatter-css3-rgb	33
color-formatter-html	32
color-formatter-xcms-cielab	31
color-formatter-xcms-cielch	31
color-formatter-xcms-cieluv	31
color-formatter-xcms-ciergb	31
color-formatter-xcms-ciexy	31
color-formatter-xcms-ciexyz	31
color-formatter-xcms-rgb	31
color-formatter-xcms-rgbi	31
color-matching-functions	25
color-object	13
colorp	13
copy-color	30

G

generic-cmy-color	18
generic-cmy-color-coordinates	19
generic-cmyk-color	19
generic-cmyk-color-coordinates	20
generic-color-object	14
generic-hsl-color	17
generic-hsl-color-coordinates	18
generic-hsv-color	16
generic-hsv-color-coordinates	17
generic-rgb-color	15
generic-rgb-color-coordinates	16

H

hsl-color-object	13
hsv-color-object	13

M

make-adobe-rgb-color	28
make-adobe-rgb-color-from-number	29
make-cielab-color	24
make-cielch-color	25
make-cieluv-color	23
make-ciergb-color	20
make-ciexyy-color	22
make-ciexyz-color	21
make-generic-cmy-color	18
make-generic-cmy-color-from-number	18
make-generic-cmyk-color	19
make-generic-cmyk-color-from-number	19
make-generic-hsl-color	17
make-generic-hsv-color	17
make-generic-rgb-color	15
make-generic-rgb-color-from-number	16
make-srgb-color	27
make-srgb-color-from-number	28

N

normalize-color	34
-----------------------	----

P

print-color-css3-hsl	33
print-color-css3-rgb	33
print-color-html	32
print-color-xcms-cielab	31
print-color-xcms-cielch	31
print-color-xcms-cieluv	31
print-color-xcms-ciergb	31

print-color-xcms-ciexyy	31
print-color-xcms-ciexyz	31
print-color-xcms-rgb	31
print-color-xcms-rgbi	31

R

read-color-css3	34
read-color-css3-hsl	34
read-color-css3-rgb	34
read-color-html	33
read-color-xcms	32
read-color-xcms-cielab	32
read-color-xcms-cielch	32
read-color-xcms-cieluv	32
read-color-xcms-ciergb	32
read-color-xcms-ciexyy	32
read-color-xcms-ciexyz	32
read-color-xcms-rgb	32
read-color-xcms-rgbi	32
rgb-color-object	13

S

srgb-color	27
srgb-color-coordinates	28

W

white-point	29
-------------------	----

Concept Index

A

absolute color space	7
Adobe RGB color space	28

C

CIE $L^*a^*b^*$ color space	23
CIE L^*C^*h color space	24
CIE $L^*u^*v^*$ color space	23
CIE RGB color space	20
CIE standard observer	25
CIE xyY color space	21
CIE XYZ color space	21
CMY color model	14, 18
CMYK color model	14, 19
color conversion	9
color coordinates	9, 10
color data type	7
color format	30
color matching functions	25
color model	7, 14
color model, CMY	14, 18
color model, CMYK	14, 19
color model, RGB	14, 15
color names	11
color space, absolute	7
color space, Adobe RGB	28
color space, CIE $L^*a^*b^*$	23
color space, CIE L^*C^*h	24
color space, CIE $L^*u^*v^*$	23
color space, CIE RGB	20
color space, CIE xyY	21
color space, CIE XYZ	21
color space, device dependent	7
color space, HSB	16
color space, HSL	17
color space, HSV	16
color space, sRGB	27
converting colors	9
coordinates, color	9, 10
creating colors	8
CSS3 format	33

D

data type, color	7
device dependent color space	7

F

formatted I/O	30
---------------------	----

H

HSB color space	16
HSL color space	17
HSV color space	16
HTML format	32

M

making colors	8
---------------------	---

N

named colors	11
--------------------	----

P

printing colors	30
-----------------------	----

R

reading colors	30
RGB color model	14, 15

S

sRGB color space	27
------------------------	----

W

white point	9, 27
white point, CIE standard illuminant	26

X

Xcms format	30
-------------------	----

