

Graded String Diagrams

Ralph Sarkis

joint work with Fabio Zanasi

March 28th, 2025


- ▶ Graded monads and categories are popular in CS [6, 7, 8, 9, 10, 11, 12, 16, 18, 20, 21, 22, 26]. Morphisms $A \rightarrow B$ come with a grade γ from a monoidal category \mathbb{G} .

Abstract

- ▶ Graded monads and categories are popular in CS [6, 7, 8, 9, 10, 11, 12, 16, 18, 20, 21, 22, 26]. Morphisms $A \rightarrow B$ come with a grade γ from a monoidal category \mathbb{G} .
- ▶ String diagrams are popular in CS [1, 2, 3, 4, 5, 13, 14, 15, 23, 24, 25, 27, 28]. Morphisms in a monoidal category are drawn as string diagrams.


Abstract

- ▶ Graded monads and categories are popular in CS [6, 7, 8, 9, 10, 11, 12, 16, 18, 20, 21, 22, 26]. Morphisms $A \rightarrow B$ come with a grade γ from a monoidal category \mathbb{G} .
- ▶ String diagrams are popular in CS [1, 2, 3, 4, 5, 13, 14, 15, 23, 24, 25, 27, 28]. Morphisms in a monoidal category are drawn as string diagrams.
- ▶ We introduce graded string diagrams with dangling wires on the bottom and laws that allow diagrammatic reasoning:



Abstract

- ▶ Graded monads and categories are popular in CS [6, 7, 8, 9, 10, 11, 12, 16, 18, 20, 21, 22, 26]. Morphisms $A \rightarrow B$ come with a grade γ from a monoidal category \mathbb{G} .
- ▶ String diagrams are popular in CS [1, 2, 3, 4, 5, 13, 14, 15, 23, 24, 25, 27, 28]. Morphisms in a monoidal category are drawn as string diagrams.
- ▶ We introduce graded string diagrams with dangling wires on the bottom and laws that allow diagrammatic reasoning:



- ▶ Application to imprecise probability.

Graded String Diagrams

Imprecise Probability

Conclusion

Monoidal Theories and String Diagrams

- ▶ The signature Σ contains operations with (co)arities drawn as ${}^n\text{---}\boxed{f}\text{---}^m$.

Monoidal Theories and String Diagrams

- ▶ The signature Σ contains operations with (co)arities drawn as $n \text{---} \boxed{f} \text{---} m$.
- ▶ Monoidal terms are constructed inductively:

$$\text{id}_0 = \text{.....} \quad \text{id}_1 = \text{---} \quad \sigma_{1,1} = \text{X}$$

$$n \text{---} \boxed{f} \text{---} m ; m \text{---} \boxed{g} \text{---} \ell = n \text{---} \boxed{f} \boxed{g} \text{---} \ell$$

$$n \text{---} \boxed{f} \text{---} m \otimes n' \text{---} \boxed{f'} \text{---} m' = \begin{array}{c} n \text{---} \boxed{f} \text{---} m \\ n' \text{---} \boxed{f'} \text{---} m' \end{array}$$

Monoidal Theories and String Diagrams

- ▶ The signature Σ contains operations with (co)arities drawn as $n \text{---} \boxed{f} \text{---} m$.
- ▶ Monoidal terms are constructed inductively:

$$\text{id}_0 = \text{.....} \quad \text{id}_1 = \text{---} \quad \sigma_{1,1} = \text{X}$$

$$n \text{---} \boxed{f} \text{---} m ; m \text{---} \boxed{g} \text{---} \ell = n \text{---} \boxed{f} \boxed{g} \text{---} \ell$$

$$n \text{---} \boxed{f} \text{---} m \otimes n' \text{---} \boxed{f'} \text{---} m' = \begin{array}{c} n \text{---} \boxed{f} \text{---} m \\ n' \text{---} \boxed{f'} \text{---} m' \end{array}$$

- ▶ From Σ and a set E of equations between terms, we generate a syntactic category $\mathcal{M}_{\Sigma,E}$ of string diagrams.

$$\begin{array}{c} \boxed{f} \\ \text{---} \end{array} \text{---} \begin{array}{c} \boxed{g} \quad \boxed{h} \\ \text{---} \end{array} = \begin{array}{c} \boxed{f} \\ \text{---} \end{array} \text{---} \begin{array}{c} \boxed{h} \\ \text{---} \end{array} \text{---} \begin{array}{c} \boxed{g} \\ \text{---} \end{array} = \begin{array}{c} \boxed{e} \\ \text{---} \end{array} \text{---} \begin{array}{c} \boxed{h} \\ \text{---} \end{array}$$

Monoidal Theories and String Diagrams

- ▶ The signature Σ contains operations with (co)arities drawn as $n \text{---} \boxed{f} \text{---} m$.
- ▶ Monoidal terms are constructed inductively:

$$\begin{array}{l} \text{id}_0 = \text{.....} \quad \text{id}_1 = \text{---} \quad \sigma_{1,1} = \text{X} \\ n \text{---} \boxed{f} \text{---} m ; m \text{---} \boxed{g} \text{---} \ell = n \text{---} \boxed{f} \boxed{g} \text{---} \ell \quad n \text{---} \boxed{f} \text{---} m \otimes n' \text{---} \boxed{f'} \text{---} m' = \begin{array}{c} n \text{---} \boxed{f} \text{---} m \\ n' \text{---} \boxed{f'} \text{---} m' \end{array} \end{array}$$

- ▶ From Σ and a set E of equations between terms, we generate a syntactic category $\mathcal{M}_{\Sigma,E}$ of string diagrams.


$$\begin{array}{c} \boxed{f} \\ \text{---} \end{array} \text{---} \begin{array}{c} \boxed{g} \quad \boxed{h} \\ \text{---} \end{array} = \begin{array}{c} \boxed{f} \\ \text{---} \end{array} \text{---} \begin{array}{c} \boxed{h} \\ \text{---} \end{array} \text{---} \text{X} = \begin{array}{c} \boxed{e} \\ \text{---} \end{array} \text{---} \begin{array}{c} \boxed{h} \\ \text{---} \end{array} \text{---} \text{X}$$

- ▶ Models of the theory (Σ, E) are monoidal functors $\mathcal{M}_{\Sigma,E} \rightarrow \mathbf{C}$.

Monoidal Theories and String Diagrams

Examples

1. With a single generator $\bullet \text{---}$ and no equations we get **FinInj**.
2. With a single generator $\text{---} \bullet$ that is *commutative and associative* we get **FinSurj**.
3. With generators \sqcup , \sqcap , \neg , \wedge , \vee , 1 , 0 , $\text{---} \bullet$, and $\text{---} \bullet \text{---}$, and equations from Boolean algebra, we get the subcategory of **FinSet** spanned by $\{1, 0\}^n$.



(All from Lafont [17].)

Graded Categories

Let \mathbb{G} be a semicartesian monoidal category.

Definition

A **\mathbb{G} -graded category** consists of

- ▶ A collection of objects $\text{Ob}(\mathbf{C})$ and sets of morphisms $\mathbf{C}_\gamma(X, Y)$ indexed by objects X, Y in \mathbf{C} and γ in \mathbb{G} .
- ▶ Compositions and identities: $\circ : \mathbf{C}_\gamma(X, Y) \times \mathbf{C}_\varepsilon(Y, Z) \rightarrow \mathbf{C}_{\gamma\varepsilon}(X, Z)$ and $\text{id}_X \in \mathbf{C}_1(X, X)$.
- ▶ **Regrading** operations $t \star - : \mathbf{C}_\varepsilon(X, Y) \rightarrow \mathbf{C}_\gamma(X, Y)$, for all $t : \gamma \rightarrow \varepsilon$.
- ▶ It is **monoidal** if it comes with a unit $I \in \text{Ob}(\mathbf{C})$ and monoidal product $\otimes : \mathbf{C}_\gamma(X, Y) \times \mathbf{C}_\varepsilon(X', Y') \rightarrow \mathbf{C}_{\gamma\varepsilon}(X \otimes X', Y \otimes Y')$.

Graded Categories

Let \mathbb{G} be a semicartesian monoidal category.

Definition

A **\mathbb{G} -graded category** consists of

- ▶ A collection of objects $\text{Ob}(\mathbf{C})$ and sets of morphisms $\mathbf{C}_\gamma(X, Y)$ indexed by objects X, Y in \mathbf{C} and γ in \mathbb{G} .
- ▶ Compositions and identities: $\circ : \mathbf{C}_\gamma(X, Y) \times \mathbf{C}_\varepsilon(Y, Z) \rightarrow \mathbf{C}_{\gamma\varepsilon}(X, Z)$ and $\text{id}_X \in \mathbf{C}_1(X, X)$.
- ▶ **Regrading** operations $t \star - : \mathbf{C}_\varepsilon(X, Y) \rightarrow \mathbf{C}_\gamma(X, Y)$, for all $t : \gamma \rightarrow \varepsilon$.
- ▶ It is **monoidal** if it comes with a unit $I \in \text{Ob}(\mathbf{C})$ and monoidal product $\otimes : \mathbf{C}_\gamma(X, Y) \times \mathbf{C}_\varepsilon(X', Y') \rightarrow \mathbf{C}_{\gamma\varepsilon}(X \otimes X', Y \otimes Y')$.

Example

The \mathbb{N} -graded Kleisli category of the graded list monad has sets as objects, and a morphism $X \xrightarrow{n} Y$ is a function sending each $x \in X$ to a list of n elements in Y .

Graded Categories

Let \mathbb{G} be a semicartesian monoidal category.

Definition

A \mathbb{G} -graded category consists of

- ▶ A collection of objects $\text{Ob}(\mathbf{C})$ and sets of morphisms $\mathbf{C}_\gamma(X, Y)$ indexed by objects X, Y in \mathbf{C} and γ in \mathbb{G} .
- ▶ Compositions and identities: $\circ : \mathbf{C}_\gamma(X, Y) \times \mathbf{C}_\varepsilon(Y, Z) \rightarrow \mathbf{C}_{\gamma\varepsilon}(X, Z)$ and $\text{id}_X \in \mathbf{C}_1(X, X)$.
- ▶ **Regrading** operations $t \star - : \mathbf{C}_\varepsilon(X, Y) \rightarrow \mathbf{C}_\gamma(X, Y)$, for all $t : \gamma \rightarrow \varepsilon$.
- ▶ It is **monoidal** if it comes with a unit $I \in \text{Ob}(\mathbf{C})$ and monoidal product $\otimes : \mathbf{C}_\gamma(X, Y) \times \mathbf{C}_\varepsilon(X', Y') \rightarrow \mathbf{C}_{\gamma\varepsilon}(X \otimes X', Y \otimes Y')$.

Example

The \mathbb{N} -graded Kleisli category of the graded list monad has sets as objects, and a morphism $X \xrightarrow{n} Y$ is a function sending each $x \in X$ to a list of n elements in Y . Graded categories generalize enriched categories and actegories [19].

Graded Monoidal Theories

- ▶ A **graded signature** Σ contains operations with (co)arities and a grade, all in \mathbb{N} , drawn as $n \text{---} \boxed{f} \text{---} m$ with a grade a below the box.

- ▶ Graded terms are constructed inductively.

$$n \text{---} \boxed{f} \text{---} m \circledcirc m \text{---} \boxed{g} \text{---} \ell = n \text{---} \boxed{f} \text{---} \boxed{g} \text{---} \ell$$

$\begin{array}{ccc} a & & b \end{array}$


$$n \text{---} \boxed{f} \text{---} m \otimes n' \text{---} \boxed{g} \text{---} m' = \begin{array}{c} n \text{---} \boxed{f} \text{---} m \\ | \\ n' \text{---} \boxed{g} \text{---} m' \end{array}$$

$\begin{array}{ccc} a & & b \end{array}$


$$\begin{array}{c} a \\ | \\ \boxed{t} \\ | \\ b \end{array} \star n \text{---} \boxed{f} \text{---} m = \begin{array}{c} n \text{---} \boxed{f} \text{---} m \\ | \\ \boxed{t} \\ | \\ b \end{array}$$

- ▶ From Σ and a set E of equations between graded terms, we generate a syntactic category $\mathcal{S}_{\Sigma, E}$ of graded string diagrams.

Graded String Diagrams



Graded String Diagrams



Models of the graded theory (Σ, E) are graded monoidal functors $\mathcal{S}_{\Sigma, E} \rightarrow \mathbf{C}$.

Graded Para Construction

An action of \mathbb{G} on \mathbf{C} given by a symmetric monoidal functor $\bullet : \mathbb{G} \times \mathbf{C} \rightarrow \mathbf{C}$ yields a \mathbb{G} -graded category through the **Para** construction. Objects of $\mathbf{Para}(\mathbb{G}, \mathbf{C})$ are objects of \mathbf{C} , and morphisms $X \xrightarrow{\gamma} Y$ are morphisms $\gamma \bullet X \rightarrow Y$ in \mathbf{C} .

Graded Para Construction

An action of \mathbb{G} on \mathbf{C} given by a symmetric monoidal functor $\bullet : \mathbb{G} \times \mathbf{C} \rightarrow \mathbf{C}$ yields a \mathbb{G} -graded category through the **Para** construction. Objects of $\mathbf{Para}(\mathbb{G}, \mathbf{C})$ are objects of \mathbf{C} , and morphisms $X \xrightarrow{\gamma} Y$ are morphisms $\gamma \bullet X \rightarrow Y$ in \mathbf{C} .

Theorem

If \mathbf{C} is presented by $(\Sigma_{\mathbf{C}}, E_{\mathbf{C}})$ (i.e. $\mathcal{M}_{\Sigma_{\mathbf{C}}, E_{\mathbf{C}}} \cong \mathbf{C}$) and $\mathbf{1}$ is strictly terminal in \mathbb{G} , then $\mathbf{Para}(\mathbb{G}, \mathbf{C})$ is presented by $\mathsf{T} := (\Sigma, E_{\mathsf{h}})$ defined by

$$\Sigma := \Sigma_{\mathbf{C}} \sqcup \{ \text{ } : 0 \xrightarrow{1} 1 \} \text{ and } E_{\mathsf{h}} := E_{\mathbf{C}} \cup \{ \text{ } = \text{ } \mid \text{ } \in \Sigma_{\mathbf{v}} \},$$

where g_0 is a term in the equivalence class of $g \bullet \text{id}_0$.

Graded Para Construction

An action of \mathbb{G} on \mathbf{C} given by a symmetric monoidal functor $\bullet : \mathbb{G} \times \mathbf{C} \rightarrow \mathbf{C}$ yields a \mathbb{G} -graded category through the **Para** construction. Objects of $\mathbf{Para}(\mathbb{G}, \mathbf{C})$ are objects of \mathbf{C} , and morphisms $X \xrightarrow{\gamma} Y$ are morphisms $\gamma \bullet X \rightarrow Y$ in \mathbf{C} .

Theorem

If \mathbf{C} is presented by $(\Sigma_{\mathbf{C}}, E_{\mathbf{C}})$ (i.e. $\mathcal{M}_{\Sigma_{\mathbf{C}}, E_{\mathbf{C}}} \cong \mathbf{C}$) and $\mathbf{1}$ is strictly terminal in \mathbb{G} , then $\mathbf{Para}(\mathbb{G}, \mathbf{C})$ is presented by $\mathsf{T} := (\Sigma, E_{\mathsf{h}})$ defined by

$$\Sigma := \Sigma_{\mathbf{C}} \sqcup \{ \text{ } : 0 \xrightarrow{1} 1 \} \text{ and } E_{\mathsf{h}} := E_{\mathbf{C}} \cup \{ \text{ } = \text{ } \mid \text{ } \in \Sigma_{\mathbf{v}} \},$$

where g_0 is a term in the equivalence class of $g \bullet \text{id}_0$.

By construction, we have

$$\mathcal{S}_{\mathsf{T}0}(n, m) \cong \mathcal{S}_{\Sigma_{\mathbf{C}}, E_{\mathbf{C}}}(n, m) \cong \mathbf{C}(n, m) \cong \mathbf{Para}(\mathbb{G}, \mathbf{C})_0(n, m)$$

Modular Completeness

Lemma

1. For any morphism \boxed{t} in \mathbf{G} , and any monoidal $\Sigma_{\mathbf{C}}$ -term t_0 in the equivalence class of $t \bullet \text{id}_0 \in \mathbf{C}$, the closure $\overline{E_h}$ contains the equation

$$\boxed{t} = \boxed{t_0}.$$

2. Given a graded Σ -term $n \text{---} \boxed{f} \text{---}^m_a$, there is a term $n \text{---} \boxed{f_0} \text{---}^m_a$ such that

$$n \text{---} \boxed{f_0} \text{---}^m_a = n \text{---} \boxed{f} \text{---}^m_a.$$

Modular Completeness

Lemma

1. For any morphism \boxed{t} in \mathbf{G} , and any monoidal $\Sigma_{\mathbf{C}}$ -term t_0 in the equivalence class of $t \bullet \text{id}_0 \in \mathbf{C}$, the closure $\overline{E_h}$ contains the equation

$$\boxed{t} = \boxed{t_0}.$$

2. Given a graded Σ -term $n \text{---} \boxed{f} \text{---}^m_a$, there is a term $n \text{---} \boxed{f_0} \text{---}^m_a$ such that

$$n \text{---} \boxed{f_0} \text{---}^m_a = n \text{---} \boxed{f} \text{---}^m_a.$$

Proof sketch for theorem.

Define the semantics of 0-graded generators as in \mathbf{C} . Define $\llbracket \boxed{} \rrbracket := \text{id}_1 \bullet \text{id}_0$.

Soundness is easy to check. Completeness follows by decomposition above and isomorphism $\mathcal{M}_{\Sigma_{\mathbf{C}}, E_{\mathbf{C}}} \cong \mathbf{C}$. □

Graded String Diagrams

Imprecise Probability

Conclusion

The objects of **FinStoch** are natural numbers and its morphisms are

$$\{m \times n \text{ stochastic matrices}\} \Leftrightarrow \{\underline{n} \rightarrow \mathcal{D}\underline{m}\}.$$

The monoidal product is the Kronecker product:

$$A \otimes A' := \begin{bmatrix} a_{11}A' & \dots & a_{1n}A' \\ \vdots & \ddots & \vdots \\ a_{n'1}A' & \dots & a_{n'n}A' \end{bmatrix}.$$

It is the independent coupling on distributions in **FinStoch**(1, m).

The objects of **FinStoch** are natural numbers and its morphisms are

$$\{m \times n \text{ stochastic matrices}\} \Leftrightarrow \{\underline{n} \rightarrow \mathcal{D}\underline{m}\}.$$

The monoidal product is the Kronecker product:

$$A \otimes A' := \begin{bmatrix} a_{11}A' & \dots & a_{1n}A' \\ \vdots & \ddots & \vdots \\ a_{n'1}A' & \dots & a_{n'n}A' \end{bmatrix}.$$

It is the independent coupling on distributions in **FinStoch**(1, m).

BinStoch is the full subcategory spanned by 2^n . It is a *prop* via $\mathbf{BinStoch}(n, m) = \mathbf{FinStoch}(2^n, 2^m)$.

A morphism $f : n \rightarrow m$ in **BinStoch** is determined by its action on the basis generated by $|1\rangle = \begin{bmatrix} 1 \\ 0 \end{bmatrix}$ and $|0\rangle = \begin{bmatrix} 0 \\ 1 \end{bmatrix}$: $\{|\vec{x}\rangle \mid \vec{x} \in \{1, 0\}^n\}$.

Presentation of **BinStoch**

Piedeleu et al. [24] add probabilistic choices to Lafont's presentation,

$$\Sigma := \{ \text{---}\sqcup\text{---}, \text{---}\triangleright\text{---}, \text{---}\bullet, \text{---}\bullet\text{---}, \text{---}\text{---}^p \text{---} \}, \quad p \in [0, 1]$$

and they interpret **probabilistic circuits** in **BinStoch**:

$$\begin{aligned} \llbracket \text{---}\sqcup\text{---} \rrbracket |x\rangle|y\rangle &= |x \text{ and } y\rangle & \llbracket \text{---}\triangleright\text{---} \rrbracket |x\rangle &= |\text{not } x\rangle & \llbracket \text{---}\bullet \rrbracket |x\rangle &= | \rangle \\ \llbracket \text{---}\bullet\text{---} \rrbracket |x\rangle &= |x\rangle|x\rangle & \llbracket \text{---}\text{---}^p \text{---} \rrbracket | \rangle &= p|1\rangle + (1-p)|0\rangle = \begin{bmatrix} p \\ 1-p \end{bmatrix}. \end{aligned}$$

Presentation of **BinStoch**


Piedeleu et al. [24] add probabilistic choices to Lafont's presentation,

$$\Sigma := \{ \text{---}\sqcup\text{---}, \text{---}\triangleright\text{---}, \text{---}\bullet\text{---}, \text{---}\frown\text{---}, \text{---}\text{p}\text{---} \}, \quad p \in [0, 1]$$

and they interpret **probabilistic circuits** in **BinStoch**:

$$\begin{aligned} \llbracket \text{---}\sqcup\text{---} \rrbracket |x\rangle|y\rangle &= |x \text{ and } y\rangle & \llbracket \text{---}\triangleright\text{---} \rrbracket |x\rangle &= |\text{not } x\rangle & \llbracket \text{---}\bullet\text{---} \rrbracket |x\rangle &= | \rangle \\ \llbracket \text{---}\frown\text{---} \rrbracket |x\rangle &= |x\rangle|x\rangle & \llbracket \text{---}\text{p}\text{---} \rrbracket | \rangle &= p|1\rangle + (1-p)|0\rangle = \begin{bmatrix} p \\ 1-p \end{bmatrix}. \end{aligned}$$

[24, Corollary 3.18] shows that **BinStoch** is presented by these generators and a cleverly chosen set of equations containing, e.g.,



$$\text{where } \tilde{p} = pq \quad \text{and} \quad \tilde{q} = \frac{p(1-q)}{1-pq} \text{ for } pq \neq 1$$

Presentation of BImP

We add nondeterministic choices to Pideleu et al.’s presentation.

$$\Sigma := \left\{ \text{AND}, \neg, \bullet, \circlearrowright, p, \circlearrowleft, \sqcup \right\}, \quad p \in [0, 1]$$

The generator $\square : 0 \xrightarrow{1} 1$ is interpreted as providing nondeterministic bits:

$$\llbracket \textcolor{brown}{\ulcorner} \rrbracket |\rangle = |1\rangle \oplus |0\rangle \quad \llbracket \textcolor{brown}{\ulcorner} \rrbracket = \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix} \quad \llbracket \textcolor{brown}{\ulcorner} \rrbracket |x\rangle = |x\rangle$$

Presentation of **BImP**


We add nondeterministic choices to Piedeleu et al.'s presentation.

$$\Sigma := \left\{ \text{AND}, \text{NOT}, \text{POINT}, \text{CNOT}, \text{P}, \text{SWAP}, \text{GEN} \right\}, \quad p \in [0, 1]$$

The generator $\text{GEN} : 0 \xrightarrow{1} 1$ is interpreted as providing nondeterministic bits:

$$\llbracket \text{GEN} \rrbracket | \rangle = |1\rangle \oplus |0\rangle \quad \llbracket \text{GEN} \rrbracket = \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix} \quad \llbracket \text{GEN} \rrbracket |x\rangle = |x\rangle$$

The grade of a circuit in \mathcal{S}_Σ is the number of nondeterministic choices at its disposal. We can regrade it with a morphism in $\mathbf{FinInj}^{\text{op}}$ that discards or swaps nondeterministic bits:



Presentation of **BImP**

We add two equations

$$\begin{array}{c} \bullet \\ | \end{array} = \begin{array}{c} \text{---} \\ \text{---} \bullet \end{array} \qquad \begin{array}{c} \text{---} \\ \diagdown \\ \diagup \\ \text{---} \end{array} = \begin{array}{c} \text{---} \\ \diagdown \\ \diagup \\ \text{---} \end{array} \begin{array}{c} \diagdown \\ \diagup \end{array}$$

to obtain a graded presentation of **BImP**. A morphism $n \text{---} \boxed{f} \text{---}^m$ in **BImP** is a list of $2^m \times 2^n$ stochastic matrices of length 2^a .

Presentation of **BImP**

We add two equations

to obtain a graded presentation of **BImP**. A morphism $n \xrightarrow[f]{a} m$ in **BImP** is a list of $2^m \times 2^n$ stochastic matrices of length 2^a . Both composition and monoidal product are computed submatrix-wise.

$$\begin{bmatrix} 1 & 1 & | & 1 & 0 & | & 0 & 1 & | & 0 & 0 \\ 0 & 0 & | & 0 & 1 & | & 1 & 0 & | & 1 & 1 \end{bmatrix} \begin{bmatrix} 1 & | & 0.5 \\ 0 & | & 0.5 \end{bmatrix} = \begin{bmatrix} 1 & | & 1 & | & 0 & | & 0 & | & 1 & | & 0.5 & | & 0.5 & | & 0 \\ 0 & | & 0 & | & 1 & | & 1 & | & 0 & | & 0.5 & | & 0.5 & | & 1 \end{bmatrix}$$

$$\begin{bmatrix} 1 & 0 & | & 0 & 1 \\ 0 & 1 & | & 1 & 0 \end{bmatrix} \otimes \begin{bmatrix} .5 & | & 0 \\ .5 & | & 1 \end{bmatrix} = \begin{bmatrix} .5 & 0 & | & 0 & 0 & | & 0 & .5 & | & 0 & 0 \\ .5 & 0 & | & 1 & 0 & | & 0 & .5 & | & 0 & 1 \\ 0 & .5 & | & 0 & 0 & | & .5 & 0 & | & 0 & 0 \\ 0 & .5 & | & 0 & 1 & | & .5 & 0 & | & 1 & 0 \end{bmatrix}$$

Regrading swaps or copies matrices.

Presentation of **BImP**

Lemma

*The $\mathbf{FinInj}^{\text{op}}$ -graded category **BImP** is obtained by applying the **Para** construction to an action of $\mathbf{FinInj}^{\text{op}}$ on **BinStoch**.*

Theorem

*The graded category **BImP** is presented by the circuits of Piedeleu et al. [24] extended with the graded generator \sqcap and the two equations above.*

Presentation of **BImP**

Lemma

The **FinInj**^{op}-graded category **BImP** is obtained by applying the **Para** construction to an action of **FinInj**^{op} on **BinStoch**.

Theorem

The graded category **BImP** is presented by the circuits of Piedeleu et al. [24] extended with the graded generator \sqcap and the two equations above.

Piedeleu et al. [24] also add conditioning to present **FinSubStoch**:

$$\text{---} \curvearrowright \quad \llbracket \text{---} \curvearrowright \rrbracket |x\rangle|y\rangle = \begin{cases} |x\rangle & x = y \\ 0 & x \neq y \end{cases}$$

Theorem


The graded category **BImSubP** is presented by the theory above extended with $\text{---} \curvearrowright$ and the equations from [24].

Boy or Girl Paradox

Your neighbors have two kids and at least one of them is a girl. What is the probability that both kids are girls?


Boy or Girl Paradox

Your neighbors have two kids and at least one of them is a girl. What is the probability that both kids are girls?



Boy or Girl Paradox


Your neighbors have two kids and at least one of them is a girl. What is the probability that both kids are girls?




Your neighbors have two kids: a toddler and a teen. You meet one of them, and she is a girl. What is the probability that both kids are girls?

Boy or Girl Paradox

Your neighbors have two kids and at least one of them is a girl. What is the probability that both kids are girls?



Your neighbors have two kids: a toddler and a teen. You meet one of them, and she is a girl. What is the probability that both kids are girls?




Imprecise Probabilistic Programming

There is a natural way to interpret a programming language with the following expressions in **BImP** (**BImSubP**).

$$e, e_1, e_2 ::= x \mid \text{flip}(p) \mid \text{knight} \mid \langle e_1, e_2 \rangle \mid \text{fst } e \mid \text{snd } e \mid \\ \dots \text{ if } e \text{ then } e_1 \text{ else } e_2 \mid \text{let } x = e_1 \text{ in } e_2 \mid (\text{observe } x)$$

e.g.




Imprecise Probabilistic Programming


There is a natural way to interpret a programming language with the following expressions in **BImP** (**BImSubP**).

$$e, e_1, e_2 ::= x \mid \text{flip}(p) \mid \text{knight} \mid \langle e_1, e_2 \rangle \mid \text{fst } e \mid \text{snd } e \mid \\ \dots \text{ if } e \text{ then } e_1 \text{ else } e_2 \mid \text{let } x = e_1 \text{ in } e_2 \mid (\text{observe } x)$$

e.g.



This language is commutative and affine (without conditioning), but it does not satisfy hoisting.



Graded String Diagrams

Imprecise Probability

Conclusion

- ▶ Use our modular completeness 'hammer' to hit some nails, e.g. **Gauss**, optics, graded trace semantics, etc.
- ▶ Compare graded monoidal theories and graded algebraic theories.
- ▶ Graded tape/sheet diagrams to model the distributive fragment.
- ▶ Quantitative equations to model probabilistic refinement of nondeterminism.

Merci !

References I

- [1] Thibaut Antoine et al. “A Complete Diagrammatic Calculus for Automata Simulation”. In: *33rd EACSL Annual Conference on Computer Science Logic (CSL 2025)*. Ed. by Jörg Endrullis and Sylvain Schmitz. Vol. 326. Leibniz International Proceedings in Informatics (LIPIcs). Dagstuhl, Germany: Schloss Dagstuhl – Leibniz-Zentrum für Informatik, 2025, 27:1–27:22. ISBN: 978-3-95977-362-1. DOI: 10.4230/LIPIcs.CSL.2025.27. URL: <https://drops.dagstuhl.de/entities/document/10.4230/LIPIcs.CSL.2025.27>.
- [2] Miriam Backens et al. “Completeness of the ZH-calculus”. In: *Compositionality Volume 5 (2023)*, 5 (2023). ISSN: 2631-4444. DOI: 10.32408/compositionality-5-5. URL: <https://compositionality.episciences.org/13524>.
- [3] John C. Baez, Brandon Coya, and Franciscus Rebro. “Props in network theory”. In: *Theory Appl. Categ.* 33 (2018), Paper No. 25, 727–783. ISSN: 1201-561X.
- [4] Guillaume Boisseau and Robin Piedeleu. “Graphical piecewise-linear algebra”. In: *Foundations of software science and computation structures*. Vol. 13242. Lecture Notes in Comput. Sci. Springer, Cham, 2022, pp. 101–119. ISBN: 978-3-030-99252-1; 978-3-030-99253-8. DOI: 10.1007/978-3-030-99253-8_6. URL: https://doi.org/10.1007/978-3-030-99253-8_6.
- [5] Filippo Bonchi et al. “Diagrammatic algebra: from linear to concurrent systems”. In: *Proc. ACM Program. Lang.* 3.POPL (Jan. 2019). DOI: 10.1145/3290338. URL: <https://doi.org/10.1145/3290338>.
- [6] Silvio Capobianco and Tarmo Uustalu. “Additive Cellular Automata Graded-Monadically”. In: *Proceedings of the 25th International Symposium on Principles and Practice of Declarative Programming*. PPDP ’23. Lisboa, Portugal: Association for Computing Machinery, 2023. ISBN: 9798400708121. DOI: 10.1145/3610612.3610625. URL: <https://doi.org/10.1145/3610612.3610625>.

References II

- [7] Ulrich Dorsch, Stefan Milius, and Lutz Schröder. “Graded monads and graded logics for the linear time–branching time spectrum”. In: *30th International Conference on Concurrency Theory*. Vol. 140. LIPIcs. Leibniz Int. Proc. Inform. Schloss Dagstuhl. Leibniz-Zent. Inform., Wadern, 2019, Art. No. 36, 16. ISBN: 978-3-95977-121-4.
- [8] Chase Ford, Stefan Milius, and Lutz Schröder. “Behavioural preorders via graded monads”. English. In: *Proceedings of the 2021 36th annual ACM/IEEE symposium on logic in computer science, LICS 2021, Rome, Italy, June 29 – July 2, 2021*. Id/No 12. Piscataway, NJ: IEEE Press, 2021, p. 13. ISBN: 978-1-6654-4895-6. DOI: 10.1109/LICS52264.2021.9470517.
- [9] Chase Ford et al. “Graded monads and behavioural equivalence games”. In: *Proceedings of the 37th Annual ACM/IEEE Symposium on Logic in Computer Science*. ACM, New York, 2022, [Article 61], 13. ISBN: 978-1-4503-9351-5. DOI: 10.1145/3531130.3533374. URL: <https://doi.org/10.1145/3531130.3533374>.
- [10] Jonas Forster et al. “Graded semantics and graded logics for Eilenberg-Moore coalgebras”. In: *Coalgebraic methods in computer science*. Vol. 14617. Lecture Notes in Comput. Sci. Springer, Cham, 2024, pp. 114–134. ISBN: 978-3-031-66437-3; 978-3-031-66438-0. DOI: 10.1007/978-3-031-66438-0_6. URL: https://doi.org/10.1007/978-3-031-66438-0_6.
- [11] Marco Gaboardi et al. “Combining effects and coefficients via grading”. In: *ICFP’16—Proceedings of the 21st ACM SIGPLAN International Conference on Functional Programming*. ACM, New York, 2016, pp. 476–489. ISBN: 978-1-4503-4219-3.

References III

- [12] Marco Gaboardi et al. “Graded Hoare Logic and its Categorical Semantics”. In: *Programming Languages and Systems: 30th European Symposium on Programming, ESOP 2021, Held as Part of the European Joint Conferences on Theory and Practice of Software, ETAPS 2021, Luxembourg City, Luxembourg, March 27 – April 1, 2021, Proceedings*. Luxembourg City, Luxembourg: Springer-Verlag, 2021, 234–263. ISBN: 978-3-030-72018-6. DOI: 10.1007/978-3-030-72019-3_9. URL: https://doi.org/10.1007/978-3-030-72019-3_9.
- [13] Amar Hadzihanovic. “A diagrammatic axiomatisation for qubit entanglement”. In: *2015 30th Annual ACM/IEEE Symposium on Logic in Computer Science (LICS 2015)*. IEEE Computer Soc., Los Alamitos, CA, 2015, pp. 573–584. ISBN: 978-1-4799-8875-4. DOI: 10.1109/LICS.2015.59. URL: <https://doi.org/10.1109/LICS.2015.59>.
- [14] Emmanuel Jeandel, Simon Perdrix, and Renaud Vilmart. “A complete axiomatisation of the ZX-calculus for Clifford+T quantum mechanics”. In: *LICS ’18—33rd Annual ACM/IEEE Symposium on Logic in Computer Science*. ACM, New York, 2018, [10 pp.] ISBN: 978-1-4503-5583-4. DOI: 10.1145/3209108.3209131. URL: <https://doi.org/10.1145/3209108.3209131>.
- [15] Emmanuel Jeandel, Simon Perdrix, and Renaud Vilmart. “Completeness of the ZX-calculus”. In: *Log. Methods Comput. Sci.* 16.2 (2020), Paper No. 11, 72. ISSN: 1860-5974. DOI: 10.23638/LMCS-16(2:11)2020. URL: [https://doi.org/10.23638/LMCS-16\(2:11\)2020](https://doi.org/10.23638/LMCS-16(2:11)2020).
- [16] Shin-ya Katsumata. “Parametric effect monads and semantics of effect systems”. In: *SIGPLAN Not.* 49.1 (Jan. 2014), 633–645. ISSN: 0362-1340. DOI: 10.1145/2578855.2535846. URL: <https://doi.org/10.1145/2578855.2535846>.

References IV

- [17] Yves Lafont. “Towards an algebraic theory of Boolean circuits”. In: *Journal of Pure and Applied Algebra* 184.2 (2003), pp. 257–310. ISSN: 0022-4049. DOI: [https://doi.org/10.1016/S0022-4049\(03\)00069-0](https://doi.org/10.1016/S0022-4049(03)00069-0). URL: <https://www.sciencedirect.com/science/article/pii/S0022404903000690>.
- [18] Jack Liell-Cock and Sam Staton. “Compositional Imprecise Probability: A Solution from Graded Monads and Markov Categories”. In: *Proc. ACM Program. Lang.* 9.POPL (Jan. 2025). DOI: 10.1145/3704890. URL: <https://doi.org/10.1145/3704890>.
- [19] Rory B. B. Lucyshyn-Wright. *V-graded categories and V-W-bigraded categories: Functor categories and bifunctors over non-symmetric bases*. 2025. arXiv: 2502.18557 [math.CT]. URL: <https://arxiv.org/abs/2502.18557>.
- [20] Paul-André Mellies. *Parametric Monads and Enriched Adjunctions*. Preprint. 2012. URL: <https://www.irif.fr/~mellies/tensorial-logic/8-parametric-monads-and-enriched-adjunctions.pdf>.
- [21] Stefan Milius, Dirk Pattinson, and Lutz Schröder. “Generic trace semantics and graded monads”. In: *6th Conference on Algebra and Coalgebra in Computer Science*. Vol. 35. LIPIcs. Leibniz Int. Proc. Inform. Schloss Dagstuhl. Leibniz-Zent. Inform., Wadern, 2015, pp. 253–269. ISBN: 978-3-939897-84-2.
- [22] Alan Mycroft, Dominic Orchard, and Tomas Petricek. “Effect systems revisited – control-flow algebra and semantics”. English. In: *Semantics, logics, and calculi. Essays dedicated to Hanne Riis Nielson and Flemming Nielson on the occasion of their 60th birthdays*. Cham: Springer, 2016, pp. 1–32. ISBN: 978-3-319-27809-4; 978-3-319-27810-0. DOI: 10.1007/978-3-319-27810-0_1. URL: kar.kent.ac.uk/61623/1/effects-revisited.pdf.

References V

- [23] Robin Piedeleu and Fabio Zanasi. “A Finite Axiomatisation of Finite-State Automata Using String Diagrams”. In: *Logical Methods in Computer Science* Volume 19, Issue 1 (Feb. 2023). DOI: 10.46298/lmcs-19(1:13)2023. URL: <https://lmcs.episciences.org/10963>.
- [24] Robin Piedeleu et al. *A Complete Axiomatisation of Equivalence for Discrete Probabilistic Programming*. 2024. arXiv: 2408.14701 [cs.LO]. URL: <https://arxiv.org/abs/2408.14701>.
- [25] Boldizsár Poór et al. “Completeness for arbitrary finite dimensions of ZXW-calculus, a unifying calculus”. In: *2023 38th Annual ACM/IEEE Symposium on Logic in Computer Science (LICS)*. IEEE Comput. Soc. Press, Los Alamitos, CA, 2023, p. 14. ISBN: 979-8-3503-3587-3.
- [26] Takahiro Sanada. “Category-Graded Algebraic Theories and Effect Handlers”. In: *Electronic Notes in Theoretical Informatics and Computer Science* Volume 1 - Proceedings of MFPS XXXVIII, 15 (2023). ISSN: 2969-2431. DOI: 10.46298/entics.10491. URL: <https://entics.episciences.org/10491>.
- [27] Dario Stein et al. *Graphical Quadratic Algebra*. 2024. arXiv: 2403.02284 [cs.LO]. URL: <https://arxiv.org/abs/2403.02284>.
- [28] Fabio Zanasi. “Interacting Hopf Algebras: the theory of linear systems”. Available at <https://theses.hal.science/tel-01218015>. Theses. ENS de Lyon, Oct. 2015. URL: <https://theses.hal.science/tel-01218015>.