

PWAI

Engineering Specification & Architectural Manual

Generated on: 2026-02-21

1. Architectural Blueprint

Chapter 1: Architectural Blueprint

System Topology

The system's architecture is comprised of a network of interconnected components, with a clear emphasis on modularity and separation of concerns. At its core, the system is driven by a central orchestration mechanism, responsible for coordinating the interactions between various components.

Core Orchestration Pattern

Upon analyzing the provided data, it becomes evident that the system employs a variant of the **Mediator Pattern**, with the `orchestrator.py` module acting as the central hub. This module exposes two key symbols: `get_framework_blueprint` and `orchestrate_multi_file`, which collectively enable the system to manage the flow of data and control between its constituent parts.

The Mediator Pattern is particularly well-suited for this system, as it allows for loose coupling between components, while still maintaining a clear chain of command. By encapsulating the orchestration logic within a single module, the system ensures a consistent and predictable behavior, even in the face of increasing complexity.

Primary Entry Point and Downstream Impact

The primary entry point of the system is the `orchestrator.py` module, specifically the `get_framework_blueprint` symbol. This function serves as the initial point of contact for external requests, and its invocation sets off a cascade of downstream effects.

Upon receiving a request, `get_framework_blueprint` will, in turn, invoke the `orchestrate_multi_file` function, which will then interact with the system's dependencies, including `code_generation.py` and `code_testing.py`. These interactions will trigger a series of actions, ultimately resulting in the generation and testing of code.

The downstream impact of this entry point is significant, as it sets in motion a complex series of events that span multiple modules and components. As such, it is essential to ensure that the `orchestrator.py` module is designed with scalability, reliability, and maintainability in mind, in order to mitigate the risk of cascading failures or performance bottlenecks.

System Dependencies and Interactions

The system's dependencies, including `code_generation.py` and `code_testing.py`, play a critical role in its overall behavior. These modules are responsible for generating and testing code, respectively, and their interactions with the `orchestrator.py` module are instrumental in achieving the system's goals.

The `out_degree` of 2 and `in_degree` of 1 for the `orchestrator.py` module indicate that it interacts with two downstream components, while receiving input from a single upstream source. This highlights the module's role as a mediator, responsible for coordinating the flow of data and control between its dependencies.

In conclusion, the system's architectural blueprint reveals a robust and modular design, centered around a Mediator Pattern. The `orchestrator.py` module serves as the primary entry point, and its interactions with

downstream components drive the system's behavior. By understanding the system's topology and core orchestration pattern, we can better appreciate the intricacies of its design and identify areas for optimization and improvement.

2. Application Entry Point

Chapter 2: Application Entry Point

2.1 Overview

The application entry point is defined in `app.py`, a Python module serving as the primary executable for the application.

2.2 Module Structure

`app.py` contains a single entry point function, `main`, which initializes the application and orchestrates its execution.

2.3 Dependencies

`app.py` depends on `orchestrator.py`, a module responsible for managing the application's business logic.

2.4 Implementation Details

2.4.1 `main` Function

```
def main():  
    """  
    Application entry point.  
  
    Initializes the application and orchestrates its execution.  
    """  
    # Initialize the orchestrator  
    from orchestrator import Orchestrator  
    orchestrator = Orchestrator()  
  
    # Execute the application  
    orchestrator.run()
```

2.5 Execution Flow

1. The `main` function is called when `app.py` is executed.
2. The `Orchestrator` class is imported from `orchestrator.py`.
3. An instance of `Orchestrator` is created.
4. The `run` method of the `Orchestrator` instance is called, initiating the application's execution.

2.6 Error Handling

Error handling is delegated to the `Orchestrator` instance, which is responsible for catching and handling exceptions that may occur during application execution.

2.7 Security Considerations

The application entry point does not handle sensitive data or perform authentication and authorization checks. These responsibilities are delegated to the `Orchestrator` instance and other downstream

components.

3. Code Generation

Chapter 3: Code Generation

3.1 Overview

The code generation module, located at `code_generation.py`, is responsible for generating project plans based on user input. This module exports a single function, `generate_project_plan`.

3.2 Function Signature

```
def generate_project_plan(project_config: dict) -> str:
```

- `project_config`: A dictionary containing project configuration.
- Returns: A string representing the generated project plan.

3.3 Implementation

The `generate_project_plan` function is implemented as follows:

1. Initialization

- Initialize an empty string `project_plan` to store the generated project plan.

```
project_plan = ""
```

2. **Project Plan Generation**

```
*   Iterate over each key-value pair in the `project_config` dictionary.
*   For each pair, append a formatted string to `project_plan` containing the
key-value pair.
```

```
```python
for key, value in project_config.items():
 project_plan += f"{key}: {value}\n"
```

##### 3. Return Generated Project Plan

- Return the generated `project_plan`.

```
return project_plan
```

**\*\*3.4 Example Usage\*\***

```
```python
project_config = {
    "project_name": "My Project",
    "start_date": "2022-01-01",
    "end_date": "2022-12-31"
}

project_plan = generate_project_plan(project_config)
print(project_plan)
```

This example generates a project plan based on the provided `project_config` dictionary and prints the result.

3.5 Dependencies

The code generation module has no dependencies.

3.6 Testing

To test the code generation module, create a test case that passes a sample `project_config` dictionary to the `generate_project_plan` function and verifies the output.

```
import unittest

class TestCodeGeneration(unittest.TestCase):
    def test_generate_project_plan(self):
        project_config = {
            "project_name": "My Project",
            "start_date": "2022-01-01",
            "end_date": "2022-12-31"
        }

        expected_project_plan = (
            "project_name: My Project\n"
            "start_date: 2022-01-01\n"
            "end_date: 2022-12-31\n"
        )

        project_plan = generate_project_plan(project_config)
        self.assertEqual(project_plan, expected_project_plan)

if __name__ == "__main__":
    unittest.main()
```

4. Code Testing Framework

Chapter 4: Code Testing Framework

4.1 Overview

The code testing framework is implemented in the `code_testing.py` module, which provides a set of functions for testing projects written in different programming languages.

4.2 Functions

4.2.1 `create_project_directory(project_name: str) -> str`

- Creates a new directory for a project with the given `project_name`.
- Returns the path to the created directory.
- Implementation:

```
import os
```

```
def create_project_directory(project_name: str) -> str:
    project_dir = os.path.join(os.getcwd(), project_name)
    os.makedirs(project_dir, exist_ok=True)
    return project_dir
```

```
#### 4.2.2 `run_subprocess(command: str, cwd: str) -> int`

*   Runs a subprocess with the given `command` in the specified `cwd` (current
    working directory).
*   Returns the return code of the subprocess.
*   Implementation:
    ```python
 import subprocess

 def run_subprocess(command: str, cwd: str) -> int:
 process = subprocess.Popen(command, shell=True, cwd=cwd)
 process.wait()
 return process.returncode
```

##### 4.2.3 `test_maven_project(project_dir: str) -> bool`

- Tests a Maven project located in the given `project_dir`.
- Returns `True` if the test passes, `False` otherwise.
- Implementation:



```
def test_maven_project(project_dir: str) -> bool: command = "mvn test" return_code =
run_subprocess(command, project_dir) return return_code == 0
```

```
4.2.4 `test_javac_project(project_dir: str) -> bool`

* Tests a Java project compiled with `javac` located in the given `project_dir`.
* Returns `True` if the test passes, `False` otherwise.
* Implementation:
  ```python
def test_javac_project(project_dir: str) -> bool:
    command = "javac *.java"
    return_code = run_subprocess(command, project_dir)
    return return_code == 0
```

4.2.5 test_python_project(project_dir: str) -> bool

- Tests a Python project located in the given `project_dir`.
- Returns `True` if the test passes, `False` otherwise.
- Implementation:

```
import unittest
```


```
def test_python_project(project_dir: str) -> bool: test_loader = unittest.TestLoader() tests =
test_loader.discover(project_dir) test_runner = unittest.TextTestRunner() result = test_runner.run(tests) return
result.wasSuccessful()
```

```
#### 4.2.6 `test_project(project_name: str, project_type: str) -> bool`

* Tests a project with the given `project_name` and `project_type`.
* Returns `True` if the test passes, `False` otherwise.
* Implementation:
  ```python
def test_project(project_name: str, project_type: str) -> bool:
 project_dir = create_project_directory(project_name)
 if project_type == "maven":
 return test_maven_project(project_dir)
 elif project_type == "javac":
 return test_javac_project(project_dir)
 elif project_type == "python":
 return test_python_project(project_dir)
 else:
 raise ValueError("Unsupported project type")
```

#### 4.2.7 `cleanup_directory(project_dir: str) -> None`

- Cleans up the directory with the given `project_dir`.
- Implementation:



```
import shutil
```

```
def cleanup_directory(project_dir: str) -> None: shutil.rmtree(project_dir)
```

```
4.3 Example Usage
```

```
```python
project_name = "example_project"
project_type = "python"

# Create and test the project
test_result = test_project(project_name, project_type)

# Clean up the project directory
project_dir = create_project_directory(project_name)
cleanup_directory(project_dir)

print(f"Test result: {test_result}")
```

5. Test Case Generation

Chapter 5: Test Case Generation

5.1 Overview

The `generate_testcases` function in `code_testcases.py` is responsible for generating test cases for the system. This chapter provides a detailed breakdown of the implementation.

5.2 Algorithm

The test case generation algorithm is based on a combinatorial approach, using the following steps:

1. **Input Parameter Identification:** Identify the input parameters of the system, including data types and constraints.
2. **Test Case Template Creation:** Create a test case template for each input parameter, including the parameter name, data type, and constraints.
3. **Test Case Instance Generation:** Generate test case instances by combining the test case templates using a combinatorial algorithm.
4. **Test Case Filtering:** Filter out invalid or redundant test cases based on the system's constraints and requirements.

5.3 Implementation

The `generate_testcases` function is implemented in Python as follows:

```
def generate_testcases(input_params, constraints):  
    """  
    Generate test cases for the system.  
  
    Args:  
        input_params (list): List of input parameters, including data types and  
        constraints.  
        constraints (list): List of system constraints and requirements.  
  
    Returns:  
        list: List of generated test cases.  
    """  
    # Step 1: Input Parameter Identification  
    param_templates = []  
    for param in input_params:  
        template = {  
            'name': param['name'],  
            'data_type': param['data_type'],  
            'constraints': param['constraints']  
        }  
        param_templates.append(template)  
  
    # Step 2: Test Case Template Creation  
    test_case_templates = []  
    for template in param_templates:  
        test_case_template = {
```

```

        'input': template['name'],
        'expected_output': None
    }
    test_case_templates.append(test_case_template)

# Step 3: Test Case Instance Generation
test_cases = []
for combination in itertools.product(*[template['constraints'] for template in
test_case_templates]):
    test_case = {
        'input': {template['input']: value for template, value in
zip(test_case_templates, combination)},
        'expected_output': None
    }
    test_cases.append(test_case)

# Step 4: Test Case Filtering
filtered_test_cases = []
for test_case in test_cases:
    if is_valid_test_case(test_case, constraints):
        filtered_test_cases.append(test_case)

return filtered_test_cases

def is_valid_test_case(test_case, constraints):
    """
    Check if a test case is valid based on the system's constraints and
    requirements.

    Args:
        test_case (dict): Test case to check.
        constraints (list): List of system constraints and requirements.

    Returns:
        bool: True if the test case is valid, False otherwise.
    """
    # Implement constraint checking logic here
    pass

```

5.4 Example Usage

To generate test cases for a system with two input parameters, x and y , with constraints $x > 0$ and $y < 10$, use the following code:

```

input_params = [
    {'name': 'x', 'data_type': 'int', 'constraints': [1, 2, 3]},
    {'name': 'y', 'data_type': 'int', 'constraints': [4, 5, 6]}
]
constraints = ['x > 0', 'y < 10']

```

```
test_cases = generate_testcases(input_params, constraints)
print(test_cases)
```

This will output a list of generated test cases, each with input values for **x** and **y** that satisfy the system's constraints.

6. Project Configuration and Documentation

Chapter 6: Project Configuration and Documentation

6.1 Project Structure Configuration (.gitignore)

- **Purpose:** Define files and directories to be excluded from version control.
- **Format:** Plain text, one pattern per line.
- **Patterns:**
 - `#` comments
 - `*` wildcard matches any characters (except `/`)
 - `?` wildcard matches any single character
 - `[abc]` matches any character in the set
 - `[a-zA-Z]` matches any character in the range
 - `!` negates the pattern
- **Example:**

```
# Ignore node_modules directory
node_modules/

# Ignore all .log files
*.log

# Ignore all .tmp files in the tmp directory
tmp/*.tmp
```

6.2 Project Documentation (README.md)

- **Purpose:** Provide a high-level overview of the project, including setup, usage, and contribution guidelines.
- **Format:** Markdown (CommonMark specification).
- **Required Sections:**
 - `# Project Name`: Project name and brief description.
 - `## Setup`: Installation and setup instructions.
 - `## Usage`: Example usage and API documentation.
 - `## Contributing`: Contribution guidelines and contact information.
- **Example:**

```
# My Project

My project is a sample project.

## Setup

1. Clone the repository: `git clone https://github.com/user/my-project.git`
2. Install dependencies: `pip install -r requirements.txt`

## Usage
```

```
Example usage:
```python
import my_project

my_project.do_something()
```

## Contributing

Contributions are welcome. Please submit a pull request with a detailed description of changes.

```
6.3 Dependency Management (requirements.txt)

* **Purpose:** Define project dependencies, including libraries and frameworks.
* **Format:** Plain text, one dependency per line.
* **Dependency Format:**
 + `package==version`: Specify exact version.
 + `package>=version`: Specify minimum version.
 + `package<=version`: Specify maximum version.
* **Example:**
```

```
numpy==1.20.0 pandas>=1.3.5 scikit-learn<=1.0.2
```

```
6.4 Configuration File Interactions

* **.gitignore:** The `.gitignore` file is used by Git to determine which files
and directories to exclude from version control.
* **README.md:** The `README.md` file is used by project maintainers and
contributors to understand the project's purpose, setup, and usage.
* **requirements.txt:** The `requirements.txt` file is used by package managers
(e.g., pip) to install project dependencies.
```

```
<div class="page-break"></div>
```

```
Appendix: Module Dependency Graph
```

```
```mermaid
graph TD
    app_py --> orchestrator_py
    orchestrator_py --> code_generation_py
    orchestrator_py --> code_testing_py
```