

```

→ WDI_LDN_3_Work git:(master) X gco wld5-ralphreid
Switched to branch 'wld5-ralphreid'
→ WDI_LDN_3_Work git:(wld5-ralphreid) X cd ralphreid/wld5/homework
→ homework git:(wld5-ralphreid) X ll
total 0
drwxr-xr-x  9 ralphreid  staff  306  5 Oct 10:48 gase
→ homework git:(wld5-ralphreid) X cd g
cd:cd:13: no such file or directory: g
→ homework git:(wld5-ralphreid) X cd gase
→ gase git:(wld5-ralphreid) X ll
total 48
-rw-r--r--  1 ralphreid  staff  180  5 Oct 10:48 brokerage.rb
-rw-r--r--  1 ralphreid  staff  368  5 Oct 10:48 client.rb
-rw-r--r--  1 ralphreid  staff    0  5 Oct 10:48 data.rb
-rw-r--r--  1 ralphreid  staff  230  5 Oct 10:48 functions.rb
-rw-r--r--  1 ralphreid  staff  368  5 Oct 10:48 main.rb
-rw-r--r--  1 ralphreid  staff  171  5 Oct 10:48 portfolio.rb
-rw-r--r--  1 ralphreid  staff  231  5 Oct 10:48 stock.rb
→ gase git:(wld5-ralphreid) X cd..
→ homework git:(wld5-ralphreid) X git add .
warning: You ran 'git add' with neither '-A (--all)' or '--ignore-removal',
whose behaviour will change in Git 2.0 with respect to paths you removed.
Paths like 'ralphreid/wld5/homework/gase/brokerage.rb' that are
removed from your working tree are ignored with this version of Git.

* 'git add --ignore-removal <pathspec>', which is the current default,
  ignores paths you removed from your working tree.

* 'git add --all <pathspec>' will let you also record the removals.

Run 'git status' to check the paths you removed from your working tree.

→ homework git:(wld5-ralphreid) X git status
# On branch wld5-ralphreid
# Changes to be committed:
#   (use "git reset HEAD <file>..." to unstage)
#
#       new file:   gase_final/brokerage.rb
#       new file:   gase_final/client.rb
#       new file:   gase_final/data.rb
#       new file:   gase_final/functions.rb
#       new file:   gase_final/main.rb
#       new file:   gase_final/portfolio.rb
#       new file:   gase_final/stock.rb
#       new file:   gase_initial/brokerage.rb
#       new file:   gase_initial/client.rb
#       new file:   gase_initial/data.rb
#       new file:   gase_initial/functions.rb
#       new file:   gase_initial/main.rb
#       new file:   gase_initial/portfolio.rb
#       new file:   gase_initial/stock.rb
#
# Changes not staged for commit:
#   (use "git add/rm <file>..." to update what will be committed)
#   (use "git checkout -- <file>..." to discard changes in working directory)
#
#       deleted:    gase/brokerage.rb
#       deleted:    gase/client.rb
#       deleted:    gase/data.rb
#       deleted:    gase/functions.rb
#       deleted:    gase/main.rb
#       deleted:    gase/portfolio.rb
#       deleted:    gase/stock.rb
#
# Untracked files:
#   (use "git add <file>..." to include in what will be committed)
#
#       ../../wld4/homework/sol_fromJon/
→ homework git:(wld5-ralphreid) X cd ..
→ wld5 git:(wld5-ralphreid) X cd ..
→ ralphreid git:(wld5-ralphreid) X cd ..
→ WDI_LDN_3_Work git:(wld5-ralphreid) X git status
# On branch wld5-ralphreid
# Changes to be committed:
#   (use "git reset HEAD <file>..." to unstage)
#
#       new file:   ralphreid/wld5/homework/gase_final/brokerage.rb

```

```

# new file: ralphreid/w1d5/homework/gase_final/client.rb
# new file: ralphreid/w1d5/homework/gase_final/data.rb
# new file: ralphreid/w1d5/homework/gase_final/functions.rb
# new file: ralphreid/w1d5/homework/gase_final/main.rb
# new file: ralphreid/w1d5/homework/gase_final/portfolio.rb
# new file: ralphreid/w1d5/homework/gase_final/stock.rb
# new file: ralphreid/w1d5/homework/gase_initial/brokerage.rb
# new file: ralphreid/w1d5/homework/gase_initial/client.rb
# new file: ralphreid/w1d5/homework/gase_initial/data.rb
# new file: ralphreid/w1d5/homework/gase_initial/functions.rb
# new file: ralphreid/w1d5/homework/gase_initial/main.rb
# new file: ralphreid/w1d5/homework/gase_initial/portfolio.rb
# new file: ralphreid/w1d5/homework/gase_initial/stock.rb
#
# Changes not staged for commit:
# (use "git add/rm <file>..." to update what will be committed)
# (use "git checkout -- <file>..." to discard changes in working directory)
#
# deleted: ralphreid/w1d5/homework/gase/brokerage.rb
# deleted: ralphreid/w1d5/homework/gase/client.rb
# deleted: ralphreid/w1d5/homework/gase/data.rb
# deleted: ralphreid/w1d5/homework/gase/functions.rb
# deleted: ralphreid/w1d5/homework/gase/main.rb
# deleted: ralphreid/w1d5/homework/gase/portfolio.rb
# deleted: ralphreid/w1d5/homework/gase/stock.rb
#
# Untracked files:
# (use "git add <file>..." to include in what will be committed)
#
# ralphreid/w1d4/homework/sol_fromJon/
→ WDI_LDN_3_Work git:(w1d5-ralphreid) ✗ git add .
warning: You ran 'git add' with neither '-A (--all)' or '--ignore-removal',
whose behaviour will change in Git 2.0 with respect to paths you removed.
Paths like 'ralphreid/w1d5/homework/gase/brokerage.rb' that are
removed from your working tree are ignored with this version of Git.

* 'git add --ignore-removal <paths>', which is the current default,
  ignores paths you removed from your working tree.

* 'git add --all <paths>' will let you also record the removals.

Run 'git status' to check the paths you removed from your working tree.

→ WDI_LDN_3_Work git:(w1d5-ralphreid) ✗ git add -A
→ WDI_LDN_3_Work git:(w1d5-ralphreid) ✗ git status
# On branch w1d5-ralphreid
# Changes to be committed:
# (use "git reset HEAD <file>..." to unstage)
#
# new file: ralphreid/w1d4/homework/sol_fromJon/README.md
# new file: ralphreid/w1d4/homework/sol_fromJon/animal-prompt.rb
# new file: ralphreid/w1d4/homework/sol_fromJon/solution/animal.rb
# new file: ralphreid/w1d4/homework/sol_fromJon/solution/data.rb
# new file: ralphreid/w1d4/homework/sol_fromJon/solution/functions.rb
# new file: ralphreid/w1d4/homework/sol_fromJon/solution/main.rb
# new file: ralphreid/w1d4/homework/sol_fromJon/solution/person.rb
# new file: ralphreid/w1d4/homework/sol_fromJon/solution/shelter.rb
# new file: ralphreid/w1d4/homework/sol_fromJon/spec/animal_spec.rb
# new file: ralphreid/w1d4/homework/sol_fromJon/spec/person_spec.rb
# new file: ralphreid/w1d4/homework/sol_fromJon/spec/shelter_spec.rb
# new file: ralphreid/w1d4/homework/sol_fromJon/spec/spec_helper.rb
# renamed: ralphreid/w1d5/homework/gase/brokerage.rb -> ralphreid/w1d5/homework/gase_final/
/brokerage.rb
# renamed: ralphreid/w1d5/homework/gase/client.rb -> ralphreid/w1d5/homework/gase_final/cl
ient.rb
# renamed: ralphreid/w1d5/homework/gase/data.rb -> ralphreid/w1d5/homework/gase_final/data
.rb
# renamed: ralphreid/w1d5/homework/gase/functions.rb -> ralphreid/w1d5/homework/gase_final
/functions.rb
# renamed: ralphreid/w1d5/homework/gase/main.rb -> ralphreid/w1d5/homework/gase_final/main
.rb
# renamed: ralphreid/w1d5/homework/gase/portfolio.rb -> ralphreid/w1d5/homework/gase_final
/portfolio.rb
# renamed: ralphreid/w1d5/homework/gase/stock.rb -> ralphreid/w1d5/homework/gase_final/sto
ck.rb
# new file: ralphreid/w1d5/homework/gase_initial/brokerage.rb
# new file: ralphreid/w1d5/homework/gase_initial/client.rb

```

```

#      new file:   ralphreid/wld5/homework/gase_initial/data.rb
#      new file:   ralphreid/wld5/homework/gase_initial/functions.rb
#      new file:   ralphreid/wld5/homework/gase_initial/main.rb
#      new file:   ralphreid/wld5/homework/gase_initial/portfolio.rb
#      new file:   ralphreid/wld5/homework/gase_initial/stock.rb
#
→ WDI_LDN_3_Work git:(wld5-ralphreid) X cd ralphreid/wld5/classwork
→ classwork git:(wld5-ralphreid) X ll
total 0
drwxr-xr-x  5 ralphreid  staff  170  5 Oct 10:48 Jon Examples
drwxr-xr-x  3 ralphreid  staff  102  5 Oct 11:41 review_session
→ classwork git:(wld5-ralphreid) X cd review_session
→ review_session git:(wld5-ralphreid) X ll
total 8
-rw-r--r--  1 ralphreid  staff   86  5 Oct 11:41 review.rb
→ review_session git:(wld5-ralphreid) X ruby review.rb
current value inside 1
current value inside 2
current value inside 3
current value inside 4
current value inside 5
→ review_session git:(wld5-ralphreid) X ruby review2.rb
["current value inside 1", "current value inside 2", "current value inside 3", "current value inside 4", "current value inside 5"]
→ review_session git:(wld5-ralphreid) X ruby review2.rb
["current value inside block 1", "current value inside block 2", "current value inside block 3", "current value inside block 4", "current value inside block 5"]
→ review_session git:(wld5-ralphreid) X ruby review3.rb
["student1--- ralph", "student2--- jj"]
→ review_session git:(wld5-ralphreid) X ruby review_object.rb

```

From: /Users/ralphreid/Dropbox/development/WDI_LDN_3_Work/ralphreid/wld5/classwork/review_session/review_object.rb @ line 10 :

```

5:   attr_reader :students, :instructors
6:   attr_writer :random_attr
7: end
8:
9:
=> 10: binding.pry

[1] pry(main)> wdi_3_ldn = Wdi.new
=> #<Wdi:0x007ffdac19e770>
[2] pry(main)> wdi_3_ldn.computers
=> nil
[3] pry(main)> wdi_3_ldn.computers = {neha: "MBA13", jamie: "MBA13", alex: "MBA13"}
[3] pry(main)* wdi_3_ldn.computers[:jamie]
SyntaxError: unexpected tIDENTIFIER, expecting '}'
   wdi_3_ldn.computers[:jamie]
   ^
[3] pry(main)> wdi_3_ldn.computers[:neha]
NoMethodError: undefined method `[]' for nil:NilClass
from (pry):3:in `<main>'
[4] pry(main)> wdi_3_ldn.computers[:neha]
ArgumentError: wrong number of arguments (1 for 0)
from (pry):4:in `<main>'
[5] pry(main)> wdi_3_ldn.computers = {neha: "MBA13", jamie: "MBA13", alex: "MBA13"}
=> {:neha=>"MBA13", :jamie=>"MBA13", :alex=>"MBA13"}
[6] pry(main)> wdi_3_ldn.computers[:neha]
ArgumentError: wrong number of arguments (1 for 0)
from (pry):6:in `<main>'
[7] pry(main)> wdi_3_ldn.computers[:neha]
=> "MBA13"
[8] pry(main)> exit
→ review_session git:(wld5-ralphreid) X ruby review_object1.rb

```

From: /Users/ralphreid/Dropbox/development/WDI_LDN_3_Work/ralphreid/wld5/classwork/review_session/review_object1.rb @ line 17 :

```

12:
13: end
14:
15:
16:
=> 17: binding.pry

[1] pry(main)> Wdi.new

```

```
=> #<Wdi:0x007ff620b61430>
[2] pry(main)> exit
→ review_session git:(w1d5-ralphreid) X ruby review_object1.rb
```

From: /Users/ralphreid/Dropbox/development/WDI_LDN_3_Work/ralphreid/w1d5/classwork/review_session/review_object1.rb @ line 18 :

```
13:
14: end
15:
16:
17:
=> 18: binding.pry
```

```
[1] pry(main)> exit
→ review_session git:(w1d5-ralphreid) X ruby review_object1.rb
```

From: /Users/ralphreid/Dropbox/development/WDI_LDN_3_Work/ralphreid/w1d5/classwork/review_session/review_object1.rb @ line 17 :

```
12:
13: end
14:
15:
16:
=> 17: binding.pry
```

```
[1] pry(main)> wdi_3_ldn = Wdi.new
=> #<Wdi:0x007ff499115a68
  @instructors=["gerry", "julien"],
  @students=["jamie", "alex", "ralph", "sharif"]>
[2] pry(main)> wdi_3_ldn.students
=> ["jamie", "alex", "ralph", "sharif"]
[3] pry(main)> exit
→ review_session git:(w1d5-ralphreid) X ruby review_object2.rb
```

From: /Users/ralphreid/Dropbox/development/WDI_LDN_3_Work/ralphreid/w1d5/classwork/review_session/review_object2.rb @ line 17 :

```
12:
13: end
14:
15:
16:
=> 17: binding.pry
```

```
[1] pry(main)> wdi_3_ldn = Wdi.new
ArgumentError: wrong number of arguments (0 for 1)
from review_object2.rb:8:in `initialize'
[2] pry(main)> students=["jamie", "alex", "ralph", "sharif"]
=> ["jamie", "alex", "ralph", "sharif"]
[3] pry(main)> wdi_3_ldn = Wdi.new students
=> #<Wdi:0x007f976b8cb590
  @instructors=["gerry", "julien"],
  @students=["jamie", "alex", "ralph", "sharif"]>
[4] pry(main)>
```