

Script-Controlled ACL – Restrict Record Access Based on Field Value

8. Project Demonstration Phase

The project demonstration presents the completed Script-Controlled ACL implementation in ServiceNow. The demonstration begins by showing the Institution Details table and the configured user roles used to control record-level access.

The demonstration shows the **u_institution_details** table containing records with ECE, EEE, and CSE branch values. The configured roles **bb1**, **bb2**, **bb3**, and **bb4** are then used to demonstrate the different Read, Create, Write, and Delete permissions.

For the Read ACL demonstration, the EEE user is used to show access to records where the Branch is EEE. The ACL uses the Branch = EEE data condition together with the required role and script. A user without the required role is shown as being denied access, while an administrator is shown to have full access.

The demonstration then verifies the Create ACL using the **bb2** role, the Write ACL using the **bb3** role, and the Delete ACL using the **bb4** role. The appropriate user is shown performing each operation on the Institution Details records.

The final demonstration confirms that the configured ACLs work together to enforce role-based and field-based record security. The complete flow shows how authorized users can perform permitted operations while unauthorized users are prevented from accessing or modifying protected records.

The demonstration therefore presents the complete documented process from ACL configuration and role assignment through Read, Create, Write, and Delete verification, concluding with administrator full-access verification.