

AWK_HW

Student Name: Abdullah Ghassan Sholi , Student #: 12027918

a)

```
(kali㉿kali)-[~/Desktop]
$ awk '{print($1,$2)}' awk.txt
firstname lastname
Herman Sanchez
Phil Parker
Bradie Garnett
Rudolf Crooks
Marcos Miller
Chad Garnett
Sally Evans
Chad Parker
```

\$1 —> refer to column 1 in Given Data

\$2 —> refer to column 2 in Given Data

b)

```
(kali㉿kali)-[~/Desktop]
$ awk 'OFS="," {print($2,$1)}' awk.txt
lastname,firstname
Sanchez,Herman
Parker,Phil
Garnett,Bradie
Crooks,Rudolf
Miller,Marcos
Garnett,Chad
Evans,Sally
Parker,Chad
```

OFS refer to Output File Separator , we can put any character which we want as OFS

c)

```
(kali㉿kali)-[~/Desktop]
$ awk 'NR>1 {print($1,$2)}' awk.txt
Herman Sanchez
Phil Parker
Bradie Garnett
Rudolf Crooks
Marcos Miller
Chad Garnett
Sally Evans
Chad Parker
```

NR refer to Number of Rows

NR > 1 for hide header (to print data without header)

d)

```
(kali㉿kali)-[~/Desktop]
$ awk 'NR>1 {print(NR-1,$1,$2)}' awk.txt
1 Herman Sanchez
2 Phil Parker
3 Bradie Garnett
4 Rudolf Crooks
5 Marcos Miller
6 Chad Garnett
7 Sally Evans
8 Chad Parker
```

NR - 1 because there is a hide row for header

e)

```
(kali㉿kali)-[~/Desktop]
$ awk 'NR>1 {if($4>50){print($1,$2)}}' awk.txt
Herman Sanchez
Marcos Miller
Chad Parker
```

if age > 50

f)

```
(kali㉿kali)-[~/Desktop]
$ awk 'NR>1 {if($5>10000){print($1,$2)}}' awk.txt
Chad Parker
```

if deposit > 10000

g)

```
(kali㉿kali)-[~/Desktop]
$ awk 'BEGIN {sum=0}{sum+=$5}END {print(sum)}' awk.txt
53900
```

h)

```
(kali㉿kali)-[~/Desktop]
$ awk '$1 ~ /^Chad$/ {print($0)}' awk.txt
Chad Garnett Miami 38 7420
Chad Parker Seattle 55 12600
```

display data for users with first name Chad

i)

```
(kali㉿kali)-[~/Desktop]
$ awk '$2 ~ /r$/ {print($0)}' awk.txt
Phil Parker Miami 45 5010
Marcos Miller Seattle 66 4300
Chad Parker Seattle 55 12600
```

j)

```
(kali㉿kali)-[~/Desktop]
$ awk 'NR>1 66 $1=$1 {x=$4%10; y=int($4/10); if(x==y){print($1,$2,$3,$4,$5)} }' awk.txt
Rudolf Crooks Miami 33 5800
Marcos Miller Seattle 66 4300
Chad Parker Seattle 55 12600
```