

**Answer:** (penalty regime: 0 %)

Reset answer

```
1  /*
2   * Complete the 'powerSum' function below.
3   *
4   * The function is expected to return an INTEGER.
5   * The function accepts following parameters:
6   * 1. INTEGER x
7   * 2. INTEGER n
8   */
9  #include<math.h>
10 int powerSum(int x, int m, int n)
11 {
12     int p=pow(m,n);
13     if(p==x)
14     {
15         return 1;
16     }
17     if(p>x)
18     {
19         return 0;
20     }
21     return powerSum(x-p,m+1,n)+powerSum(x,m+1,n);
22 }
```

|   | Test                             | Expected | Got |   |
|---|----------------------------------|----------|-----|---|
| ✓ | printf("%d", powerSum(10, 1, 2)) | 1        | 1   | ✓ |

Passed all tests! ✓

**Answer:** (penalty regime: 0 %)

Reset answer

```
1  /*
2   * Complete the 'myFunc' function below.
3   *
4   * The function is expected to return an INTEGER.
5   * The function accepts INTEGER n as parameter.
6   */
7
8  int myFunc(int n)
9  {
10     return n==1 || n%10==0;
11 }
12
```

|   | Test                      | Expected | Got |   |
|---|---------------------------|----------|-----|---|
| ✓ | printf("%d", myFunc(1))   | 1        | 1   | ✓ |
| ✓ | printf("%d", myFunc(2))   | 0        | 0   | ✓ |
| ✓ | printf("%d", myFunc(10))  | 1        | 1   | ✓ |
| ✓ | printf("%d", myFunc(25))  | 0        | 0   | ✓ |
| ✓ | printf("%d", myFunc(200)) | 1        | 1   | ✓ |