

NETZWERK ACADEMY

# HTML, CSS,JAVASCRIPT

CREATED BY: ROHIT

# HTML, CSS and JavaScript Notes

Created By: Rohit Kolhapure

Netzwerk Academy

# HTML

## 1.1 Introduction

In this section, various component of HTML is discussed to design a web page. The basic structure for an HTML page is shown below.

- Entries inside the `</... />` are known as tags. Most of the tags has an opening and closing e.g. `<head>` (opening head) and `</head>` (closing head). Some of the tags do not have closing tags e.g. `<!DOCTYPE ... >` and `<br />`. We need to write the HTML codes inside the tags.
- The comments are written between `'<!--'` and `'-->'`.
- Here Line 1 gives the details of the 'HTML version' to the web-browser. The 'html' tells it is version 5.
- The 'head' tag (Lines 3-5) contains the header related tags e.g. 'title for the page' and 'links for the css files' etc.
- The 'body' tag (7-11) contains the actual HTML code which is displayed on the web-browser. Also, we add all the JavaScript related codes just before the closing body tag (`</body>`).

```

1 <!DOCTYPE html>      <!-- tells browser about the html version -->
2 <html> <!-- beginning of the html document -->
3   <head>
4       <!-- header related tags e.g. title, links etc. -->
5   </head>
6
7   <body>
8       <!-- actual html document here -->
9
10      <!-- add JavaScript files here -->
11
12  </body>
</html>

```

## 1.2 First code

In below code, the message "Hello World" is displayed on the HTML page. The [Fig. 1.1](#) is the resultant HTML page.

- The title (Line 4) appears on the top of the browser.
- The tag `<h1>` is called 'header' tag, which has the larger size than the normal text (see the size of 'HelloWorld!').
- The tag `<p>` is called the 'paragraph' tag, which can be used to write the paragraphs.

```

<!DOCTYPE html>
<html>
<head>
    <title>HTML Tutorial</title>
</head>
<body>
    <h1> Hello World! </h1>
    <p> This is the first HTML code </p>

```



Fig. First code

### 1.3 Basic tags

- The [Table 1.1](#) shows the list of tags which are required for writing the basic 'HTML' codes i.e. without any style e.g. bold, italics and numbering etc.

Table 1.1: List of basic tags

Tag	Description	Example
h1, . . . , h6	Header tag h1 to h6	<h2> Hi </h2>
p	paragraphs (Line changes at the end)	<p> Hi </p>
span	No line change after span	<span>Hi</span> Bye.
div	make division between contents	<div> . . . </div>
a	hyperlink	see <a href="#">Section 1.9</a>
center	Move content to center	<center> Hi </center>
br	Line break (no closing tag)	  or  
hr	horizontal line (no closing tag)	<hr /> or <hr>
pre	preserve formatting	<pre> .....</pre>
table	insert table	see <a href="#">Section 1.5</a>

- Let's see the example of each of these tags,

---

**Note:** All the new codes are added below the previous codes in the 'body' tag. Therefore only newly added codes are shown in the tutorial.

---

```

<h2> Heading 2 </h2>
  <h6> Heading 6 </h6>
  <p> This is paragraph </p>

  <span> This is span.</span>
  <span> The 'br' tag is used after span to break the line </span>
  <br/>

  <div style="color:blue;">
    The 'div' tag can be used for formatting the tags inside it at once using 'style' and 'classes'
  etc.

    <p> This paragraph is inside the 'div' tag </p>
    <span> This span is inside the 'div' tag </span>
    <br/>

  </div>

  <center>
    <h3> Heading 3 is centered</h3>
    <p><span> Centered span inside the paragraph.</span><p>
  </center>

  Two horizontal line is drawn using two 'hr' tag.
  <hr />
  <hr>

  <pre> 'pre' tag preserve the formatting (good for writing codes)

      # Python code
      x = 2
      y = 3

```

- Fig. Below is the output of above code. Read the text to understand each tag,

## Heading 2

### Heading 6

This is paragraph

This is span. The 'br' tag is used after span to break the line

The 'div' tag can be used for formatting the tags inside it at once using 'style' and 'classes' etc.

This paragraph is inside the 'div' tag

This span is inside the 'div' tag

### Heading 3 is centered

Centered span inside the paragraph.

Two horizontal line is drawn using two 'hr' tag.

'pre' tag preserve the formatting (good for writing codes)

```

# Python code
x = 2
y = 3
print(x+y)

```

Fig. Basic tags: Attribute 'style' is used in 'div' tag

## 1.4 Attributes

In above fig, we saw an example of attribute (i.e. style) which changed the color of all the elements to 'blue' inside the 'div' tag.

### 1.4.1 Attribute 'name' and 'value'

- Attribute is defined inside the opening part of a 'tag'. For example, in the below code, the attribute 'style' is defined inside the 'div' tag.

```
<div style="color:blue;">
</div>
```

- An attribute has two parts i.e. 'name' and 'value'. For example, in the above code, **name** and **value** of the attribute are 'style' and 'blue' respectively.

### 1.4.2 Core attributes

Below are the three core attributes which are used frequently in web design.

- id** : The 'id' is the **unique** name which can be given to any tag. This is very useful in distinguishing the element with other elements.

```
<p id='para1'> This is paragraph with id 'para1' </p>
<p id='para2'> This is paragraph with id 'para2' </p>
```

- class** : The attribute 'class' can be used with multiple tags. This is very useful in making groups in HTML design.

```
<p class="c_blue"> This is paragraph with class 'blue' </p>
<span class="c_blue"> This is span with class 'blue' </span>
```

- style** : We already see the example of style attribute, which can be used to change the formatting of the text in HTML design. We can specify various styles which are discussed in [section 2](#).

```
<p style="font-weight:bold; color:red;">Style attribute is used to bold and color </p>
```

**Note:** Above three attributes are used with 'CSS (cascading style sheet)' and JavaScript/jQuery, which are the very handy tools to enhance the look and functionalities of the web-page respectively. The CSS is discussed in next section, whereas JavaScript and jQuery are discussed in section 3 respectively.

- Also we can define multiple attributes for one tag as shown below,

```
<p class="my_class" id="para_with_class" style="color:green"> Multiple attributes </p>
```

- The other useful attributes are listed in [Table 1.2](#)

Table 1.2: List of attributes

Name	Values	Description
id	user defined names	<p id='p_1'> Hi </p>
class	user defined names	<p class='p_class'> Hi </p>
style	CSS styles	<p style="color:red; font-weight:bold;"> Hi </p>
align	left, right, center	horizontal alignment
width	numeric value or % value	width of images and tables etc.
height	numeric value	height of images and tables etc.

## 1.5 Tables

In this section, we will learn to draw tables along with some attributes which are discussed in [Table 1.2](#). [Table 1.3](#) shows the list of tags available to create the table, which are used in [Listing 1.1](#).

Table 1.3: Tags and attributes for creating tables

Tag	Description
table	beginning and end of table
tr	row of table
th	header cell
td	data cell
<b>Attributes</b>	
rowspan	number of rows to merge
colspan	number of columns to merge
border	width of border
cellpadding	width of whitespace between two border
cellspacing	width of whitespace within a border
bgcolor	background color
bordercolor	color of border
width	width of table (numeric or %)
height	height of table (numeric)
caption	caption for table

- Some of the attributes of [Table 1.3](#) are used in below example,

Listing 1.1: Table with border and color

```

1 <!-- border - color, width and height -->
2 <table border="1" bordercolor="black" width="450" height="100">
3 <caption>Table 1 : Various tags of table</caption>
4   <tr bgcolor="red" > <!-- row -->
5     <th>Column 1</th> <!-- header -->
6     <th>Column 2</th>
7     <th>Column 3</th>
8   </tr>
9
10  <tr bgcolor="cyan"> <!-- background color -->
11    <td>Data 1</td> <!-- data -->
12    <td>Data 2</td>
13    <td>Data 3</td>
14  </tr>
15
16  <tr bgcolor="yellow"> <!-- row -->
17    <td colspan="2">New Data 1</td> <!-- column span -->
18    <td>New Data 2</td> <!-- data -->
19  </tr>
20 </table>
21
22
23
24
25
26 <!-- width in % -->
27 <table border="1" bordercolor="black" width="80%" height="100">
28 <caption> Table 2 : Width is 80%</caption>
29   <tr bgcolor="red" >
30     <th>Column 1</th>
31     <th>Column 2</th>
32     <th>Column 3</th>
33   </tr>

```

(continues on next page)

(continued from previous page)

```

33 <tr bgcolor="cyan"> <!-- row -->
34 <td>Data 1</td> <!-- data -->
35 <td>Data 2</td>
36 <td>Data 3</td>
37 </tr>
38 </table>
39

```

- Fig. 1.3 is the output of above code,

Table 1 : Various tags of table

Column 1	Column 2	Column 3
Data 1	Data 2	Data 3
New Data 1		New Data 2

Table 2 : Width is 80%

Column 1	Column 2	Column 3
Data 1	Data 2	Data 3

Fig. 1.3: Table generated by Table 1.3

## 1.6 Text formatting

In this section, we will see some of the text formatting options (see Table 1.4) e.g. bold, italic, subscript and strikeetc.

Table 1.4: Text formatting

Tag	Description
b	bold
i	italic
u, ins	underline
strike, del	strike
sup	superscript
sub	subscript
big	big size text
small	small size text

- Below are the some of the examples of text formatting, whose results are shown in Fig. 1.4,

```

<!-- Text formatting -->
<p>This is <b>bold</b> text</p>
<p>This is <del>striked</del> text</p>
<p>This is <sub>subscript</sub> text</p>

```

## 1.7 Images

Image tag has two important attributes i.e. 'src' and 'alt' as described below,

- **src** : tells the location of 'image' file e.g. in Line 2 the image 'logo.jpg' will be searched inside the folder 'img'.



This is **bold** text

This is ~~striked~~ text

This is <sub>subscript</sub> text

Fig. 1.4: Text formatting

- **alt** : is the 'alternate text' which is displayed if image is not found. For example, in Line 6, the name of the image is incorrectly written i.e. 'logoa' (instead of 'logo'), therefore the value of 'alt' i.e. 'Missing Logo.jpg' will be displayed as shown in [Fig. 1.5](#).

```
1 <!-- Images -->
2 
3
4 <br/> <br/>
5
6 
```

---

**Note:** We can use other attributes as well e.g. '**height**', '**align**' and '**border**' etc.

---

## 1.8 Lists

There are three type of lists in HTML,

- Unordered list : bullet are used in it (see Lines 2 and 9)
- Ordered list : numbers are used in it (see Lines 15, 22 and 28)
- Definition list : This can be used for writing definitions in HTML (see Line 35)

```

1 <!-- Lists -->
2 <!-- unordered list -->
3 <ul> Unordered List
4   <li>Pen</li>
5   <li>Pencil</li>
6   <li>Eraser</li>
7 </ul>
8
9 <ul type="circle"> Change bullets : 'square', 'circle' or 'disc'
10  <li>Pen</li>
11  <li>Pencil</li>
12  <li>Eraser</li>
13 </ul>
14
15 <!-- ordered list -->
16
17 <ol> Ordered List
18   <li>Pen</li>
19   <li>Pencil</li>
20   <li>Eraser</li>
21 </ol>
22
23 <ol type="i"> Change style : 'i', 'I', 'l', 'a' or 'A'
24   <li>Pen</li>
25   <li>Pencil</li>
26   <li>Eraser</li>
27 </ol>
28
29 <ol type="i" start="5"> Start from 'v'
30   <li>Pen</li>
31   <li>Pencil</li>
32   <li>Eraser</li>
33 </ol>
34
35 <!-- Definition list -->
36 <dl> Definition list -->
37   <dt> <h4>HTML Definition
38   <dd> HTML is easy </dd>
39   <dd> HTML is good </dd>

```

The outputs of above codes are shown in Fig. 1.6,

## 1.9 Links

```

<!-- links -->
<p>Go to paragraph with<a href="#para1"> id='para1'</a></p>
<a href="http://pythondsp.readthedocs.io"> PythonDSP </a>

<br>
<p><a href="js.html" target="_self"> JavaScript Tutorial</a> in same window.</p>
<p><a href="js.html" target="_blank"> JavaScript Tutorial</a> in new Window.</p>

```

(continues on next page)

### Unordered List

- Pen
- Pencil
- Eraser

Change bullets : 'square', 'circle' or 'disc'

- Pen
- Pencil
- Eraser

### Ordered List

1. Pen
2. Pencil
3. Eraser

Change style : 'i', 'I', '1', 'a' or 'A'

- i. Pen
- ii. Pencil
- iii. Eraser

Start from 'v'

- v. Pen
- vi. Pencil
- vii. Eraser

### HTML Definition List

HTML is easy  
HTML is good

Fig. 1.6: Lists

(continued from previous page)

```
<p><a href="http://pythondsp.readthedocs.io/pdf">Download PDF, DOC or Zip Files</a></p>
```

```
<p><a href="mailto:pythondsp@gmail.com">Email me</a></p>
```

```
<p><a href="mailto:pythondsp@gmail.com?subject=Feedback&body=Your feedback here">Feedback email</a></p>
```

Go to paragraph with [id='para1'](#)

[PythonDSP](#)

[JavaScript Tutorial](#) in same window.

[JavaScript Tutorial](#) in new Window.

[Download PDF, DOC or Zip Files](#)

[Email me](#)

[Feedback email](#)

---

**Note:** We can change the color of the links using 'alink (active link)', 'link' and 'vlink (visited link)', by defining these attributes in the 'body tag' as shown below,

```
<body alink="green" link="blue" vlink="red">
```

---

## 1.10 Forms

Forms can have different types of controls to collect the input-data from users, which are listed below and shown in [Table 1.5](#),

- Text input
- Text area
- Radio button
- Checkbox
- Select box
- File select
- Buttons
- Submit and reset buttons
- Hidden input

Table 1.5: List of control inputs and their attributes

Control	Attributes	Values	Description
Input : text	type	text, password	
	value	user-defined	initial value in the area
	name	user-defined	name send to server
	size	numeric value	width of the text area
	maxlength	numeric value	maximum number of characters
Input : radio	type	radio	
	name	user-defined	name send to server
	value	user-defined value	value of the button if selected
	checked		check the button by default
Input : check box	type	checkbox	
	name	user-defined	name send to server
	value	user-defined value	value of the box if selected
	checked		check the box by default
Input : button	type	button	trigger client side script
		submit	submit the form and run 'action'
		reset	reset form
		image	create image button
	method	get, post	get or post method
	action	user-defined	action to perform on <b>submit</b>
Input : hidden	type	hidden	will not display on html, but can be used for sending information to server
Selection box	name	user-defined	name send to server
	size	numeric value	enables scroll (default dropdown)
	multiple	numeric value	select multiple items
	value	user-defined value	value of the item if selected
	selected		select item by default
Text area	rows, cols	numeric value	number of rows and cols
	name	user-defined	name send to server

- Below are the exmaple of the control inputs described in [Table 1.5](#)

```

<!-- Forms -->
<form>
  <h4>Text input </h4>
  Name : <input type="text" name="user_name" size="4" value="e.g. meher21" maxlength="10"><br>
  Password : <input type="password" name="user_pass" ><br>

  <h4> Radio button: name should be same</h4>
  <input type="radio" name="r_gender"> Male
  <input type="radio" name="r_gender"> Female
  <input type="radio" name="r_gender" checked> Infant

  <h4> Check box : name should be different</h4>
  <input type="checkbox" name="c_male" checked> Male
  <input type="checkbox" name="c_female"> Female
  <input type="checkbox" name="c_infant"> Infant

  <h4> Select box : drop-down</h4>
  <select name="s_box">
    <option value="s_male">Male</option>
    <option value="s_female" selected>Female</option>
    <option value="s_infant">Infant</option>
  </select>

  <h4> Select box : scroll</h4>

```

(continues on next page)

(continued from previous page)

```

<select name="s_box" size="4" multiple>
  <option value="s_male" selected>Male</option>
  <option value="s_female" selected>Female</option>
  <option value="s_infant">Infant 1</option>
  <option value="s_infant" selected>Infant 2</option>
  <option value="s_infant">Infant 3</option>
  <option value="s_infant">Infant 4</option>
</select>

<h4> Text area</h4>
<textarea rows="10" cols="80" name="txt_area">Initial Text
x = 2
y = 3
</textarea> <!-- formatting work as pre -->

</form>

```

Fig. 1.7 is the output of above code,

- Below is the code which shows the working of various buttons. Note that **method** and **action** are defined in this form, which will be triggered on 'submit' button. Lastly, 'hidden' option is used in this example.

```

<form method="get|post" action="jquery.html">
  <h4> Buttons and Hidden</h4>

  Name : <input type="text" name="user_name" size="4" value="Meher" maxlength="16"><br>
  Password : <input type="password" name="user_pass" ><br>

  <input type="button" onclick="alert('Hello')" name="b_alert" value="Say Hello"/><br>
  <input type="submit" name="b_submit" value="Go to jQuery"/>
  <input type="reset" name="b_reset" value="Reset"/><br>

  <input type="hidden" name="h_data" value="html_tutorial">

</form>

```

Fig. 1.8 is the output of above code,

**Text input**Name : Password : **Radio button: name should be same**☐ Male ☐ Female ☒ Infant**Check box : name should be different**☒ Male ☐ Female ☐ Infant**Select box : drop-down****Select box : scroll**

Male

Female

Infant 1

Infant 2

**Text area**

```
Initial Text
  x = 2
  y = 3
```

Fig. 1.7: Various control inputs for creating form

## Buttons and Hidden

Name :

Password :

Fig. 1.8: Various buttons and hidden-input in the form



## Section 2

# Cascading Style Sheets (CSS)

### 2.1 Introduction

CSS is used to enhance the look of the web page. In [Section 1.4.2](#), we saw the attribute 'style', which is used for changing the color of the text. Let's rewrite the example of 'style' as shown in next section.

#### 2.1.1 Inline CSS

- Below code is an example of 'inline CSS', where the styles are defined inside the individual tags.

```
1 <!-- css.html -->
2
3 <!DOCTYPE html>
4 <html>
5 <head>
6   <title>CSS Tutorial</title>
7
8 </head>
9 <body>
10
11   <h3 style="color:blue"> Heading 1 </h3>
12   <h3 style="color:blue"> Heading 3 </h3>
13   <h3 style="color:blue"> Heading 3 </h3>
14
15 </body>
16 </html>
```

In the above code, we have three 'headings' with font-color as 'blue'. Suppose, we want to change the color to red, then we must go to individual 'h3' tag and then change the color. This is easy in this case, but if we have 100 headings in 5 different 'html' files, then this process is not very handy. In such cases, CSS can be quite useful as shown in next section.

#### 2.1.2 Embedded CSS

In the below code, the style is embedded inside the 'style' tag as shown in Lines 8-17. Here, we have defined two classes i.e. 'h3\_blue (Lines 21-23)' and 'h3\_red (Lines 26-28)'. Then, the **selectors** at Lines 9 and 13 targets the class 'h3\_blue' & 'h3\_red', and change the color to blue and red respectively. In this chapter, we will discuss these selectors (e.g. h3.h3\_blue) in more details.

---

#### Note:

- In CSS, the comments are written between /\* and \*/.
-

- CSS has three parts,
  - **Selectors** e.g. p, h3.h3\_blue
  - **Properties** e.g. color
  - **Values** of properties e.g. red

```

1 <!-- css.html -->
2 <!DOCTYPE html>
3 <html>
4 <head>
5   <title>CSS Tutorial</title>
6   <style type="text/css">
7     h3.h3_blue{ /*change color to blue*/
8       color: blue;
9     }
10
11     h3.h3_red{ /*change color to red*/
12       color:red;
13     }
14   </style>
15 </head>
16 <body>
17
18   <h3 class="h3_blue"> Heading 1 </h3>
19   <h3 class="h3_blue"> Heading 3 </h3>
20   <h3 class="h3_blue"> Heading 3 </h3>
21
22   <h3 class="h3_red"> Heading 1 </h3>
23   <h3 class="h3_red"> Heading 3 </h3>
24   <h3 class="h3_red"> Heading 3 </h3>
25
26 </body>
27 </html>

```

### 2.1.3 External CSS

We can write the 'CSS' code in different file and then import the file into 'html' document as shown in this section. In this way, we can manage the files easily.

- The 'CSS' code is saved in the file 'my\_css.css' which is saved inside the folder 'asset/css'.

```

/* asset/css/my_css.css */
h3.h3_blue{
  color: blue;
}
h3.h3_red{
  color:red;
}

```

- Next, we need to import the CSS file into the 'html' file as shown in Line 7.

```

1 <!-- css.html -->
2

```

(continues on next page)

## 2.1. Introduction

# Heading 1

### Heading 3

### Heading 3

# Heading 1

### Heading 3

### Heading 3

Fig. 2.1: Embedded CSS

(continued from previous page)

```

3 <!DOCTYPE html>
4 <html>
5 <head>
6   <title>CSS Tutorial</title>
7   <link rel="stylesheet" type="text/css" href="asset/css/my_css.css">
8 </head>
9 <body>
10
11   <h3 class='h3_blue'> Heading 1 </h3>
12   <h3 class='h3_blue'> Heading 3 </h3>
13   <h3 class='h3_blue'> Heading 3 </h3>
14
15   <h3 class='h3_red'> Heading 1 </h3>
16   <h3 class='h3_red'> Heading 3 </h3>
17   <h3 class='h3_red'> Heading 3 </h3>
18
19 </body>
20 </html>
21

```

## 2.2 Basic CSS Selectors

There are three types of selectors in CSS,

- **Element** : can be selected using it's name e.g. 'p', 'div' and 'h1' etc.
- **Class** : can be selected using '.className' operator e.g. '.h3\_blue'.
- **ID** : can be selected using '#idName' e.g. '#my\_para'.We

will use following HTML for understanding the selectors,

```
<!-- css.html -->
1
2 <!DOCTYPE html>
3 <html>
4 <head>
5     <title>CSS Selectors</title>
6     <link rel="stylesheet" type="text/css" href="asset/css/my_css.css">
7 </head>
8 <body>
9     <h3>CSS Selectors</h3>
10
11     <p class='c_head'> Paragraph with class 'c_head' </p>
12     <p id='i_head'> Paragraph with id 'i_head' </p>
13
14 </body>
15 </html>
```

- Below code shows the example of different selectors, and the output is shown in [Fig. 2.2](#)

```
1 /* asset/css/my_css.css */
2
3 /*element selection*/
4 h3 {
5     color: blue;
6 }
7
8
9
10 /*class selection*/
11 .c_head{
12     font-family: cursive;
13     color: orange;
14 }
15
16
17
18 /*id selection*/
19 #i_head{
20     font-variant: small-caps;
21     color: red;
22 }
```

## CSS Selectors

Paragraph with class 'c\_head'

PARAGRAPH WITH ID 'I\_HEAD'

Fig. 2.2: Selectors : element, class and id

## 2.3 Hierarchy

In previous section, we saw the example of selectors. In this section, we will understand the hierarchy of the styling-operations.

**Important:** Below is the priority level for the CSS,

### 2.3. Hierarchy

- Priority level:
  - ID (highest priority)
  - Class
  - Element
- If two CSS has same priority, then CSS rule at the last will be applicable.

- Below is the html code with following tags,
  - ‘p’ tag
  - ‘p’ tag with class ‘c\_head’
  - ‘p’ tag with class ‘c\_head’ and id ‘i\_head’

```

1 <!-- css.html -->
2
3 <!DOCTYPE html>
4 <html>
5 <head>
6   <title>CSS Selectors</title>
7   <link rel="stylesheet" type="text/css" href="asset/css/my_css.css">
8 </head>
9 <body>
10  <p>Paragraph</p>
11
12  <p class='c_head'> Paragraph with class 'c_head' </p>
13
14  <p class='c_head' id='i_head'> Paragraph with class 'c_head' and id 'i_head' </p>
15
16 </body>
17 </html>

```

Below is the CSS code. Let's understand the formatting of all three 'p' tags individually. The results are shown in [Fig. 2.3](#).

- **'p' tag at Line 13 of html** : Since, 'id' has highest priority, therefore CSS rule for '#i\_head' (Line 12) will not be overridden by Line 24; hence the color is **red**. Line 13 has 'p' tag, therefore 'font-variant' rule will be applied by Line 17. Also, this tag has class 'c\_head', therefore 'font' will be set to 'cursive'. Hence, the line is **"all-caps with font-cursive in red color"**.
- **'p' tag at Line 12 of html** : Similarly, the 'head' tag has higher priority than 'element' therefore color of this line is **orange** and font-family is 'cursive'. Also, Line 17 will make it **all caps**.
- **'p' tag at Line 10 of html** : Color defined at Line 18 will be overridden by Line 24; hence the color will be **blue**. Also, Line 17 will make it **all caps**.

```

1 /* asset/css/my_css.css */
2
3 /*class selection*/
4 .c_head{
5   font-family: cursive;
6   color: orange;           /*override the blue color*/
7 }
8
9
10
11 /*id selection*/
12 #i_head{
13   color: red;
14 }
15
16
17 /*element selection*/
18 p {
19   font-variant: small-caps;
20   color: blue;
21 }

```

(continues on next page)

## 2.3. Hierarchy

(continued from previous page)

```

22  /*element selection*/
23  p {
24      color: green;
25  }

```

PARAGRAPH

PARAGRAPH WITH CLASS 'C\_HEAD'

PARAGRAPH WITH CLASS 'C\_HEAD' AND ID 'I\_HEAD'

Fig. 2.3: Priority level for CSS rule

## 2.4 More selectors

Table 2.1 shows the combinations of selectors to target the various elements of the HTML. Also, some of the example of 'Attribute selector' is shown in this section.

Table 2.1: List of selectors

Selectors	Description
h1, p, span etc.	element selector
.className	class selector
#idName	id selector
*	Universal selector (selects everything)
h1.className	select h1 with class 'className'
h1#idName	select h1 with id 'idName'
p span	descendant selector (select span which is inside p)
p > span	child selector ('span' which is direct descendant of 'p')
h1, h2, p	group selection (select h1, h2 and p)
span[my_id]	select 'span' with attribute 'my_id'
span[my_id=m_span]	select 'span' with attribute 'my_id=m_span'

### 2.4.1 Attribute selector

- Add below code at the end of the html file. In these lines 'custom attributes' are added (i.e. my\_id).

```

<!-- css.html -->

<span my_id='m_span'> Span with attribute 'my_id' with value 'm_span' </span>
<br>
<span my_id='m_span2'> Span with attribute 'my_id' with value 'm_span2' </span>

```

- These custom attributes can be selected as below,

```

/*attribute selection*/
span[my_id] { /* select 'span' with attribute 'my_id' */
    color: green;
    font-weight: bold
}

```

(continues on next page)

(continued from previous page)

```

}

span[my_id=m_span] { /* select 'span' with attribute 'my_id = m_span' */
    color: red;
}

```

## 2.5 More properties

Table 2.2 shows the some more important properties which can be used in CSS,

Table 2.2: More CSS properties

Property	Syntax	Description/possible values
size	20%	size = 20%
	20px	20 pixel
	2em	2*font-size
	2mm, 2cm, 2in	2 mm, cm and inch
color	names	e.g. red, blue, green
	hex code (#RRGGBB or #RGB)	#FFF000 or #FFF
	rgb(num, num, num)	rgb(0, 0, 255) or rgb(20%, 10%, 70%)
link	a:link	a:link {color: red}
	a:hover	
	a:visited	
	a:active	
Font	font-family	serif, cursive
	font-style	normal, italic, oblique
	font-variant	normal, small-caps
	font-weight	normal, bold, bolder, lighter, 100-900
	font-size	10px, small, medium, large etc.
Text	color	red, #FFF
	letter-spacing	10px
	word-spacing	10 px
	text-align	right, left, center
	text-decoration	underline, overline, line-through, none
	text-transform	capitalize, uppercase, lowercase, none
	white-space	pre, normal, nowrap
	text-shadow	text-shadow:5px 5px 8px red;
	Image	border
Border	height, width	100px, 20%
	border-style	solid, dashed, dotted, double, none etc.
	border-top-style	
	border-bottom-style	
	border-left-style	
	border-right-style	
	border-width	4px, 4pt
	border-bottom-width	similarly use 'top', 'left', 'right'
	border (shortcut)	1px solid blue'
	Margin	margin, margin-left etc.
Padding	padding (top, bottom, left, right)	'10px 10px 2px 2px' or '10px 2px'
	padding-right, padding-left etc.	

## Bonus Section

# Bootstrap

### 3.1 Introduction

One of the problem with basic HTML design is that the webpage may look different in different browser or device(e.g. mobile, tablet and laptop). Therefore, we may need to modify the code according to browser or device. The problem can be easily resolved by using Bootstrap.

Bootstrap is a framework which uses HTML, CSS and JavaScript for the web design. It is supported by all the major browsers e.g. Firefox, Opera and Chrome etc. Further, Bootstrap includes several predefined classes for easy layouts e.g. dropdown buttons, navigation bar and alerts etc. Lastly, it is responsive in nature i.e. the layout changes automatically according to the device e.g. mobile or laptop etc.

### 3.2 Setup

Bootstrap needs atleast 3 files for its operation which can be [downloaded from the Bootstrap website](#).

- **bootstrap.css (Line 7)** : This file contains various CSS for bootstrap.
- **bootstrap.js (Line 16)** : This file contains various JavaScript functionalities e.g. dropdown and alerts etc.
- **jQuery.js (Line 17)** : This file is the jQuery library which can be downloaded from the 'jQuery' website. It is required for proper working of 'bootstrap.js'.

#### 3.2.1 Download and include files

These files are downloaded and saved inside the 'asset' folder. Next, we need to include these files in the HTML document as below,

```
1 <!DOCTYPE html>
2 <html>
3 <head>
4   <title>Bootstrap Tutorial</title>
5
6   <!-- CSS -->
7   <link href="asset/css/bootstrap.min.css" rel="stylesheet">
8   <!-- Add Custom CSS below -->
9
10
11 </head>
12 <body>
13
14
15   <!-- Javascript -->
   <!-- put jQuery.js before bootstrap.min.js; and then add custom jquery -->
```

(continues on next page)



(continued from previous page)

```

16 <script src="asset/js/jquery-3.3.1.min.js"></script>
17 <script src="asset/js/bootstrap.min.js"></script>
18 </body>
19 </html>

```

### 3.2.2 Add CDN

Another way to include the files is CDN. In this method, we need not to download the files, but provide the link to these files, as shown in Lines 8, 17 and 19 of below code. Note that, in this case the code will not work in offline mode.

```

1 <!DOCTYPE html>
2 <html>
3 <head>
4   <title>Bootstrap Tutorial</title>
5   <!-- CSS -->
6   <!-- Latest compiled and minified CSS -->
7   <link rel="stylesheet" href="https://maxcdn.bootstrapcdn.com/bootstrap/3.3.7/css/bootstrap.min.css"
8     integrity="sha384-BVYiiSIfFeK1dGmJRAkyuHAHRg32OmUcww7on3RYdg4Va+PmSTsz/K68vbdEjh4u" crossorigin=
9     "anonymous">
10   <!-- Add Custom CSS below -->
11
12 </head>
13 <body>
14
15   <!-- Javascript -->
16   <!-- jQuery -->
17   <script src="https://ajax.googleapis.com/ajax/libs/jquery/3.3.1/jquery.min.js"></script>
18   <!-- Latest compiled and minified JavaScript -->
19   <script src="https://maxcdn.bootstrapcdn.com/bootstrap/3.3.7/js/bootstrap.min.js" integrity="sha384-
20     Tc5IQib027qvyjSMfHjOMaLkfuWVxZxUPnCA7l2mCWNIpG9mGCD8wGNlCPD7Txa" crossorigin="anonymous"></script>
21 </body>
22 </html>

```

**Note:** In this tutorial, we have used the first method i.e. download the files and include in the html document.

### 3.2.3 Check setup

Let's write our first code to check the correct setup of the Bootstrap.

**Note:** We need not to memorize the code for creating the 'dropdown' button. All the templates are available on the [Bootstrap website](#). Copy and paste the code from there and modify the code according to need as shown in this tutorial.

```

1 <!DOCTYPE html>
2 <html>
3 <head>
4   <title>Bootstrap Tutorial</title>
5   <!-- CSS -->
6   <link href="asset/css/bootstrap.min.css" rel="stylesheet">
7   <!-- Add Custom CSS below -->
8

```

(continues on next page)

## 3.2. Setup

(continued from previous page)

```

9
10 </head>
11 <body>
12
13     <div class="dropdown">
14         <button class="btn btn-success dropdown-toggle" type="button" id="dropdownMenu1" data-toggle=
15         "dropdown" aria-haspopup="true" aria-expanded="true">
16             Dropdown
17         <span class="caret"></span>
18         </button>
19         <ul class="dropdown-menu" aria-labelledby="dropdownMenu1">
20             <li><a href="#">Action</a></li>
21             <li><a href="#">Another action</a></li>
22             <li><a href="#">Something else here</a></li>
23             <li role="separator" class="divider"></li>
24             <li><a href="#">Separated link</a></li>
25         </ul>
26     </div>
27
28     <!-- Javascript -->
29     <!-- put jQuery.js before bootstrap.min.js; and then add custom jquery-->
30     <script src="asset/js/jquery-3.3.1.min.js"></script>
31     <script src="asset/js/bootstrap.min.js"></script>
32 </body>
</html>

```

The resultant web page is shown in Fig. 3.1,




Fig. 3.1: Click on the 'Dropdown' button

### 3.3 Grid system

Bootstrap divides the **each row** into **12 columns**. Then following commands can be used to specify the widththe columns

- **col-lg-4** : It will select 4 columns. Choose any number between 1-12. The 'lg' stand for **large screen** (e.g.large computer screen).
- **col-md-5** : 'md' = medium screen
- **col-sm-3** : 'sm' = small screen
- **col-xs-3** : 'xs' = extra small screen
- **col-lg-offset-4** : skip first 4 columns. Simimlary use 'md', 'sm' and 'xs' with offset

### 3.3. Grid system

### 3.3.1 Example

Below is an example of grid system. Read the content of the Lines 13-16 to understand it. The resultant webpage is shown in Fig. 3.2.

#### Note:

- For easy visualization, in the below code the CSS code (Lines 9-21) is used to fill the columns with colors and border.
- The columns (Lines 28-30) should be defined inside the class 'row' (Line 27).
- Also, sum of the widths of individual columns should not be greater than 12.
- Lastly, if we use 'col-md-4' without defining the 'lg', 'sm' and 'xs', then 'md' rule will be applicable to higher size screen 'lg', but **not** on the lower size screen 'sm' and 'xs'. Similarly, if we use 'sm' without defining the 'lg', 'md' and 'xs', then rule will be applicable to higher size screen i.e. 'lg' and 'md' but not on 'xs'

```

1 <!DOCTYPE html>
2 <html>
3 <head>
4   <title>Bootstrap Tutorial</title>
5
6   <!-- CSS -->
7   <link href="asset/css/bootstrap.min.css" rel="stylesheet">
8   <!-- Add Custom CSS below -->
9   <style type="text/css">
10     .col-xs-1, .col-xs-2, .col-xs-3, .col-xs-4, .col-xs-5, .col-xs-6, .col-xs-7, .col-xs-8,
11     .col-sm-1, .col-sm-2, .col-sm-3, .col-sm-4, .col-sm-5, .col-sm-6, .col-sm-7, .col-sm-8,
12     .col-md-1, .col-md-2, .col-md-3, .col-md-4, .col-md-5, .col-md-6, .col-md-7, .col-md-8,
13     .col-lg-1, .col-lg-2, .col-lg-3, .col-lg-4, .col-lg-5, .col-lg-6, .col-lg-7, .col-lg-8 {
14       background-color: green;
15       color: white;
16       font-weight: bold;
17       border: 1px solid red;
18       height: 3em; /*height of the box*/
19       text-align: center; /*vertical center the text*/
20     }
21   </style>
22
23 </head>
24
25 <body>
26
27   <div class="row">
28     <div class="col-md-2 col-xs-4">col-md-2, col-xs-4</div>
29     <div class="col-md-6 col-xs-4">col-md-6, col-xs-4</div>
30     <div class="col-md-4 col-xs-4">col-md-4, col-xs-4</div>
31   </div>
32
33   <!-- Javascript -->
34   <!-- put jQuery.js before bootstrap.min.js; and then add custom jquery-->
35   <script src="asset/js/jquery-3.3.1.min.js"></script>
36   <script src="asset/js/bootstrap.min.js"></script>
37 </body>
38 </html>

```



Fig. 3.2: Different grid-size (i.e. 2, 6, 4) for 'medium' and 'large' screen

### 3.3. Grid system



Fig. 3.3: Equal grid-size (i.e. 4) for 'extra small' and 'small' screen

### 3.3.2 Nested columns

We can further divide a column into small columns by defining a class 'row' (Line 30) inside the 'column' (Line 29), as shown in Lines 29-34.

```

1 <!DOCTYPE html>
2 <html>
3 <head>
4   <title>Bootstrap Tutorial</title>
5
6   <!-- CSS -->
7   <link href="asset/css/bootstrap.min.css" rel="stylesheet">
8   <!-- Add Custom CSS below -->
9   <style type="text/css">
10     .col-xs-1, .col-xs-2, .col-xs-3, .col-xs-4, .col-xs-5, .col-xs-6, .col-xs-7, .col-xs-8,
11     .col-sm-1, .col-sm-2, .col-sm-3, .col-sm-4, .col-sm-5, .col-sm-6, .col-sm-7, .col-sm-8,
12     .col-md-1, .col-md-2, .col-md-3, .col-md-4, .col-md-5, .col-md-6, .col-md-7, .col-md-8,
13     .col-lg-1, .col-lg-2, .col-lg-3, .col-lg-4, .col-lg-5, .col-lg-6, .col-lg-7, .col-lg-8 {
14       background-color: green;
15       color: white;
16       font-weight: bold;
17       border: 1px solid red;
18       height: 3em; /*height of the box*/
19       text-align: center; /*vertical center the text*/
20     }
21   </style>
22
23 </head>
24
25 <body>
26
27   <div class="row">
28     <div class="col-md-2 col-xs-4">col-md-2, col-xs-4</div>
29     <div class="col-md-6 col-xs-4">
30       <div class="row">
31         <div class="col-xs-6">col-xs-6</div>
32         <div class="col-xs-6">col-xs-6</div>
33       </div>
34     <div class="col-md-4 col-xs-4">col-md-4, col-xs-4</div>
35   </div>
36
37   <!-- Javascript -->
38   <!-- put jQuery.js before bootstrap.min.js; and then add custom jquery -->
39   <script src="asset/js/jquery-3.3.1.min.js"></script>
40   <script src="asset/js/bootstrap.min.js"></script>
41 </body>
42 </html>

```

### 3.3.3 Offset

We can skip the columns using 'offset' as shown in Line 27; and the corresponding html page is shown in [Fig. 3.4](#),

```

1 <!DOCTYPE html>
2 <html>
3 <head>
4   <title>Bootstrap Tutorial</title>
5
6   <!-- CSS -->
7   <link href="asset/css/bootstrap.min.css" rel="stylesheet">
8   <!-- Add Custom CSS below -->
9   <style type="text/css">
10     .col-xs-1, .col-xs-2, .col-xs-3, .col-xs-4, .col-xs-5, .col-xs-6, .col-xs-7, .col-xs-8,
11     .col-sm-1, .col-sm-2, .col-sm-3, .col-sm-4, .col-sm-5, .col-sm-6, .col-sm-7, .col-sm-8,
12     .col-md-1, .col-md-2, .col-md-3, .col-md-4, .col-md-5, .col-md-6, .col-md-7, .col-md-8,
13     .col-lg-1, .col-lg-2, .col-lg-3, .col-lg-4, .col-lg-5, .col-lg-6, .col-lg-7, .col-lg-8 {
14       background-color: green;
15       color: white;
16       font-weight: bold;
17       border: 1px solid red;
18       height: 3em; /*height of the box*/
19       text-align: center; /*vertical center the text*/
20     }
21   </style>
22 </head>
23 <body>
24
25   <div class="col-md-offset-2 col-md-2">col-md-2</div>
26
27   <div class="col-md-8">col-md-8</div>
28 </div>
29
30   <!-- Javascript -->
31   <!-- put jQuery.js before bootstrap.min.js; and then add custom jquery -->
32   <script src="asset/js/jquery-3.3.1.min.js"></script>
33   <script src="asset/js/bootstrap.min.js"></script>
34 </body>

```

col-md-offset-2

col-md-2

col-md-8

Fig. 3.4: Offset

## 3.4 Components

Once we understand the 'html', 'css' and 'Bootstrap-grid' understood, then the use of Bootstrap-components are straightforward. Just copy and paste the code from the [Bootstrap website](#) and modify it according to the requirement.

In this section, we will use following template.

```

<!DOCTYPE html>
<html>
<head>
  <title>Bootstrap Tutorial</title>
  <!-- CSS -->
  <link href="asset/css/bootstrap.min.css" rel="stylesheet">
  <!-- Add Custom CSS below -->
</head>

```

(continues on next page)

(continued from previous page)

```

<body>

  <!-- Javascript -->
  <!-- put jQuery.js before bootstrap.min.js; and then add custom jquery -->
  <script src="asset/js/jquery-3.3.1.min.js"></script>
  <script src="asset/js/bootstrap.min.js"></script>
</body>
</html>

```

### 3.4.1 Labels

- The class 'label' is used to create the label (Line 11).
- The class 'label-info' sets the color of the label to 'blue' (Line 11).
- The size of the 'labels' can be changes using 'element' tags (e.g. 'h3' in Line 11) outside the 'span' tag (Line 11).

**Note:** Bootstrap provides 6 color option,

- danger
- default
- info
- primary
- success
- warning

```

1 <!DOCTYPE html>
2 <html>
3 <head>
4   <title>Bootstrap Tutorial</title>
5   <!-- CSS -->
6   <link href="asset/css/bootstrap.min.css" rel="stylesheet">
7   <!-- Add Custom CSS below -->
8 </head>
9
10 <body>
11   <h3>Example heading <span class="label label-info">New</span></h3>
12   <hr>
13
14   <!-- Javascript -->
15   <!-- put jQuery.js before bootstrap.min.js; and then add custom jquery -->
16   <script src="asset/js/jquery-3.3.1.min.js"></script>
17   <script src="asset/js/bootstrap.min.js"></script>
18 </body>
19 </html>

```

- Fig. 3.5 is the output of above code,




Fig. 3.5: Label

**Note:** All the codes will be added in the 'body' tag, and the new code will be inserted below the previous codes. Therefore full HTML code is not added in the tutorial.

### 3.4.2 Buttons

The element 'button' can be used to create the button in Bootstrap as shown below,

**Note:**

- We can use 'lg', 'md' and 'xs' etc. to set the size of the button.
- In Line 3, a glyphicon is added (i.e. trash sign). More glyphicon can be found on the [Bootstrap-webpage](#).

```
<h3> Buttons </h3>
<button type="button" class="btn btn-primary">Sign in</button>
<button type="button" class="btn btn-danger"> Delete <span class="glyphicon glyphicon-trash"><span></
→button>
<button type="submit" class="btn btn-lg btn-success">Submit</button>
<button type="submit" class="btn btn-md btn-success">Submit</button>
<button type="submit" class="btn btn-sm btn-success">Submit</button>
```

- [Fig. 3.6](#) is the output of above code,




Fig. 3.6: Buttons

### 3.4.3 Forms

In this section, 4 types of forms are added,

#### 3.4.3.1 Basic form

Output of below code is shown in [Fig. 3.7](#),

```
<h2> Basic form </h2>
<div class="row">
<div class="col-sm-5" style="background: pink">
<div class="panel-body">
  <form role="form">
    <div class="form-group">
      <label for="exampleInputEmail1">Email address</label>
      <input class="form-control" id="exampleInputEmail1" placeholder="Enter email" type="email">
    </div>
    <div class="form-group">
      <label for="exampleInputPassword1">Password</label>
      <input class="form-control" id="exampleInputPassword1" placeholder="Password" type="password"
→">
  </div>
```

(continues on next page)

## 3.4. Components

(continued from previous page)

```

<div class="form-group">
  <label for="exampleInputFile">File input</label>
  <input id="exampleInputFile" type="file">
  <p class="help-block">Example block-level help text here.</p>
</div>
<div class="checkbox">
  <label>
    <input type="checkbox"> Check me out
  </label>
</div>
<button type="submit" class="btn btn-info">Submit</button>
</form>
</div>
</div>
</div>
<br><br>

```

## Basic form

**Email address**

Enter email

**Password**

Password

**File input**

Browse... No file selected.

Example block-level help text here.

☐ Check me out

Submit

Fig. 3.7: Basic form

### 3.4.4 Horizontal form

Output of below code is shown in Fig. 3.8,

```

<h3> Horizontal form </h3>
<div class="row">

```

(continues on next page)

## 3.4. Components



(continued from previous page)

```

<div class="col-sm-5" style="background: pink">
<div class="panel-body">
  <form class="form-horizontal" role="form">
    <div class="form-group">
      <label for="inputEmail1" class="col-lg-2 col-sm-2 control-label">Email</label>
      <div class="col-lg-10">
        <input class="form-control" id="inputEmail1" placeholder="Email" type="email">
        <p class="help-block">Example block-level help text here.</p>
      </div>
    </div>
    <div class="form-group">
      <label for="inputPassword1" class="col-lg-2 col-sm-2 control-label">Password</label>
      <div class="col-lg-10">
        <input class="form-control" id="inputPassword1" placeholder="Password" type="password">
      </div>
    </div>
    <div class="form-group">
      <div class="col-lg-offset-2 col-lg-10">
        <div class="checkbox">
          <label>
            <input type="checkbox"> Remember me
          </label>
        </div>
      </div>
    </div>
    <div class="form-group">
      <div class="col-lg-offset-2 col-lg-10">
        <button type="submit" class="btn btn-danger">Sign in</button>
      </div>
    </div>
  </form>
</div>
</div>
</div>

```

#### 3.4.4.1 Inline form

Output of below code is shown in [Fig. 3.9](#),

```


<h2> Inline form </h2>
<div class="row">
<div class="col-sm-5" style="background: pink">
<div class="panel-body">
  <form class="form-inline" role="form">
    <div class="form-group">
      <label class="sr-only" for="exampleInputEmail2">Email address</label>
      <input class="form-control" id="exampleInputEmail2" placeholder="Enter email" type="email">
    </div>
    <div class="form-group">
      <label class="sr-only" for="exampleInputPassword2">Password</label>
      <input class="form-control" id="exampleInputPassword2" placeholder="Password" type="password"
    </div>
    <div class="checkbox">
      <label>
        <input type="checkbox"> Remember me
      </label>
    </div>
    <button type="submit" class="btn btn-success">Sign in</button>
  </form>

```

(continues on next page)

### 3.4. Components

## Horizontal form




A horizontal form layout on a pink background. It features two input fields: 'Email' and 'Password'. Below the 'Email' field is a line of block-level help text: 'Example block-level help text here.' Below the 'Password' field is a checkbox labeled 'Remember me'. At the bottom is a red 'Sign in' button.

Fig. 3.8: Horizontal form

(continued from previous page)

```
</div>
</div>
</div>
<br><br>
```

## Inline form



An inline form layout on a pink background. It features two input fields: 'Enter email' and 'Password'. Below the 'Enter email' field is a checkbox labeled 'Remember me'. To the right of the checkbox is a green 'Sign in' button.

Fig. 3.9: Inline form

### 3.4.4.2 Modal form

Modal form appears in the pop-up window. Output of below code is shown in [Fig. 3.10](#),

```
<!-- modal form -->
<h3> Modal form </h3>

<div class="row">
<div class="col-sm-5" style="background: pink">
```

(continues on next page)

(continued from previous page)

```

<div class="panel-body">
  <!-- button to generate model form -->
  <a href="#myModal" data-toggle="modal" class="btn btn-xs btn-success">Form in Modal
</a>

  <!-- model form settings -->

  <div aria-hidden="true" aria-labelledby="myModalLabel" role="dialog" tabindex="-1" id="myModal"
→class="modal fade">
    <div class="modal-dialog">
      <div class="modal-content">
        <div class="modal-header">
          <button aria-hidden="true" data-dismiss="modal" class="close" type="button">&times;</
→button>
          <h4 class="modal-title">Form Tittle</h4>
        </div>
        <div class="modal-body">

          <!-- actual form -->
          <form role="form">
            <div class="form-group">
              <label for="exampleInputEmail1">Email address</label>
              <input class="form-control" id="exampleInputEmail3" placeholder="Enter email
→" type="email">

            </div>
            <div class="form-group">
              <label for="exampleInputPassword1">Password</label>
              <input class="form-control" id="exampleInputPassword3" placeholder="Password
→" type="password">

            </div>
            <div class="form-group">
              <label for="exampleInputFile">File input</label>
              <input id="exampleInputFile3" type="file">
              <p class="help-block">Example block-level help text here.</p>
            </div>
            <div class="checkbox">
              <label>
                <input type="checkbox"> Check me out
              </label>
            </div>
            <button type="submit" class="btn btn-default">Submit</button>
          </form>
          <!-- actual form ends -->

        </div>
      </div>
    </div>
  </div>
</div>
</div>
</div>
<hr>

```

### 3.4.5 Form elements

Output of below code is shown in Fig. 3.11,




Fig. 3.10: Modal form

```

<!-- Form elements -->
<h3> Form elements </h3>
<div class="row">
  <div class="col-sm-5" style="background: pink">
    <div class="panel-body">
      <form class="form-horizontal tasi-form" method="get">
        <div class="form-group">
          <label class="col-sm-2 col-sm-2 control-label">Default</label>
          <div class="col-sm-10">
            <input class="form-control" type="text">
          </div>
        </div>
        <div class="form-group">
          <label class="col-sm-2 col-sm-2 control-label">Help text</label>
          <div class="col-sm-10">
            <input class="form-control" type="text">
            <span class="help-block">A block of help text that breaks onto a new line and may
      ...extend beyond one line.</span>
          </div>
        </div>
        <div class="form-group">
          <label class="col-sm-2 col-sm-2 control-label">Rounder</label>
          <div class="col-sm-10">
            <input class="form-control round-input" type="text">
          </div>
        </div>
        <div class="form-group">
          <label class="col-sm-2 col-sm-2 control-label">Input focus</label>

```

(continues on next page)

(continued from previous page)

```

        <div class="col-sm-10">
            <input class="form-control" id="focusedInput" value="This is focused..." type="text">
        </div>
    </div>
    <div class="form-group">
        <label class="col-sm-2 col-sm-2 control-label">Disabled</label>
        <div class="col-sm-10">
            <input class="form-control" id="disabledInput" placeholder="Disabled input here..."
→disabled="disabled" type="text">
        </div>
    </div>
    <div class="form-group">
        <label class="col-sm-2 col-sm-2 control-label">Placeholder</label>
        <div class="col-sm-10">
            <input class="form-control" placeholder="placeholder" type="text">
        </div>
    </div>
    <div class="form-group">
        <label class="col-sm-2 col-sm-2 control-label">Password</label>
        <div class="col-sm-10">
            <input class="form-control" placeholder="" type="password">
        </div>
    </div>
    <div class="form-group">
        <label class="col-lg-2 col-sm-2 control-label">Static control</label>
        <div class="col-lg-10">
            <p class="form-control-static">email@example.com</p>
        </div>
    </div>
</form>
</div>
</div>
</div>

```

### 3.4.6 Control size

Output of below code is shown in [Fig. 3.12](#),

```

<!-- Control size -->
<h3>Control size</h3>
<div class="row">
<div class="col-sm-5" style="background: pink">
<div class="panel-body">
    <form class="form-horizontal tasi-form" method="get">
        <div class="form-group">
            <label class="col-sm-2 control-label col-lg-2" for="inputSuccess">Control sizing</label>
            <div class="col-lg-10">
                <input class="form-control input-lg m-bot15" placeholder=".input-lg" type="text">
                <input class="form-control m-bot15" placeholder="Default input" type="text">
                <input class="form-control input-sm m-bot15" placeholder=".input-sm" type="text">

                <select class="form-control input-lg m-bot15">
                    <option selected="selected">Option 1</option>
                    <option>Option 2</option>
                    <option>Option 3</option>
                </select>
                <select class="form-control m-bot15">
                    <option selected="selected">Option 1</option>
                    <option>Option 2</option>
                    <option>Option 3</option>
                </select>
            </div>
        </div>
    </form>
</div>
</div>

```

(continues on next page)

## Form elements

<b>Default</b>	<input type="text"/>
<b>Help text</b>	<input type="text"/> A block of help text that breaks onto a new line and may extend beyond one line.
<b>Rounder</b>	<input type="text"/>
<b>Input focus</b>	<input type="text" value="This is focused..."/>
<b>Disabled</b>	<input type="text" value="Disabled input here..."/>
<b>Placeholder</b>	<input type="text" value="placeholder"/>
<b>Password</b>	<input type="password"/>
<b>Static control</b>	email@example.com

Fig. 3.11: Form elements

(continued from previous page)

```

        <option>Option 3</option>
      </select>
      <select class="form-control input-sm m-bot15">
        <option selected="selected">Option 1</option>
        <option>Option 2</option>
        <option>Option 3</option>
      </select>
    </div>
  </div>
</form>
</div>
</div>
</div>

```

## Control size




Fig. 3.12: Form elements

### 3.4.7 More buttons

Output of below code is shown in [Fig. 3.13](#),

```

<h3>Buttons</h3>
<div class="row">
  <div class="col-sm-12" style="background: pink">
    <div class="panel-body">
      <form class="form-horizontal tasi-form" method="get">
        <div class="form-group">
          <label class="col-sm-2 control-label col-lg-2" for="inputSuccess">Checkboxes and
→radios</label>
          <div class="col-lg-10">
            <div class="checkbox">
              <label>
                <input value="" type="checkbox">
                  Option one is this and that—be sure to include why it's great
              </label>
            </div>
            <div class="checkbox">

```

(continues on next page)

(continued from previous page)

```

        <label>
            <input value="" type="checkbox">
            Option one is this and that—be sure to include why it's great option one
        </label>
    </div>

    <div class="radio">
        <label>
            <input name="optionsRadios" id="optionsRadios1" value="option1" checked=
→"checked" type="radio">
            Option one is this and that—be sure to include why it's great
        </label>
    </div>
    <div class="radio">
        <label>
→"radio">
            <input name="optionsRadios" id="optionsRadios2" value="option2" type=
→one
            Option two can be something else and selecting it will deselect option 1
        </label>
    </div>

    </div>
→label>
</div>
<div class="form-group">
    <label class="col-sm-2 control-label col-lg-2" for="inputSuccess">Inline checkboxes</
    <div class="col-lg-10">
        <label class="checkbox-inline">
            <input id="inlineCheckbox1" value="option1" type="checkbox"> 1
        </label>
        <label class="checkbox-inline">
            <input id="inlineCheckbox2" value="option2" type="checkbox"> 2
        </label>
        <label class="checkbox-inline">
            <input id="inlineCheckbox3" value="option3" type="checkbox"> 3
        </label>
    </div>
</div>
<div class="form-group">
    <label class="col-sm-2 control-label col-lg-2" for="inputSuccess">Selects</label>
    <div class="col-lg-10">
        <select id="select-dropdown-num" class="form-control m-bot15">
            <option selected="selected">1</option>
            <option>2</option>
            <option>3</option>
            <option>4</option>
            <option>5</option>
        </select>

        <select multiple="multiple" class="form-control">
            <option>1</option>
            <option>2</option>
            <option>3</option>
            <option>4</option>
            <option>5</option>
        </select>
    </div>
</div>

```

(continues on next page)

### 3.4. Components



(continued from previous page)

```

<div class="form-group">
  <label class="col-sm-2 control-label col-lg-2" for="inputSuccess">Column sizing</
→label>
  <div class="col-lg-10">
    <div class="row">
      <div class="col-lg-2">
        <input class="form-control" placeholder=".col-lg-2" type="text">
      </div>
      <div class="col-lg-3">
        <input class="form-control" placeholder=".col-lg-3" type="text">
      </div>
      <div class="col-lg-4">
        <input class="form-control" placeholder=".col-lg-4" type="text">
      </div>
    </div>
  </div>
</div>
</div>
</div>
</div>

```

## Buttons

The screenshot shows a pink background with the following elements:

- Checkboxes and radios:** Four options with labels. The third option is selected with a radio button.
- Inline checkboxes:** Three checkboxes labeled 1, 2, and 3. All are unchecked.
- Selects:** A dropdown menu showing '1' and a list box showing '1', '2', '3', and '4'.
- Column sizing:** Three text input fields with placeholders '.col-lg-2', '.col-lg-3', and '.col-lg-4'.

Fig. 3.13: Buttons

### 3.4.8 Input group

Output of below code is shown in Fig. 3.14,

```

<!-- Input groups -->
<h3>Input groups</h3>
<div class="row">
<div class="col-sm-12" style="background: pink">
<div class="panel-body">
  <form class="form-horizontal" method="get">
    <div class="form-group">
      <label class="col-sm-2 control-label col-lg-2">Basic examples</label>
      <div class="col-lg-10">
        <div class="input-group m-bot15">
          <span class="input-group-addon">@</span>
          <input class="form-control" placeholder="Username" type="text">
        </div>

```

(continues on next page)

```

        <div class="input-group m-bot15">
            <input class="form-control" type="text">
            <span class="input-group-addon">.00</span>
        </div>

        <div class="input-group m-bot15">
            <span class="input-group-addon">$</span>
            <input class="form-control" type="text">
            <span class="input-group-addon">.00</span>
        </div>
    </div>
</div>
<div class="form-group">
    <label class="col-sm-2 control-label col-lg-2">Sizing</label>
    <div class="col-lg-10">
        <div class="input-group input-group-lg m-bot15">
            <span class="input-group-addon">@</span>
            <input class="form-control input-lg" placeholder="Username" type="text">
        </div>

        <div class="input-group m-bot15">
            <span class="input-group-addon">@</span>
            <input class="form-control" placeholder="Username" type="text">
        </div>

        <div class="input-group input-group-sm m-bot15">
            <span class="input-group-addon">@</span>
            <input class="form-control" placeholder="Username" type="text">
        </div>
    </div>
</div>
<div class="form-group">
    <label class="col-sm-2 control-label col-lg-2">Checkboxes and radio</label>
    <div class="col-lg-10">
        <div class="input-group m-bot15">
            <span class="input-group-addon">
                <input type="checkbox">
            </span>
            <input class="form-control" type="text">
        </div>

        <div class="input-group m-bot15">
            <span class="input-group-addon">
                <input type="radio">
            </span>
            <input class="form-control" type="text">
        </div>
    </div>
</div>
<div class="form-group">
    <label class="col-sm-2 control-label col-lg-2">Button addons</label>
    <div class="col-lg-10">
        <div class="input-group m-bot15">
            <span class="input-group-btn">
                <button class="btn btn-white" type="button">Go!</button>
            </span>
            <input class="form-control" type="text">
        </div>
    </div>

```

(continues on next page)

```

<div class="input-group m-bot15">
  <input class="form-control" type="text">
  <span class="input-group-btn">
    <button class="btn btn-white" type="button">Go!</button>
  </span>
</div>

  <div class="input-group m-bot15">
    <div class="input-group-btn">
      <button type="button" class="btn btn-white dropdown-toggle" data-toggle="dropdown"
->">Action <span class="caret"></span></button>
      <ul class="dropdown-menu">
        <li><a href="#">Action</a></li>
        <li><a href="#">Another action</a></li>
        <li><a href="#">Something else here</a></li>
        <li class="divider"></li>
        <li><a href="#">Separated link</a></li>
      </ul>
    </div>
    <input class="form-control" type="text">
  </div>
  <div class="input-group m-bot15">
    <input class="form-control" type="text">
    <div class="input-group-btn">
      <button type="button" class="btn btn-white dropdown-toggle" data-toggle="dropdown"
->">Action <span class="caret"></span></button>
      <ul class="dropdown-menu pull-right">
        <li><a href="#">Action</a></li>
        <li><a href="#">Another action</a></li>
        <li><a href="#">Something else here</a></li>
        <li class="divider"></li>
        <li><a href="#">Separated link</a></li>
      </ul>
    </div>
  </div>
</div>
</div>

<div class="form-group">
  <label class="col-sm-2 control-label col-lg-2">Segmented buttons</label>
  <div class="col-lg-10">
    <div class="input-group m-bot15">
      <div class="input-group-btn">
        <button tabIndex="-1" class="btn btn-white" type="button">Action</button>
        <button tabIndex="-1" data-toggle="dropdown" class="btn btn-white dropdown-toggle"
->" type="button">
          <span class="caret"></span>
        </button>
        <ul role="menu" class="dropdown-menu">
          <li><a href="#">Action</a></li>
          <li><a href="#">Another action</a></li>
          <li><a href="#">Something else here</a></li>
          <li class="divider"></li>
          <li><a href="#">Separated link</a></li>
        </ul>
      </div>
      <input class="form-control" type="text">
    </div>
  </div>

```

(continued from previous page)

```

<div class="input-group m-bot15">
  <input class="form-control" type="text">
  <div class="input-group-btn">
    <button tabindex="-1" class="btn btn-white" type="button">Action</button>
    <button tabindex="-1" data-toggle="dropdown" class="btn btn-white dropdown-toggle
→" type="button">
      <span class="caret"></span>
    </button>
    <ul role="menu" class="dropdown-menu pull-right">
      <li><a href="#">Action</a></li>
      <li><a href="#">Another action</a></li>
      <li><a href="#">Something else here</a></li>
      <li class="divider"></li>
      <li><a href="#">Separated link</a></li>
    </ul>
  </div>
</div>
</div>
</div>
</form>
</div>
</div>

```

### Input groups

Fig. 3.14: Input groups

### 3.4.9 Navigation bar (navbar)

For navbar, one more 'css' file is added at Line 8. This CSS will create the space at the top for the 'navbar' so that it will not overlap with the contents of the HTML page. Further, Lines 13-44 adds various links to the navbar. Lastly, we can add HTML content below Line 46.

Output of below code is shown in Fig. 3.15,

```

1 <!DOCTYPE html>
2 <html>
3 <head>

```

(continues on next page)

## 3.4. Components

(continued from previous page)

```

4      <title>Bootstrap Tutorial</title>
5      <!-- CSS -->
6      <link href="asset/css/bootstrap.min.css" rel="stylesheet">
7      <!-- Add Custom CSS below -->
8      <link href="asset/css/theme.css" rel="stylesheet"> <!-- make space at the top for nav-bar -->
9  </head>
10
11  <body>
12
13      <div class="navbar navbar-inverse navbar-fixed-top">
14          <div class="container">
15              <div class="navbar-header">
16                  <button type="button" class="navbar-toggle" data-toggle="collapse" data-target=".navbar-
17  → collapse">
18                      <span class="icon-bar"></span>
19                      <span class="icon-bar"></span>
20                      <span class="icon-bar"></span>
21                  </button>
22                  <a class="navbar-brand hidden-sm" href="http://pythondsp.readthedocs.io/">PythonDSP</a>
23              </div>
24              <div class="row">
25                  <div class="navbar-collapse collapse">
26                      <ul class="nav navbar-nav">
27
28                          <li><a href="basic.html">HTML</a></li>
29                          <li><a href="css.html">CSS</a></li>
30
31
32
33                          <li class="dropdown">
34                              <a href="#" class="dropdown-toggle" data-toggle="dropdown">More<b class="caret"></b></a>
35                              <ul class="dropdown-menu">
36                                  <li><a href="bootstrap.html">Bootstrap</a></li>
37                                  <li><a href="js.html">Javascript</a></li>
38                                  <li><a href="jquery.html">jQuery</a></li>
39                              </ul>
40                          </li>
41
42                      </ul>
43                  </div>
44              </div>
45          </div><!-- /.nav - collapse -->
46      </div>
47
48      <!-- Javascript -->
49      <!-- put jQuery.js before bootstrap.min.js; and then add custom jquery -->
50      <script src="asset/js/jquery-3.3.1.min.js"></script>
51      <script src="asset/js/bootstrap.min.js"></script>
52  </body>
53  </html>

```




Fig. 3.15: Navigation bar (navbar)

## Section 3

# JavaScript

### 4.1 Introduction

- JavaScript is a dynamic language which is used for designing the web pages on the client side.
- It is case sensitive language.
- It is untyped language i.e. a variable can hold any type of value.
- // is used for comments.
- ; i used for line termination.
- JavaScript code should be added at the end i.e. **just above the closing-body-tag**.
- It is better to write the JavaScript code in separate file as shown in next section.

### 4.2 First code

The JavaScript code can be written in the 'html' file or in the separate 'JavaScript file (.js)' as shown in this section,

#### 4.2.1 JavaScript in HTML file

In HTML file, the JavaScript codes can be written inside the 'script' tag as shown in Lines 11-13 of below code. The code will write the message "Hello World from JavaScript!" on the web page. Open the 'js.html' in the browser to see the message.

```
1 <!-- js.html -->
2
3 <!DOCTYPE html>
4 <html>
5 <head>
6   <title>JavaScript</title>
7 </head>
8 <body>
9
10
11   <script type="text/javascript">
12     document.write("Hello World from JavaScript!<br>");
13   </script>
14
15 </body>
16 </html>
```

- Below is the output on the HTML page,
-

```
Hello World from JavaScript!
```

#### 4.2.1.1 JavaScript in separate file

- The JavaScript code is saved in the file 'my\_javascript.js' which is located inside the folders 'asset/js'. Note that, no 'script tag' is used here.

```
1 // asset/js/my_javascript.js
2
3 document.write("Hello World from JavaScript!<br>");
```

- Next we need to import the .js file in the HTML file as shown below,

```
1 <!-- js.html -->
2
3 <!DOCTYPE html>
4 <html>
5 <head>
6   <title>JavaScript</title>
7 </head>
8 <body>
9
10
11
12   <!-- import JavaScript files here -->
13   <script src="asset/js/my_javascript.js"></script>
14
15 </body>
16 </html>
```

- Now, open the 'js.html' file in the browser and it will display the message.

---

**Note:** We will use the second method in this tutorial.

---

## 4.3 Keywords, Datatypes, Variables and Operators

### 4.3.1 Keywords

- Below are the reserved keywords in the JavaScript which can not be used as 'variable' and 'function' names etc.



Table 4.1: List of keywords

Keywords			
abstract	boolean	break	byte
case	catch	char	class
const	continue	debugger	default
delete	do	double	else
enum	export	extends	false
final	float	for	function
goto	if	implements	import
in	int	interface	long
native	new	null	package
private	protected	public	return
short	static	super	switch
this	throw	throws	transient
true	try	typeof	var
void	volatile	while	with

### 4.3.2 Datatypes

JavaScript has three types of data,

- **Numbers** : 123, 32.32
- **Strings** : "Meher", "Krishna Patel", "123"
- **Boolean** : true, false

---

**Note:** All the numbers are considered as 'floating point'.

---

### 4.3.3 Variables

Variables can be define using keyword 'var'. Further, JavaScript is untyped language i.e. a variable can hold anytype of value.

- In the below HTML, 'p' tag with id 'p\_name' is defined at Line 10. This id will be used to write some text using JavaScript,

```

1 <!-- js.html -->
2
3 <!DOCTYPE html>
4 <html>
5 <head>
6   <title>JavaScript</title>
7 </head>
8 <body>
9
10  <p id='p_name'></p>
11
12  <!-- import JavaScript files here -->
13  <script src="asset/js/my_javascript.js"></script>
14
15
16 </body>
</html>
```

- Two **variables** are defined at Lines 9-10 of type 'string' and 'float' respectively. Then '**getElementByld**' is used to locate the tag with id 'p\_name' and the text is inserted as shown in Line 11. Lastly, the '+' signis used to concatenate the values as Line 11.

```

1 // asset/js/my_javascript
2
3
4 // print message on the webpage
5 document.write("Hello World from JavaScript!<br>");
6
7
8 // variable example
9 var your_name = "Rohit";
10 var age = 20;
11 document.getElementById("p_name").innerHTML= "Hello " + your_name + "<br>Age : " + age;

```

- Below is the output of above codes. Note that the message 'Hello World from JavaScript!' is added at the end as 'JavaScript' file is imported at the end.

**Warning:** If we import the 'JavaScript' file between the 'ending-head-tag' and 'start-body-tag', then Message 'Hello Rohit...' will not be displayed as 'JavaScript' will execute before the loading of the page; and JavaScript can not find the id 'p\_name'.

Hello Rohit  
Age : 20

Hello World from JavaScript!

**Note:** All the JavaScript/HTML codes will be added below the existing codes, therefore only the newly added code will be shown in the rest of the tutorial.

- 'prompt' can be used to read the values from the user.

```

// prompt
var x = prompt("enter a number");
document.write("2 * ", x, " = ", 2*x + "<br>");

```

A pop-up window will appear due to prompt. If we provide the input value as 3, then below output will be generated,

2 \* 3 = 6

**Note:** The ',' and '+' can be used to combine various outputs as shown in above example

### 4.3.4 Operators

Various operators are shown in this section. The usage of some of these operators are shown in [Section 4.4](#).

#### 4.3.4.1 Arithmetic operators

- +
- 
- \*
- /
- % : modulus i.e remainder of the division
- ++ (increment)
- (decrement)

#### 4.3.4.2 Assignment operators

- =
- +=
- -=
- \*=
- /=
- %=

#### 4.3.4.3 Comparison operators

- == (compare only values not type)
- === (compare both values and type)
- !=
- >
- <
- >=
- <=

#### 4.3.4.4 Conditional operator

- ?:

e.g. `'( a > b ) ? a/b : b/a )'` i.e if `'a>b'` then do `'a/b'` else do `'b/a'`

#### 4.3.4.5 Logical operators

- && (logical and)
- || (logical or)
- ! (logical not)

#### 4.3.4.6 Bitwise operators

- & (and)
- | (or)
- ^ (xor)
- ~ (not)

### 4.3.5 String to number conversion

'Number' is used to convert the string into numbers.

```
// string to number conversion
document.write("2 + Number('3.4') = ", 2 + Number('3.4'), "<br>");
```

Below is the output of above code,

```
2 + Number('3.4') = 5.4
```

### 4.3.6 Convert to integer

A string or float value can be converted into integer using 'parseInt'

```
// int conversion
document.write("2 + parseInt('3.4') = ", 2 + parseInt('3.4'), "<br>"); // string to int
document.write("2 + parseInt(3.4) = ", 2 + parseInt(3.4), "<br>"); // float to int
```

Below are the outputs of above code,

```
2 + parseInt('3.4') = 5
2 + parseInt(3.4) = 5
```

### 4.3.7 Convert to float

The 'parseFloat' or 'Number' can be used to convert the value into float values.

```
document.write("2 + parseFloat('3.4') = ", 2 + parseFloat("3.4"), "<br>"); // parseFloat
```

### 4.3.8 Math

'Math' library contains various useful function as shown below,

```
// math
document.write("pi = ", Math.PI, "<br>");
document.write("e = ", Math.E, "<br>");
document.write("similarly we can use 'abs', 'floor', 'ceil' and 'round' etc. <br>")
document.write("random number : ", Math.ceil(Math.random()*20), "<br>"); // enter random number
```

Below are the outputs of above code,

```
pi = 3.141592653589793
e = 2.718281828459045
similarly we can use 'abs', 'floor', 'ceil' and 'round' etc.
random number : 16
```

### 4.3.9 String

Below are the some of the useful 'string-styles',

```
// string
document.write("meher".toUpperCase(), "<br>") // uppercase

w = "Krishna"
document.write(w.toLowerCase(), "<br>") // lowercase
document.write(w.small(), "<br>") // small
document.write(w.bold(), "<br>") // bold
document.write(w.strike(), "<br>") // strike
document.write(w.fontSize("5em"), "<br>") // strike
document.write(w.link("http://pythondsp.readthedocs.io"), "<br>") // link
document.write(w.fontcolor("red").fontSize("12em"), "<br>") // multiple
```

The outputs are shown in [Fig. 4.1](#)

### 4.3.10 Arrays

In JavaScript, the arrays can store different types of values as shown in below code,

MEHER  
 krishna  
 Krishna  
**Krishna**  
~~Krishna~~  
 Krishna  
Krishna  
 Krishna

Fig. 4.1: String styles

```
// arrays
arr = [15, 30, "Meher"]
for(a in arr)
  document.write(arr[a], " ");
document.write("<br>");

document.write(arr.pop(), "<br>"); //remove last
element arr.push("Krishna"); // add element to end
document.write(arr.pop(), "<br>");
document.write("lenght of array: ", arr.length, "<br>");
```

Below are the output of above code,

```
15 30 Meher
Meher
Krishna
lenght of array: 2
```

## 4.4 Control structure, loops and functions

### 4.4.1 If-else

In the below code, three conditions are checked for the variable 'age'; and corresponding message is printed.

```
// asset/js/my_javascript

// if-else
age = 10;
if (age > 3 && age < 6){
  document.write("Age : " + age + "<b> go to kindergarten</b>");
}
else if ( age >=6 && age < 18){
  document.write("Age : " + age + "<b> go to school</b>");
}
else{
  document.write("Age : " + age + "<h> go to college</h>");
```

(continues on next page)

(continued from previous page)

```
}  
document.write("<br>");
```

- Since age is 10, therefore 'else if' statement is satisfied and we will get below output,

Age : 10 go to school

#### 4.4.2 Switch-case-default

Below is an example of Switch-case-default statement,

```
// asset/js/my_javascript  
  
// switch-case  
var grade = 'A';  
document.write("Grade " + grade + " : ");  
switch(grade){  
    case 'A':  
        document.write("Very good grade!");  
        break;  
    case 'B':  
        document.write("Good grade!");  
        break;  
    default: // if grade is neither 'A ' nor 'B '  
        document.write("Enter correct grade");  
}  
document.write("<br>");
```

- Below is the output of above code,

Grade A : Very good grade!

#### 4.4.3 For loop

Below code prints the value from 5-0,

```
// For loop  
for (i=5; i>=0; i--){  
    document.write(i + " ");  
}  
document.write("<br>");
```

- Below is the output,

5 4 3 2 1 0

#### 4.4.4 While loop

Below code prints the value from 0-4,

```
// While loop  
x=0;  
while(x < 5){  
    document.write(x + " ");  
    x++;  
}  
document.write("<br>");
```

#### 4.4.5 do-while

Below code prints the value from 0-2,

```
// do-while
x=0;
do{
    document.write(x + " ");
    x++;
}while(x < 3);
document.write("<br>");
```

Below is the output,

0 1 2

#### 4.4.6 for-in loop

The 'for-in' loop can be used to iterate over the array as shown below,

```
// for-in loop
arr = [10, 12, 31]; // array
for (a in arr){
    document.write(arr[a] + " ");
}
document.write("<br>");
```

#### 4.4.7 Continue and break

Continue and break statements are used inside the 'loop' statements.

- Continue will skip the loop and go to next iteration, if the condition is met. In the below code, 3 will not be printed at the output.

```
// continue
for (i=5; i>=0; i--){
    if (i==3){ // skip 3
        continue;
    }
    document.write(i + " ");
}
document.write("<br>");
```

Below is the output where 3 is not printed in the output.

5 4 2 1 0

- 'Break' statement will quit the loop if the condition is met. In the below code, the for loop will be terminated at 'i=3', therefore only 5 and 4 will be printed,

```
// break
for (i=5; i>=0; i--){
    if (i==3){ // exit loop when i=3
        break;
    }
    document.write(i + " ");
}
document.write("<br>");
```

Below is the output of the above code,

5 4

### 4.4.8 Functions

In the below code a function 'add2Num' is defined which adds the two numbers and returns the result.

```
// function
function add2Num(num1, num2){ // function definition
    return num1 + num2;
}
sum = add2Num(2, 3); // function
call document.write("2 + 3 = " +
sum); document.write("<br>");
```

Below is the output,

2 + 3 = 5

## 4.5 Event handling

One of the main usage of JavaScript is 'event handling'. "Mouse click" and 'pressing keys on keyboard' are the example of 'events'. With the help of JavaScript, we can perform certain actions at the occurrence of the events, as shown below.

- 'alert' is used to display message in the 'pop up' window.

```
function alertMessage(message){
    alert(message)
}
```

- In Line 13, message 'Hello' is shown in the pop-up window on the event 'onclick'. Note that "JavaScript:void(0)" is used here, which **does not** refresh the page.
- Line 15 is same as Line 13, but "JavaScript:void(0)" is not used, therefore page will be **refreshed**.
- Line 17 calls the function 'alertMessage' to display the message, which is defined in the above code.
- Lines 19-25 use different events i.e. 'onmouseover', 'onmouseleave', 'onmouseup' and 'onmousedown'; and the color and the text of the string changes based on these operations.

```
<!-- js.html -->
<!DOCTYPE html>
<html>
<head>
    <title>JavaScript</title>
</head>
<body>
    <p id="p_name"></p>

    <a href="JavaScript:void(0)", onclick="alert("Hello")">Say Hello</a><br> <!-- do not re    the page.
    <!-->

    <a href="", onclick="alert("Hello")">Say Bye</a><br> <!-- reload the page -->

    <a href="JavaScript:void(0)", onclick="alertMessage("Bye via function")">Bye-function</a><br>

    <a href="JavaScript:void(0)",
```

### 4.5. Event handling



(continued from previous page)

```
onmouseover="this.style.color='red'",
onmouseleave="this.style.color='blue'",
onmouseup="this.text='Not clicked'",
onmousedown="this.text='You clicked me'">
  Not clicked
</a><br>
```

```
<!-- import      files here -->
<script
```

```
</body>
</html>
```

---

## Project 1: Digital Clock

```
<!doctype html>
<html lang="en">

<head>
  <!-- Required meta tags -->
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1, shrink-to-fit=no">

  <!-- Bootstrap CSS -->
  <link rel="stylesheet"
    href="https://stackpath.bootstrapcdn.com/bootstrap/4.5.0/css/bootstrap.min.css"
    integrity="sha384-
    9aIt2nRpC12Uk9gS9baDl411NQApFmC26EwAOH8WgZl5MYXxPfc+NcPb1dKGj7Sk"
    crossorigin="anonymous">

  <title>Hello, world!</title>
  <script>
    let a;
    let date;
    let time;
    const options = { weekday: 'long', year: 'numeric', month: 'long', day: 'numeric' };
    setInterval(() => {
      a = new Date();
      date = a.toLocaleDateString(undefined, options);
      time = a.getHours() + ':' + a.getMinutes() + ':' + a.getSeconds();
      document.getElementById('time').innerHTML = time + "<br>on " + date;
    }, 1000);
  </script>
</head>

<body>
  <nav class="navbar navbar-expand-lg navbar-light bg-light">
    <a class="navbar-brand" href="#">Navbar</a>
    <button class="navbar-toggler" type="button" data-toggle="collapse" data-
    target="#navbarSupportedContent"
      aria-controls="navbarSupportedContent" aria-expanded="false" aria-label="Toggle navigation">
      <span class="navbar-toggler-icon"></span>
    </button>

    <div class="collapse navbar-collapse" id="navbarSupportedContent">
      <ul class="navbar-nav mr-auto">
        <li class="nav-item active">
          <a class="nav-link" href="#">Home <span class="sr-only">(current)</span></a>
        </li>
        <li class="nav-item">
          <a class="nav-link" href="#">Link</a>
        </li>
        <li class="nav-item dropdown">
          <a class="nav-link dropdown-toggle" href="#" id="navbarDropdown" role="button"
            data-toggle="dropdown" aria-haspopup="true" aria-expanded="false">
            Dropdown
          </a>
          <div class="dropdown-menu" aria-labelledby="navbarDropdown">
            <a class="dropdown-item" href="#">Action</a>
            <a class="dropdown-item" href="#">Another action</a>
            <div class="dropdown-divider"></div>
            <a class="dropdown-item" href="#">Something else here</a>
          </div>
        </li>
      </ul>
    </div>
  </nav>
```

```
</li>
<li class="nav-item">
  <a class="nav-link disabled" href="#" tabindex="-1" aria-disabled="true">Disabled</a>
</li>
</ul>
<form class="form-inline my-2 my-lg-0">
  <input class="form-control mr-sm-2" type="search" placeholder="Search" aria-label="Search">
  <button class="btn btn-outline-success my-2 my-sm-0" type="submit">Search</button>
</form>
</div>
</nav>
<div class="container my-4">
  <div class="jumbotron">
    <h1 class="display-4">Current time Is: <span id="time"></span></h1>
    <p class="lead">We have got you covered. This is a simple hero unit, a simple jumbotron-style
    component for
    calling extra attention to featured content or information.</p>
    <hr class="my-4">
    <p>We are here to show you the time for different countries</p>
    <a class="btn btn-primary btn-lg" href="#" role="button">Browse Times</a>
  </div>
</div>

<!-- Optional JavaScript -->
<!-- jQuery first, then Popper.js, then Bootstrap JS -->
<script src="https://code.jquery.com/jquery-3.5.1.slim.min.js"
  integrity="sha384-
  DfXdz2htPHolsSSs5nCTpuj/zy4C+OGpamoFVy38MVBnE+IbbVYUew+OrCXaRkfj"
  crossorigin="anonymous"></script>
<script src="https://cdn.jsdelivr.net/npm/popper.js@1.16.0/dist/umd/popper.min.js"
  integrity="sha384-
  Q6E9RHvbIyZFJoft+2mJbHaEWldlvI9IOYy5n3zV9zzTtmI3UksdQRVvoxMfooAo"
  crossorigin="anonymous"></script>
<script src="https://stackpath.bootstrapcdn.com/bootstrap/4.5.0/js/bootstrap.min.js"
  integrity="sha384-
  OgVRvuATP1z7JjHLkuOU7Xw704+h835Lr+6QL9UvYjZE3Ipu6Tp75j7Bh/kRoJkI"
  crossorigin="anonymous"></script>
</body>
</html>
```

## Project 2: TODO list

```
<!doctype html>
<html lang="en">

<head>
  <!-- Required meta tags -->
  <meta charset="utf-8">
  <meta name="viewport" content="width=device-width, initial-scale=1, shrink-to-fit=no">

  <!-- Bootstrap CSS -->
  <link rel="stylesheet" href="https://stackpath.bootstrapcdn.com/bootstrap/4.5.0/css/bootstrap.min.css"
    integrity="sha384-9aIt2nRpC12Uk9gS9baDl411NQApFmC26EwAOH8WgZl5MYYYxFfc+NcPb1dKGj7Sk"
    crossorigin="anonymous">

  <title>TODOs List</title>
</head>

<body>
  <nav class="navbar navbar-expand-lg navbar-dark bg-dark">
    <a class="navbar-brand" href="#">TODOs List</a>
    <button class="navbar-toggler" type="button" data-toggle="collapse" data-
      target="#navbarSupportedContent"
      aria-controls="navbarSupportedContent" aria-expanded="false" aria-label="Toggle navigation">
      <span class="navbar-toggler-icon"></span>
    </button>

    <div class="collapse navbar-collapse" id="navbarSupportedContent">
      <ul class="navbar-nav mr-auto">
        <li class="nav-item active">
          <a class="nav-link" href="#">Home <span class="sr-only">(current)</span></a>
        </li>
        <li class="nav-item">
          <a class="nav-link" href="#">About</a>
        </li>
        <li class="nav-item dropdown">
          <a class="nav-link dropdown-toggle" href="#" id="navbarDropdown" role="button"
            data-toggle="dropdown" aria-haspopup="true" aria-expanded="false">
            Items
          </a>
          <div class="dropdown-menu" aria-labelledby="navbarDropdown">
            <a class="dropdown-item" href="#">Action</a>
            <a class="dropdown-item" href="#">Another action</a>
            <div class="dropdown-divider"></div>
            <a class="dropdown-item" href="#">Something else here</a>
          </div>
        </li>
        <li class="nav-item">
          <a class="nav-link" href="#" tabindex="-1" aria-disabled="true">Contact</a>
        </li>
      </ul>
      <form class="form-inline my-2 my-lg-0">
        <input class="form-control mr-sm-2" type="search" placeholder="Search" aria-label="Search">
        <button class="btn btn-outline-success my-2 my-sm-0" type="submit">Search</button>
      </form>
    </div>
  </nav>

  <div class="container my-4">
    <h2 class="text-center">TODOs List</h2>
```

---

```
<div class="form-group">
  <label for="title">Title</label>
  <input type="text" class="form-control" id="title" aria-describedby="emailHelp">
  <small id="emailHelp" class="form-text text-muted">Add an item to the list</small>
</div>

<div class="form-group">
  <label for="description">Description</label>
  <textarea class="form-control" id="description" rows="3"></textarea>
</div>

<button id="add" class="btn btn-primary">Add to list</button>
<button id="clear" class="btn btn-primary" onclick="clearStorage()">Clear list</button>

<div id="items" class="my-4">
  <h2>Your Items</h2>
  <table class="table">
    <thead>
      <tr>
        <th scope="col">SNo</th>
        <th scope="col">Item Title</th>
        <th scope="col">Item Description</th>
        <th scope="col">Actions</th>
      </tr>
    </thead>
    <tbody id="tableBody">
      <tr>
        <th scope="row">1</th>
        <td>Get some Coffee</td>
        <td>You need coffee as you are a coder</td>
        <td><button class="btn btn-sm btn-primary">Delete</button></td>
      </tr>
    </tbody>
  </table>
</div>
</div>

<!-- Optional JavaScript -->
<!-- jQuery first, then Popper.js, then Bootstrap JS -->
<script src="https://code.jquery.com/jquery-3.5.1.slim.min.js"
  integrity="sha384-DfXdz2htPHolsSSs5nCTpuj/zy4C+OGpamoFVy38MVBnE+IbbVYUew+OrCXaRkfj"
  crossorigin="anonymous"></script>
<script src="https://cdn.jsdelivr.net/npm/popper.js@1.16.0/dist/umd/popper.min.js"
  integrity="sha384-Q6E9RHvbIyZFJoft+2mJbHaEWldlvI9IOYy5n3zV9zzTtmI3UksdQRVvoxMfooAo"
  crossorigin="anonymous"></script>
<script src="https://stackpath.bootstrapcdn.com/bootstrap/4.5.0/js/bootstrap.min.js"
  integrity="sha384-OgVRvuATP1z7JjHLkuOU7Xw704+h835Lr+6QL9UvYjZE3Ipu6Tp75j7Bh/kR0JkI"
  crossorigin="anonymous"></script>
<script>
  function getAndUpdate(){
    console.log("Updating List...");
    tit = document.getElementById('title').value;
    desc = document.getElementById('description').value;
    if (localStorage.getItem('itemsJson')==null){
      itemJsonArray = [];
      itemJsonArray.push([tit, desc]);
      localStorage.setItem('itemsJson', JSON.stringify(itemJsonArray))
    }
  }
</script>
```

---

```
    else{
        itemJsonArrayStr = localStorage.getItem('itemsJson')
        itemJsonArray = JSON.parse(itemJsonArrayStr);
        itemJsonArray.push([tit, desc]);
        localStorage.setItem('itemsJson', JSON.stringify(itemJsonArray))
    }
    update();
}

function update(){
    if (localStorage.getItem('itemsJson')==null){
        itemJsonArray = [];
        localStorage.setItem('itemsJson', JSON.stringify(itemJsonArray))
    }
    else{
        itemJsonArrayStr = localStorage.getItem('itemsJson')
        itemJsonArray = JSON.parse(itemJsonArrayStr);
    }
    // Populate the table
    let tableBody = document.getElementById("tableBody");
    let str = "";
    itemJsonArray.forEach((element, index)=>{
        str += `
        <tr>
        <th scope="row">${index + 1}</th>
        <td>${element[0]}</td>
        <td>${element[1]}</td>
        <td><button class="btn btn-sm btn-primary" onclick="deleted(${index})">Delete</button></td>
        </tr>`;
    });
    tableBody.innerHTML = str;
}
add = document.getElementById("add");
add.addEventListener("click", getAndUpdate);
update();
function deleted(itemIndex){
    console.log("Delete", itemIndex);
    itemJsonArrayStr = localStorage.getItem('itemsJson')
    itemJsonArray = JSON.parse(itemJsonArrayStr);
    // Delete itemIndex element from the array
    itemJsonArray.splice(itemIndex, 1);
    localStorage.setItem('itemsJson', JSON.stringify(itemJsonArray));
    update();
}

function clearStorage(){
    if (confirm("Do you areally want to clear?")){
        console.log('Clearing the storage')
        localStorage.clear();
        update()
    }
}
</script>
</body>
</html>
```

---