4. TRAIN RESERVATION SYSTEM:

```
<!DOCTYPE html>
<html>
<head>
<title>Train Reservation System</title>
<style>
body{font-family:Arial;background:#eee;text-align:center}
header{background:#234;color:white;padding:20px}
button,input,select{padding:10px;margin:5px}
.train{background:white;margin:15px;padding:15px}
</style>
</head>
<body>

<header>
<h1>🚆 Train Reservation System</h1>
<button onclick="home()">Home</button>
<button onclick="search()">Search Train</button>
<button onclick="login()">Login</button>
<button onclick="register()">Register</button>
<button onclick="pnr()">Check PNR</button>
<button onclick="admin()">Admin</button>
</header>

<div id="app">
<h2>Welcome to Railway Reservation</h2>
<p>Search trains and reserve your tickets online.</p>
</div>

<script>
function home(){
app.innerHTML="<h2>Welcome</h2><p>Book your train tickets easily.</p>";
}
```

```
function search(){
app.innerHTML=`
<h2>Search Train</h2>
<input placeholder="Origin Station">
<input placeholder="Destination Station">
<input type="date">
<select><option>AC</option><option>Sleeper</option><option>General</option></select>
<button onclick="alert('Train Found')">Search</button>
<div class="train"><h3>Express Train</h3>
<p>Available Seats: 25</p><p>Fare: $50</p>
<button onclick="book()">Book Ticket</button></div>`;
}

function book(){
alert("Ticket Booked! PNR: TR123456");
}

function login(){
app.innerHTML=`
<h2>Passenger Login</h2>
<input placeholder="Username">
<input type="password" placeholder="Password">
<button onclick="alert('Login Successful')">Login</button>`;
}

function register(){
app.innerHTML=`
<h2>Passenger Registration</h2>
<input placeholder="Name"><input placeholder="Email">
<input placeholder="Password">
<button onclick="alert('Registration Successful')">Register</button>`;
}

function pnr(){
```

```
app.innerHTML=`
<h2>Check PNR Status</h2>
<input placeholder="Enter PNR Number">
<button onclick="alert('Status: Confirmed')">Check Status</button>
<p>PNR Status: Confirmed / RAC / Waiting List</p>`;
}

function admin(){
app.innerHTML=`
<h2>Admin Panel</h2>
<input placeholder="Train Name">
<input placeholder="Train Number">
<input placeholder="Available Seats">
<button onclick="alert('Train Details Updated')">Update Train</button>
<button onclick="alert('Refund Processed')">Process Refund</button>
<p>Admin manages trains, fares, users, PNR and payments.</p>`;
}
</script>
</body>
</html>
```

