5. FLIGHT RESERVATION SYSTEM

```
<!DOCTYPE html>
<html>
<head>
<title>Flight Reservation System</title>
<style>
body{font-family:Arial;background:#eee;text-align:center}
header{background:#234;color:white;padding:20px}
button,input,select{padding:10px;margin:5px}
.flight{background:white;margin:15px;padding:15px}
</style>
</head>
<body>

<header>
<h1>✈️ Flight Reservation System</h1>
<button onclick="home()">Home</button>
<button onclick="search()">Search Flight</button>
<button onclick="login()">Login</button>
<button onclick="bookings()">My Ticket</button>
<button onclick="status()">Booking Status</button>
<button onclick="admin()">Admin</button>
</header>

<div id="app">
<h2>Welcome to Flight Reservation</h2>
<p>Search and book your flight tickets online.</p>
</div>

<script>
function home(){
app.innerHTML="<h2>Welcome</h2><p>Book your flight easily and securely.</p>";
}
```

```
function search(){
app.innerHTML=`
<h2>Search Flight</h2>
<input placeholder="Destination">
<input type="date">
<select><option>Economy</option><option>Business</option></select>
<button onclick="alert('Flight Found')">Search</button>
<div class="flight"><h3>Air India</h3>
<p>Chennai to Delhi</p><p>Seats Available: 20</p>
<p>Fare: $150</p>
<button onclick="book()">Book Ticket</button></div>`;
}

function book(){
alert("Ticket Booked Successfully!");
}

function login(){
app.innerHTML=`
<h2>Customer Login</h2>
<input placeholder="Email">
<input type="password" placeholder="Password">
<button onclick="alert('Login Successful')">Login</button>
<p>Forgot Password?</p>`;
}

function bookings(){
app.innerHTML=`
<h2>My Ticket</h2>
<p>Flight: Air India</p><p>Status: Confirmed</p>
<button onclick="alert('Ticket Printed')">Print Ticket</button>
<button onclick="alert('Ticket Cancelled')">Cancel Ticket</button>`;
}
```

```
function status(){
app.innerHTML=`
<h2>Booking Status</h2>
<input placeholder="Booking ID">
<button onclick="alert('Status: Confirmed')">Check Status</button>`;
}

function admin(){
app.innerHTML=`
<h2>Admin Panel</h2>
<input placeholder="Flight Name">
<input placeholder="Available Seats">
<input placeholder="Flight Fare">
<button onclick="alert('Flight Updated')">Update Flight</button>
<button onclick="alert('Report Generated')">Admin Report</button>
<p>Admin manages flights, seats, users and bookings.</p>`;
}
</script>
</body>
</html>
```

OUTPUT:

