

Nearest Neighbors

Project: Responsible Plant Classifier

1. Your mission

Your learning target

I can compute absolute distances and rank training neighbours.

I can apply a declared neighbour count and distance tie rule.

I can evaluate neighbour predictions without using validation labels as neighbours.

Remember before reading

Close your notes first. A rough first answer helps us choose the right starting point; it is not a score for your ability.

Without opening the old lesson, explain one key idea from Decision Trees. Give an example and a mistake that the idea helps you avoid.

Without opening the old lesson, explain one key idea from Dataset Cards. Give an example and a mistake that the idea helps you avoid.

Without opening the old lesson, explain one key idea from Label Quality. Give an example and a mistake that the idea helps you avoid.

After trying, check the relevant lesson or ask your teacher. Change the part of your explanation that the evidence shows was wrong.

k-nearest neighbors predicts from nearby labeled examples under a chosen feature scale, distance rule, and value of k.



LEARNING TARGET Training lengths 2(H),6(S),10(H); query=8. Compute distances. Explain the tie and why combining length in mm with width in cm changes a two-feature distance.

Builder name and experiment date:

Readiness for the connected explanation

What does a fitted depth-one tree store, and what does it do with a new example?

This week's end goal

By the end, I can explain nearest neighbors using a traced example and a stated limitation.

2. Notice the evidence

PICTURE ENTRY

Notice → **Predict** → **Explain**

Begin with visible evidence; do not explain more than the picture and information support.



MYSTERY The team must use nearest neighbors to solve a model-building problem. What information do they have? What important evidence is still missing?

Name three visible details without interpreting them.

Predict the data, model, or evaluation decision being made.

Identify one hidden assumption that could change the result.

State what evidence would confirm or reject your prediction.

My prediction and supporting evidence:

A closer explanation

A nearest-neighbour classifier predicts using nearby training examples rather than following a fitted tree. This week we store labelled examples, measure how different their feature values are from a new query, and let selected neighbours vote. Nearby means close under our chosen feature and distance, not necessarily similar in every real-world way.

Our new fictional dataset has a distance reading in centimetres and a separately reviewed lane label. Each row comes from a distinct trip, and validation trips are separate. Only the numeric reading measures similarity. IDs identify rows and break distance ties; they are not numeric features. These invented readings are not a robot safety system.

ID · Reading in cm · Label

ID: A

Reading in cm: 2

Label: blocked

ID: B

Reading in cm: 4

Label: clear

ID: C

Reading in cm: 8

Label: clear

ID: D

Reading in cm: 10

Label: blocked

ID: E

Reading in cm: 12

Label: clear

For this one-dimensional feature, distance is $\text{abs}(\text{training reading} - \text{query reading})$. abs removes the sign. Set $k=3$ and give each selected neighbour one vote. Order equal distances by ID alphabetically, declared before scoring. In this binary, three-vote exercise the label vote cannot tie, but the distances can.

3. See how it works

ML MECHANISM

Input → **Model** → **Evidence**

Trace the information, fitted behavior, and evaluation proof separately.



IN

INPUT

Calculate distances and compare $k=1$ with $k=3$.



ML

MODEL

k-nearest neighbors predicts from nearby labeled examples under a chosen feature scale, distance rule, and value of k .

OUT

EVIDENCE

Calculate distances and compare $k=1$ with $k=3$.

QUESTION Calculate distances and compare $k=1$ with $k=3$.

MODEL IDEA k -nearest neighbors predicts from nearby labeled examples under a chosen feature scale, distance rule, and value of k .

PROOF NEEDED Use an unseen case, visible calculation, error analysis, and a stated limitation.

UNDER THE HOOD New leaf has normalized features (2, 3). Using Manhattan distance, add the absolute coordinate differences. Training leaves at (2, 2), (4, 3), and (1, 5) have distances 1, 2, and 3 from (2, 3).

Draw a fresh data → model → prediction → evaluation trace:

A closer explanation

```
train = [("A", 2, "blocked"), ("B", 4, "clear"),
         ("C", 8, "clear"), ("D", 10, "blocked"),
         ("E", 12, "clear")]

query = 3

ranked = sorted((abs(x - query), item_id, label)
                for item_id, x, label in train)

near = ranked[:3]

labels = [row[2] for row in near]

prediction = "clear"

if labels.count("blocked") > labels.count("clear"):
```

```
prediction = "blocked"

print([row[1] for row in near])

print(prediction)
```

For query 3, distances to A through E are 1,1,5,7,9 cm. sorted orders tuples by distance first, then the unique ID. `ranked[:3]` takes the first three rows. The output is ['A', 'B', 'C'] then clear: one blocked vote and two clear votes.

If `k` were 1 under the same distance tie rule, A would win and predict blocked. Changing `k` can change a prediction. We declared `k=3` for this exercise; do not choose `k` after seeing the desired answer and pretend the method was unchanged.

The code assumes unique IDs, numeric readings, only clear or blocked labels and at least three training rows. It does not validate those conditions. A larger `k` than the stored row count would not produce the promised number of votes. Keep unresolved review labels under a separate documented policy.

Connect the picture and the explanation


Point to the input, the deciding step and the result in this week's visual. Explain the same step in ordinary words. A picture helps when you can say what each part represents.

4. Compare the cases

EVALUATION DESIGN

Four Tests, Four Kinds of Evidence

A system is not understood until it survives more than one comfortable example.






BOUNDARY CASE

Value near a threshold or class boundary



MISSING CASE

Unknown field, label, or necessary evidence



NORMAL Expected data and expected behavior.

BOUNDARY Value close to a threshold, ambiguous label, or uncertain prediction.

MISSING Necessary field, label, source, or measurement is unavailable.

SHIFTED New lighting, species, device, subgroup, or time condition.

RELEASE RULE Passing one case never proves generalization. Predefine expected behavior for all four categories.

Which case most threatens today's claim, and why?

Change one thing in the pictured case

Change: Move the query to length7 cm.

Prediction: $k=1$ predicts spotted from B, distance1; $k=3$ remains spotted.

Reason: Distances become 5, 1, 4 cm, so the nearest tie disappears.

5. Words that unlock the idea

VOCABULARY

Words You Can Calculate and Defend

A definition matters when it lets you interpret a new dataset, model, or result.

1

DISTANCE

numeric measure of
dissimilarity

2

NEIGHBOR

nearby labeled training
example

3

K

number of neighbors voting

4

SCALING

make feature ranges
comparable

Term · Precise meaning · My ML example

Term: distance

Precise meaning: numeric measure of dissimilarity

My ML example: _____

Term: neighbor

Precise meaning: nearby labeled training example

My ML example: _____

Term: k

Precise meaning: number of neighbors voting

My ML example: _____

Term: scaling

Precise meaning: make feature ranges comparable

My ML example: _____

MISCONCEPTION TO REPAIR Nearest neighbor means the photo that looks most similar to a person.

Repair the claim using a definition, calculation, or test record:

Words used in the closer explanation

Word · Meaning

Word: Distance

Meaning: A numerical measure of difference between selected feature values

Word: Neighbour

Meaning: A stored training example close under the chosen distance

Word: k

Meaning: The number of neighbours selected for a prediction

Word: Vote

Meaning: A contribution of a selected neighbour's label to the predicted class

6. Follow a worked example

WORKED EVIDENCE

Reason Step by Step

Predict first. Then check each step. A correct answer without visible evidence cannot be audited.

Four-step worked evidence for Week 12: Nearest Neighbors

Step · Evidence and reasoning

Step: 1

Evidence and reasoning: New leaf has normalized features (2, 3).

Step: 2

Evidence and reasoning: Using Manhattan distance, add the absolute coordinate differences. Training leaves at (2, 2), (4, 3), and (1, 5) have distances 1, 2, and 3 from (2, 3).

Step: 3

Evidence and reasoning: With $k=1$, nearest label wins; with $k=3$, majority among all three wins.

Step: 4

Evidence and reasoning: Rescale features and retest because centimeters must not overwhelm a 0–1 color score.

Trace these corrected steps. Keep the stated metric, assumptions and interpretation when you change the case.

STEP 1 New leaf has normalized features (2, 3).

STEP 2 Using Manhattan distance, add the absolute coordinate differences. Training leaves at (2, 2), (4, 3), and (1, 5) have distances 1, 2, and 3 from (2, 3).

STEP 3 With $k=1$, nearest label wins; with $k=3$, majority among all three wins.

STEP 4 Rescale features and retest because centimeters must not overwhelm a 0–1 color score.

CHECK Verify the denominator, unit, split, class definition, and data version before interpreting a score.

Recalculate, retrace, or restate the evidence independently:

A closer explanation

Three selected neighbours for query 3

Stored example · Feature distance · One label vote

Stored example: A at 2 cm

Feature distance: abs 2 minus 3 is 1

One label vote: blocked

Stored example: B at 4 cm

Feature distance: abs 4 minus 3 is 1

One label vote: clear

Stored example: C at 8 cm

Feature distance: abs 8 minus 3 is 5

One label vote: clear

Select neighbours by feature distance and the declared ID tie rule. Read their training labels to vote only after selecting them.

Store the training examples and the method settings. At prediction time, compare the query only with stored training examples. Do not add the query's reference label or other validation labels to the neighbour pool. No cutoff or tree is fitted here, but retaining training examples is still part of the learning method.

Why do A and B tie for distance to query 3? Which wins for $k=1$ under our rule, and why does $k=3$ predict differently? Does the ID rule establish which label is true?

A vote share of two out of three describes these neighbours. It is not a verified two-thirds probability that the new scene is clear. A prediction can be wrong even when the nearest examples agree.

Learn from the worked case

Cover the result before checking it. Say what is given, choose the procedure, and follow one step at a time. Then uncover the result and explain your first mismatch. Ask why a step is allowed, not only what number it produces.

A pictorial worked case: Nearest Neighbors

Let a nearest-neighbour picture show each distance before voting.


The facts we will use

Training: A length 2 healthy; B length 8 spotted; C length 11 spotted. Query length 5 cm. Distance is absolute difference; ties use alphabetically earlier ID.

All inputs and outcomes in this worked example are invented classroom data; no real model run is claimed.

AI ACADEMY / AI-4/12

One-dimensional neighbours shown along length axis



Horizontal: length (cm); vertical: fixed display row, $y=0$

1: A healthy at (2, 0)

2: B spotted at (8, 0)

3: C spotted at (11, 0)

Cross: query at (5, 0)

Distance rule: Absolute length difference; ties use alphabetically earlier ID

Nearest Neighbors

Start with the supplied facts

Follow each arrow. Ask which fact allows the next step.



1. Measure distances

To A: $|5-2|=3$; B: $|5-8|=3$; C: $|5-11|=6$ cm.



2. Apply k=1 rule

A and B tie nearest; declared ID tie-break chooses A, predicting healthy.



3. Compare k=3

All three vote: two spotted and one healthy, so k=3 predicts spotted.

CHANGE ONE THING

Move the query to length 7 cm.

Explain the changed result using the matching lesson.

Read the picture one step at a time

Step · What happens and why

Step: 1. Measure distances

What happens and why: To A: $|5-2|=3$; B: $|5-8|=3$; C: $|5-11|=6$ cm.

Step: 2. Apply k=1 rule

What happens and why: A and B tie nearest; declared ID tie-break chooses A, predicting healthy.

Step: 3. Compare $k=3$

What happens and why: All three vote: two spotted and one healthy, so $k=3$ predicts spotted.

Match each pictured step to the supplied facts. This is a worked teaching case, not an independent assessment.

Why this result follows

Read the picture in order. All three vote: two spotted and one healthy, so $k=3$ predicts spotted. The arrows show which recorded input or intermediate result each decision uses. Explain the deciding step aloud before checking the changed case; pointing to the final answer alone does not show how it follows.

What this example does not establish

Length alone is a toy feature, not a disease diagnosis. Distance choices and feature scaling can change neighbours.

Read the labelled picture: Why is the $k=1$ outcome at length5 not uniquely determined without a tie rule? Point to the relevant step in the picture, then write the changed result and the rule or evidence that supports it.

Change one thing: Move the query to length7 cm. Predict the result before checking the explanation. What remains the same?

7. Find and repair a mistake

ERROR DETECTIVE

Compare → Diagnose → Repair

Do not patch the answer. Find the earliest unsupported assumption, data problem, or experiment error.



COMPARE • DIAGNOSE • REPAIR

Tempting claim: Nearest neighbor means the photo that looks most similar to a person.
Inspect the dataset, split, calculation, error type, subgroup, or experiment record; identify one testable cause; change one factor; rerun the same evidence.

Evidence record · Expected · Actual · Likely cause / next test

Evidence record: normal case

Expected: passes

Actual: _____

Likely cause / next test: _____

Evidence record: boundary case

Expected: defined behavior

Actual: _____

Likely cause / next test: _____

Evidence record: missing case

Expected: safe fallback

Actual: _____

Likely cause / next test: _____

Evidence record: shifted case

Expected: measured limit

Actual: _____

Likely cause / next test: _____

CLAIM TO CHALLENGE Nearest neighbor means the photo that looks most similar to a person.

Diagnose one cause and name the cleanest next experiment:

A closer explanation

All distances here use one feature measured in the same unit. With multiple features, their units and scales affect which examples appear close. A large numerical range can dominate a distance calculation. Next week we will address scaling and learn any scaling values from training data only.

Identical readings from different trips can have different labels, and an exact match does not certify truth. Keep related examples grouped across splits as in Week 6. Testing an example against a pool containing itself can make a one-neighbour score misleadingly high; it does not show performance on a new trip.

A learner adds each labelled validation query to the stored pool, then uses $k=1$ and reports

perfect predictions. Explain what the result fails to test and how to restore the intended comparison.

8. Practise together

ML STUDIO

Specify Before You Run

A trustworthy result can be reproduced from the recorded data, code, settings, and evaluation rule.



FREEZE THE EXPERIMENT

Record question, intended use, data version, grouped split, preprocessing, features, model settings, seed, metric, predictions, errors, subgroup results, and human review before claiming improvement.

Experiment record

QUESTION + intended use + success threshold

DATA version + grouped split + leakage check

CODE/preprocessing + features + model + settings + seed

METRICS + positive class + units + denominators

PREDICTIONS + errors + subgroup slices + limitations

HUMAN reviewer + release, revise, limit, or stop decision

Write the minimum record needed to reproduce today's result:

A closer explanation

Keep $k=3$ and the original five training rows. Validation queries with reference labels are (3,blocked), (9,blocked), (11,clear). Their selected neighbour IDs are A B C, C D E, and D E C respectively. Each group votes clear. Only the last prediction matches, so accuracy is $1/3$, about 33.3 percent.

The training-majority baseline also predicts clear because three training labels are clear and two are blocked. It gets the same $1/3$ on these validation rows. Record all distances, selected IDs and errors. Trying more k values is a development choice to document; preserve a separate final test for a final evaluation.

Practise with less help: Apply neighbour and tie rules

Use workbook W2 for the connected example “Nearest neighbours and distances”. First fill the input and rule boxes. Try the middle steps before asking for a hint. After a hint, try the next step yourself.

Plan · Do · Check

Plan: What is given? Which rule or procedure applies?

Do: Record each intermediate step.

Check: Does the result follow? What remains unknown?

Explain your trace to a partner. Your partner points to one step to check. Swap roles on the next case. Each person writes their own explanation.

Check your reasoning

Use the worked case for Nearest neighbours and distances. Proposed explanation: “A negative difference is a negative distance”. Decide whether this explanation is supported. Point to the step or supplied fact that decides; explain your repair if needed.

Answer on your own before discussion. If you are unsure, say which step you need help with.

Explain the picture

Why is the $k=1$ outcome at length5 not uniquely determined without a tie rule? Point to the relevant step in the picture, then write the changed result and the rule or evidence that supports it.

My explanation using a pictured step and the given facts

This is supported practice. Keep the separately named independent case for an attempt before feedback.

9. Run the investigation

EVIDENCE LAB

Predict → Run → Calculate → Interpret

Keep the test conditions fixed, record every result, and change only one planned factor.

LAB

PREDICT → RUN → CALCULATE → INTERPRET

Neighbor Map: compute distances, rank neighbors, compare k values, and show how scaling changes one result.

1. Write the hypothesis and expected evidence before running.
2. Neighbor Map: compute distances, rank neighbors, compare k values, and show how scaling changes one result.
3. Run one normal, one boundary, one missing, and one shifted case.
4. Calculate the metric from raw counts or row-level errors.
5. Interpret what changed, what did not, and what remains unsafe or unknown.

Case · Prediction · Actual · Calculation / evidence · Meaning / next test

Case: Normal

Prediction: _____

Actual: _____

Calculation / evidence: _____

Meaning / next test: _____

Case: Boundary

Prediction: _____

Actual: _____

Calculation / evidence: _____

Meaning / next test: _____

Case: Missing

Prediction: _____

Actual: _____

Calculation / evidence: _____

Meaning / next test: _____

Case: Shifted

Prediction: _____

Actual: _____

Calculation / evidence: _____

Meaning / next test: _____

Plan → try → check

Before trying: what do I expect, and why? While trying: which step could first go wrong? Afterwards: what did I actually observe, and what should change? Keep “not run” if you only traced the procedure.

10. Build your understanding

MASTERY

From Knowing the Word to Owning the Idea

Move upward only when you can produce evidence without copying the example.



ML BUILDER MASTERY

1 Define • 2 Calculate • 3 Trace code • 4 Run experiment • 5 Diagnose errors • 6 Improve one cause • 7 Defend limits

DEFINE Use all four terms precisely: distance, neighbor, k, scaling.

CALCULATE Reproduce the worked evidence with units and denominator.

TRACE Explain the data, code or decision path.

DIAGNOSE Nearest neighbor means the photo that looks most similar to a person.

TRANSFER Solve a fresh dataset or model case.

IMPROVE Change one cause and rerun fixed evidence.

DEFEND State intended use, metric, limitation, and human responsibility.

MASTERY RULE A coached calculation becomes mastery only after a different case is completed independently.

11. Connect your project

CUMULATIVE PROJECT

Responsible Plant Classifier

Every week adds one reviewable artifact to the same evidence-based capstone.



RESPONSIBLE PLANT CLASSIFIER

Implement a transparent k-NN paper prototype for the Plant Classifier and record the chosen features, scaling, distance, and k.

THIS WEEK'S CHECKPOINT Implement a transparent k-NN paper prototype for the Plant Classifier and record the chosen features, scaling, distance, and k.

Which requirement or risk does this artifact address?

Which dataset, split, code, and metric version does it use?

What normal and shifted cases were tested?

What remains uncertain or weak?

What decision still belongs to a teacher or qualified human?

RESPONSIBLE RELEASE Never use this classroom prototype for medical, pesticide, agricultural, or other consequential decisions.

My evidence-linked project decision:

Evidence for your project


For your Responsible Plant Classifier, save the input, procedure, observed result and limitation of this check. Label this worked example as practice; use a different, previously unreviewed case when checking independent understanding.

12. Show what you know

INDEPENDENT PROOF

Explain • Calculate • Transfer • Defend

Complete this with a fresh case after guided practice and compare it with the mastery criteria.



INDEPENDENT ML BUILDER PROOF

Calculate distances and compare $k=1$ with $k=3$.

REQUIRED PROOF Calculate distances and compare $k=1$ with $k=3$.

- ☐ Define the task, feature/target roles, and intended-use boundary.
- ☐ Show the calculation, code trace, or experiment record.
- ☐ Test a normal case and one revealing boundary, missing, or shifted case.
- ☐ Diagnose one failure without changing several factors at once.
- ☐ Name a limitation, fairness concern, and the human-review action.

Independent evidence and defense:

My level: ☐ Not yet ☐ With one hint ☐ Independently ☐ I can teach and defend it

NEXT BRIDGE Carry the experiment evidence into: Train a Classifier.

13. Study a complete case

Week 12 Worked case

Use the supplied details to practise the weekly concept before attempting the independent question. This case extends the illustrated lesson.

The situation

One-dimensional training points: 2 healthy, 4 healthy, 8 spotted. Query=6; absolute distance.

The question

Find $k=1$ neighbours and handle ties.

Worked explanation

Distances 4,2,2. Points 4 and 8 tie with different labels. Use a predefined tie policy or uncertainty. Scaling matters with differently measured features.

Explain it in your own words

Which detail supports the answer, and why does it matter?

Write or draw your reasoning and evidence.

Trace the supplied case visually

Absolute distance from query 6

Evidence or stage · Value or result

Evidence or stage: Point 2, healthy

Value or result: 4

Evidence or stage: Point 4, healthy

Value or result: 2

Evidence or stage: Point 8, spotted

Value or result: 2

One-dimensional training points: 2 healthy, 4 healthy, 8 spotted. Query=6; absolute distance.

Find k=1 neighbours and handle ties.

Distances 4,2,2. Points 4 and 8 tie with different labels. Use a predefined tie policy or uncertainty. Scaling matters with differently measured features.

14. Try a new case independently

Independent case: Changed independent case

Training points: A length1 healthy, B length5 spotted, C length9 healthy. Query length7. Use absolute distance; for a nearest-neighbor tie choose the alphabetically earlier ID. Compare $k=1$ and $k=3$.

My independent explanation, trace and limits

Attempt this case before feedback. Record any help. Earlier examples below are further practice; a case already practised with feedback cannot establish fresh transfer.

Week 12 Independent application

Close the worked explanation. Apply the idea to this different question without copying.

For one feature, labeled points are 2:fern and 8:grass. A new point is 6. Under one-nearest-neighbor with absolute distance, predict its label.

My answer, with a trace, calculation or supporting evidence

Write or draw your reasoning and evidence.

Create and test

Change one relevant detail. Predict the result before testing. Include a boundary or missing-information case when it helps reveal a limit.

My changed input and expected result

Write or draw your reasoning and evidence.

Connect to your project

Implement a transparent k-NN paper prototype for the Plant Classifier and record the chosen features, scaling, distance, and k.

The evidence I will keep

Write or draw your reasoning and evidence.

Your teacher has the independent answer and scoring criteria. Complete the matching workbook week to keep your practice evidence together.

Transfer practice from the original programme

Training lengths 2(H),6(S),10(H); query=8. Compute distances. Explain the tie and why combining length in mm with width in cm changes a two-feature distance.

Explain the mechanism, evidence and one limit.

Use feedback to improve

Attempt the independent case before hints. Record whether you worked alone, used a hint or followed a model. After feedback, fix the first unsupported step and explain why it changed. A later check uses a changed case, not a copied answer.

15. Your lesson route

Start with this question: Let a nearest-neighbour picture show each distance before voting.

By the end, I can · How I will show it

By the end, I can: Compute absolute distances and rank training neighbours

How I will show it: Explain the deciding step, show a trace or test, and state one limit.

By the end, I can: Apply a declared neighbour count and distance tie rule

How I will show it: Explain the deciding step, show a trace or test, and state one limit.

By the end, I can: Evaluate neighbour predictions without using validation labels as neighbours

How I will show it: Explain the deciding step, show a trace or test, and state one limit.

Remember → watch and explain → try with help → investigate → try independently → keep project evidence. Your teacher may spread this lesson across several classes.

Keep your first prediction. Compare it with what the evidence shows and explain any change.

16. Finish and return

Close your notes. Explain this goal in your own words: Compute absolute distances and rank training neighbours

My deciding step, evidence and one remaining question

If you are unsure, return to the worked picture and explain one arrow. If you are ready, change an input or assumption and justify your prediction.

Save your workbook evidence. At the next review, try a different case before opening your old answer.

17. Supported practice, repair and portfolio

Use this supported practice once, in the browser or on paper. Keep the reserved independent assessment for a separate first attempt before teacher feedback.

Let a nearest-neighbour picture show each distance before voting.

Practice 1: explain the deciding evidence

Which labelled step matches this detail? All three vote: two spotted and one healthy, so $k=3$ predicts spotted.

1. Measure distances
2. Compare $k=3$
3. Apply $k=1$ rule

My selected conclusion, deciding fact and explanation

Hint if needed: Read the steps in the pictorial case. Match the supplied detail to the stage that performs or records it.

After your attempt, compare with the supported explanation: Compare $k=3$ All three vote: two spotted and one healthy, so $k=3$ predicts spotted. Read the picture in order. All three vote: two spotted and one healthy, so $k=3$ predicts spotted. The arrows show which recorded input or intermediate result each decision uses. Explain the deciding step aloud before checking the changed case; pointing to the final answer alone does not show how it follows.

Practice 2: explain the deciding evidence

Changed-case practice: Move the query to length 7 cm. Which conclusion is supported by the supplied

facts?

1. This one example guarantees correct results for every future input.
2. $k=1$ predicts spotted from B, distance1; $k=3$ remains spotted.
3. We can decide the result without examining the changed input or the procedure.

My selected conclusion, deciding fact and explanation

Hint if needed: Use the changed condition and the deciding step in the pictorial trace. The answer must say what follows from those facts.

After your attempt, compare with the supported explanation: $k=1$ predicts spotted from B, distance1; $k=3$ remains spotted. Distances become 5, 1, 4 cm, so the nearest tie disappears.

Repair a missing building block

Review Decision Trees (ai-4/11). Goal: Fit a root question and leaf predictions from training examples. Short practice: Which input distinguishes the original and changed tree? Point to the relevant step in the picture, then write the changed result and the rule or evidence that supports it.. Return to this week and explain what you changed.

Review Dataset Cards (ai-4/9). Goal: Inspect row meaning missing values and repeated records. Short practice: What two counts should the revised card show? Point to the relevant step in the picture, then write the changed result and the rule or evidence that supports it.. Return to this week and explain what you changed.

Review Label Quality (ai-4/6). Goal: Write an observable label rule with boundaries and a review option. Short practice: Why should two annotators not vote away Z's missing evidence? Point to the relevant step in the picture, then write the changed result and the rule or evidence that supports it.. Return to this week and explain what you changed.

Predict, run and debug

The browser lab lets you edit the supported Python examples already included in this lesson. Predict first, run, inspect the actual output or error, change one input, then run again. Keep code, predictions, actual results and a reasoned revision together. On paper, label your result as a trace rather than an execution.

Keep your completed work

Use Download completed work in the hosted lesson to export your answers, reflections, practice feedback and code-run evidence. Open the HTML copy to read or print it. Drafts stay in this browser when storage is available; clear drafts on a shared device.