

Loops and trace tables

Project: Python readiness portfolio

1. Your mission

Your learning target

I can trace variable values before and after each loop iteration.

I can use the excluded stop value in range correctly.

I can explain initialization and test zero one and several iterations.

Remember before reading

Close your notes first. A rough first answer helps us choose the right starting point; it is not a score for your ability.

Without opening the old lesson, explain one key idea from Branching and boundary tests. Give an example and a mistake that the idea helps you avoid.

Without opening the old lesson, explain one key idea from Expressions and operator order. Give an example and a mistake that the idea helps you avoid.

After trying, check the relevant lesson or ask your teacher. Change the part of your explanation that the evidence shows was wrong.

This week you will practise:

Trace variable values before and after each loop iteration

Use the excluded stop value in range correctly

Explain initialization and test zero one and several iterations

Retrieve what you already know

Starting with $\text{total} = 2$, what does $\text{total} = \text{total} + 3$ store?

My starting explanation

This week's end goal

Trace loops and trace tables and explain the changed program before running it.

2. Notice the evidence

Imagine adding numbered counters: first 1, then 2, then 3. A loop can repeat the same addition with a different number each time. This week you will predict each change before running a short Python script. Tracing repeated calculations prepares you to inspect the data processing used in larger AI applications.

In `for turn in range(1, 4)`, Python supplies 1, 2 and 3 in order. The start is included and the stop is excluded. The indented body runs once for each supplied value. The colon and four-space indentation mark that body. This lesson uses integer range values with the default positive step of 1.

List the given facts and one fact that is not supplied.

3. See how it works

```
total = 0

for turn in range(1, 4):
    total = total + turn

print(total)
```

State after each addition

turn · total before · total after

turn: 1

total before: 0

total after: 1

turn: 2

total before: 1

total after: 3

turn: 3

total before: 3

total after: 6

Initialize total to 0 before the loop. The unindented print runs once afterward.

The output is 6. Before the first iteration, total is 0. Each assignment reads the previous total and adds the current turn. After turn 3, the range is exhausted, so execution continues after the loop. The table records state; it does not create extra instructions.

Connect the picture and the explanation

Point to the input, the deciding step and the result in this week's visual. Explain the same step in ordinary words. A picture helps when you can say what each part represents.

4. Compare the cases

Compare a familiar case with a changed case

Copy the worked script. Change the range to range(2, 5). Record turn, total before and total after each iteration. Predict the single output, then run and compare.

Keep the procedure fixed. Explain what changed in the inputs and result.

Change one thing in the pictured case

Change: Replace range(1,5) with range(1,1).

Prediction: No values are visited and the final output is 0.

Reason: The accumulator starts at zero and an empty loop never changes it.

5. Words that unlock the idea

Word · Meaning

Word: Loop

Meaning: A block of instructions that can run repeatedly

Word: Iteration

Meaning: One execution of a loop body

Word: Accumulator

Meaning: A variable that keeps a running result

Word: Initialization

Meaning: Giving a variable its starting value

Word: Trace table

Meaning: A record of variable values as instructions execute

Use two terms to explain a step in this week's example.

6. Follow a worked example

Range expression · Values supplied · Number of iterations

Range expression: range(1, 4)

Values supplied: 1, 2, 3

Number of iterations: 3

Range expression: range(1, 2)

Values supplied: 1

Number of iterations: 1

Range expression: range(1, 1)

Values supplied: No values

Number of iterations: 0

Range expression: range(4)

Values supplied: 0, 1, 2, 3

Number of iterations: 4

With one argument, range starts at zero. range(4) supplies four values but none is 4. If the worked script uses range(1, 1), the body never runs and the initialized total remains 0. Do not rely on a variable first assigned inside a loop: a zero-iteration run might never assign it.

Replace range(1, 4) with range(1, 3) in the worked script. Predict the supplied values and final total. What stop value is needed to include 3?

Learn from the worked case

Cover the result before checking it. Say what is given, choose the procedure, and follow one step at a time. Then uncover the result and explain your first mismatch. Ask why a step is allowed, not only what number it produces.

A pictorial worked case: Loops and trace tables

Accumulate a short range. A running total adds the integers visited by range(1,5).

The facts we will use

Python 3: total=0; for value in range(1,5): total+=value; print(total). The print is after the loop.

Running total after each visited value

	Current value	Running total
Visit 1	1	1
Visit 2	2	3
Visit 3	3	6
Visit 4	4	10

Read a cell using both its row and column labels.

Loops and trace tables

Start with the supplied facts

Follow each arrow. Ask which fact allows the next step.



1. Visit the range

Values are 1,2,3,4; the stop value 5 is excluded.



2. Trace running total

Totals after each addition are 1,3,6,10.



3. Print after the loop

The final displayed value is 10.

CHANGE ONE THING

Replace `range(1,5)` with `range(1,1)`.

Explain the changed result using the matching lesson.

Read the picture one step at a time

Step · What happens and why

Step: 1. Visit the range

What happens and why: Values are 1,2,3,4; the stop value 5 is excluded.

Step: 2. Trace running total

What happens and why: Totals after each addition are 1,3,6,10.

Step: 3. Print after the loop

What happens and why: The final displayed value is 10.

Match each pictured step to the supplied facts. This is a worked teaching case, not an independent assessment.

Why this result follows

A loop repeats an operation for each visited value. A trace table distinguishes the current value from the accumulator; the range stop is not included.

What this example does not establish

This bounded loop does not train an AI model; other loop conditions may require separate termination checks.

Read the labelled picture: List the four visited values and their running totals. Explain why 5 is absent and what prints for range(1,1).

Change one thing: Replace range(1,5) with range(1,1). Predict the result before checking the explanation. What remains the same?

7. Find and repair a mistake

```
total = 0

for turn in range(1, 4):

    total = 0

    total = total + turn

print(total)
```

This faulty version prints 3. The extra reset discards earlier additions on every iteration. Remove the indented reset while keeping initialization before the loop. Then test zero, one and several iterations: the one-iteration case alone cannot reveal this reset bug.

Moving print(total) into the correct loop produces three lines, 1 then 3 then 6. Moving it out produces only the final 6. Trace both values and output events. A loop follows written instructions; repeating them does not make the program learn.

Locate the earliest unsupported step

For the faulty script with range(1, 4), record total after each addition. Explain the wrong final output and remove only the faulty reset.

State one repair and the checks you would rerun.

8. Practise together

List the values supplied by `range(2, 5)` and explain why 5 is absent. How many times does its body run?

Replace `range(1, 4)` with `range(1, 3)` in the worked script. Predict the supplied values and final total. What stop value is needed to include 3?

Explain your prediction to a partner before comparing results.

Practise with less help: Trace before running

Use workbook W2 for the connected example “Loops and trace tables”. First fill the input and rule boxes. Try the middle steps before asking for a hint. After a hint, try the next step yourself.

Plan · Do · Check

Plan: What is given? Which rule or procedure applies?

Do: Record each intermediate step.

Check: Does the result follow? What remains unknown?

Explain your trace to a partner. Your partner points to one step to check. Swap roles on the next case. Each person writes their own explanation.

Check your reasoning

Use the worked case for Loops and trace tables. Proposed explanation: “The stop value is included”. Decide whether this explanation is supported. Point to the step or supplied fact that decides; explain your repair if needed.

Answer on your own before discussion. If you are unsure, say which step you need help with.

Explain the picture

List the four visited values and their running totals. Explain why 5 is absent and what prints for range(1,1).

My explanation using a pictured step and the given facts

This is supported practice. Keep the separately named independent case for an attempt before feedback.

9. Run the investigation

Predict, investigate and preserve the evidence

Copy the worked script. Change the range to range(2, 5). Record turn, total before and total after each iteration. Predict the single output, then run and compare.

```
total = 0
for turn in range(1, 4):
    total = total + turn
print(total)
```

```
total = 0
for turn in range(1, 4):
    total = 0
```

```
total = total + turn  
  
print(total)
```

Record · Your evidence

Record: Given input and fixed rule

Your evidence: _____

Record: Prediction before checking

Your evidence: _____

Record: Actual result, or “not run”

Your evidence: _____

Record: First mismatch and one explanation

Your evidence: _____

Record: Boundary or missing input and expected response

Your evidence: _____

On paper, trace the supplied procedure. If code is provided, predict before running it in a local practice file. Never write an expected answer as though it were an observed run.

Plan → try → check

Before trying: what do I expect, and why? While trying: which step could first go wrong? Afterwards: what did I actually observe, and what should change? Keep “not run” if you only traced the procedure.

10. Build your understanding

Explain → apply → challenge

List the values supplied by `range(2, 5)` and explain why 5 is absent. How many times does its body run?

For the faulty script with `range(1, 4)`, record total after each addition. Explain the wrong final output and remove only the faulty reset.

In your counter script, range(-2) performs no iterations. Does returning the initial 5 make negative rounds valid? Explain what the script checks and what it assumes.

Explain which evidence supports your conclusion and which claim remains unproved.

11. Connect your project

Add a labelled loops and trace tables evidence sheet to Python readiness portfolio. Show how you can trace variable values before and after each loop iteration. Use the supplied fictional case and keep its inputs, intermediate steps, calculation or prediction, and limitation. Connect this record to last week's record; a matching answer without a trace is insufficient.

Project evidence · Record

Project evidence: Component and version

Record: _____

Project evidence: Inputs permitted at prediction time

Record: _____

Project evidence: Trace and comparison with earlier work

Record: _____

Project evidence: Failure, limit and human review

Record: _____

Evidence for your project

For Python readiness before the Responsible Plant Classifier, retain a trace of the values, the predicted outputs and the changed-case explanation. Use actual Python 3 results to check the prediction after

reasoning first.

12. Show what you know

Write the expected range values and trace table before running. Keep predicted and observed output separate, then explain the first row where they differ. For a loop that should add a fixed amount repeatedly, zero iterations should preserve the initial amount. One iteration checks one update; several check accumulation.

A learner checks the reset bug using only range(1, 2) and sees the expected answer 1. Explain why this does not establish correctness, and give a revealing test with its expected correct output.

In your counter script, range(-2) performs no iterations. Does returning the initial 5 make negative rounds valid? Explain what the script checks and what it assumes.

My limited claim and a useful next check

13. Study a complete case

Complete evidence record

State after each addition

turn · total before · total after

turn: 1

total before: 0

total after: 1

turn: 2

total before: 1

total after: 3

turn: 3

total before: 3

total after: 6

Initialize total to 0 before the loop. The unindented print runs once afterward.

Follow the input through the stated procedure to its result. Cover the result first, predict it, then explain every intermediate step. The text/table accompanies the figure so the example can be read without colour.

My complete trace of the worked case

14. Try a new case independently

Independent case: Count iterations and a stopping point

List every value visited and each running total. Then predict the result for range(2,2).

```
total = 0
for value in range(2, 6):
    total = total + value
print(total)
```

My independent explanation, trace and limits

Attempt this case before feedback. Record any help. Earlier examples below are further practice; a case already practised with feedback cannot establish fresh transfer.

Attempt this without hints

A box starts with 5 counters. Each round adds 2 counters. Use rounds = 3, an initialized total and for turn in range(rounds). Print the final total once after the loop. Trace the totals and predict fresh runs with rounds 0, 1 and 3. Assume rounds is a nonnegative integer.

My independent procedure, result and limitation

Record support used: none, hint or teacher explanation. After feedback, a different case is needed to demonstrate independence.

Use feedback to improve

Attempt the independent case before hints. Record whether you worked alone, used a hint or followed a model. After feedback, fix the first unsupported step and explain why it changed. A later check uses a changed case, not a copied answer.

15. Your lesson route

Start with this question: Accumulate a short range. A running total adds the integers visited by range(1,5).

By the end, I can · How I will show it

By the end, I can: Trace variable values before and after each loop iteration

How I will show it: Explain the deciding step, show a trace or test, and state one limit.

By the end, I can: Use the excluded stop value in range correctly

How I will show it: Explain the deciding step, show a trace or test, and state one limit.

By the end, I can: Explain initialization and test zero one and several iterations

How I will show it: Explain the deciding step, show a trace or test, and state one limit.

Remember → watch and explain → try with help → investigate → try independently → keep project evidence. Your teacher may spread this lesson across several classes.

Keep your first prediction. Compare it with what the evidence shows and explain any change.

16. Finish and return

Close your notes. Explain this goal in your own words: Trace variable values before and after each loop iteration

My deciding step, evidence and one remaining question

If you are unsure, return to the worked picture and explain one arrow. If you are ready, change an input or assumption and justify your prediction.

Save your workbook evidence. At the next review, try a different case before opening your old answer.

17. Supported practice, repair and portfolio

Use this supported practice once, in the browser or on paper. Keep the reserved independent assessment for a separate first attempt before teacher feedback.

Accumulate a short range. A running total adds the integers visited by range(1,5).

Practice 1: explain the deciding evidence

Which labelled step matches this detail? The final displayed value is 10.

1. Trace running total
2. Print after the loop
3. Visit the range

My selected conclusion, deciding fact and explanation

Hint if needed: Read the steps in the pictorial case. Match the supplied detail to the stage that performs or records it.

After your attempt, compare with the supported explanation: Print after the loop The final displayed value is 10. A loop repeats an operation for each visited value. A trace table distinguishes the current value from the accumulator; the range stop is not included.

Practice 2: explain the deciding evidence

Changed-case practice: Replace range(1,5) with range(1,1). Which conclusion is supported by the supplied facts?

1. We can decide the result without examining the changed input or the procedure.
2. No values are visited and the final output is 0.
3. This one example guarantees correct results for every future input.

My selected conclusion, deciding fact and explanation

Hint if needed: Use the changed condition and the deciding step in the pictorial trace. The answer must say what follows from those facts.

After your attempt, compare with the supported explanation: No values are visited and the final output is 0. The accumulator starts at zero and an empty loop never changes it.

Repair a missing building block

Review Branching and boundary tests (python-bridge/5). Goal: Trace the selected branch in an if elif else chain. Short practice: Trace -2, 4 and 5 through the branches. Explain why the negative check comes first and what label -2 gets if it is removed.. Return to this week and explain what you changed.

Review Expressions and operator order (python-bridge/3). Goal: Evaluate numeric expressions using Python's grouping rules. Short practice: Trace the operation order in both expressions. Identify which picture step changes with parentheses and predict both results when the multiplier becomes four.. Return to this week and explain what you changed.

Predict, run and debug

The browser lab lets you edit the supported Python examples already included in this lesson. Predict first, run, inspect the actual output or error, change one input, then run again. Keep code, predictions, actual results and a reasoned revision together. On paper, label your result as a trace rather than an execution.

Keep your completed work

Use Download completed work in the hosted lesson to export your answers, reflections, practice feedback and code-run evidence. Open the HTML copy to read or print it. Drafts stay in this browser when storage is available; clear drafts on a shared device.