

Bias terms and decision boundaries

Project: Image-pattern Network Investigation

1. Your mission

Your learning target

I can calculate a weighted score with a bias term.

I can locate and test a two-feature decision boundary.

I can explain how changing the bias shifts a boundary without training.

Remember before reading

Close your notes first. A rough first answer helps us choose the right starting point; it is not a score for your ability.

Without opening the old lesson, explain one key idea from Dot products and weighted sums. Give an example and a mistake that the idea helps you avoid.

After trying, check the relevant lesson or ask your teacher. Change the part of your explanation that the evidence shows was wrong.

This week you will practise:

Calculate a weighted score with a bias term

Locate and test a two-feature decision boundary

Explain how changing the bias shifts a boundary without training

Retrieve what you already know

For $w = [2, -1]$ and $x = [3, 5]$, what are the contributions and dot product?

My starting explanation

This week's end goal

By the end, I can explain bias terms and decision boundaries using a traced example and a stated limitation.

2. Notice the evidence

Use the fictional parcel schema [width in cm, height in cm]. Our model computes $z = 2 \text{ times width} - \text{height} - 3$. The weights are [2, -1]; the bias b is -3. Compute the weighted sum first, then add the bias once. The result is an affine score: a weighted sum plus a constant offset.

Now declare a classification rule: predict class 1 when z is at least 0, and class 0 when z is below 0. Equality belongs to class 1. These are invented categories for arithmetic practice, not a real parcel decision. The weights and bias are supplied, so this is a forward calculation, not training.

Input [width, height] · Score z · Prediction

Input [width, height]: [4, 2]

Score z : $8 - 2 - 3 = 3$

Prediction: 1

Input [width, height]: [2, 4]

Score z : $4 - 4 - 3 = -3$

Prediction: 0

Input [width, height]: [3, 3]

Score z : $6 - 3 - 3 = 0$

Prediction: 1 at equality

A bias is a mathematical parameter. It is not the same use of the word as unfair treatment; numerical offset alone does not establish whether a system is fair.

List the given facts and one fact that is not supplied.

3. See how it works

Set z to zero to locate the boundary: $2 \text{ times width} - \text{height} - 3 = 0$, so $\text{height} = 2 \text{ times width} - 3$. Plot width on the horizontal axis and height on the vertical axis. Boundary points include (2, 1), (3, 3) and (4, 5). Join them with a straight line and label the axes in cm.

At width 3, height 2 gives score 1 and class 1; height 3 gives score 0 and class 1; height 4 gives score -1 and class 0. Under this axis convention class 1 lies on or below the boundary. One point on each side checks that orientation.

```
def classify(width, height, bias=-3):  
    score = 2 * width - height + bias  
    return score, int(score >= 0)  
  
for height in [2, 3, 4]:  
    print(classify(3, height))  
  
# (1, 1), (0, 1), (-1, 0)
```

The code assumes valid numerical measurements in the agreed units. Changing $\geq$ to $>$ changes the equality case, even though the drawn line remains in the same place.

Connect the picture and the explanation

Point to the input, the deciding step and the result in this week's visual. Explain the same step in ordinary words. A picture helps when you can say what each part represents.

4. Compare the cases

Compare a familiar case with a changed case

For the worked model, find boundary points at width 2 and width 4. Test [4, 4] and [4, 6] to identify the class on each side.

Keep the procedure fixed. Explain what changed in the inputs and result.

Change one thing in the pictured case

Change: Change bias from -3 to -1.

Prediction: A score becomes 2 and B score 0; both predict class 1.

Reason: Increasing bias by 2 adds 2 to every score without changing the weights.

5. Words that unlock the idea

Word · Meaning

Word: Bias term

Meaning: An additive parameter applied after a weighted sum

Word: Decision boundary

Meaning: Input locations where the declared classification rule changes class

Word: Affine function

Meaning: A weighted sum plus a constant offset

Word: Threshold rule

Meaning: A stated comparison that converts a score into a class

Use two terms to explain a step in this week's example.

6. Follow a worked example

Hold the weights fixed while shifting the boundary

Bias · Score at [3, 3] · Boundary equation

Bias: b is -3

Score at [3, 3]: $6 - 3 - 3$ gives 0

Boundary equation: height = 2 width - 3

Bias: b is -1

Score at [3, 3]: $6 - 3 - 1$ gives 2

Boundary equation: height = 2 width - 1

Bias: Increase b by 2

Score at [3, 3]: Every score rises by 2

Boundary equation: Slope remains 2

The boundary moves parallel to itself because the weights stay fixed. An increased score does not always change a class: only inputs crossing the declared threshold change.

For [3, 4], compare z and prediction with bias -3 and bias -1. Explain which parameter changed.

Learn from the worked case

Cover the result before checking it. Say what is given, choose the procedure, and follow one step at a time. Then uncover the result and explain your first mismatch. Ask why a step is allowed, not only what number it produces.

A pictorial worked case: Bias terms and decision boundaries

Move a toy boundary with a bias while keeping its input weights fixed.

The facts we will use

Score $z = 2u - v - 3$; predict class 1 when $z \geq 0$. Inputs $A = [2, 1]$, $B = [1, 1]$.

All inputs and outcomes in this worked example are invented classroom data; no real model run is claimed.

Input A reaches the inclusive boundary

Input 2 x weight 2 = 4

Input 1 x weight -1 = -1

Add the products and bias -3: total = 0

Keep the total (identity) -> output 0

Bias terms and decision boundaries

Start with the supplied facts

Follow each arrow. Ask which fact allows the next step.



1. Trace input A

A score= $4-1-3=0$, so class 1 at the declared inclusive boundary.



2. Trace input B

B score= $2-1-3=-2$, so class 0.



3. Read boundary

The boundary is $v=2u-3$; the bias sets its position.

CHANGE ONE THING

Change bias from -3 to -1.

Explain the changed result using the matching lesson.

Read the picture one step at a time

Step · What happens and why

Step: 1. Trace input A

What happens and why: A score= $4-1-3=0$, so class 1 at the declared inclusive boundary.

Step: 2. Trace input B

What happens and why: B score= $2-1-3=-2$, so class 0.

Step: 3. Read boundary

What happens and why: The boundary is $v=2u-3$; the bias sets its position.

Match each pictured step to the supplied facts. This is a worked teaching case, not an independent assessment.

Why this result follows

The bias adds the same offset after the input contributions. It moves the dividing line without changing the weights that set the line's orientation. Class 1 includes score zero under our stated rule. That is why B changes class when the bias rises by two: its score moves from minus two onto the included boundary.

What this example does not establish

A linear boundary is a toy classifier rule. Raw score size does not automatically describe confidence or probability.

7. Find and repair a mistake

Without a bias, this score would be $z = 2 \text{ times width} - \text{height}$ and its zero line would pass through $(0, 0)$. The offset lets the boundary move away from the origin. In this parcel schema zero dimensions are invalid measurements; the origin is still useful as a point on the extended mathematical graph.

Changing bias from -3 to -1 increases every score by 2, but does not rotate the line. Changing a weight can rotate or otherwise change the boundary. Neither change is automatically an improvement. To compare models, retain labels, a declared metric, the same evaluation records and the separate training, validation and test roles.

Locate the earliest unsupported step

At [3, 3], compare prediction under $z \geq 0$ with prediction under $z > 0$. Does changing this comparison move the zero line?

State one repair and the checks you would rerun.

8. Practise together

Use $z = 2 \text{ times width} - \text{height} - 3$ at $[5, 4]$. Give the weighted sum, bias, final score and prediction under $z \geq 0$.

For $[3, 4]$, compare z and prediction with bias -3 and bias -1 . Explain which parameter changed.

Explain your prediction to a partner before comparing results.

Practise with less help: Plot and label the boundary

Use workbook W2 for the connected example “Bias terms and decision boundaries”. First fill the input and rule boxes. Try the middle steps before asking for a hint. After a hint, try the next step yourself.

Plan · Do · Check

Plan: What is given? Which rule or procedure applies?

Do: Record each intermediate step.

Check: Does the result follow? What remains unknown?

Explain your trace to a partner. Your partner points to one step to check. Swap roles on the next case. Each person writes their own explanation.

Check your reasoning

Use the worked case for Bias terms and decision boundaries. Proposed explanation: “Add bias to each contribution”. Decide whether this explanation is supported. Point to the step or supplied fact that decides; explain your repair if needed.

Answer on your own before discussion. If you are unsure, say which step you need help with.

Explain the picture

Is B positive under the original or changed model? Point to the relevant step in the picture, then write the changed result and the rule or evidence that supports it.

My explanation using a pictured step and the given facts

This is supported practice. Keep the separately named independent case for an attempt before feedback.

9. Run the investigation

Predict, investigate and preserve the evidence

For the worked model, find boundary points at width 2 and width 4. Test [4, 4] and [4, 6] to identify the class on each side.

```
def classify(width, height, bias=-3):  
    score = 2 * width - height + bias  
    return score, int(score >= 0)  
  
for height in [2, 3, 4]:  
    print(classify(3, height))  
  
# (1, 1), (0, 1), (-1, 0)
```

Record · Your evidence

Record: Given input and fixed rule

Your evidence: _____

Record: Prediction before checking

Your evidence: _____

Record: Actual result, or “not run”

Your evidence: _____

Record: First mismatch and one explanation

Your evidence: _____

Record: Boundary or missing input and expected response

Your evidence: _____

On paper, trace the supplied procedure. If code is provided, predict before running it in a local practice file. Never write an expected answer as though it were an observed run.

Plan → try → check

Before trying: what do I expect, and why? While trying: which step could first go wrong? Afterwards: what did I actually observe, and what should change? Keep “not run” if you only traced the procedure.

10. Build your understanding

Explain → apply → challenge

Use $z = 2 \text{ times width} - \text{height} - 3$ at $[5, 4]$. Give the weighted sum, bias, final score and prediction under $z \geq 0$.

At $[3, 3]$, compare prediction under $z \geq 0$ with prediction under $z > 0$. Does changing this comparison move the zero line?

A teammate says that raising b must improve the model because all scores rise. What information is needed before accepting an improvement claim?

Explain which evidence supports your conclusion and which claim remains unproved.

11. Connect your project

Add a labelled bias terms and decision boundaries evidence sheet to Image-pattern Network Investigation. Show how you can calculate a weighted score with a bias term. Use the supplied fictional case and keep its inputs, intermediate steps, calculation or prediction, and limitation. Connect this record to last week's record; a matching answer without a trace is insufficient.

Project evidence · Record

Project evidence: Component and version

Record: _____

Project evidence: Inputs permitted at prediction time

Record: _____

Project evidence: Trace and comparison with earlier work

Record: _____

Project evidence: Failure, limit and human review

Record: _____

Evidence for your project

For your Image-pattern Network Investigation, save the input, procedure, observed result and limitation of this check. Label this worked example as practice; use a different, previously unreviewed case when checking independent understanding.

12. Show what you know

The boundary states what this particular formula predicts. It does not establish the true classes of all possible inputs. A point very far from the line need not have a reliable prediction when the model, features or data are inappropriate. The raw score is not calibrated confidence or a physical distance from the line.

A team changes b after seeing final-test mistakes and reports the same cases as an untouched test of the new model. Explain the error and the next step.

Next week, we transform scores with activation functions before discussing layers.

A teammate says that raising b must improve the model because all scores rise. What information is needed before accepting an improvement claim?

My limited claim and a useful next check

13. Study a complete case

Complete evidence record

Hold the weights fixed while shifting the boundary

Bias · Score at [3, 3] · Boundary equation

Bias: b is -3

Score at [3, 3]: $6 - 3 - 3$ gives 0

Boundary equation: height = 2 width - 3

Bias: b is -1

Score at [3, 3]: $6 - 3 - 1$ gives 2

Boundary equation: height = 2 width - 1

Bias: Increase b by 2

Score at [3, 3]: Every score rises by 2

Boundary equation: Slope remains 2

The boundary moves parallel to itself because the weights stay fixed. An increased score does not always change a class: only inputs crossing the declared threshold change.

Follow the input through the stated procedure to its result. Cover the result first, predict it, then explain every intermediate step. The text/table accompanies the figure so the example can be read without colour.

My complete trace of the worked case

14. Try a new case independently

Independent case: Analyse a new model independently

A new model has $w = [-1, 2]$, $b = -2$, inputs $[u, v]$ and class 1 when $z \geq 0$. Calculate scores and classes for $[2, 1]$, $[2, 2]$, $[2, 3]$. Write the boundary as v in terms of u . Then change only b to 0 and recompute $[2, 1]$.

My independent explanation, trace and limits

Attempt this case before feedback. Record any help. Earlier examples below are further practice; a case already practised with feedback cannot establish fresh transfer.

Attempt this without hints

A new model has $w = [-1, 2]$, $b = -2$, inputs $[u, v]$ and class 1 when $z \geq 0$. Calculate scores and classes for $[2, 1]$, $[2, 2]$, $[2, 3]$. Write the boundary as v in terms of u . Then change only b to 0 and recompute $[2, 1]$.

My independent procedure, result and limitation

Record support used: none, hint or teacher explanation. After feedback, a different case is needed to demonstrate independence.

Use feedback to improve

Attempt the independent case before hints. Record whether you worked alone, used a hint or followed a model. After feedback, fix the first unsupported step and explain why it changed. A later check uses a changed case, not a copied answer.