

Confusion Matrix

Project: Responsible Plant Classifier

1. Confusion Matrix

Teach the learning cycle

Primary target: Build a labelled confusion matrix from matched reference and prediction pairs

Session · Sequence and minutes · Resources

Session: Session 1 · Understand · 45 min

Sequence and minutes: 0–7: recall and prerequisite; 7–15: inspect the concrete case and predict; 15–30: teacher models the worked trace; 30–40: learners explain a step using the text and visual; 40–45: check the core idea.

Resources: Sections 1–6; record the brief recall in the workbook.

Session: Session 2 · Practise · 45 min

Sequence and minutes: 0–5: retrieve the procedure; 5–15: W2 completion practice; 15–23: explain and check with a partner; 23–30: each learner answers the misconception check; 30–40: targeted reteaching or a harder variation; 40–45: prepare the investigation.

Resources: Sections 7–10; use the matching workbook W2 and misconception check.

Session: Session 3 · Investigate and transfer · 45 min

Sequence and minutes: 0–5: retrieve the decision rule; 5–20: investigate or trace; 20–30: start the independent case; 30–38: connect the project; 38–43: act on feedback; 43–45: plan the return check.

Resources: Sections 9 and 11–14. Give extra time to finish the full task set; use Section 15 when the week includes a coding lab.

This is a starting allocation of 135 minutes, not a validated duration. Preserve all named topics. Schedule extra time for connected examples, the full investigation, independent cases and project building. Repeated copies of a case share one recorded attempt; they are not new evidence.

Case exposure check: this source example appears in ai-2/13, ai-4/15. Reuse a familiar case for recall or

modelling; verify that the case used to assess transfer has not already received feedback.

Retrieval answer guidance

Scores and Calibration Intuition

Without opening the old lesson, explain one key idea from Scores and Calibration Intuition. Give an example and a mistake that the idea helps you avoid.

Look for: Interpret calibration using groups of forecasts

Reference example, not the only acceptable wording: Teacher explanation: $2/10=.2$ and $6/10=.6$.

Nearest Neighbors

Without opening the old lesson, explain one key idea from Nearest Neighbors. Give an example and a mistake that the idea helps you avoid.

Look for: Compute absolute distances and rank training neighbours

Reference example, not the only acceptable wording: Distances to A,B,C,D,E are 1,1,5,7,9 cm. A and B are equally far from 3 on the numeric feature; their labels do not enter the distance calculation.

Dataset Cards

Without opening the old lesson, explain one key idea from Dataset Cards. Give an example and a mistake that the idea helps you avoid.

Look for: Inspect row meaning missing values and repeated records

Reference example, not the only acceptable wording: One row is intended to represent one indoor practice trip. The source is a teacher-authored fictional export for this lesson, duration uses minutes, and None means unknown rather than zero.

Use the student module and workbook section with this exact week title. The worked case, independent question and answers below form one aligned lesson sequence.

What the learner must demonstrate

Positive=spotted. TP=6,FN=2,FP=3,TN=9. Draw a matrix with actual labels in rows and predictions in columns. Compute total and accuracy.

Concept to explain

A confusion matrix separates true positives, false positives, false negatives, and true negatives so error types remain visible.

Term · Meaning

Term: true positive

Meaning: positive case predicted positive

Term: false positive

Meaning: negative case predicted positive

Term: false negative

Meaning: positive case predicted negative

Term: true negative

Meaning: negative case predicted negative

Prepare the class

Use the supplied scenario, student illustrations and blank paper. For numeric work, offer counters or a calculator after learners show the setup. Fictional records are supplied; personal data and paid accounts are unnecessary.

Allow 80 minutes: recall 8; explanation 12; worked demonstration 15; guided practice 20; independent assessment 15; project and reflection 10. Extend the lab into a second session when needed.

Preparation for the connected explanation

Teach two 45-minute sessions. Start with ID cards and a physical two-by-two table so students count matched pairs before learning abbreviations. Use blocked as positive consistently. Keep raw counts visible and postpone precision and recall formulas to later weeks.

Readiness answer

IDs preserve which reference belongs to each prediction and which examples were wrong. The same accuracy can come from different predictions and error patterns.

Printed lesson and workbook

Eight ID cards carrying the worked reference and prediction pairs

Two-by-two sorting mat labelled reference rows and prediction columns

Optional Python 3 editor with no packages required

End goal for the pictorial case

By the end, I can explain confusion matrix using a traced example and a stated limitation.

This added worked case illustrates the week's main idea. Retain all original and connected topics; schedule its practice within the teaching cycle.

2. Explain the mechanism

Explain the mechanism

Trace the information, fitted behavior, and evaluation proof separately.

QUESTION Construct all four cells from twenty predictions and verify the total.

MODEL IDEA A confusion matrix separates true positives, false positives, false negatives, and true negatives so error types remain visible.

PROOF NEEDED Use an unseen case, visible calculation, error analysis, and a stated limitation.

UNDER THE HOOD For spotted=positive: TP=6, FP=3, FN=2, TN=9. Check total: $6 + 3 + 2 + 9 = 20$ cases.

Draw a fresh data → model → prediction → evaluation trace:

Predict first. Then check each step. A correct answer without visible evidence cannot be audited.

STEP 1 For spotted=positive: TP=6, FP=3, FN=2, TN=9.

STEP 2 Check total: $6 + 3 + 2 + 9 = 20$ cases.

STEP 3 Correct predictions = TP + TN = 15; accuracy = $15 \div 20 = 75\%$.

STEP 4 Inspect false alarms and misses separately before choosing an improvement.

CHECK Verify the denominator, unit, split, class definition, and data version before interpreting a score.

Recalculate, retrace, or restate the evidence independently:

Concrete teaching case

Positive is spotted. TP=8, FP=2, FN=4, TN=6.

Build actual-row/predicted-column matrix and total.

Exact explanation to model

Actual spotted row is 8 spotted,4 healthy; actual healthy row is 2 spotted,6 healthy. Total=20; correct=14. State axes and positive class.

Explain the added worked example

A confusion matrix shows which labels a classifier mixes up. It counts examples after predictions are made; it does not fit or repair the classifier. Week 12 had reference/prediction pairs clear/clear, blocked/blocked, clear/blocked. A labelled table can preserve the type of that error as well as the total score.

This week uses eight new fictional evaluation records from a frozen classifier. They are not extra predictions from the Week 12 code. Each ID appears once with a reviewed reference and one prediction. The grouped table below lists every ID. Keep reference and prediction paired by ID before counting.

Use reference labels for rows and predicted labels for columns. On both axes the order is clear, then blocked. Declare blocked as the positive class and clear as negative. Positive means the condition of interest, not good or safe. A missed blocked case and a false alarm are different errors.

index maps clear to 0 and blocked to 1. Each paired record adds one to its reference row and prediction column. The script prints `[[2, 1], [2, 3]]` then `5 8`. It assumes unique IDs and only these two labels. Check IDs and missing or unresolved references before counting; the code does not validate all those conditions.

The diagonal cells count correct predictions: $2+3=5$. Off-diagonal cells count mistakes: $1+2=3$. Every record must contribute exactly once. This is a count matrix, not percentages or probabilities. Keep the axis labels even when copying the numbers.

Key terms

Term · Meaning

Term: Confusion matrix

Meaning: A table counting reference and prediction combinations

Term: Positive class

Meaning: The class chosen as the condition of interest

Term: False positive

Meaning: A positive prediction when the reference is negative

Term: False negative

Meaning: A negative prediction when the reference is positive

Model the reasoning aloud

Use the complete worked example below before asking learners to complete W2. Reveal a small part, invite a prediction, then explain the deciding step. These teacher notes contain solutions; do not reveal the independent case answer during modelling.

Blocked is the positive class

Reference and prediction · Cell name · IDs and count

Reference and prediction: clear then clear

Cell name: True negative TN

IDs and count: V1 V2 count 2

Reference and prediction: clear then blocked

Cell name: False positive FP

IDs and count: V3 count 1

Reference and prediction: blocked then clear

Cell name: False negative FN

IDs and count: V4 V5 count 2

Reference and prediction: blocked then blocked

Cell name: True positive TP

IDs and count: V6 V7 V8 count 3

Read reference first and prediction second. Here a false positive is a false blocked alarm; a false negative is a missed blocked case.

Place V3 and V4 in the matrix. Explain which is a false positive and which is a false negative when blocked is positive.

True means prediction agrees with the reference. It does not prove that the reference annotation is infallible. Resolve disputed labels with the documented review policy rather than silently changing them to match predictions.

Thinking move · Teacher prompt

Thinking move: Plan

Teacher prompt: What is given? What is the question? Which procedure fits these facts?

Thinking move: Do

Teacher prompt: Point to each input and intermediate step in the worked trace. Name the rule that allows the next step.

Thinking move: Check

Teacher prompt: Does the output answer the question? Which assumption or limitation prevents a larger claim?

Use the diagram and verbal explanation together. Ask learners to match a sentence to a specific visual step; do not assign learners fixed visual or auditory learning styles.

A pictorial worked case: Confusion Matrix

Read the confusion matrix as four distinct stories about a plant decision.

The facts we will use

Positive means spotted. Toy results: TP=4, FN=1, FP=3, TN=12. Rows are actual spotted/healthy; columns predicted spotted/healthy.

All inputs and outcomes in this worked example are invented classroom data; no real model run is claimed.

Positive means spotted

	predicted spotted	predicted healthy
actual spotted	4	1
actual healthy	3	12

Read a cell using both its row and column labels.

Confusion Matrix

Start with the supplied facts

Follow each arrow. Ask which fact allows the next step.



1. Fill actual spotted row

Actual spotted: [4, 1]. Four caught; one missed.



2. Fill actual healthy row

Actual healthy: [3, 12]. Three false alarms; twelve correctly clear.



3. Compute accuracy

Correct=4+12=16 of total 20, giving 80%.

CHANGE ONE THING

A review corrects one missed spotted leaf, moving it from FN to TP.

Explain the changed result using the matching lesson.

Read the picture one step at a time

Step · What happens and why

Step: 1. Fill actual spotted row

What happens and why: Actual spotted: [4, 1]. Four caught; one missed.

Step: 2. Fill actual healthy row

What happens and why: Actual healthy: [3, 12]. Three false alarms; twelve correctly clear.

Step: 3. Compute accuracy

What happens and why: Correct=4+12=16 of total 20, giving 80%.

Match each pictured step to the supplied facts. This is a worked teaching case, not an independent assessment.

Why this result follows

Read the picture in order. Correct=4+12=16 of total 20, giving 80%. The arrows show which recorded input or intermediate result each decision uses. Explain the deciding step aloud before checking the changed case; pointing to the final answer alone does not show how it follows.

What this example does not establish

The matrix depends on positive-class definition and reference labels. Accuracy alone hides the difference between misses and false alarms.

Change one thing in the pictured case

Change: A review corrects one missed spotted leaf, moving it from FN to TP.

Prediction: Counts become TP 5, FN 0, FP 3, TN 12; accuracy is $17/20=85\%$.

Reason: One decision becomes correct while the total number of evaluated leaves remains 20.

Ask while showing the picture

Cover the result. Ask learners to name the inputs and predict the next step. Uncover one step, connect the icon to the actual procedure, and explain its evidence. Then change the supplied condition and compare. The picture is a representation; it does not document execution of a real AI model.

3. Demonstrate and guide practice

Demonstrate and guide practice

Board sequence

Write the given facts: Positive is spotted. TP=8, FP=2, FN=4, TN=6.

Write the question to explain: Build actual-row/predicted-column matrix and total.

Reveal after predictions: Actual spotted row is 8 spotted, 4 healthy; actual healthy row is 2 spotted, 6 healthy. Total=20; correct=14. State axes and positive class.

Keep for an independent attempt: Treat fern as positive. Counts are TP=6, FP=2, FN=3 and TN=9. How many examples and how many correct predictions are there?

Classroom dialogue

Ask: Which facts are given, and which would we have to assume? Learners mark relevant details before discussing answers.

Say: Predict first. Show the rule, information path or calculation that would produce the result. A correct guess is not yet an explanation.

Reveal reasoning one step at a time. Explain why a tempting alternative fails. Write units and denominators for arithmetic, trace conditions for decisions, and identify supporting sources for claims.

In pairs, one learner solves while the other checks evidence; exchange roles. Remove the worked answer before independent assessment.

Model these guided questions

Guided: V3 belongs at reference clear/predicted blocked, FP. V4 belongs at reference blocked/predicted clear, FN. Exit: both have five diagonal matches, but distribute three mistakes differently: $FP=1, FN=2$ versus $FP=0, FN=3$. Report identical evaluation records, axes, label order, positive class, totals and task consequences before comparing.

Case-specific teaching sequence

Stage · Teacher action

Stage: Session 1 start to 7 minutes

Teacher action: Retrieve the three Week 12 reference/prediction pairs and explain why accuracy loses error detail.

Stage: 7 to 18 minutes

Teacher action: Sort all eight new ID cards into labelled cells. Complete W1 before showing code output.

Stage: 18 to 32 minutes

Teacher action: Trace the counting code. Connect each increment to a cell and check the diagonal.

Stage: 32 to 45 minutes

Teacher action: Declare blocked positive, read the visual and complete W2 and the guided question.

Stage: Session 2 start to 8 minutes

Teacher action: Retrieve row versus column meaning and the positive class without relying on cell position alone.

Stage: 8 to 20 minutes

Teacher action: Check totals and compare equal-accuracy matrices in W3. Explain the different error tradeoffs.

Stage: 20 to 35 minutes

Teacher action: Collect W4 independently before support. Require labelled axes, totals and ID-level error explanations.

Stage: 35 to 45 minutes

Teacher action: Use W5 and the exit question to limit claims. Offer the fresh retry after feedback and record support.

Reduce help deliberately

Completion task: Declare blocked positive. Give TP,TN,FP,FN counts and explain V3 and V4 in plain language. Does positive mean a desirable outcome?

Teacher check: TP=3, TN=2, FP=1, FN=2. V3 predicts blocked for a reference-clear case, a false alarm or FP. V4 predicts clear for a reference-blocked case, a missed blocked case or FN. Positive names the chosen class; it does not mean desirable.

Start by identifying the given inputs together. Leave the intermediate steps blank. If needed, model one step, then withdraw that help on the next step. Move to a full trace only when the partial trace is understood. For partners, alternate explainer and checker; collect a response from every learner before discussion.

Individual reasoning check

Use the worked case for Confusion matrices. Proposed explanation: "Positive means good". Decide whether this explanation is supported. Point to the step or supplied fact that decides; explain your repair if needed.

Expected correction: Positive is the chosen condition of interest; blocked is positive in this exercise.

Collect explanations, not only yes/no votes. If a misunderstanding is common, re-model the relevant step for the class. If it affects a few learners, give a short targeted group explanation while others solve a more demanding variation.

Pictorial practice question

Why is adding TP alone without reducing FN an incorrect revision? Point to the relevant step in the picture,

then write the changed result and the rule or evidence that supports it.

Reasoned teacher answer

The same leaf changes category; it does not become a new evaluated case. Move one count from FN to TP to preserve the total 20. Changed-case check: Counts become TP 5, FN 0, FP 3, TN 12; accuracy is $17/20=85\%$. One decision becomes correct while the total number of evaluated leaves remains 20.

Changed-case reasoning: Counts become TP 5, FN 0, FP 3, TN 12; accuracy is $17/20=85\%$. One decision becomes correct while the total number of evaluated leaves remains 20.

Collect each learner's explanation before discussion. Use the first missing connection between input, deciding step and result to choose support. This question is worked-case practice, not fresh mastery evidence.

4. Run the weekly evidence lab

Run the weekly evidence lab

Keep the test conditions fixed, record every result, and change only one planned factor.

1. Write the hypothesis and expected evidence before running.
2. Matrix Build: convert twenty actual/predicted pairs into four cells, recompute totals, and explain each error in plain language.
3. Run one normal, one boundary, one missing, and one shifted case.
4. Calculate the metric from raw counts or row-level errors.
5. Interpret what changed, what did not, and what remains unsafe or unknown.

Make the lab runnable

Use the concrete case as the shared normal case and the independent question as a second case. Each pair creates a boundary or missing-information case and predicts its result before testing. Keep the expected result separate from an observed mistake.

Record · What to capture

Record: Input or evidence

What to capture: Exact data, instruction or claim

Record: Expected result

What to capture: Answer or safe fallback declared before the run

Record: Observed result

What to capture: Actual result, including errors

Record: Explanation

What to capture: Rule, calculation or evidence explaining the outcome

Record: Next test

What to capture: One justified change and a new prediction

Diagnose and reteach

MISCONCEPTION TO REPAIR The diagonal alone tells everything important about a classifier.

For guessing, return to given facts and request a trace. For vocabulary without application, use one example and one non-example. For arithmetic errors, check the setup before the calculation. Finish with a different uncoached case before recording mastery.

Address these additional misconceptions

Positive means good: Positive is the chosen condition of interest; blocked is positive in this exercise.

A matrix has one universal visual orientation: Check whether rows are references or predictions and inspect class order. Our convention uses reference rows and prediction columns.

Zero errors in a cell means no future risk: It is an observed count on one evaluation set. Coverage, sample size and future conditions still matter.

Match the support to the first error

What the response shows · Next teaching action

What the response shows: Missing or misread facts

Next teaching action: Read the case aloud, mark supplied versus unknown facts, and let the learner restate it.

What the response shows: Wrong procedure

Next teaching action: Return to the deciding step in the worked case. Contrast it with the proposed incorrect explanation.

What the response shows: Arithmetic or implementation error

Next teaching action: Trace intermediate values or lines; preserve the first mismatch and retry that step.

What the response shows: Correct result without a reason

Next teaching action: Ask for a trace and a changed case before marking independent understanding.

What the response shows: An unsupported wider claim

Next teaching action: Ask which supplied evidence supports the claim and which further observation would be needed.

Offer an oral explanation, drawing, enlarged visual or fewer examples when that removes a reading/writing barrier. Keep the same reasoning goal. Stretch secure learners by changing a boundary or assumption and asking them to defend the effect, not simply by assigning more of the same questions.

5. Assess and explain the answers

Assess and explain the answers

Worked case answer

Actual spotted row is 8 spotted, 4 healthy; actual healthy row is 2 spotted, 6 healthy. Total=20; correct=14. State axes and positive class.

Independent question

Treat fern as positive. Counts are TP=6, FP=2, FN=3 and TN=9. How many examples and how many correct predictions are there?

Expected independent answer

Total is $6+2+3+9 = 20$. Correct predictions are $TP+TN = 15$; accuracy is $15/20 = 75\%$.

What counts as evidence

Criterion · 0 points · 1 point · 2 points

Criterion: Result

0 points: Incorrect or absent

1 point: Partly correct

2 points: Correct with necessary conditions

Criterion: Reasoning

0 points: No supporting trace

1 point: Some steps

2 points: Clear mechanism, calculation or source support

Criterion: Limit

0 points: Overclaims certainty

1 point: Vague limitation

2 points: Relevant uncertainty or missing fact

Criterion: Transfer

0 points: Copies without adapting

1 point: Adapts with prompts

2 points: Solves a changed case independently

Use 6/8 as a classroom checkpoint, with 2 required for both Result and Reasoning. This is a proposed teaching rule, not a validated certification threshold. Do not count a coached answer as independent mastery; correct unsafe or unsupported claims regardless of total.

Feedback

Ask the learner to find the evidence that challenges this claim: “False positives and false negatives belong in the correct-prediction total.” Keep the first attempt and an uncoached retry separate.

Original transfer answer

Actual-positive row is 6 predicted-positive and 2 predicted-negative; actual-negative row is 3 and 9. Total=20, correct=15, accuracy=75%. Axes and class labels are essential; swapping FP and FN changes later metrics.

Explanations for the additional workbook examples

W1 Build the count matrix

Use all eight worked IDs. Draw a matrix with reference rows and prediction columns, both ordered clear

then blocked. Place the IDs in cells before writing the counts.

Reference clear/predicted clear contains V1,V2: 2. Clear/blocked contains V3: 1. Blocked/clear contains V4,V5: 2. Blocked/blocked contains V6,V7,V8: 3. Matrix $[[2,1],[2,3]]$.

W2 Explain the two error types

Declare blocked positive. Give TP,TN,FP,FN counts and explain V3 and V4 in plain language. Does positive mean a desirable outcome?

TP=3, TN=2, FP=1, FN=2. V3 predicts blocked for a reference-clear case, a false alarm or FP. V4 predicts clear for a reference-blocked case, a missed blocked case or FN. Positive names the chosen class; it does not mean desirable.

W3 Audit totals and equal accuracy

Give the worked row totals, column totals, total count and accuracy. Compare its errors with $[[3,0],[3,2]]$ using the same axes and eight reference records.

Rows total 3,5; columns total 4,4; total 8; accuracy $(2+3)/8=5/8=62.5$ percent. The comparison matrix also scores 5/8, but has FP=0 and FN=3 rather than FP=1 and FN=2. Same accuracy can hide different error types.

W4 Count a fresh evaluation independently

Each pair below is reference then prediction: R1 clear/clear, R2 clear/blocked, R3 clear/blocked, R4 blocked/blocked, R5 blocked/clear, R6 blocked/blocked. Use clear then blocked on both axes and reference rows. Build the matrix, give row and column totals, name TP,TN,FP,FN with blocked positive, and calculate accuracy.

Matrix $[[1,2],[1,2]]$. Row totals 3,3; column totals 2,4; total 6. TP=2,TN=1,FP=2,FN=1. Accuracy $(1+2)/6=3/6=50$ percent. False alarms are R2,R3; the missed blocked case is R5.

W5 Interpret a zero count carefully

A report gives zero false positives but omits the evaluated sample size, axes and class definitions. What information is missing, and why does zero not prove that future false alarms are impossible?

Request split and sample size, labelled reference/prediction axes, class order and positive-class definition, plus the remaining counts. Zero describes only the observed evaluation cases; limited coverage or few negative cases may hide future errors. It is not a guarantee.

Assess independent transfer

Selected case: On20 cases: true positives5, false negatives4, false positives2, true negatives9. Build the confusion matrix with actual class as rows and predicted class as columns. Compute accuracy.

Selected case answer

Actual positive row: predicted positive5, predicted negative4. Actual negative row: predicted positive2, predicted negative9. Total20; correct14; accuracy70%. Actual positives total9. State the positive-class definition before interpreting the errors.

Dimension · Evidence required

Dimension: Explanation

Evidence required: Names the applicable idea or procedure and ties it to the supplied facts.

Dimension: Trace and result

Evidence required: Preserves the given inputs and shows the relevant intermediate steps; distinguishes a prediction from an observed execution.

Dimension: Limits

Evidence required: States the assumptions, missing evidence or conditions under which the result would change.

Record each dimension as not yet, with support, or independent. Accept a valid alternative procedure with a defensible trace. Do not penalise an honestly recorded model failure if the learner correctly explains its evidence and limits.

Feedback that the learner uses

Name the earliest unsupported step and give one action to repair it. Have the learner make that repair now and explain why. Then assess the relevant skill on a fresh, fully specified case. Confirm it was not previously practised with feedback; solve and check the new case before assigning it. A follow-up design prompt is a starting brief, not automatically an equivalent test.

6. Connect and extend learning

Connect and extend learning

Responsible Plant Classifier

Publish the Plant Classifier confusion matrix with positive-class definition, counts, denominator, and test-set version.

Keep the decision, input, result, explanation and remaining limitation in the project evidence record. Retrieve this record next week rather than restarting the project.

Support and stretch

Use a tiny labelled dataset, explicit units and a named positive class. Stretch: require a baseline, held-out evaluation and subgroup or shifted-condition analysis with denominators.

Exit reflection

Ask for one decision the learner can now justify and one situation requiring more evidence or human review. Confidence ratings are separate from correct independent performance.

Bridge to the next week

Next: Week 16: Accuracy and Imbalance. Retrieve today's evidence and identify what carries forward and what is new.

Support and fresh reassessment

Give a blank labelled matrix and move one ID card at a time. Ask for reference first, prediction second before naming a cell. Extension: declare clear positive without changing the worked records. Then $TP=2, TN=3, FP=2, FN=1$; explain why the original matrix counts and accuracy remain unchanged if axis order stays clear then blocked.

Require W4 $[[1,2],[1,2]]$, row totals 3,3, column totals 2,4, $TP=2, TN=1, FP=2, FN=1$ and accuracy 3/6. Fresh retry: S1 blocked/blocked, S2 blocked/clear, S3 clear/clear, S4 clear/clear, S5 clear/blocked, always reference first. Matrix $[[2,1],[1,1]]$, rows 3,2, columns 3,2, $TP=1, TN=2, FP=1, FN=1$, accuracy 3/5. Require labelled axes and blocked positive before accepting abbreviations.

Week 14 covers accuracy and class imbalance. Carry forward row totals, class definitions and the full confusion matrix. Teacher reference: https://scikit-learn.org/stable/modules/generated/sklearn.metrics.confusion_matrix.html (reference rows, prediction columns and label order; reviewed 2026-09-28).

Plan the delayed return

Suggested return points in this level: ai-4/16, ai-4/18, ai-4/21. Use actual classroom dates, adjusting for holidays and gaps. One, three and six teaching weeks are scheduling choices, not a claimed optimal spacing.

At a delayed check, ask for the idea from memory and a changed application. Compare with the earlier independent response and record support used. For a new level, revisit the previous capstone before checking the new prerequisites.

Record · Teacher evidence

Record: Learner code and date

Teacher evidence: _____

Record: Concept and case used; prior exposure

Teacher evidence: _____

Record: Explanation / trace / limits

Teacher evidence: _____

Record: Support and first repair

Teacher evidence: _____

Record: Changed case and delayed outcome

Teacher evidence: _____

Record: Next teaching action

Teacher evidence: _____

Use the evidence to choose reteaching or the next step. A completed page, confidence rating or attractive project does not by itself demonstrate understanding.

Project evidence from this case

For your Responsible Plant Classifier, save the input, procedure, observed result and limitation of this check. Label this worked example as practice; use a different, previously unreviewed case when checking independent understanding.