

Parameters and architecture

Project: Image-pattern Network Investigation

1. Recall and choose your starting point

Try the recall before opening notes. Then use a different colour or a labelled second line to correct your explanation.

Forward passes by hand

Without opening the old lesson, explain one key idea from Forward passes by hand. Give an example and a mistake that the idea helps you avoid.

My remembered idea, example and correction

Activation functions

Without opening the old lesson, explain one key idea from Activation functions. Give an example and a mistake that the idea helps you avoid.

My remembered idea, example and correction

Representing inputs as vectors

Without opening the old lesson, explain one key idea from Representing inputs as vectors. Give an example and a mistake that the idea helps you avoid.

My remembered idea, example and correction

2. Practise with fading help

Use W2: Sort the quantities for Parameters and architecture. Record the answer once; the lesson and workbook refer to the same attempt.

Given inputs · Procedure I chose · Middle steps · Result and check

Given inputs: _____

Procedure I chose: _____

Middle steps: _____

Result and check: _____

The step I completed without help, and the hint I needed

3. Individual reasoning check

Use the worked case for Parameters and architecture. Proposed explanation: “Count one bias per input”. Decide whether this explanation is supported. Point to the step or supplied fact that decides; explain your repair if needed.

My explanation before partner discussion

4. Independent transfer case

Independent case: Count a new architecture independently

A dense 3 to 2 to 2 network uses ReLU in the hidden layer and identity in the output layer, with one bias per unit. Give each layer count and the total. If hidden width becomes 4, recount and explain why activation values are excluded.

My independent explanation, trace and limits

Attempt this case before feedback. Record any help. Earlier examples below are further practice; a case already practised with feedback cannot establish fresh transfer.

5. W1 Count a single layer

A dense layer has 4 inputs and 2 outputs with one bias per output. Count weights, biases and total.

My reasoning and evidence

6. W2 Sort the quantities

Classify hidden activation 0.7, weight -2, hidden width 3 and learning rate 0.1 as computed value, parameter, architecture choice or training setting.

My reasoning and evidence

7. W3 Change the bias convention

Recount the 2 to 3 to 1 model if every bias is omitted. State what the original count assumed.

My reasoning and evidence

8. W4 Count a new architecture independently

A dense 3 to 2 to 2 network uses ReLU in the hidden layer and identity in the output layer, with one bias per unit. Give each layer count and the total. If hidden width becomes 4, recount and explain why activation values are excluded.

My reasoning and evidence

9. W5 Limit a size claim

A team says its 26-parameter model must outperform a 14-parameter model. Give a fair check and one reason the claim is unsupported.

My reasoning and evidence

10. Project checkpoint and reflection

Add a labelled parameters and architecture evidence sheet to Image-pattern Network Investigation. Show how you can distinguish architectural choices from parameter values. Use the supplied fictional case and keep its inputs, intermediate steps, calculation or prediction, and limitation. Connect this record to last week's record; a matching answer without a trace is insufficient.

My project change, supporting evidence and remaining limit

11. Feedback, return check and learning record

Evidence · My record

Evidence: Worked alone / hint / model

My record: _____

Evidence: First step I repaired and why

My record: _____

Evidence: New case checked later; date and result

My record: _____

Evidence: What I can now explain without notes

My record: _____

Evidence: One remaining question

My record: _____

Revisit this idea with your teacher after a delay. Familiarity is different from explaining and using it on a changed case.

12. Pictorial case practice: Parameters and architecture

Count trainable weights and biases separately from activation functions.

Dense toy architecture 2 inputs → 3 hidden units → 1 output. Every hidden and output unit has one bias; hidden activation is ReLU.

All inputs and outcomes in this worked example are invented classroom data; no real model run is claimed.

Trainable parameter count

	weights	biases	total
input to hidden	6	3	9
hidden to output	3	1	4

Read a cell using both its row and column labels.

Parameters and architecture

Start with the supplied facts

Follow each arrow. Ask which fact allows the next step.



1. Count first layer

$2 \times 3 = 6$ weights plus 3 biases gives 9 parameters.



2. Count output layer

$3 \times 1 = 3$ weights plus 1 bias gives 4 parameters.



3. Total

Total trainable parameters $= 9 + 4 = 13$; ReLU adds no parameters here.

CHANGE ONE THING

Increase hidden width from 3 to 4.

Explain the changed result using the matching lesson.

How many new parameters did that one hidden unit add? Point to the relevant step in the picture, then write the changed result and the rule or evidence that supports it.

My picture-based explanation and changed-case prediction

Support used: alone / hint / worked example. This record is practice evidence.

Project connection: For your Image-pattern Network Investigation, save the input, procedure, observed result and limitation of this check. Label this worked example as practice; use a different, previously unreviewed case when checking independent understanding.