

Pooling and spatial information

Project: Image-pattern Network Investigation

1. Prepare the purpose, prerequisites and materials

Teach the learning cycle

Primary target: Compute max and mean pooling under an explicit window rule

Session · Sequence and minutes · Resources

Session: Session 1 · Understand · 45 min

Sequence and minutes: 0–7: recall and prerequisite; 7–15: inspect the concrete case and predict; 15–30: teacher models the worked trace; 30–40: learners explain a step using the text and visual; 40–45: check the core idea.

Resources: Sections 1–6; record the brief recall in the workbook.

Session: Session 2 · Practise · 45 min

Sequence and minutes: 0–5: retrieve the procedure; 5–15: W2 completion practice; 15–23: explain and check with a partner; 23–30: each learner answers the misconception check; 30–40: targeted reteaching or a harder variation; 40–45: prepare the investigation.

Resources: Sections 7–10; use the matching workbook W2 and misconception check.

Session: Session 3 · Investigate and transfer · 45 min

Sequence and minutes: 0–5: retrieve the decision rule; 5–20: investigate or trace; 20–30: start the independent case; 30–38: connect the project; 38–43: act on feedback; 43–45: plan the return check.

Resources: Sections 9 and 11–14. Give extra time to finish the full task set; use Section 15 when the week includes a coding lab.

This is a starting allocation of 135 minutes, not a validated duration. Preserve all named topics. Schedule extra time for connected examples, the full investigation, independent cases and project building. Repeated copies of a case share one recorded attempt; they are not new evidence.

Retrieval answer guidance

Convolution as a local operation

Without opening the old lesson, explain one key idea from Convolution as a local operation. Give an example and a mistake that the idea helps you avoid.

Look for: Compute a local weighted sum at each valid image position

Reference example, not the only acceptable wording: Teacher explanation: Window rows are [2, 0] and [1, 3]. Products are 2, 0, 0 and 3, giving output 5.

Learned representations

Without opening the old lesson, explain one key idea from Learned representations. Give an example and a mistake that the idea helps you avoid.

Look for: Trace an input through a hidden representation and a decision rule

Reference example, not the only acceptable wording: Teacher explanation: The vectors are [5, 0], [0, 5] and [0, 0]. Predictions are 1, 0 and 0. Equal width and height does not satisfy strictly greater.

Regularisation and early stopping

Without opening the old lesson, explain one key idea from Regularisation and early stopping. Give an example and a mistake that the idea helps you avoid.

Look for: Separate a weight penalty from prediction error

Reference example, not the only acceptable wording: Teacher explanation: MSE 0, penalty 2, total J 2, total gradient 2. Zero data gradient does not remove the penalty gradient.

Use two 45-minute sessions. Prepare a labelled 4 by 4 grid with four window outlines. State complete windows, stride 2 and no padding before any arithmetic. Keep pooling separate from ReLU, and discuss loss of location through explicit collisions. Reference for the floor-based pooling convention: <https://docs.pytorch.org/docs/stable/generated/torch.nn.modules.pooling.MaxPool2d.html> . No software library is required.

Outcomes

Compute max and mean pooling under an explicit window rule

Use collisions to explain lost spatial information

Test boundary and movement claims with revealing examples

Preparation

Printed lesson and workbook; paper and pencil

Calculator and optional local Python 3 editor; no packages or AI accounts needed

Use the fictional examples supplied; prepare the fresh retry before class

Prerequisite answer

Only the start at row 0 column 0 fits. The output shape is 1 by 1 under the complete-window rule.

End goal for the pictorial case

By the end, I can explain pooling and spatial information using a traced example and a stated limitation.

This added worked case illustrates the week's main idea. Retain all original and connected topics; schedule its practice within the teaching cycle.

2. Explain and model the mechanism

A fictional single-channel feature map has rows [1, 4, 2, 0], [3, 2, 5, 1], [0, 6, 1, 3] and [2, 4, 2, 7]. Use a 2 by 2 window, stride 2, no padding and only complete windows. Coordinates are zero-based. The four starts are [0, 0], [0, 2], [2, 0] and [2, 2].

Max pooling keeps the largest value in each window. Mean pooling adds the four values and divides by 4. Neither operation learns weights in this lesson. These are fixed summaries of the incoming feature map, unlike the trainable kernel parameters introduced last week.

The max output is [[4, 5], [6, 7]], and the mean output is [[2.5, 2], [3, 3.25]]. Both have shape 2 by 2. Sixteen values become four, but the four outputs still preserve the coarse arrangement of the four regions.

This code assumes a nonempty rectangular numeric map at least 2 by 2. It uses only complete 2 by 2 windows, stride 2 and no padding. It returns two separate summaries of the same map; it does not apply one pooling operation after the other.

For this complete-window rule the output shape is $\text{floor}((H - 2) / 2) + 1$ by $\text{floor}((W - 2) / 2) + 1$. A 3 by 3 map produces just one output; its last row and last column are not read. Do not silently invent a partial-window rule or pad missing positions.

Term · Meaning

Term: Max pooling

Meaning: Replacing each window by its largest value

Term: Mean pooling

Meaning: Replacing each window by the arithmetic mean of its values

Term: Spatial information

Meaning: Information about where values occur and how positions relate

Term: Pooling collision

Meaning: Different inputs producing the same pooled values

A maximum does not identify its location

Input window rows · Maximum · Mean

Input window rows: [4 0] and [0 0]

Maximum: 4

Mean: 1

Input window rows: [0 4] and [0 0]

Maximum: 4

Mean: 1

Input window rows: [4 4] and [4 4]

Maximum: 4

Mean: 4

The first two windows differ in the position of their nonzero value yet have the same maximum and mean. The third has the same maximum but a different mean. Each summary retains some distinctions and discards others.

Guided: both windows have maximum 6 and mean 1.5. Either scalar alone cannot distinguish their different nonzero positions. Exit: the first two visual windows collide, so exact reconstruction is impossible from the pooled values alone. The 8 crossing from column 1 to column 2 changes the pooled map, so universal shift invariance does not follow.

Model the reasoning aloud

Use the complete worked example below before asking learners to complete W2. Reveal a small part, invite a prediction, then explain the deciding step. These teacher notes contain solutions; do not reveal the independent case answer during modelling.

A maximum does not identify its location

Input window rows · Maximum · Mean

Input window rows: [4 0] and [0 0]

Maximum: 4

Mean: 1

Input window rows: [0 4] and [0 0]

Maximum: 4

Mean: 1

Input window rows: [4 4] and [4 4]

Maximum: 4

Mean: 4

The first two windows differ in the position of their nonzero value yet have the same maximum and mean. The third has the same maximum but a different mean. Each summary retains some distinctions and discards others.

Compare windows $[[0, 0], [6, 0]]$ and $[[0, 0], [0, 6]]$. Compute both summaries. Can a deterministic head receiving only either scalar distinguish bottom-left from bottom-right?

Thinking move · Teacher prompt

Thinking move: Plan

Teacher prompt: What is given? What is the question? Which procedure fits these facts?

Thinking move: Do

Teacher prompt: Point to each input and intermediate step in the worked trace. Name the rule that allows the next step.

Thinking move: Check

Teacher prompt: Does the output answer the question? Which assumption or limitation prevents a larger claim?

Use the diagram and verbal explanation together. Ask learners to match a sentence to a specific visual step; do not assign learners fixed visual or auditory learning styles.

A pictorial worked case: Pooling and spatial information

Pool a small map and show the detail it cannot retain.

The facts we will use

Feature map rows [1, 4, 2, 0],[3, 2, 5, 1]. Pool non-overlapping2x2 windows, stride2, no padding.

All inputs and outcomes in this worked example are invented classroom data; no real model run is claimed.

AI ACADEMY / AI-5/22

Two adjacent pooling windows

	left0	left1	right0	right1
row0	1	4	2	0
row1	3	2	5	1

Read a cell using both its row and column labels.

Pooling and spatial information

Start with the supplied facts

Follow each arrow. Ask which fact allows the next step.



1. Left window

Values 1, 4, 3, 2: max 4, mean 2.5.



2. Right window

Values 2, 0, 5, 1: max 5, mean 2.



3. Compare summaries

Max map $[[4, 5]]$, mean map $[[2.5, 2]]$, both shape 1 x 2.

CHANGE ONE THING

Swap 1 and 4 within the left window.

Explain the changed result using the matching lesson.

Read the picture one step at a time

Step · What happens and why

Step: 1. Left window

What happens and why: Values 1, 4, 3, 2: max 4, mean 2.5.

Step: 2. Right window

What happens and why: Values 2, 0, 5, 1: max 5, mean 2.

Step: 3. Compare summaries

What happens and why: Max map $[[4, 5]]$, mean map $[[2.5, 2]]$, both shape 1×2 .

Match each pictured step to the supplied facts. This is a worked teaching case, not an independent assessment.

Why this result follows

Pooling compresses each local window into a summary. Maximum keeps its largest value; mean keeps its average. Neither summary records where each value appeared. Swapping values inside one window leaves both summaries unchanged here, so the pooled output cannot reconstruct the original arrangement. The chosen window, stride and boundary policy determine the output shape.

What this example does not establish

Pooling is a declared aggregation, not automatic improvement; losing location can harm tasks that need precise positions.

Change one thing in the pictured case

Change: Swap 1 and 4 within the left window.

Prediction: Both pooled maps remain unchanged.

Reason: Max and mean ignore the positions of values inside the same window.

Ask while showing the picture

Cover the result. Ask learners to name the inputs and predict the next step. Uncover one step, connect the icon to the actual procedure, and explain its evidence. Then change the supplied condition and compare. The picture is a representation; it does not document execution of a real AI model.

3. Demonstrate and guide practice

Time or stage · Teacher action

Time or stage: Session 1 start to 7 minutes

Teacher action: Retrieve valid window starts and mark the four nonoverlapping regions.

Time or stage: 7 to 18 minutes

Teacher action: Calculate both summaries in the first region, then complete W1.

Time or stage: 18 to 32 minutes

Teacher action: Trace the remaining regions and run or hand-trace the optional code.

Time or stage: 32 to 45 minutes

Teacher action: Use W2 and the visual to distinguish lost location from retained regional arrangement.

Time or stage: Session 2 start to 8 minutes

Teacher action: Complete the guided collision and discuss why storing a maximum position is still insufficient for reconstruction.

Time or stage: 8 to 20 minutes

Teacher action: Use W3 to expose the omitted border, then trace the movement counterexample in W5.

Time or stage: 20 to 35 minutes

Teacher action: Collect W4 independently, requiring signed sums and both maps without applying ReLU.

Time or stage: 35 to 45 minutes

Teacher action: Use the exit response to qualify claims, then administer the fresh retry.

Use the worked example in Sections 3 and 6. Collect a prediction before revealing its result; ask the learner to point to each intermediate fact.

Provide separate columns for window values, sum, divisor, maximum and mean. Use numbered positions rather than colour alone. Extension: enumerate all sixteen binary 2 by 2 windows, group them by maximum and mean, and identify collisions under each summary.

Reduce help deliberately

Completion task: Give two different 2 by 2 windows containing exactly one 4 and three zeros that have the same maximum and mean. Explain why either scalar alone cannot identify the position of the 4.

Teacher check: Teacher explanation: For example, $[[4, 0], [0, 0]]$ and $[[0, 4], [0, 0]]$ both give maximum 4 and mean 1. A deterministic head receiving the same scalar must give the same output, so it cannot distinguish those positions.

Start by identifying the given inputs together. Leave the intermediate steps blank. If needed, model one step, then withdraw that help on the next step. Move to a full trace only when the partial trace is understood. For partners, alternate explainer and checker; collect a response from every learner before discussion.

Individual reasoning check

Use the worked case for Pooling and spatial information. Proposed explanation: “Max pooling turns negative numbers into zero”. Decide whether this explanation is supported. Point to the step or supplied fact that decides; explain your repair if needed.

Expected correction: That is a ReLU behaviour, not the maximum of an all-negative window.

Collect explanations, not only yes/no votes. If a misunderstanding is common, re-model the relevant step for the class. If it affects a few learners, give a short targeted group explanation while others solve a more demanding variation.

Pictorial practice question

Can the max map reveal where the 4 originally appeared? Point to the relevant step in the picture, then write the changed result and the rule or evidence that supports it.

Reasoned teacher answer

No. The original 4 was top-right in the left window, but after swapping it is top-left; the pooled value 4 is identical. Changed-case check: Both pooled maps remain unchanged. Max and mean ignore the positions of values inside the same window.

Changed-case reasoning: Both pooled maps remain unchanged. Max and mean ignore the positions of values inside the same window.

Collect each learner’s explanation before discussion. Use the first missing connection between input, deciding step and result to choose support. This question is worked-case practice, not fresh mastery evidence.

4. Run the investigation and diagnose misconceptions

Max pooling turns negative numbers into zero: That is a ReLU behaviour, not the maximum of an all-negative window.

Pooling removes all spatial information: A local pooled grid retains coarse regional arrangement while losing within-window detail.

Saving the maximum position restores the input: Other values remain unknown even when a unique maximum location is recorded.

Use Section 9 for the evidence ledger. Add a boundary or missing-input case and record the expected response before checking. More successful repeats of one case do not establish wider coverage.

Match the support to the first error

What the response shows · Next teaching action

What the response shows: Missing or misread facts

Next teaching action: Read the case aloud, mark supplied versus unknown facts, and let the learner restate it.

What the response shows: Wrong procedure

Next teaching action: Return to the deciding step in the worked case. Contrast it with the proposed incorrect explanation.

What the response shows: Arithmetic or implementation error

Next teaching action: Trace intermediate values or lines; preserve the first mismatch and retry that step.

What the response shows: Correct result without a reason

Next teaching action: Ask for a trace and a changed case before marking independent understanding.

What the response shows: An unsupported wider claim

Next teaching action: Ask which supplied evidence supports the claim and which further observation would be needed.

Offer an oral explanation, drawing, enlarged visual or fewer examples when that removes a reading/writing barrier. Keep the same reasoning goal. Stretch secure learners by changing a boundary or assumption and asking them to defend the effect, not simply by assigning more of the same questions.

5. Assess and explain the answers

Guided and exit questions

Guided: both windows have maximum 6 and mean 1.5. Either scalar alone cannot distinguish their different nonzero positions. Exit: the first two visual windows collide, so exact reconstruction is impossible from the pooled values alone. The 8 crossing from column 1 to column 2 changes the pooled map, so universal shift invariance does not follow.

W1 Calculate both summaries

For the lesson window starting at [2, 2], list the four values, sum, maximum and mean. State the complete pooled output shape.

Teacher explanation: Values are 1, 3, 2 and 7. Sum is 13, maximum 7 and mean 3.25. Each pooled output has shape 2 by 2.

W2 Prove that location can be lost

Give two different 2 by 2 windows containing exactly one 4 and three zeros that have the same maximum and mean. Explain why either scalar alone cannot identify the position of the 4.

Teacher explanation: For example, $\begin{bmatrix} 4 & 0 \\ 0 & 0 \end{bmatrix}$ and $\begin{bmatrix} 0 & 4 \\ 0 & 0 \end{bmatrix}$ both give maximum 4 and mean 1. A deterministic head receiving the same scalar must give the same output, so it cannot distinguish those positions.

W3 Audit an omitted border

Apply the lesson complete-window rule to $\begin{bmatrix} 1 & 2 & 99 \\ 3 & 4 & 99 \end{bmatrix}$. Give the output shape and both outputs. Explain why neither output includes 99.

Teacher explanation: Shape is 1 by 1. Only $\begin{bmatrix} 1 & 2 \\ 3 & 4 \end{bmatrix}$ is read, giving maximum 4 and mean 2.5. The final row and column lie outside the only complete stride-2 window.

W4 Pool a new map independently

Use rows $[-4, -1, 2, 6]$, $[-3, -2, 4, 0]$, $[5, 1, -8, -2]$, $[3, 7, -4, -6]$. Under the lesson rule, give all four sums, the max map and the mean map. Explain why replacing a negative maximum by zero is an error here.

Teacher explanation: Window sums in row order are -10, 12, 16 and -20. Max map is $\begin{bmatrix} -1 & 6 \\ 7 & -2 \end{bmatrix}$. Mean map is $\begin{bmatrix} -2.5 & 3 \\ 4 & -5 \end{bmatrix}$. Zero is not in either all-negative window; pooling is not ReLU and must return the largest actual value.

W5 Check the movement boundary

A 2 by 4 map is zero except for 8 at row 0 column 1. Move the 8 to column 2 and set its old position to zero. Give the max and mean maps before and after. What claim does this refute?

Teacher explanation: Before: max $\begin{bmatrix} 8 & 0 \end{bmatrix}$, mean $\begin{bmatrix} 2 & 0 \end{bmatrix}$. After: max $\begin{bmatrix} 0 & 8 \end{bmatrix}$, mean $\begin{bmatrix} 0 & 2 \end{bmatrix}$. Crossing a pooling boundary changes the output, refuting guaranteed invariance to every one-pixel movement.

Independent assessment and fresh retry

W4 requires sums -10, 12, 16, -20, max map $\begin{bmatrix} -1 & 6 \\ 7 & -2 \end{bmatrix}$ and mean map $\begin{bmatrix} -2.5 & 3 \\ 4 & -5 \end{bmatrix}$. Fresh retry: rows $[-6, -2, 1, 5]$ and $[-4, -8, 3, 7]$. Output shape is 1 by 2. Sums are -20 and 16; max map is $\begin{bmatrix} -2 & 7 \end{bmatrix}$ and mean map is $\begin{bmatrix} -5 & 4 \end{bmatrix}$. Require a signed maximum rather than a zero-clamped answer.

Assess independent transfer

Selected case: Use rows $[-4, -1, 2, 6]$, $[-3, -2, 4, 0]$, $[5, 1, -8, -2]$, $[3, 7, -4, -6]$. Under the lesson rule, give all four sums, the max map and the mean map. Explain why replacing a negative maximum by zero is an error here.

Selected case answer

Teacher explanation: Window sums in row order are -10, 12, 16 and -20. Max map is $\begin{bmatrix} -1 & 6 \\ 7 & -2 \end{bmatrix}$. Mean

map is $[-2.5, 3]$, $[4, -5]$. Zero is not in either all-negative window; pooling is not ReLU and must return the largest actual value.

Dimension · Evidence required

Dimension: Explanation

Evidence required: Names the applicable idea or procedure and ties it to the supplied facts.

Dimension: Trace and result

Evidence required: Preserves the given inputs and shows the relevant intermediate steps; distinguishes a prediction from an observed execution.

Dimension: Limits

Evidence required: States the assumptions, missing evidence or conditions under which the result would change.

Record each dimension as not yet, with support, or independent. Accept a valid alternative procedure with a defensible trace. Do not penalise an honestly recorded model failure if the learner correctly explains its evidence and limits.

Feedback that the learner uses

Name the earliest unsupported step and give one action to repair it. Have the learner make that repair now and explain why. Then assess the relevant skill on a fresh, fully specified case. Confirm it was not previously practised with feedback; solve and check the new case before assigning it. A follow-up design prompt is a starting brief, not automatically an equivalent test.

6. Connect the project, support and next lesson

Add a labelled pooling and spatial information evidence sheet to Image-pattern Network Investigation. Show how you can compute max and mean pooling under an explicit window rule. Use the supplied fictional case and keep its inputs, intermediate steps, calculation or prediction, and limitation. Connect this record to last week's record; a matching answer without a trace is insufficient.

Provide separate columns for window values, sum, divisor, maximum and mean. Use numbered positions rather than colour alone. Extension: enumerate all sixteen binary 2 by 2 windows, group them by maximum and mean, and identify collisions under each summary.

Week 23 trains and evaluates a small image model with a declared baseline and data split.

Retain the project ledger and assess a changed case after support. Check the relevant prerequisite before

carrying this component forward.

Plan the delayed return

Suggested return points in this level: ai-5/23, ai-5/25, ai-5/28. Use actual classroom dates, adjusting for holidays and gaps. One, three and six teaching weeks are scheduling choices, not a claimed optimal spacing.

At a delayed check, ask for the idea from memory and a changed application. Compare with the earlier independent response and record support used. For a new level, revisit the previous capstone before checking the new prerequisites.

Record · Teacher evidence

Record: Learner code and date

Teacher evidence: _____

Record: Concept and case used; prior exposure

Teacher evidence: _____

Record: Explanation / trace / limits

Teacher evidence: _____

Record: Support and first repair

Teacher evidence: _____

Record: Changed case and delayed outcome

Teacher evidence: _____

Record: Next teaching action

Teacher evidence: _____

Use the evidence to choose reteaching or the next step. A completed page, confidence rating or attractive project does not by itself demonstrate understanding.

Project evidence from this case

For your Image-pattern Network Investigation, save the input, procedure, observed result and limitation of this check. Label this worked example as practice; use a different, previously unreviewed case when checking independent understanding.

7. Prepare, teach and assess

Teaching target: Compute max and mean pooling under an explicit window rule

Prepare the labelled worked-case picture, the matching workbook, fictional input cards and a place for individual responses. Check a local Python 3 environment before class; have a paper-trace version ready.

Session · Plan · Resources

Session: Session 1 · Understand · 45 min

Plan: 0–7: recall and prerequisite; 7–15: inspect the concrete case and predict; 15–30: teacher models the worked trace; 30–40: learners explain a step using the text and visual; 40–45: check the core idea.

Resources: Sections 1–6; record the brief recall in the workbook.

Session: Session 2 · Practise · 45 min

Plan: 0–5: retrieve the procedure; 5–15: W2 completion practice; 15–23: explain and check with a partner; 23–30: each learner answers the misconception check; 30–40: targeted reteaching or a harder variation; 40–45: prepare the investigation.

Resources: Sections 7–10; use the matching workbook W2 and misconception check.

Session: Session 3 · Investigate and transfer · 45 min

Plan: 0–5: retrieve the decision rule; 5–20: investigate or trace; 20–30: start the independent case; 30–38: connect the project; 38–43: act on feedback; 43–45: plan the return check.

Resources: Sections 9 and 11–14. Give extra time to finish the full task set; use Section 15 when the week includes a coding lab.

Before class, solve the supported practice: Give two different 2 by 2 windows containing exactly one 4 and three zeros that have the same maximum and mean. Explain why either scalar alone cannot identify the position of the 4.

Reasoned practice answer: Teacher explanation: For example, $[[4, 0], [0, 0]]$ and $[[0, 4], [0, 0]]$ both give maximum 4 and mean 1. A deterministic head receiving the same scalar must give the same output, so it cannot distinguish those positions.

Check every learner before discussion: Use the worked case for Pooling and spatial information. Proposed explanation: “Max pooling turns negative numbers into zero”. Decide whether this explanation is supported.

Point to the step or supplied fact that decides; explain your repair if needed.

Misconception repair: That is a ReLU behaviour, not the maximum of an all-negative window.

Support: read the exact case aloud, enlarge the labelled picture, supply input cards and model only the first deciding step. Accept a spoken explanation or drawing; retain the reasoning goal.

Extension: Swap 1 and 4 within the left window. Require a prediction and a reason before comparing.

Expected result: Both pooled maps remain unchanged. Reason: Max and mean ignore the positions of values inside the same window.

Independent assessment: withhold the reserved answer until the learner has attempted the new case.

Record support separately from correctness.

Criterion · Not yet · With support · Independent

Criterion: Explanation

Not yet: Names an answer without a deciding fact

With support: Uses a hint to link fact and decision

Independent: Explains the deciding fact in own words

Criterion: Trace or test

Not yet: Cannot connect input and result

With support: Completes steps with prompts

Independent: Traces or tests a changed case accurately

Criterion: Limits and revision

Not yet: Claims more than evidence supports

With support: Names a limit after a prompt

Independent: States a defensible limit and useful next test

Project checkpoint: Evaluate and revise. Compare with your starting method, explain errors and record a justified revision.

Use the weekly teacher answer for topic-specific reasoning. A saved progress tick is an activity record; judge mastery from the learner's explanation and evidence.