

Embeddings and neighbourhoods

Project: Image-pattern Network Investigation

1. Prepare the purpose, prerequisites and materials

Teach the learning cycle

Primary target: Look up a vector using a token ID and preserve sequence shape

Session · Sequence and minutes · Resources

Session: Session 1 · Understand · 45 min

Sequence and minutes: 0–7: recall and prerequisite; 7–15: inspect the concrete case and predict; 15–30: teacher models the worked trace; 30–40: learners explain a step using the text and visual; 40–45: check the core idea.

Resources: Sections 1–6; record the brief recall in the workbook.

Session: Session 2 · Practise · 45 min

Sequence and minutes: 0–5: retrieve the procedure; 5–15: W2 completion practice; 15–23: explain and check with a partner; 23–30: each learner answers the misconception check; 30–40: targeted reteaching or a harder variation; 40–45: prepare the investigation.

Resources: Sections 7–10; use the matching workbook W2 and misconception check.

Session: Session 3 · Investigate and transfer · 45 min

Sequence and minutes: 0–5: retrieve the decision rule; 5–20: investigate or trace; 20–30: start the independent case; 30–38: connect the project; 38–43: act on feedback; 43–45: plan the return check.

Resources: Sections 9 and 11–14. Give extra time to finish the full task set; use Section 15 when the week includes a coding lab.

This is a starting allocation of 135 minutes, not a validated duration. Preserve all named topics. Schedule extra time for connected examples, the full investigation, independent cases and project building. Repeated copies of a case share one recorded attempt; they are not new evidence.

Retrieval answer guidance

Sequence representations

Without opening the old lesson, explain one key idea from Sequence representations. Give an example and a mistake that the idea helps you avoid.

Look for: Encode an ordered sequence with an explicit vocabulary

Reference example, not the only acceptable wording: Teacher explanation: IDs are [2, 3, 4, 0], mask [1, 1, 1, 0], real length 3 and final real event STOP at position 2.

Training a small image model

Without opening the old lesson, explain one key idea from Training a small image model. Give an example and a mistake that the idea helps you avoid.

Look for: Trace a complete image model with fixed features and one trained weight

Reference example, not the only acceptable wording: Teacher explanation: $d = 2$, $h_1 = 2$ and $h_2 = 0$. Score is 0.9, prediction class 1 and squared error $(0.9 - 1)^2 = 0.01$.

Image tensors and channels

Without opening the old lesson, explain one key idea from Image tensors and channels. Give an example and a mistake that the idea helps you avoid.

Look for: Read a pixel using declared row column and channel axes

Reference example, not the only acceptable wording: Teacher explanation: The RGB pixel is [0, 0, 255]; its blue value is 255. Shape is 2 by 2 by 3, with four pixels and twelve channel values.

Use two 45-minute sessions. Begin with the difference between an identifier and its looked-up vector. The original table is authored, not learned; the separate one-row update demonstrates optimisation under a stated artificial objective. Do not attach invented semantic labels to the two coordinate axes. Keep original and updated table versions separate.

Outcomes

Look up a vector using a token ID and preserve sequence shape

Calculate nearest neighbours with an explicit distance and tie rule

Distinguish constructed vectors from learned features and limit similarity claims

Preparation

Printed lesson and workbook; paper and pencil

Calculator and optional local Python 3 editor; no packages or AI accounts needed

Use the fictional examples supplied; prepare the fresh retry before class

Prerequisite answer

IDs are assigned identifiers. Their numerical order and spacing have no declared semantic meaning; a consistent relabelling can change those differences without changing the symbols.

End goal for the pictorial case

By the end, I can explain embeddings and neighbourhoods using a traced example and a stated limitation.

This added worked case illustrates the week's main idea. Retain all original and connected topics; schedule its practice within the teaching cycle.

2. Explain and model the mechanism

Continue the fictional robot vocabulary and add WAIT as ID 5. Use the table below, chosen by the lesson author for arithmetic practice. These coordinates are not measured robot properties and were not learned from data. Each token ID selects one row; the resulting two-component vector is its embedding in this example.

The table shape is 6 by 2: six vocabulary entries and embedding dimension 2. The ID sequence [2, 4, 0, 0] becomes [[2, 0], [0, 2], [0, 0], [0, 0]], with shape 4 by 2. Its mask remains [1, 1, 0, 0]. The vector dimension is not the sequence length or vocabulary size.

A zero PAD vector does not remove the need for masking. Averaging all four vectors above gives [0.5, 0.5]; averaging only the two real vectors gives [1, 1]. UNK is a real position when it replaces an unknown symbol, so its vector is not automatically excluded.

Use squared Euclidean distance: square each component difference and add. From GO [2, 0] to TURN [1, 1], the distance is $(2 - 1)^2 + (0 - 1)^2 = 2$. To STOP it is 8; to WAIT it is 5. TURN is therefore the nearest of those three under this table and metric.

The candidate set excludes PAD, UNK and the query token itself. Otherwise a query would normally retrieve itself at distance zero. This code assumes finite numeric components and uses exact ties, appropriate for these integer examples. Floating-point comparisons in other experiments need a declared precision policy.

Term · Meaning

Term: Embedding table

Meaning: A table assigning a fixed-length numerical vector to each token ID

Term: Embedding dimension

Meaning: The number of components in each embedding vector

Term: Neighbourhood

Meaning: Nearby candidates under a stated representation and distance rule

Term: Squared Euclidean distance

Meaning: The sum of squared component differences between two vectors

One query can have two closest candidates

Candidate vector · Query vector · Squared distance

Candidate vector: GO [2, 0]

Query vector: [1, 0]

Squared distance: 1

Candidate vector: TURN [1, 1]

Query vector: [1, 0]

Squared distance: 1

Candidate vector: WAIT [0, 1]

Query vector: [1, 0]

Squared distance: 2

Candidate vector: STOP [0, 2]

Query vector: [1, 0]

Squared distance: 5

The nearest set is GO and TURN. Alphabetical display order does not break the mathematical tie or make one candidate more similar.

Guided: STOP distances to GO, TURN and WAIT are 8, 2 and 1, so WAIT is nearest. Exit: the original table and squared Euclidean rule place TURN nearest to GO among the stated candidates. That is not proof of equivalent meaning or substitutability. A lower artificial training objective only supports improvement on that objective; useful task behaviour requires appropriate independent evaluation and error analysis.

Model the reasoning aloud

Use the complete worked example below before asking learners to complete W2. Reveal a small part, invite a prediction, then explain the deciding step. These teacher notes contain solutions; do not reveal the independent case answer during modelling.

One query can have two closest candidates

Candidate vector · Query vector · Squared distance

Candidate vector: GO [2, 0]

Query vector: [1, 0]

Squared distance: 1

Candidate vector: TURN [1, 1]

Query vector: [1, 0]

Squared distance: 1

Candidate vector: WAIT [0, 1]

Query vector: [1, 0]

Squared distance: 2

Candidate vector: STOP [0, 2]

Query vector: [1, 0]

Squared distance: 5

The nearest set is GO and TURN. Alphabetical display order does not break the mathematical tie or make one candidate more similar.

Using STOP [0, 2] as the query, calculate distances to GO, TURN and WAIT. Exclude STOP itself and both reserved entries. Which candidate is nearest?

Thinking move · Teacher prompt

Thinking move: Plan

Teacher prompt: What is given? What is the question? Which procedure fits these facts?

Thinking move: Do

Teacher prompt: Point to each input and intermediate step in the worked trace. Name the rule that allows the next step.

Thinking move: Check

Teacher prompt: Does the output answer the question? Which assumption or limitation prevents a larger claim?

Use the diagram and verbal explanation together. Ask learners to match a sentence to a specific visual step; do not assign learners fixed visual or auditory learning styles.

A pictorial worked case: Embeddings and neighbourhoods


Measure embedding neighbours without turning numerical proximity into factual certainty.

The facts we will use

Toy table $P=[0, 1]$, $Q=[3, 1]$, $R=[1, 4]$; query $[1, 1]$. Use squared Euclidean distance.

All inputs and outcomes in this worked example are invented classroom data; no real model run is claimed.

Squared Euclidean embedding distances



Horizontal: first embedding coordinate; vertical: second embedding coordinate

1: P at (0, 1)

2: Q at (3, 1)

3: R at (1, 4)

Cross: query at (1, 1)

Distance rule: Squared Euclidean distance

Embeddings and neighbourhoods

Start with the supplied facts

Follow each arrow. Ask which fact allows the next step.



1. Distance to P

$$(1-0)^2 + (1-1)^2 = 1.$$



2. Distances to Q/R

Q distance 4; R distance 9.



3. Select neighbour

P is nearest under the declared metric; this is a geometric result, not proof of meaning.

CHANGE ONE THING

Move the query to [2, 1].

Explain the changed result using the matching lesson.

Read the picture one step at a time

Step · What happens and why

Step: 1. Distance to P

What happens and why: $(1-0)^2 + (1-1)^2 = 1.$

Step: 2. Distances to Q/R

What happens and why: Q distance 4; R distance 9.

Step: 3. Select neighbour

What happens and why: P is nearest under the declared metric; this is a geometric result, not proof of meaning.

Match each pictured step to the supplied facts. This is a worked teaching case, not an independent assessment.

Why this result follows

An embedding stores each item as an ordered vector. Under squared Euclidean distance, subtract matching coordinates, square their differences and add. The smallest total identifies the nearest supplied vector. These invented coordinates let us check geometry exactly; a claim that neighbours share meaning needs evidence about how the representation was learned and used.

What this example does not establish

Embedding geometry depends on training, metric and scale; proximity does not prove truth, causation or source permission.

Change one thing in the pictured case

Change: Move the query to [2, 1].

Prediction: Q becomes nearest with squared distance1; P distance4; R distance10.

Reason: Changing the query position changes geometric neighbours while the stored table remains fixed.

Ask while showing the picture

Cover the result. Ask learners to name the inputs and predict the next step. Uncover one step, connect the icon to the actual procedure, and explain its evidence. Then change the supplied condition and compare. The picture is a representation; it does not document execution of a real AI model.

3. Demonstrate and guide practice

Time or stage · Teacher action

Time or stage: Session 1 start to 7 minutes

Teacher action: Retrieve arbitrary IDs and label vocabulary size, sequence length and vector dimension.

Time or stage: 7 to 18 minutes

Teacher action: Trace table lookups and masks, then complete W1.

Time or stage: 18 to 32 minutes

Teacher action: Compute GO distances by hand and run or trace the nearest-neighbour code.

Time or stage: 32 to 45 minutes

Teacher action: Use W2 and the visual to preserve ties under an explicit candidate policy.

Time or stage: Session 2 start to 8 minutes

Teacher action: Complete the guided STOP query before changing any table row.

Time or stage: 8 to 20 minutes

Teacher action: Trace the isolated learning update and complete W3, noting the resulting collision.

Time or stage: 20 to 35 minutes

Teacher action: Collect W4 independently, requiring distances, the full nearest set and an order-loss explanation.

Time or stage: 35 to 45 minutes

Teacher action: Use W5 and the exit response to audit interpretation and version consistency, then administer the fresh retry.

Use the worked example in Sections 3 and 6. Collect a prediction before revealing its result; ask the learner to point to each intermediate fact.

Provide separate columns for token, ID and vector. Use a distance ledger with two differences, two squares and a sum; allow calculators. Extension: consistently permute all table row IDs and show that token-level neighbour results stay unchanged, then deliberately omit the table permutation to expose the mismatch.

Reduce help deliberately

Completion task: For query [1, 0], compute squared distances to GO, TURN, STOP and WAIT in the original table. Return all nearest candidates.

Teacher check: Teacher explanation: Distances are 1, 1, 5 and 2 respectively. The nearest set is GO and TURN; ordering their names does not remove the tie.

Start by identifying the given inputs together. Leave the intermediate steps blank. If needed, model one step, then withdraw that help on the next step. Move to a full trace only when the partial trace is

understood. For partners, alternate explainer and checker; collect a response from every learner before discussion.

Individual reasoning check

Use the worked case for Embeddings and neighbourhoods. Proposed explanation: “Token ID differences define embedding distances”. Decide whether this explanation is supported. Point to the step or supplied fact that decides; explain your repair if needed.

Expected correction: The ID selects a row; distances are computed between row vectors.

Collect explanations, not only yes/no votes. If a misunderstanding is common, re-model the relevant step for the class. If it affects a few learners, give a short targeted group explanation while others solve a more demanding variation.

Pictorial practice question

What would justify claiming nearby vectors mean related topics? Point to the relevant step in the picture, then write the changed result and the rule or evidence that supports it.

Reasoned teacher answer

Evidence about how the table was learned plus task-specific evaluation. These invented coordinates alone establish only distances. Changed-case check: Q becomes nearest with squared distance1; P distance4; R distance10. Changing the query position changes geometric neighbours while the stored table remains fixed.

Changed-case reasoning: Q becomes nearest with squared distance1; P distance4; R distance10. Changing the query position changes geometric neighbours while the stored table remains fixed.

Collect each learner’s explanation before discussion. Use the first missing connection between input, deciding step and result to choose support. This question is worked-case practice, not fresh mastery evidence.

4. Run the investigation and diagnose misconceptions

Token ID differences define embedding distances: The ID selects a row; distances are computed between row vectors.

Nearest always means interchangeable: Closeness depends on representation, metric and candidates, and need not preserve task labels or meaning.

A learned embedding cannot lose identity: Two rows can coincide, and sequence aggregation can create additional collisions.

Use Section 9 for the evidence ledger. Add a boundary or missing-input case and record the expected response before checking. More successful repeats of one case do not establish wider coverage.

Match the support to the first error

What the response shows · Next teaching action

What the response shows: Missing or misread facts

Next teaching action: Read the case aloud, mark supplied versus unknown facts, and let the learner restate it.

What the response shows: Wrong procedure

Next teaching action: Return to the deciding step in the worked case. Contrast it with the proposed incorrect explanation.

What the response shows: Arithmetic or implementation error

Next teaching action: Trace intermediate values or lines; preserve the first mismatch and retry that step.

What the response shows: Correct result without a reason

Next teaching action: Ask for a trace and a changed case before marking independent understanding.

What the response shows: An unsupported wider claim

Next teaching action: Ask which supplied evidence supports the claim and which further observation would be needed.

Offer an oral explanation, drawing, enlarged visual or fewer examples when that removes a reading/writing barrier. Keep the same reasoning goal. Stretch secure learners by changing a boundary or assumption and asking them to defend the effect, not simply by assigning more of the same questions.

5. Assess and explain the answers

Guided and exit questions

Guided: STOP distances to GO, TURN and WAIT are 8, 2 and 1, so WAIT is nearest. Exit: the original table and squared Euclidean rule place TURN nearest to GO among the stated candidates. That is not proof of equivalent meaning or substitutability. A lower artificial training objective only supports improvement on that objective; useful task behaviour requires appropriate independent evaluation and error analysis.

W1 Trace the lookup shape

Using the original table, embed TURN WAIT STOP with one right-padding slot. Give the vector sequence,

mask and shape.

Teacher explanation: Vectors are $[[1, 1], [0, 1], [0, 2], [0, 0]]$, mask $[1, 1, 1, 0]$ and shape 4 by 2.

W2 Calculate distances and a tie

For query $[1, 0]$, compute squared distances to GO, TURN, STOP and WAIT in the original table. Return all nearest candidates.

Teacher explanation: Distances are 1, 1, 5 and 2 respectively. The nearest set is GO and TURN; ordering their names does not remove the tie.

W3 Trace a trainable row

For the isolated GO-row update, give the gradient, updated vector, starting loss and new loss. Which other token now shares the vector?

Teacher explanation: Gradient $[4, -4]$, updated vector $[1, 1]$, loss 8 before and 2 after. TURN already has $[1, 1]$. This collision does not establish equivalent meaning.

W4 Find a neighbourhood independently

A separate table contains A $[0, 0]$, B $[2, 0]$ and C $[1, 2]$. For query $[1, 0]$, give all squared distances and every nearest candidate. Then calculate the mean of A and B and compare it with the query. Can that mean identify which ordered pair produced it?

Teacher explanation: Distances to A, B and C are 1, 1 and 4. A and B tie. Their mean is $[1, 0]$, equal to the query. Reversing A B to B A gives the same mean, so the mean alone cannot identify the order.

W5 Keep the lookup consistent

A developer swaps the IDs of GO and STOP but leaves the embedding rows unchanged. What goes wrong, and what must be saved or changed together?

Teacher explanation: Each token now selects the other token's old row, changing the encoded input. Save and update the vocabulary-to-row mapping and table together, along with version and downstream model. ID relabelling is harmless only when every lookup and consumer stays consistent.

Independent assessment and fresh retry

W4 requires distances 1, 1, 4, both A and B, mean $[1, 0]$ and a reversed-order collision. Fresh retry: query $[0, 1]$, candidates D $[0, 0]$, E $[0, 2]$, F $[3, 1]$. Distances are 1, 1, 9; D and E tie. Their mean is $[0, 1]$, and swapping their order leaves it unchanged.

Assess independent transfer

Selected case: A separate table contains A $[0, 0]$, B $[2, 0]$ and C $[1, 2]$. For query $[1, 0]$, give all squared distances and every nearest candidate. Then calculate the mean of A and B and compare it with the query. Can that mean identify which ordered pair produced it?

Selected case answer

Teacher explanation: Distances to A, B and C are 1, 1 and 4. A and B tie. Their mean is [1, 0], equal to the query. Reversing A B to B A gives the same mean, so the mean alone cannot identify the order.

Dimension · Evidence required

Dimension: Explanation

Evidence required: Names the applicable idea or procedure and ties it to the supplied facts.

Dimension: Trace and result

Evidence required: Preserves the given inputs and shows the relevant intermediate steps; distinguishes a prediction from an observed execution.

Dimension: Limits

Evidence required: States the assumptions, missing evidence or conditions under which the result would change.

Record each dimension as not yet, with support, or independent. Accept a valid alternative procedure with a defensible trace. Do not penalise an honestly recorded model failure if the learner correctly explains its evidence and limits.

Feedback that the learner uses

Name the earliest unsupported step and give one action to repair it. Have the learner make that repair now and explain why. Then assess the relevant skill on a fresh, fully specified case. Confirm it was not previously practised with feedback; solve and check the new case before assigning it. A follow-up design prompt is a starting brief, not automatically an equivalent test.

6. Connect the project, support and next lesson

Add a labelled embeddings and neighbourhoods evidence sheet to Image-pattern Network Investigation. Show how you can look up a vector using a token id and preserve sequence shape. Use the supplied fictional case and keep its inputs, intermediate steps, calculation or prediction, and limitation. Connect this record to last week's record; a matching answer without a trace is insufficient.

Provide separate columns for token, ID and vector. Use a distance ledger with two differences, two squares and a sum; allow calculators. Extension: consistently permute all table row IDs and show that token-level neighbour results stay unchanged, then deliberately omit the table permutation to expose the mismatch.

Week 27 explores similarity and normalisation, including changes in neighbour ranking.

Retain the project ledger and assess a changed case after support. Check the relevant prerequisite before carrying this component forward.

Plan the delayed return

Suggested return points in this level: ai-5/27, ai-5/29, ai-5/32. Use actual classroom dates, adjusting for holidays and gaps. One, three and six teaching weeks are scheduling choices, not a claimed optimal spacing.

At a delayed check, ask for the idea from memory and a changed application. Compare with the earlier independent response and record support used. For a new level, revisit the previous capstone before checking the new prerequisites.

Record · Teacher evidence

Record: Learner code and date

Teacher evidence: _____

Record: Concept and case used; prior exposure

Teacher evidence: _____

Record: Explanation / trace / limits

Teacher evidence: _____

Record: Support and first repair

Teacher evidence: _____

Record: Changed case and delayed outcome

Teacher evidence: _____

Record: Next teaching action

Teacher evidence: _____

Use the evidence to choose reteaching or the next step. A completed page, confidence rating or attractive project does not by itself demonstrate understanding.

Project evidence from this case

For your Image-pattern Network Investigation, save the input, procedure, observed result and limitation of this check. Label this worked example as practice; use a different, previously unreviewed case when checking independent understanding.

7. Prepare, teach and assess

Teaching target: Look up a vector using a token ID and preserve sequence shape

Prepare the labelled worked-case picture, the matching workbook, fictional input cards and a place for individual responses. Check a local Python 3 environment before class; have a paper-trace version ready.

Session · Plan · Resources

Session: Session 1 · Understand · 45 min

Plan: 0–7: recall and prerequisite; 7–15: inspect the concrete case and predict; 15–30: teacher models the worked trace; 30–40: learners explain a step using the text and visual; 40–45: check the core idea.

Resources: Sections 1–6; record the brief recall in the workbook.

Session: Session 2 · Practise · 45 min

Plan: 0–5: retrieve the procedure; 5–15: W2 completion practice; 15–23: explain and check with a partner; 23–30: each learner answers the misconception check; 30–40: targeted reteaching or a harder variation; 40–45: prepare the investigation.

Resources: Sections 7–10; use the matching workbook W2 and misconception check.

Session: Session 3 · Investigate and transfer · 45 min

Plan: 0–5: retrieve the decision rule; 5–20: investigate or trace; 20–30: start the independent case; 30–38: connect the project; 38–43: act on feedback; 43–45: plan the return check.

Resources: Sections 9 and 11–14. Give extra time to finish the full task set; use Section 15 when the week includes a coding lab.

Before class, solve the supported practice: For query [1, 0], compute squared distances to GO, TURN, STOP and WAIT in the original table. Return all nearest candidates.

Reasoned practice answer: Teacher explanation: Distances are 1, 1, 5 and 2 respectively. The nearest set is GO and TURN; ordering their names does not remove the tie.

Check every learner before discussion: Use the worked case for Embeddings and neighbourhoods.

Proposed explanation: “Token ID differences define embedding distances”. Decide whether this

explanation is supported. Point to the step or supplied fact that decides; explain your repair if needed.

Misconception repair: The ID selects a row; distances are computed between row vectors.

Support: read the exact case aloud, enlarge the labelled picture, supply input cards and model only the first deciding step. Accept a spoken explanation or drawing; retain the reasoning goal.

Extension: Move the query to [2, 1]. Require a prediction and a reason before comparing. Expected result: Q becomes nearest with squared distance1; P distance4; R distance10. Reason: Changing the query position changes geometric neighbours while the stored table remains fixed.

Independent assessment: withhold the reserved answer until the learner has attempted the new case. Record support separately from correctness.

Criterion · Not yet · With support · Independent

Criterion: Explanation

Not yet: Names an answer without a deciding fact

With support: Uses a hint to link fact and decision

Independent: Explains the deciding fact in own words

Criterion: Trace or test

Not yet: Cannot connect input and result

With support: Completes steps with prompts

Independent: Traces or tests a changed case accurately

Criterion: Limits and revision

Not yet: Claims more than evidence supports

With support: Names a limit after a prompt

Independent: States a defensible limit and useful next test

Project checkpoint: Prepare the demonstration. Gather reproducible instructions, evidence, access checks and remaining limitations.

Use the weekly teacher answer for topic-specific reasoning. A saved progress tick is an activity record; judge mastery from the learner's explanation and evidence.