Regularisation and early stopping

Learn to understand, design, build, test and explain AI systems responsibly.

Project: Image-pattern Network Investigation

TEACHER GUIDE · 1 OF 9

Prepare the purpose, prerequisites and materials

> Prepare Regularisation and early stopping: check the target, prerequisites, resources and adaptable teaching schedule.

Teach the learning cycle

Primary target: Separate a **weight penalty** from **prediction** error

Session · Sequence and minutes · Resources

> **Session:** Session 1 · Understand · 45 min
>
> **Sequence and minutes:** 0–7: recall and prerequisite; 7–15: inspect the concrete case and predict; 15–30: teacher models the worked trace; 30–40: learners explain a step using the text and visual; 40–45: check the core idea.
>
> **Resources:** Use Your mission, Notice the evidence, See how it works, Words that unlock the idea and Follow a worked example; record recall in the workbook.

> **Session:** Session 2 · Practise · 45 min
>
> **Sequence and minutes:** 0–5: retrieve the procedure; 5–15: W2 completion practice; 15–23: explain and check with a partner; 23–30: each learner answers the misconception check; 30–40: targeted reteaching or a harder variation; 40–45: prepare the investigation.
>
> **Resources:** Use Find and repair a mistake, Practise together and Build your understanding; use the matching workbook W2 and Individual reasoning check.

> **Session:** Session 3 · Investigate and transfer · 45 min
>
> **Sequence and minutes:** 0–5: retrieve the decision rule; 5–20: investigate or trace; 20–30: start the independent case; 30–38: connect the project; 38–43: act on feedback; 43–45: plan the return check.
>
> **Resources:** Use Run the investigation, Connect your project and Try a new case independently. Allow extra time for the full task set. When code is supplied, use the examples in See how it works or Follow a worked example and the browser lab in Supported practice, repair and portfolio.

This is a starting allocation of 135 minutes, not a validated duration. Preserve all named topics. Schedule extra time for connected examples, the full investigation, independent cases and project building.

Repeated copies of a case share one recorded attempt; they are not new **evidence**.

Retrieval answer guidance

Training and validation curves

Without opening the old lesson, explain one key idea from **Training** and validation curves. Give an example and a mistake that the idea helps you avoid.

Look for: Compute comparable **training** and validation losses at saved checkpoints

Reference example, not the only acceptable wording: Teacher explanation: **Prediction**s [3, 4], residuals [-1.5, -2], squares [2.25, 4], MSE 3.125.

Batching and epochs

Without opening the old lesson, explain one key idea from Batching and epochs. Give an example and a mistake that the idea helps you avoid.

Look for: Distinguish an example a batch an update and an epoch

Reference example, not the only acceptable wording: Teacher explanation: Batch lengths 4, 4, 2; three updates per epoch, nine total updates and 30 example visits.

Gradients with a numerical check

Without opening the old lesson, explain one key idea from Gradients with a numerical check. Give an example and a mistake that the idea helps you avoid.

Look for: Estimate one partial derivative while other parameters stay fixed

Reference example, not the only acceptable wording: Teacher explanation: **Prediction** 3, residual 0, loss 0, gradient [0, 0].

For the compact alternative schedule, use two 45-minute sessions. Keep **prediction** error, penalty and total objective in separate columns. Teach early stopping as a second **mechanism** with a precise state machine on paper.

Cover future curve values until a decision is made; do not reward retrospective selection as if it were a live stopping rule.

Outcomes

Separate a **weight penalty** from **prediction** error

Trace a regularised update under a stated objective

Apply a stopping rule and **restore** the best observed checkpoint

Preparation

Printed lesson and workbook; paper and pencil

Calculator and optional local Python 3 editor; no packages or AI accounts needed

Use the fictional examples supplied; prepare the fresh retry before class

Prerequisite answer

Restore the parameters saved at the chosen checkpoint. The last parameters produced by **training** may have a different validation loss.

End goal for the pictorial case

By the end, I can explain **regularisation** and early stopping using a traced example and a stated limitation.

This added worked case illustrates the week’s main idea. Retain all original and connected topics; schedule its practice within the teaching cycle.

Explain and model the mechanism

> Model Regularisation and early stopping using the supplied case, labelled mechanism and reasoning. Make the scope of each conclusion explicit.

Keep h = ReLU(x), y = vh, train only v on (1, 2) and (2, 4), and freeze all hidden parameters and the zero **output** bias. **Training** MSE is L(v) = 2.5(v - 2) squared.

Define J(v) = L(v) + lambda times v squared, with lambda nonnegative. Only this one **output** weight is penalised here.

For lambda = 0.5, the penalty at v = 1.5 is 0.5 times 2.25 = 1.125. **Prediction** MSE is 0.625, so total objective J is 1.75. Keep these quantities separate in logs.

A smaller total objective does not automatically mean a smaller **prediction** error.

Among these three candidates, the smallest penalised objective is at v = 1.5, whereas the smallest **training** MSE is at v = 2. Penalising a weight changes the tradeoff.

It does not guarantee better validation performance or fair outcomes.

The data gradient is 5(v - 2). The penalty gradient is 2 times lambda times v, giving total gradient 5(v - 2) + 2 lambda v. At v = 1.5 and lambda = 0.5, these contributions are -2.5 and 1.5, so total gradient is -1.

A rate 0.1 step gives v = 1.6.

Assume finite numeric values and nonnegative penalty. At the new v, data loss is 0.4, penalty 1.28 and total 1.68.

Choose penalty strength using a declared validation **prediction** metric, not by comparing total objectives with different lambdas as if they were the same measure.

Term	Meaning
Regularisation	A constraint or training procedure intended to limit fitting choices and improve generalisation
Weight penalty	An added objective term that discourages specified large parameter values
Patience	The allowed run of consecutive non-improving evaluations before stopping under a stated rule
Restore	Reload the parameters saved at the selected checkpoint

Patience two with strict improvement

EPOCH	VALIDATION MSE	DECISION
0 then 1 then 2	4 then 2 then 1.5	Save each improved state
3 then 4	1.6 then 1.4	Wait once then reset
5 then 6	1.45 then 1.46	Two misses so stop at 6

Initial checkpoint is epoch 0. Evaluate once after each epoch. A strict decrease is improvement; an exact tie is a miss. Reset the miss count after improvement and stop at two consecutive misses. Restore epoch 4, the best observed checkpoint.

Explain Regularisation and early stopping · 1

Guided: miss counts at epochs 3, 4, 5, 6 are 1, 0, 1, 2. Stop at 6 and **restore** 4. Exit: using final parameters ignores restoration; selecting **patience** with test losses uses test data for development.

Restore the selected checkpoint, choose policy using validation, then freeze it before evaluating suitable untouched final examples.

Model the reasoning aloud

Use the complete worked example below before asking learners to complete W2. Reveal a small part, invite a **prediction**, then explain the deciding step.

These teacher notes contain solutions; do not reveal the independent case answer during modelling.

Patience two with strict improvement

EPOCH	VALIDATION MSE	DECISION
0 then 1 then 2	4 then 2 then 1.5	Save each improved state
3 then 4	1.6 then 1.4	Wait once then reset
5 then 6	1.45 then 1.46	Two misses so stop at 6

Initial checkpoint is epoch 0. Evaluate once after each epoch. A strict decrease is improvement; an exact tie is a miss. Reset the miss count after improvement and stop at two consecutive misses. Restore epoch 4, the best observed checkpoint.

At epochs 3, 4, 5 and 6, record the miss count after evaluation. Which epoch stops training, and which epoch supplies the restored parameters?

Thinking move	Teacher prompt
Plan	What is given? What is the question? Which procedure fits these facts?

Thinking move	Teacher prompt
Do	Point to each input and intermediate step in the worked trace. Name the rule that allows the next step.
Check	Does the output answer the question? Which assumption or limitation prevents a larger claim?

Use the diagram and verbal explanation together. Ask learners to match a sentence to a specific visual step; do not assign learners fixed visual or auditory learning styles.

A pictorial worked case: Regularisation and early stopping

Separate a **regularisation** penalty from **prediction** loss and an early-stopping rule.

The facts we will use

> **Supplied facts**
>
> Toy objective $J(a)=(a-3)^2+2a^2$; start $a = 0$; gradient $6a-6$; rate $1/6$. Separate validation losses: [5, 3, 3, 4], **patience** 1, no ties as improvement.

> **Supplied facts**
>
> All **input**s and outcomes in this worked example are invented classroom data; no real model run is claimed.

AI ACADEMY / AI-5/16

Regularisation and early stopping

Start with the supplied facts

Follow each arrow. Ask which fact allows the next step.



1. Regularised update

At 0 gradient -6; update gives a = 1.



2. Split objective

At 1 prediction term 4, penalty 2, total 6; at 0 total 9.



3. Early-stop separately

Best validation checkpoint is 2 with loss 3; checkpoint 3 is no improvement, so stop at 3.

CHANGE ONE THING

Change patience from 1 to2 under the same tie rule.

Explain the changed result using the matching lesson.

Follow the labelled picture with the matching explanation. Open the vector diagram

Read the picture one step at a time

STEP	WHAT HAPPENS AND WHY
1. Regularised update	At 0 gradient -6; update gives a = 1.
2. Split objective	At 1 prediction term 4, penalty 2, total 6; at 0 total 9.
3. Early-stop separately	Best validation checkpoint is 2 with loss 3; checkpoint 3 is no improvement, so stop at 3.

Match each pictured step to the supplied facts. This is a worked teaching case, not an independent assessment.

Why this result follows

Why the result follows

Regularisation adds a parameter penalty to the **training** objective. Here it discourages large a, so the objective balances **prediction** error against that penalty.

Early stopping is a different decision based on the supplied validation sequence. A tied validation loss is not improvement under this policy; stop when the **patience** allowance is used and **restore** the best checkpoint.

What this example does not establish

Keep the stated limit

Regularisation and early stopping are different tools; neither guarantees better

performance in every dataset.

Change one thing in the pictured case

Change one thing

Change: Change **patience** from 1 to2 under the same tie rule.

Predicted result

Prediction: Stop at checkpoint 4; still **restore** checkpoint 2.

Why the result follows

Reason: Checkpoints 3 and 4 are two consecutive non-improvements; a later stop does not redefine the best checkpoint.

Ask while showing the picture

Ask while showing the picture · 2

Cover the result. Ask learners to name the **input**s and predict the next step. Uncover one step, connect the icon to the actual procedure, and explain its **evidence**. Then change the supplied condition and compare.

The picture is a representation; it does not document execution of a real AI model.

Demonstrate and guide practice

> Demonstrate Regularisation and early stopping, reduce support deliberately and check individual reasoning before discussing answers.

Time or stage	Teacher action
Session 1 start to 7 minutes	Retrieve checkpoint restoration and introduce the named penalised weight.
7 to 18 minutes	Calculate the objective table and W1, identifying the nonzero penalty gradient at v = 2.
18 to 32 minutes	Trace the worked regularised update and use W2 for the next step.
32 to 45 minutes	Run or trace the code and distinguish objective reduction from validation evidence.
Session 2 start to 8 minutes	Reveal the validation sequence one epoch at a time; complete the guided miss counts.
8 to 20 minutes	Complete W3 before revealing the future value; compare stopping and restored epochs.
20 to 35 minutes	Collect W4 independently, scoring the arithmetic and the tied-loss policy separately.
35 to 45 minutes	Discuss W5 and the exit response, then use the fresh retry and record the complete policy.

Use See how it works and Follow a worked example. Collect a **prediction** before revealing its result; ask the learner to point to each intermediate fact.

Use a ledger with columns epoch, metric, best epoch and miss count; cover future rows. Extension: solve 5(v - 2) + 2 lambda v = 0 to obtain v = 10 / (5 + 2 lambda).

For nonnegative lambda, discuss why the optimum moves toward zero without claiming this always improves **prediction**.

Reduce help deliberately

Completion practice

Completion task: Start v = 1.6 with lambda = 0.5 and rate 0.1. Calculate both gradient contributions, new v and new **prediction** MSE.

Reasoning to listen for

Teacher check: Teacher explanation: Data gradient -2, penalty gradient 1.6, total -0.4. New v = 1.64; **prediction** MSE is 2.5 times 0.36 squared = 0.324.

Start by identifying the given **input**s together. Leave the intermediate steps blank. If needed, model one step, then withdraw that help on the next step. Move to a full trace only when the partial trace is understood.

For partners, alternate explainer and checker; collect a response from every learner before discussion.

Individual reasoning check

Use the worked case for **Regularisation** and early stopping. Proposed explanation: “Zero **prediction** error means no regularised update”. Decide whether this explanation is supported.

Point to the step or supplied fact that decides; explain your repair if needed.

Expected repair

Expected correction: The penalty gradient can remain nonzero.

Collect explanations, not only yes/no votes. If a misunderstanding is common, re-model the relevant step for the class.

If it affects a few learners, give a short targeted group explanation while others solve a more demanding variation.

Pictorial practice question

Why should the penalty value not be reported as validation error? Point to the relevant step in the picture, then write the changed result and the rule or **evidence** that supports it.

Reasoned teacher answer

It is part of the **training** objective, not the measured validation **prediction** loss. Report these separate quantities with their definitions. Changed-case check: Stop at checkpoint 4; still **restore** checkpoint 2.

Checkpoints 3 and 4 are two consecutive non-improvements; a later stop does not redefine the best checkpoint.

Changed-case reasoning: Stop at checkpoint 4; still **restore** checkpoint 2. Checkpoints 3 and 4 are two consecutive non-improvements; a later stop does not redefine the best checkpoint.

Collect each learner's explanation before discussion. Use the first missing connection between **input**, deciding step and result to choose support. This question is worked-case practice, not fresh mastery **evidence**.

Run the investigation and diagnose misconceptions

> Run the Regularisation and early stopping investigation and use the first unsupported step to choose a teaching response.

Zero **prediction** error means no regularised update: The penalty gradient can remain nonzero.

Early stopping adds a **weight penalty**: It limits **training** duration using a validation rule; a **weight penalty** changes the objective.

Restore the epoch where stopping happened: **Restore** the best observed checkpoint under the declared rule, which can be earlier.

Use Run the investigation for the **evidence** ledger. Add a boundary or missing-**input** case and record the expected response before checking. More successful repeats of one case do not establish wider coverage.

Match the support to the first error

What the response shows	Next teaching action
Missing or misread facts	Read the case aloud, mark supplied versus unknown facts, and let the learner restate it.
Wrong procedure	Return to the deciding step in the worked case. Contrast it with the proposed incorrect explanation.
Arithmetic or implementation error	Trace intermediate values or lines; preserve the first mismatch and retry that step.
Correct result without a reason	Ask for a trace and a changed case before marking independent understanding.
An unsupported wider claim	Ask which supplied evidence supports the claim and which further observation would be needed.

Offer an oral explanation, drawing, enlarged visual or fewer examples when that removes a reading/writing barrier. Keep the same reasoning goal.

Stretch secure learners by changing a boundary or assumption and asking them to defend the effect, not simply by assigning more of the same questions.

Assess and explain the answers

> Use the Regularisation and early stopping questions, teacher keys and criteria after the relevant attempts. Previously discussed cases are practice; protect the separately selected independent task.

Guided and exit questions

Guided: miss counts at epochs 3, 4, 5, 6 are 1, 0, 1, 2. Stop at 6 and **restore** 4. Exit: using final parameters ignores restoration; selecting **patience** with test losses uses test data for development.

Restore the selected checkpoint, choose policy using validation, then freeze it before evaluating suitable untouched final examples.

W1 Separate the objective terms

Workbook question · W1

At v = 2 and lambda = 0.5 in the lesson, compute **prediction** MSE, penalty, total objective and total gradient. Does zero **training** MSE make this gradient zero?

Teacher reasoning · W1

Teacher explanation: MSE 0, penalty 2, total J 2, total gradient 2. Zero data gradient does not remove the penalty gradient.

W2 Trace the next update

Workbook question · W2

Start v = 1.6 with lambda = 0.5 and rate 0.1. Calculate both gradient contributions, new v and new **prediction** MSE.

Teacher reasoning · W2

Teacher explanation: Data gradient -2, penalty gradient 1.6, total -0.4. New v = 1.64; **prediction** MSE is 2.5 times 0.36 squared = 0.324.

W3 Apply patience without peeking

Workbook question · W3

Validation MSE at epochs 0 to 7 is [4, 2, 1.5, 1.6, 1.4, 1.45, 1.46, 1.3]. Apply the lesson policy with **patience** 2. Give the stop epoch, **restore**d epoch and why the listed epoch 7 cannot change this decision.

Teacher reasoning · W3

Teacher explanation: Stop at epoch 6 after misses at 5 and 6; **restore** epoch 4 with MSE 1.4. A live run has stopped before observing epoch 7; hindsight cannot be included in that policy decision.

W4 Transfer both rules independently

Workbook question · W4

For a new objective J(a) = (a - 2) squared + a squared, gradient 4a - 4, start a = 0 and take one step at rate 0.25. Give new a, **prediction** error term, penalty and total J.

Separately apply **patience** 2 with strict improvement to validation values [3, 2, 2, 2, 1] at epochs 0 to 4; report the stop and **restore**d epochs.

Teacher reasoning · W4

Teacher explanation: The update gives a = 1. **Prediction** error 1, penalty 1, total J 2. For the separate curve, epoch 1 is best at 2; ties at 2 and 3 are two misses, so stop at epoch 3 and **restore** epoch 1.

Epoch 4 is not observed by that live policy.

W5 Compare penalties fairly

Workbook question · W5

A team compares lambda 0 and lambda 0.5 by choosing whichever has the smaller penalised **training** objective. Explain why this does not establish the better **prediction** model and name a suitable development comparison.

Teacher reasoning · W5

Teacher explanation: The objectives use different penalties, and both are **training** quantities. Compare the candidates on the same fixed validation examples using the same declared **prediction** metric, such as ordinary MSE.

Reserve final test examples from setting selection.

Independent assessment and fresh retry

Teacher key · Independent assessment and fresh retry

W4 requires a = 1 and terms 1, 1, 2 plus stop epoch 3 and **restore**d epoch 1. Fresh retry: J(b) = (b - 3) squared + 0.5b squared, gradient 3b - 6; start b = 0, rate 0.25. New b = 1.5, data term 2.25, penalty 1.125, total 3.375.

On validation [5, 3, 3.2, 3.1] with **patience** 2, stop at 3 and **restore** 1.

Assess independent transfer

Independent question · withhold the key

Selected case: For a new objective J(a) = (a - 2) squared + a squared, gradient 4a - 4, start a = 0 and take one step at rate 0.25. Give new a, **prediction** error term, penalty and total J.

Separately apply **patience** 2 with strict improvement to validation values [3, 2, 2, 2, 1] at epochs 0 to 4; report the stop and **restore**d epochs.

Selected case answer

Teacher key · Selected case answer

Teacher explanation: The update gives a = 1. **Prediction** error 1, penalty 1, total J 2. For the separate curve, epoch 1 is best at 2; ties at 2 and 3 are two misses, so stop at epoch 3 and **restore** epoch 1.

Epoch 4 is not observed by that live policy.

Dimension	Evidence required
Explanation	Names the applicable idea or procedure and ties it to the supplied facts.
Trace and result	Preserves the given inputs and shows the relevant intermediate steps; distinguishes a prediction from an observed execution.
Limits	States the assumptions, missing evidence or conditions under which the result would change.

Teacher key · Selected case answer

Record each dimension as not yet, with support, or independent. Accept a valid alternative procedure with a defensible trace.

Do not penalise an honestly recorded model failure if the learner correctly explains its **evidence** and limits.

Feedback that the learner uses

Name the earliest unsupported step and give one action to repair it. Have the learner make that repair now and explain why. Then assess the relevant skill on a fresh, fully specified case.

Confirm it was not previously practised with feedback; solve and check the new case before assigning it. A follow-up design prompt is a starting brief, not automatically an equivalent test.

Connect the project, support and next lesson

> Connect Regularisation and early stopping to Image-pattern Network Investigation, adapt support and plan a later changed-case check.

Add a labelled **regularisation** and early stopping **evidence** sheet to Image-pattern Network Investigation. Show how you can separate a **weight penalty** from **prediction** error.

Use the supplied fictional case and keep its **input**s, intermediate steps, calculation or **prediction**, and limitation. Connect this record to last week's record; a matching answer without a trace is insufficient.

Use a ledger with columns epoch, metric, best epoch and miss count; cover future rows. Extension: solve 5(v - 2) + 2 lambda v = 0 to obtain v = 10 / (5 + 2 lambda).

For nonnegative lambda, discuss why the optimum moves toward zero without claiming this always improves **prediction**.

Week 17 investigates initialisation and reproducibility.

Retain the project ledger and assess a changed case after support. Check the relevant prerequisite before carrying this component forward.

Plan the delayed return

Suggested return points in this level: ai-5/17, ai-5/19, ai-5/22. Use actual classroom dates, adjusting for holidays and gaps. One, three and six teaching weeks are scheduling choices, not a claimed optimal spacing.

At a delayed check, ask for the idea from memory and a changed application. Compare with the earlier independent response and record support used.

For a new level, revisit the previous capstone before checking the new prerequisites.

Record	Teacher evidence
Learner code and date	
Concept and case used; prior exposure	

Record	Teacher evidence
Explanation / trace / limits	
Support and first repair	
Changed case and delayed outcome	
Next teaching action	

Use the **evidence** to choose reteaching or the next step. A completed page, confidence rating or attractive project does not by itself demonstrate understanding.

Project evidence from this case

For your Image-pattern Network Investigation, save the **input**, procedure, observed result and limitation of this check.

Label this worked example as practice; use a different, previously unreviewed case when checking independent understanding.

Prepare, teach and assess

> Use this preparation summary alongside the detailed Regularisation and early stopping lesson; it is a checklist rather than a replacement for the full sequence.

Teaching target

Teaching target: Separate a **weight penalty** from **prediction** error

Prepare the labelled worked-case picture, the matching workbook, fictional **input** cards and a place for individual responses. Check a local Python 3 environment before class; have a paper-trace version ready.

Session · Plan · Resources

> **Session:** Session 1 · Understand · 45 min
>
> **Plan:** 0–7: recall and prerequisite; 7–15: inspect the concrete case and predict; 15–30: teacher models the worked trace; 30–40: learners explain a step using the text and visual; 40–45: check the core idea.
>
> **Resources:** Use Your mission, Notice the evidence, See how it works, Words that unlock the idea and Follow a worked example; record recall in the workbook.

> **Session:** Session 2 · Practise · 45 min
>
> **Plan:** 0–5: retrieve the procedure; 5–15: W2 completion practice; 15–23: explain and check with a partner; 23–30: each learner answers the misconception check; 30–40: targeted reteaching or a harder variation; 40–45: prepare the investigation.
>
> **Resources:** Use Find and repair a mistake, Practise together and Build your understanding; use the matching workbook W2 and Individual reasoning check.

> **Session:** Session 3 · Investigate and transfer · 45 min
>
> **Plan:** 0–5: retrieve the decision rule; 5–20: investigate or trace; 20–30: start the independent case; 30–38: connect the project; 38–43: act on feedback; 43–45: plan the return check.
>
> **Resources:** Use Run the investigation, Connect your project and Try a new case independently. Allow extra time for the full task set. When code is supplied, use the examples in See how it works or Follow a worked example and the browser lab in Supported practice, repair and portfolio.

Before class, solve the supported practice: Start v = 1.6 with lambda = 0.5 and rate 0.1. Calculate both gradient contributions, new v and new **prediction** MSE.

Supported practice answer

Reasoned practice answer: Teacher explanation: Data gradient -2, penalty gradient 1.6, total -0.4. New v = 1.64; **prediction** MSE is 2.5 times 0.36 squared = 0.324.

Check every learner before discussion: Use the worked case for **Regularisation** and early stopping. Proposed explanation: “Zero **prediction** error means no regularised update”. Decide whether this explanation is supported.

Point to the step or supplied fact that decides; explain your repair if needed.

Repair the misconception

Misconception repair: The penalty gradient can remain nonzero.

Support without giving away the answer

Support: read the exact case aloud, enlarge the labelled picture, supply **input** cards and model only the first deciding step. Accept a spoken explanation or drawing; retain the reasoning goal.

Extend the reasoning

Extension: Change **patience** from 1 to2 under the same tie rule. Require a **prediction** and a reason before comparing. Expected result: Stop at checkpoint 4; still **restore** checkpoint 2.

Reason: Checkpoints 3 and 4 are two consecutive non-improvements; a later stop does not redefine the best checkpoint.

Protect the independent attempt

Independent assessment: withhold the reserved answer until the learner has attempted the new case. Record support separately from correctness.

Criterion	Not yet	With support	Independent
Explanation	Names an answer without a deciding fact	Uses a hint to link fact and decision	Explains the deciding fact in own words

Criterion	Not yet	With support	Independent
Trace or test	Cannot connect input and result	Completes steps with prompts	Traces or tests a changed case accurately
Limits and revision	Claims more than evidence supports	Names a limit after a prompt	States a defensible limit and useful next test

Project checkpoint

Project checkpoint: Test changed cases. Keep normal, boundary and failure cases; compare expected and observed results.

Use the weekly teacher answer for topic-specific reasoning. A saved progress tick is an activity record; judge mastery from the learner's explanation and **evidence**.

TEACHER GUIDE · 8 OF 9

Use feedback, labs and repair paths

> Use feedback, earlier review and portfolios purposefully. Apply the coding routine only when this lesson has an executable lab.

Use the two formative questions as supported practice, not as independent mastery scores. Discuss the deciding **evidence** rather than accepting a guessed selection.

The feedback comes from the reviewed public worked case. Do not reveal the separately reserved independent teacher answer until the learner has attempted that case.

Ask students to predict before running code. Preserve errors and actual **output**s; collect a changed test and an explanation. The branch-boundary and indexing lessons deliberately include failure cases.

Use the earlier worked-explanation links to address a specific missing building block, then return to the current question. Adapt this suggestion after observing the learner; it is not an automatic diagnosis.


Collect the completed-work portfolio as **evidence**. Record support separately from correctness, and assess explanation, trace/test and limitations. Progress ticks and quiz selections alone do not establish mastery.

Visual concept journey

> Show one Regularisation and early stopping graphic at a time, request a prediction and discuss its trace before the independent assessment.

Use one picture at a time. Hide a worked result before asking for a **prediction**, then reveal it for feedback. These are supported teaching cases; retain the separate independent assessment for a fresh first attempt.

01. Regularisation and early stopping: the case



Follow the labelled picture with the matching explanation. Open the vector diagram

Separate a **regularisation** penalty from **prediction** loss and an early-stopping rule. Supplied facts: Toy objective J(a)=(a-3)²+2a²; start a = 0; gradient 6a-6; rate 1/6.


Separate validation losses:[5, 3, 3, 4], **patience** 1, no ties as improvement. All **input**s and outcomes in this worked example are invented classroom data; no real model run is claimed.

Point to the given fact that matters most. Explain why it matters.

Discuss while showing the picture

Teacher prompt: Point to the given fact that matters most. Explain why it matters. Ask learners to describe one label or arrow in ordinary words. Use the adjacent transcript if the image is difficult to see.

02. Follow the deciding steps



Follow the labelled picture with the matching explanation. Open the vector diagram


Regularised update: At 0 gradient -6; update gives a = 1. → Split objective: At 1 **prediction** term 4, penalty 2, total 6; at 0 total 9. → Early-stop separately: Best validation checkpoint is 2 with loss 3; checkpoint 3 is no improvement, so stop at 3.

Point to each numbered stage and explain which recorded **input** it uses.

Discuss while showing the picture

Teacher prompt: Point to each numbered stage and explain which recorded **input** it uses. Ask learners to describe one label or arrow in ordinary words. Use the adjacent transcript if the image is difficult to see.

03. Patience two with strict improvement



Follow the labelled picture with the matching explanation. Open the vector diagram


Patience two with strict improvement. 0 then 1 then 2 | 4 then 2 then 1.5 | Save each improved state. 3 then 4 | 1.6 then 1.4 | Wait once then reset. 5 then 6 | 1.45 then 1.46 | Two misses so stop at 6

Read the labels and values. Explain the relationship the model shows.

Discuss while showing the picture

Teacher prompt: Read the labels and values. Explain the relationship the model shows. Ask learners to describe one label or arrow in ordinary words. Use the adjacent transcript if the image is difficult to see.

04. Change one thing. Trace what follows.



Follow the labelled picture with the matching explanation. Open the vector diagram

Original case: Best validation checkpoint is 2 with loss 3; checkpoint 3 is no improvement, so stop at 3. Changed condition: Change **patience** from 1 to2 under the same tie rule.

Expected result: Stop at checkpoint 4; still **restore** checkpoint 2. Reason: Checkpoints 3 and 4 are two consecutive non-improvements; a later stop does not redefine the best checkpoint.


> Predict before checking the worked changed-case result. Name what changed and what the supplied facts allow you to conclude.

Discuss while showing the picture

Teacher prompt: Predict before checking the worked changed-case result. Name what changed and what the supplied facts allow you to conclude. Ask learners to describe one label or arrow in ordinary words.

Use the adjacent transcript if the image is difficult to see. Changed-case reasoning: Checkpoints 3 and 4 are two consecutive non-improvements; a later stop does not redefine the best checkpoint.

05. Connect the explanation to its limit



Follow the labelled picture with the matching explanation. Open the vector diagram

Regularisation adds a parameter penalty to the **training** objective. Here it discourages large a, so the objective balances **prediction** error against that penalty.

Early stopping is a different decision based on the supplied validation sequence. A tied validation loss is not improvement under this policy; stop when the **patience** allowance is used and **restore** the best checkpoint.

Limit: **Regularisation** and early stopping are different tools; neither guarantees better performance in every dataset.


Explain the case, then point to a limit on the claim.

Discuss while showing the picture

Teacher prompt: Explain the case, then point to a limit on the claim. Ask learners to describe one label or arrow in ordinary words. Use the adjacent transcript if the image is difficult to see.

Keep the stated scope: **Regularisation** and early stopping are different tools; neither guarantees better performance in every dataset.

06. Make the idea visible in your project



Follow the labelled picture with the matching explanation. Open the vector diagram

For your Image-pattern Network Investigation, save the **input**, procedure, observed result and limitation of this check.

Label this worked example as practice; use a different, previously unreviewed case when checking independent understanding. Draw your **input**, deciding step, result and limit.

Supported question: Why should the penalty value not be reported as validation error? Point to the relevant step in the picture, then write the changed result and the rule or **evidence** that supports it.

Draw your project trace and justify the deciding step using **evidence**.

Discuss while showing the picture

Teacher prompt: Draw your project trace and justify the deciding step using **evidence**. Ask learners to describe one label or arrow in ordinary words. Use the adjacent transcript if the image is difficult to see.

Supported practice key: It is part of the **training** objective, not the measured validation **prediction** loss. Report these separate quantities with their definitions.

Changed-case check: Stop at checkpoint 4; still **restore** checkpoint 2. Checkpoints 3 and 4 are two consecutive non-improvements; a later stop does not redefine the best checkpoint.

Save or print your responses for your portfolio. Progress and drafts on the hosted website stay in the current browser. Use only fictional or teacher-approved data.