Branching and boundary tests

Learn to understand, design, build, test and explain AI systems responsibly.

Project: Python readiness portfolio

TEACHER GUIDE · 1 OF 9

Prepare the purpose, prerequisites and materials

> Prepare Branching and boundary tests: check the target, prerequisites, resources and adaptable teaching schedule.

Teach the learning cycle

Primary target: Trace the selected **branch** in an if elif else chain

Session · Sequence and minutes · Resources

> **Session:** Session 1 · Understand · 45 min
>
> **Sequence and minutes:** 0–7: recall and prerequisite; 7–15: inspect the concrete case and predict; 15–30: teacher models the worked trace; 30–40: learners explain a step using the text and visual; 40–45: check the core idea.
>
> **Resources:** Sections 1–6; record the brief recall in the workbook.

> **Session:** Session 2 · Practise · 45 min
>
> **Sequence and minutes:** 0–5: retrieve the procedure; 5–15: W2 completion practice; 15–23: explain and check with a partner; 23–30: each learner answers the misconception check; 30–40: targeted reteaching or a harder variation; 40–45: prepare the investigation.
>
> **Resources:** Sections 7–10; use the matching workbook W2 and misconception check.

> **Session:** Session 3 · Investigate and transfer · 45 min

> **Sequence and minutes:** 0–5: retrieve the decision rule; 5–20: investigate or trace; 20–30: start the independent case; 30–38: connect the project; 38–43: act on feedback; 43–45: plan the return check.
>
> **Resources:** Use “Run the investigation”, “Connect your project”, “Show what you know”, “Study a complete case” and “Try a new case independently”. Give extra time for the full task set. If this week has a coding lab, use its named section; section numbers can change when extra explanations are included.

This is a starting allocation of 135 minutes, not a validated duration. Preserve all named topics. Schedule extra time for connected examples, the full investigation, independent cases and project building.

Repeated copies of a case share one recorded attempt; they are not new **evidence**.

Case exposure check: this source example appears in ai-2/3, python-bridge/5. Reuse a familiar case for recall or modelling; verify that the case used to assess transfer has not already received feedback.

Retrieval answer guidance

Boolean conditions

Without opening the old lesson, explain one key idea from Boolean **condition**s. Give an example and a mistake that the idea helps you avoid.

Look for: Translate stated requirements into comparisons

Reference example, not the only acceptable wording: (minutes <= 12) and quiet. At most includes equality, so <= is required; the nonnegative integer and Boolean **input** contract still applies.

Values variables and types

Without opening the old lesson, explain one key idea from Values variables and types. Give an example and a mistake that the idea helps you avoid.

Look for: Distinguish integer, floating-point, text and Boolean values

Reference example, not the only acceptable wording: 12 is int; 1.5 is float; "12" is str; False is bool; "False" is str. Quotes mark text even when the characters spell a Boolean name.

Teach ordered selection and **indentation** using a written **input** contract. A script can cover all **branch**es while missing an equality bug. Reference: https://docs.python.org/3/tutorial/controlflow.html#if-statements.

The new task requires one four-way chain; independently correct equivalent **condition**s are acceptable.

Outcomes

Trace the selected **branch** in an if elif else chain

Use **indentation** to identify which statements belong to a **branch**

Test values at and around a decision **boundary**

Preparation

Python 3 editor and **branch**es.py

The written duration rule and **boundary** case cards

Blank trace table with a skipped marker

Prerequisite answer

<= accepts equality; < excludes it. At 12 the two **condition**s produce different Boolean values.

End goal for the pictorial case

Trace **branch**ing and **boundary** tests and explain the changed program before running it.

This added worked case illustrates the week's main idea. Retain all original and connected topics; schedule its practice within the teaching cycle.

TEACHER GUIDE · 2 OF 9

Explain and model the mechanism

> Model Branching and boundary tests using the supplied case, labelled mechanism and

> reasoning. Make the scope of each conclusion explicit.

Explain Branching and boundary tests · 1

A fictional activity sorter labels a supplied integer duration. Negative values are Invalid; values from zero through 12 are Short; larger values are Long. The labels describe duration only.

Write this requirement before the program so that a test has an expected answer independent of the code.

Explain Branching and boundary tests · 2

An if statement selects a block when its **condition** is true. An elif is considered only if earlier **condition**s in the same chain were false. An else handles the remaining cases. Colons end the **condition** lines.

Use four spaces for the indented statements and keep related **branch**es aligned.

The **output** is Short. For 12, the first **condition** is false and the second is true. The else block is skipped. print(label) is not indented, so it runs after the selected **branch**.

Each path assigns label before this line reads it. Change only minutes and save before each fresh run.

Term	Meaning
Branch	A possible path through a program
Condition	An expression used to decide which path to take
Indentation	Leading spaces that identify a Python code block
Boundary	A value where a classification may change
Regression check	A previous test rerun after an edit to detect a new failure

One chain chooses one label

INPUT	CHECKS IN ORDER	SELECTED LABEL
-1	Below zero is True	Invalid
12	Below zero False; <= 12 True	Short
13	Both checks False	Long

Later branches in this chain are skipped after a condition succeeds.

The faulty < 12 version prints Long for 12, contrary to the inclusive Short rule. Repair to <= 12 and rerun 11 or 13 as well as 12.

Exit: exact 12 is missing. -1, 2 and 20 can visit all **branch**es even when the equality comparison is wrong.

Model the reasoning aloud

Use the complete worked example below before asking learners to complete W2. Reveal a small part, invite a **prediction**, then explain the deciding step.

These teacher notes contain solutions; do not reveal the independent case answer during modelling.

Input minutes	Expected label	Reason for this test
-1	Invalid	Negative input rejection
0	Short	Lowest valid duration
11	Short	Just below the upper boundary

Input minutes	Expected label	Reason for this test
12	Short	Exact upper boundary
13	Long	Just above the boundary

These tests exercise every **branch** and the equality case. A change from <= 12 to < 12 is exposed by 12; testing 11 alone misses it.

Branch coverage means every **branch** was exercised, but it does not prove every **condition** is correct.

> **Suppose the program uses < 12 instead of <= 12. What is printed for 12, why does that violate the written rule, and which earlier test should still pass after repair?**

Thinking move	Teacher prompt
Plan	What is given? What is the question? Which procedure fits these facts?
Do	Point to each input and intermediate step in the worked trace. Name the rule that allows the next step.
Check	Does the output answer the question? Which assumption or limitation prevents a larger claim?

Use the diagram and verbal explanation together. Ask learners to match a sentence to a specific visual step; do not assign learners fixed visual or auditory learning styles.

A pictorial worked case: Branching and boundary tests

Check invalid values before **branch**ing. A toy shelf label uses fewer than five books as "small", otherwise "large", but negative counts are invalid.

The facts we will use

Supplied facts

Python 3: if count<0: label="invalid"; elif count<5: label="small"; else: label="large". Read as indented **branch**es.

AI ACADEMY / PYTHON-BRIDGE/5

Branching and boundary tests

Start with the supplied facts

Follow each arrow. Ask which fact allows the next step.



1. Check validity

For count=-2, the first condition selects invalid.





2. Check small boundary

For count=4, validity passes and count<5 selects small.





3. Handle equality

For count=5, both earlier conditions fail, so large is selected.

CHANGE ONE THING

Remove the first negative-count branch.

Explain the changed result using the matching lesson.

Follow the labelled picture with the matching explanation. Open the vector diagram

Read the picture one step at a time

STEP	WHAT HAPPENS AND WHY
1. Check validity	For count=-2, the first condition selects invalid.
2. Check small boundary	For count=4, validity passes and count<5 selects small.
3. Handle equality	For count=5, both earlier conditions fail, so large is selected.

Match each pictured step to the supplied facts. This is a worked teaching case, not an independent assessment.

Why this result follows

Why the result follows

An if/elif/else chain selects the first matching **branch**. Putting invalid handling first prevents a negative count from being mislabelled as a small valid collection.

What this example does not establish

Keep the stated limit

The toy procedure assumes numeric counts; validate types and define missing-value behaviour before using it in a real service.

Change one thing in the pictured case

Change one thing

Change: Remove the first negative-count **branch**.

Predicted result

Prediction: A count of -2 would incorrectly receive small.

Why the result follows

Reason: Negative two is less than five, but it is not a permitted measured count.

Ask while showing the picture

Ask while showing the picture · 3

Cover the result. Ask learners to name the **input**s and predict the next step. Uncover one step, connect the icon to the actual procedure, and explain its **evidence**. Then change the supplied **condition** and compare.

The picture is a representation; it does not document execution of a real AI model.

Demonstrate and guide practice

> Demonstrate Branching and boundary tests, reduce support deliberately and check individual reasoning before discussing answers.

Choose the pacing route

Compact alternative: this two-session sequence covers selected core tasks. Use the three-session weekly plan for the full lesson, independent transfer, feedback and project work; allow extra time for extensions.

Time or stage	Teacher action
Session 1 start to 7 minutes	Retrieve inclusive comparison and collect the prerequisite.
7 to 20 minutes	Translate the duration rule and complete W1.
20 to 33 minutes	Trace the diagram and code, marking skipped branches.
33 to 45 minutes	Complete W2 with predicted and actual outputs.
Session 2 start to 8 minutes	Retrieve why equality needs a separate test.
8 to 20 minutes	Run the faulty two-if script and complete W3 and the guided question.
20 to 35 minutes	Collect the new sorter in W4 before hints.
35 to 45 minutes	Use W5 and the exit to distinguish coverage from correctness.

Use the worked example in Sections 3 and 6. Collect a **prediction** before revealing its result; ask the learner to point to each intermediate fact.

Provide movable **branch** cards and align the four-space blocks on a ruled page. Permit an oral trace alongside the script and record help.

Extension: swap the zero and <= 6 checks and find the smallest nonnegative counterexample.

Reduce help deliberately

Completion practice

Completion task: For -1, 12 and 13, record checked **condition**s, skipped **condition**s and the final label. Run each as a fresh script after predicting.

Reasoning to listen for

Teacher check: -1: first True, second skipped, Invalid. 12: first False, second True, Short. 13: both False, else selected, Long. Retain observed results separately.

Start by identifying the given **input**s together. Leave the intermediate steps blank. If needed, model one step, then withdraw that help on the next step. Move to a full trace only when the partial trace is understood.

For partners, alternate explainer and checker; collect a response from every learner before discussion.

Individual reasoning check

Use the worked case for **Branch**ing and **boundary** tests. Proposed explanation: “Every **condition** in the chain always runs”. Decide whether this explanation is supported.

Point to the step or supplied fact that decides; explain your repair if needed.

Expected repair

Expected correction: Once one **condition** succeeds, later alternatives are skipped.

Collect explanations, not only yes/no votes. If a misunderstanding is common, re-model the relevant step for the class.

If it affects a few learners, give a short targeted group explanation while others solve a more demanding variation.

Pictorial practice question

Trace -2, 4 and 5 through the **branch**es. Explain why the negative check comes first and what label -2 gets if it is removed.

Reasoned teacher answer

The labels are invalid, small and large. The first **branch** stops negative **input**s before the small rule. Without it, -2<5 produces small and breaks the **input** contract.

Changed-case reasoning: A count of -2 would incorrectly receive small. Negative two is less than five, but it is not a permitted measured count.

Collect each learner's explanation before discussion. Use the first missing connection between **input**, deciding step and result to choose support. This question is worked-case practice, not fresh mastery **evidence**.

TEACHER GUIDE · 4 OF 9

Run the investigation and diagnose misconceptions

> Run the Branching and boundary tests investigation and use the first unsupported step to choose a teaching response.

Every **condition** in the chain always runs: Once one **condition** succeeds, later alternatives are skipped.

Two if statements behave like if then elif: Independent if statements can both run and overwrite a result.

Indentation is cosmetic: Leading spaces define the **branch** body.

Every **branch** tested means every **input** correct: A missing equality case can hide a wrong comparison.

Use Section 9 for the **evidence** ledger. Add a **boundary** or missing-**input** case and record the expected response before checking. More successful repeats of one case do not establish wider coverage.

Match the support to the first error

What the response shows	Next teaching action
Missing or misread facts	Read the case aloud, mark supplied versus unknown facts, and let the learner restate it.

What the response shows	Next teaching action
Wrong procedure	Return to the deciding step in the worked case. Contrast it with the proposed incorrect explanation.
Arithmetic or implementation error	Trace intermediate values or lines; preserve the first mismatch and retry that step.
Correct result without a reason	Ask for a trace and a changed case before marking independent understanding.
An unsupported wider claim	Ask which supplied evidence supports the claim and which further observation would be needed.

Offer an oral explanation, drawing, enlarged visual or fewer examples when that removes a reading/writing barrier. Keep the same reasoning goal.

Stretch secure learners by changing a **boundary** or assumption and asking them to defend the effect, not simply by assigning more of the same questions.

Assess and explain the answers

> Use the Branching and boundary tests questions, teacher keys and criteria after the relevant attempts. Previously discussed cases are practice; protect the separately selected independent task.

Guided and exit questions

The faulty < 12 version prints Long for 12, contrary to the inclusive Short rule. Repair to <= 12 and rerun 11 or 13 as well as 12.

Exit: exact 12 is missing. -1, 2 and 20 can visit all **branch**es even when the equality comparison is wrong.

W1 Explain the chain

Workbook question · W1

Describe the purpose of if, elif and else in the worked duration sorter. Explain why print(label) is outside the indented **branch**es.

Teacher reasoning · W1

if tests negative first; elif checks <= 12 only after that fails; else handles the rest. Unindented print runs after any selected **branch**, whose assignment gives label a value.

W2 Trace the tested path

Workbook question · W2

For -1, 12 and 13, record checked **condition**s, skipped **condition**s and the final label. Run each as a fresh script after predicting.

Teacher reasoning · W2

-1: first True, second skipped, Invalid. 12: first False, second True, Short. 13: both False, else selected, Long. Retain observed results separately.

W3 Repair the overwritten result

Workbook question · W3

Trace the two-independent-if example for -1. Identify which assignment overwrites the earlier label and make the smallest repair.

Teacher reasoning · W3

The first assignment sets Invalid; the second if also succeeds and changes label to Short. Replace the second if with elif. The repaired **output** is Invalid.

W4 Build a new sorter independently

Workbook question · W4

Use an integer tiles count. Label a negative value Invalid, zero Empty, 1 through 6 Small and values above 6 Large. Write an ordered if elif else script and predict -1, 0, 1, 6 and 7. Include one print after the chain.

Teacher reasoning · W4

Use if tiles < 0, elif tiles == 0, elif tiles <= 6, else, assigning the respective labels and printing after the chain. **Output**s Invalid, Empty, Small, Small, Large. Zero must be handled before the <= 6 **branch**.

W5 Choose revealing regression tests

Workbook question · W5

A repair changes the small-count **condition** from < 6 to <= 6. Name the case that exposes the original error and two different kinds of earlier cases to rerun.

Teacher reasoning · W5

6 exposes the original wrong Large label. Rerun zero for Empty and a negative count for Invalid, or 7 for Large. Passing only 6 does not check earlier **branch**es.

Independent assessment and fresh retry

Teacher key · Independent assessment and fresh retry

W4 must assign one correct label on all five cases and explain zero before the small **branch**. After support, retry a shelf-count sorter with Empty at zero, Few for 1 through 4, Many above 4 and Invalid below zero.

Expected **output**s at -1, 0, 4, 5 are Invalid, Empty, Few, Many.

Assess independent transfer

Independent question · withhold the key

Selected case: Predict the action for 30, then trace 29 and -1. Explain why validity is checked before the lamp decision.

```
reading = 30
if not 0 <= reading <= 100:
    action = "invalid"
elif reading < 30:
    action = "on"
else:
    action = "off"
print(action)
```

Selected case answer

Teacher key · Selected case answer

30 gives off, 29 gives on, -1 gives invalid. Checking validity first prevents an invalid negative reading from being accepted as a lamp-on decision.

Dimension	Evidence required
Explanation	Names the applicable idea or procedure and ties it to the supplied facts.
Trace and result	Preserves the given inputs and shows the relevant intermediate steps; distinguishes a prediction from an observed execution.
Limits	States the assumptions, missing evidence or conditions under which the result would change.

Teacher key · Selected case answer

Record each dimension as not yet, with support, or independent. Accept a valid alternative procedure with a defensible trace.

Do not penalise an honestly recorded model failure if the learner correctly explains its **evidence** and limits.

Feedback that the learner uses

Name the earliest unsupported step and give one action to repair it. Have the learner make that repair now and explain why. Then assess the relevant skill on a fresh, fully specified case.

Confirm it was not previously practised with feedback; solve and check the new case before assigning it. A follow-up design prompt is a starting brief, not automatically an equivalent test.

Connect the project, support and next lesson

> Connect Branching and boundary tests to Python readiness portfolio, adapt support and plan a later changed-case check.

Add a labelled **branch**ing and **boundary** tests **evidence** sheet to Python readiness portfolio. Show how you can trace the selected **branch** in an if elif else chain.

Use the supplied fictional case and keep its **input**s, intermediate steps, calculation or **prediction**, and limitation. Connect this record to last week's record; a matching answer without a trace is insufficient.

Provide movable **branch** cards and align the four-space blocks on a ruled page. Permit an oral trace alongside the script and record help.

Extension: swap the zero and <= 6 checks and find the smallest nonnegative counterexample.

Week 6 repeats a block with loops and records each change in state.

Retain the project ledger and assess a changed case after support. Check the relevant prerequisite before carrying this component forward.

Plan the delayed return

Suggested return points in this level: python-bridge/6, python-bridge/8, python-bridge/11. Use actual classroom dates, adjusting for holidays and gaps.

One, three and six teaching weeks are scheduling choices, not a claimed optimal spacing.

At a delayed check, ask for the idea from memory and a changed application. Compare with the earlier independent response and record support used.

For a new level, revisit the previous capstone before checking the new prerequisites.

Record	Teacher evidence
Learner code and date	
Concept and case used; prior exposure	
Explanation / trace / limits	
Support and first repair	
Changed case and delayed outcome	
Next teaching action	

Use the **evidence** to choose reteaching or the next step. A completed page, confidence rating or attractive project does not by itself demonstrate understanding.

Project evidence from this case

For Python readiness before the Responsible Plant Classifier, retain a trace of the values, the predicted **output**s and the changed-case explanation. Use actual Python 3 results to check the **prediction** after reasoning first.

Prepare, teach and assess

> Use this preparation summary alongside the detailed Branching and boundary tests lesson; it is a checklist rather than a replacement for the full sequence.

Teaching target

Teaching target: Trace the selected **branch** in an if elif else chain

Prepare the labelled worked-case picture, the matching workbook, fictional **input** cards and a place for individual responses. Check a local Python 3 environment before class; have a paper-trace version ready.

Session · Plan · Resources

> **Session:** Session 1 · Understand · 45 min
>
> **Plan:** 0–7: recall and prerequisite; 7–15: inspect the concrete case and predict; 15–30: teacher models the worked trace; 30–40: learners explain a step using the text and visual; 40–45: check the core idea.
>
> **Resources:** Sections 1–6; record the brief recall in the workbook.

> **Session:** Session 2 · Practise · 45 min

> **Plan:** 0–5: retrieve the procedure; 5–15: W2 completion practice; 15–23: explain and check with a partner; 23–30: each learner answers the misconception check; 30–40: targeted reteaching or a harder variation; 40–45: prepare the investigation.
>
> **Resources:** Sections 7–10; use the matching workbook W2 and misconception check.

> **Session:** Session 3 · Investigate and transfer · 45 min
>
> **Plan:** 0–5: retrieve the decision rule; 5–20: investigate or trace; 20–30: start the independent case; 30–38: connect the project; 38–43: act on feedback; 43–45: plan the return check.
>
> **Resources:** Use “Run the investigation”, “Connect your project”, “Show what you know”, “Study a complete case” and “Try a new case independently”. Give extra time for the full task set. If this week has a coding lab, use its named section; section numbers can change when extra explanations are included.

Before class, solve the supported practice: For -1, 12 and 13, record checked **condition**s, skipped **condition**s and the final label. Run each as a fresh script after predicting.

Supported practice answer

Reasoned practice answer: -1: first True, second skipped, Invalid. 12: first False, second True, Short. 13: both False, else selected, Long. Retain observed results separately.

Check every learner before discussion: Use the worked case for **Branch**ing and **boundary** tests. Proposed explanation: “Every **condition** in the chain always runs”. Decide whether this explanation is supported.

Point to the step or supplied fact that decides; explain your repair if needed.

Repair the misconception

Misconception repair: Once one **condition** succeeds, later alternatives are skipped.

Support without giving away the answer

Support: read the exact case aloud, enlarge the labelled picture, supply **input** cards and model only the first deciding step. Accept a spoken explanation or drawing; retain the reasoning goal.

Extend the reasoning

Extension: Remove the first negative-count **branch**. Require a **prediction** and a reason before comparing. Expected result: A count of -2 would incorrectly receive small.

Reason: Negative two is less than five, but it is not a permitted measured count.

Protect the independent attempt

Independent assessment: withhold the reserved answer until the learner has attempted the new case. Record support separately from correctness.

Criterion	Not yet	With support	Independent
Explanation	Names an answer without a deciding fact	Uses a hint to link fact and decision	Explains the deciding fact in own words
Trace or test	Cannot connect input and result	Completes steps with prompts	Traces or tests a changed case accurately
Limits and revision	Claims more than evidence supports	Names a limit after a prompt	States a defensible limit and useful next test

Project checkpoint

Project checkpoint: Python readiness portfolio. Keep runnable code, **prediction**s, actual **output**s, one repaired error and an explanation of a function on changed **input**s.

Use the weekly teacher answer for topic-specific reasoning. A saved progress tick is an activity record; judge mastery from the learner's explanation and **evidence**.

TEACHER GUIDE · 8 OF 9

Use feedback, labs and repair paths

> Use feedback, earlier review and portfolios purposefully. Apply the coding routine only when this lesson has an executable lab.

Use the two formative questions as supported practice, not as independent mastery scores. Discuss the deciding **evidence** rather than accepting a guessed selection.

The feedback comes from the reviewed public worked case. Do not reveal the separately reserved independent teacher answer until the learner has attempted that case.

Ask students to predict before running code. Preserve errors and actual **output**s; collect a changed test and an explanation. The **branch**-**boundary** and indexing lessons deliberately include failure cases.

Use the earlier worked-explanation links to address a specific missing building block, then return to the current question. Adapt this suggestion after observing the learner; it is not an automatic diagnosis.

Collect the completed-work portfolio as **evidence**. Record support separately from correctness, and assess explanation, trace/test and limitations. Progress ticks and quiz selections alone do not establish mastery.

TEACHER GUIDE · 9 OF 9


Visual concept journey

> Show one Branching and boundary tests graphic at a time, request a prediction and discuss

> its trace before the independent assessment.

Use one picture at a time. Hide a worked result before asking for a **prediction**, then reveal it for feedback. These are supported teaching cases; retain the separate independent assessment for a fresh first attempt.

01. Branching and boundary tests: the case



Follow the labelled picture with the matching explanation. Open the vector diagram

Check invalid values before **branch**ing. A toy shelf label uses fewer than five books as "small", otherwise "large", but negative counts are invalid.


Supplied facts: Python 3: if count<0: label="invalid"; elif count<5: label="small"; else: label="large". Read as indented **branch**es.

> Point to the given fact that matters most. Explain why it matters.

Discuss while showing the picture

Teacher prompt: Point to the given fact that matters most. Explain why it matters. Ask learners to describe one label or arrow in ordinary words. Use the adjacent transcript if the image is difficult to see.

02. Follow the deciding steps



Follow the labelled picture with the matching explanation. Open the vector diagram


Check validity: For count=-2, the first **condition** selects invalid. → Check small **boundary**: For count=4, validity passes and count<5 selects small. → Handle equality: For count=5, both earlier **condition**s fail, so large is selected.

Point to each numbered stage and explain which recorded **input** it uses.

Discuss while showing the picture

Teacher prompt: Point to each numbered stage and explain which recorded **input** it uses. Ask learners to describe one label or arrow in ordinary words. Use the adjacent transcript if the image is difficult to see.

03. Check invalid values before the size rule



Follow the labelled picture with the matching explanation. Open the vector diagram


First ask count less than zero: yes selects invalid. Otherwise ask count less than five: yes selects small; no selects large. Separate **input** traces are minus two invalid, four small, five large.

Read the labels and values. Explain the relationship the model shows.

Discuss while showing the picture

Teacher prompt: Read the labels and values. Explain the relationship the model shows. Ask learners to describe one label or arrow in ordinary words. Use the adjacent transcript if the image is difficult to see.

04. Change one thing. Trace what follows.



Follow the labelled picture with the matching explanation. Open the vector diagram

Original case: For count=5, both earlier **condition**s fail, so large is selected. Changed **condition**: Remove the first negative-count **branch**. Expected result: A count of -2 would incorrectly receive small.

Reason: Negative two is less than five, but it is not a permitted measured count.


Predict before checking the worked changed-case result. Name what changed and what the supplied facts allow you to conclude.

Discuss while showing the picture

Teacher prompt: Predict before checking the worked changed-case result. Name what changed and what the supplied facts allow you to conclude. Ask learners to describe one label or arrow in ordinary words.

Use the adjacent transcript if the image is difficult to see. Changed-case reasoning: Negative two is less than five, but it is not a permitted measured count.

05. Connect the explanation to its limit



Follow the labelled picture with the matching explanation. Open the vector diagram

An if/elif/else chain selects the first matching **branch**. Putting invalid handling first prevents a negative count from being mislabelled as a small valid collection.

Limit: The toy procedure assumes numeric counts; validate types and define missing-value behaviour before using it in a real service.


Explain the case, then point to a limit on the claim.

Discuss while showing the picture

Teacher prompt: Explain the case, then point to a limit on the claim. Ask learners to describe one label or arrow in ordinary words. Use the adjacent transcript if the image is difficult to see.

Keep the stated scope: The toy procedure assumes numeric counts; validate types and define missing-value behaviour before using it in a real service.

06. Make the idea visible in your project



Follow the labelled picture with the matching explanation. Open the vector diagram

For Python readiness before the Responsible Plant Classifier, retain a trace of the values, the predicted **output**s and the changed-case explanation. Use actual Python 3 results to check the **prediction** after reasoning first.

Draw your **input**, deciding step, result and limit. Supported question: Trace -2, 4 and 5 through the **branch**es. Explain why the negative check comes first and what label -2 gets if it is removed.

Draw your project trace and justify the deciding step using **evidence**.

Discuss while showing the picture

Teacher prompt: Draw your project trace and justify the deciding step using **evidence**. Ask learners to describe one label or arrow in ordinary words. Use the adjacent transcript if the image is difficult to see.

Supported practice key: The labels are invalid, small and large. The first **branch** stops negative **input**s before the small rule. Without it, -2<5 produces small and breaks the **input** contract.

Save or print your responses for your portfolio. Progress and drafts on the hosted website stay in the current browser. Use only fictional or teacher-approved data.