Debugging shapes and gradients

Learn to understand, design, build, test and explain AI systems responsibly.

Project: Image-pattern Network Investigation

Prepare the purpose, prerequisites and materials

> Prepare Debugging shapes and gradients: check the target, prerequisites, resources and adaptable teaching schedule.

Teach the learning cycle

Primary target: Check dimension **contract**s before computing a layer

Session · Sequence and minutes · Resources

> **Session:** Session 1 · Understand · 45 min
>
> **Sequence and minutes:** 0–7: recall and prerequisite; 7–15: inspect the concrete case and predict; 15–30: teacher models the worked trace; 30–40: learners explain a step using the text and visual; 40–45: check the core idea.
>
> **Resources:** Sections 1–6; record the brief recall in the workbook.

> **Session:** Session 2 · Practise · 45 min
>
> **Sequence and minutes:** 0–5: retrieve the procedure; 5–15: W2 completion practice; 15–23: explain and check with a partner; 23–30: each learner answers the misconception check; 30–40: targeted reteaching or a harder variation; 40–45: prepare the investigation.
>
> **Resources:** Sections 7–10; use the matching workbook W2 and misconception check.

> **Session:** Session 3 · Investigate and transfer · 45 min

> **Sequence and minutes:** 0–5: retrieve the decision rule; 5–20: investigate or trace; 20–30: start the independent case; 30–38: connect the project; 38–43: act on feedback; 43–45: plan the return check.
>
> **Resources:** Sections 9 and 11–14. Give extra time to finish the full task set; use Section 15 when the week includes a coding lab.

This is a starting allocation of 135 minutes, not a validated duration. Preserve all named topics. Schedule extra time for connected examples, the full investigation, independent cases and project building.

Repeated copies of a case share one recorded attempt; they are not new **evidence**.

Retrieval answer guidance

Initialisation and reproducibility

Without opening the old lesson, explain one key idea from Initialisation and reproducibility. Give an example and a mistake that the idea helps you avoid.

Look for: Trace how starting values affect a fixed **training** budget

Reference example, not the only acceptable wording: Teacher explanation: States are -2, 0 and 1. Final **training** MSE is 2.5. Each step halves the signed distance from 2.

Training and validation curves

Without opening the old lesson, explain one key idea from **Training** and validation curves. Give an example and a mistake that the idea helps you avoid.

Look for: Compute comparable **training** and validation losses at saved checkpoints

Reference example, not the only acceptable wording: Teacher explanation: **Prediction**s [3, 4], residuals [-1.5, -2], squares [2.25, 4], MSE 3.125.

Training a small network

Without opening the old lesson, explain one key idea from **Training** a small network. Give an example and a mistake that the idea helps you avoid.

Look for: Trace repeated forward loss gradient and update steps

Reference example, not the only acceptable wording: Teacher explanation: **Prediction**s [0, 0], errors [-2, -4], MSE 10, gradient -10 and new v = 1.

Use two 45-minute sessions. Start with an axis **contract** and a deliberately wrong intermediate value. Keep the dense-layer example separate from the scalar gradient diagnostic.

The central assessment is locating the first error and preserving meaningful **regression check**s, not merely getting a program to execute.

Outcomes

Check dimension **contract**s before computing a layer

Locate the first wrong value in a forward or gradient trace

Verify a repair with independent checks and limited claims

Preparation

Printed lesson and workbook; paper and pencil

Calculator and optional local Python 3 editor; no packages or AI accounts needed

Use the fictional examples supplied; prepare the fresh retry before class

Prerequisite answer

A deterministic error can repeat perfectly. Independent expected values and checks of intermediate computations are needed.

End goal for the pictorial case

By the end, I can explain debugging **shape**s and gradients using a traced example and a stated limitation.

This added worked case illustrates the week’s main idea. Retain all original and connected topics; schedule its practice within the teaching cycle.

Explain and model the mechanism

> Model Debugging shapes and gradients using the supplied case, labelled mechanism and reasoning. Make the scope of each conclusion explicit.

For this lesson, a dense layer stores one **output** unit per weight-matrix row. If an **input** has two features and the layer has three units, W has three rows and two columns, b has length 3, and one **input** x has length 2.

Compute z for each unit, then apply ReLU to each component.

Use W rows [1, 0], [0, 1], [1, -1] and b = [0, 0, 1]. For x = [1, 2], the scores are [1, 2, 0] and the activations are [1, 2, 0].

A batch stores examples in rows: **input**s [[1, 2], [3, 1]] have **shape** 2 by 2, and **output**s have **shape** 2 by 3.

Other software may use a transposed weight convention. The key is to record and follow one **contract**. An array with the right number of values can still be wrong if features or axes are swapped.

Python zip stops when its shortest **input** ends. Without a length check, a missing feature can silently remove a contribution.

Reject malformed dimensions before computing: do not pad, truncate or re**shape** a mismatched **input** just to make the calculation run.

The function assumes finite numeric values; it checks dimensions, not every possible **input** fault. Evaluate the two batch rows independently and stack their **output**s.

Retain tests that reject a missing **input** feature, a short weight row and an incorrect bias count.

Term	Meaning
Shape	The sizes of an array along its declared axes
Contract	A stated condition that inputs and outputs must satisfy
Partial gradient	The change rate of a scalar loss with respect to one parameter while others are fixed

Term	Meaning
Regression check	A saved check rerun after a repair to detect the return of a defect

Repair from the first disagreement

TRACE STAGE FOR X [1 2]	EXPECTED RESULT	SUBMITTED RESULT
Input and dimensions	x length 2 W 3 by 2 b length 3	Dimensions match
Scores before ReLU	[1, 2, 0]	[1, 2, -1]
Hidden activations	[1, 2, 0]	[1, 2, 0]

The submitted third score omits bias 1. ReLU hides the error for this input, so matching final activations are not enough. At x = [3, 1], the same omission changes the third activation from 3 to 2.

Explain Debugging shapes and gradients · 1

Guided: correct scores [0, 2, -1], activations [0, 2, 0]. With the third bias omitted, scores become [0, 2, -2], but activations stay [0, 2, 0]. Exit: neither check is sufficient.

Verify the intermediate score, coordinate meanings and expected update, use multiple independent **input**s and retain malformed-dimension checks.

Model the reasoning aloud

Use the complete worked example below before asking learners to complete W2. Reveal a small part, invite a **prediction**, then explain the deciding step.

These teacher notes contain solutions; do not reveal the independent case answer during modelling.

Repair from the first disagreement

TRACE STAGE FOR X [1 2]	EXPECTED RESULT	SUBMITTED RESULT
Input and dimensions	x length 2 W 3 by 2 b length 3	Dimensions match
Scores before ReLU	[1, 2, 0]	[1, 2, -1]
Hidden activations	[1, 2, 0]	[1, 2, 0]

The submitted third score omits bias 1. ReLU hides the error for this input, so matching final activations are not enough. At x = [3, 1], the same omission changes the third activation from 3 to 2.

Trace x = [0, 2] with the correct layer. Then omit the third bias. Which scores differ, and why do the activation vectors still agree?

Thinking move	Teacher prompt
Plan	What is given? What is the question? Which procedure fits these facts?
Do	Point to each input and intermediate step in the worked trace. Name the rule that allows the next step.
Check	Does the output answer the question? Which assumption or limitation prevents a larger claim?

Use the diagram and verbal explanation together. Ask learners to match a sentence to a specific visual step; do not assign learners fixed visual or auditory learning styles.

A pictorial worked case: Debugging shapes and gradients

Catch a gradient -order bug before the optimiser changes parameters.

The facts we will use

> **Supplied facts**
>
> Toy $y=2a+3c$, target 4, start $[a, c]=[1, 0]$. Loss $(y-4)^2$. Program claims gradient $[-12,-8]$ in order $[a, c]$.

> **Supplied facts**
>
> All **input**s and outcomes in this worked example are invented classroom data; no real model run is claimed.

AI ACADEMY / AI-5/18

Debugging shapes and gradients

Start with the supplied facts

Follow each arrow. Ask which fact allows the next step.



1. Compute correct gradient

y = 2, residual -2: gradient [-8,-12], not [-12,-8].



2. Check coordinates

Step 0.1: a losses 3.24, 4.84 give -8; c losses 2.89, 5.29 give -12.



3. Apply correct update

At rate 0.01: new [a, c]=[1.08, 0.12]; y = 2.52, loss 2.1904.

CHANGE ONE THING

The program changes its declared order to [c, a] and returns [-12,-8].

Explain the changed result using the matching lesson.

Follow the labelled picture with the matching explanation. Open the vector diagram

Read the picture one step at a time

STEP	WHAT HAPPENS AND WHY
1. Compute correct gradient	y = 2, residual -2: gradient [-8,-12], not [-12,-8].
2. Check coordinates	Step 0.1: a losses 3.24, 4.84 give -8; c losses 2.89, 5.29 give -12.
3. Apply correct update	At rate 0.01: new [a, c]=[1.08, 0.12]; y = 2.52, loss 2.1904.

Match each pictured step to the supplied facts. This is a worked teaching case, not an independent assessment.

Why this result follows

Why the result follows

Array **shape** and coordinate meaning both matter. A vector with two entries can have the right length but assign each derivative to the wrong parameter.

Label the entries a and c, then perturb one coordinate at a time to check their slopes. Repairing the coordinate mapping is necessary before using the gradient to update the network.

What this example does not establish

Keep the stated limit

A correct gradient at one point does not establish every batch, **shape** or activation path is

implemented correctly.

Change one thing in the pictured case

Change one thing

Change: The program changes its declared order to [c, a] and returns [-12,-8].

Predicted result

Prediction: That vector now matches the declared coordinate order.

Why the result follows

Reason: Gradient values are meaningful only when their parameter names and array positions agree.

Ask while showing the picture

Ask while showing the picture · 2

Cover the result. Ask learners to name the **input**s and predict the next step. Uncover one step, connect the icon to the actual procedure, and explain its **evidence**. Then change the supplied condition and compare.

The picture is a representation; it does not document execution of a real AI model.

Demonstrate and guide practice

> Demonstrate Debugging shapes and gradients, reduce support deliberately and check individual reasoning before discussing answers.

Time or stage	Teacher action
Session 1 start to 7 minutes	Retrieve the difference between repeated and independently checked results; label all axes.
7 to 18 minutes	Trace both batch examples and use W1 to reject a dimension mismatch.
18 to 32 minutes	Run or trace the guarded dense-layer function and test invalid dimensions.
32 to 45 minutes	Use the visual and W2 to show how ReLU can hide a bias omission on one input.
Session 2 start to 8 minutes	Complete the guided x = [0, 2] trace, comparing scores with activations.
8 to 20 minutes	Probe w and b separately in the scalar diagnostic, then complete W3.
20 to 35 minutes	Collect W4 independently with four probe losses, ordered gradients and the corrected update.
35 to 45 minutes	Use W5 and the exit response to retain a regression checklist; administer the fresh retry.

Use the worked example in Sections 3 and 6. Collect a **prediction** before revealing its result; ask the learner to point to each intermediate fact.

Provide labelled columns for **input**s, scores, activations and parameter coordinates; allow calculators.

Extension: test several positive and negative **input**s against an independent explicit formula and explain why a test at a ReLU corner needs different reasoning from a smooth gradient check.

Reduce help deliberately

Completion practice

Completion task: Compute scores and activations for x = [3, 1] with the lesson layer, then omit the third bias. Identify the first discrepancy and the resulting activation error.

Reasoning to listen for

Teacher check: Teacher explanation: Correct scores and activations are [3, 1, 3]. Omitting the third bias produces [3, 1, 2]. The third score is the first discrepancy and now survives ReLU.

Start by identifying the given **input**s together. Leave the intermediate steps blank. If needed, model one step, then withdraw that help on the next step. Move to a full trace only when the partial trace is understood.

For partners, alternate explainer and checker; collect a response from every learner before discussion.

Individual reasoning check

Use the worked case for Debugging **shape**s and gradients. Proposed explanation: “Matching **output shape** guarantees the computation”. Decide whether this explanation is supported.

Point to the step or supplied fact that decides; explain your repair if needed.

Expected repair

Expected correction: Correct dimensions can hide swapped features, missing biases or wrong axis meanings.

Collect explanations, not only yes/no votes. If a misunderstanding is common, re-model the relevant step for the class.

If it affects a few learners, give a short targeted group explanation while others solve a more demanding variation.

Pictorial practice question

What should a debugging record pair with every gradient value? Point to the relevant step in the picture, then write the changed result and the rule or **evidence** that supports it.

Reasoned teacher answer

Parameter name and index, expected **shape**, analytic derivative and numerical check; correct [a, c] gradient is [-8,-12]. Changed-case check: That vector now matches the declared coordinate order.

Gradient values are meaningful only when their parameter names and array positions agree.

Changed-case reasoning: That vector now matches the declared coordinate order. Gradient values are meaningful only when their parameter names and array positions agree.

Collect each learner's explanation before discussion. Use the first missing connection between **input**, deciding step and result to choose support. This question is worked-case practice, not fresh mastery **evidence**.

TEACHER GUIDE · 4 OF 9

Run the investigation and diagnose misconceptions

> Run the Debugging shapes and gradients investigation and use the first unsupported step to choose a teaching response.

Matching **output shape** guarantees the computation: Correct dimensions can hide swapped features, missing biases or wrong axis meanings.

Matching final activations proves all scores: ReLU can map different negative scores to the same zero.

Decreasing loss proves a correct gradient: An incorrect direction can still improve one case; compare coordinate probes and exact update expectations.

Use Section 9 for the **evidence** ledger. Add a boundary or missing-**input** case and record the expected response before checking. More successful repeats of one case do not establish wider coverage.

Match the support to the first error

What the response shows	Next teaching action
Missing or misread facts	Read the case aloud, mark supplied versus unknown facts, and let the learner restate it.
Wrong procedure	Return to the deciding step in the worked case. Contrast it with the proposed incorrect explanation.
Arithmetic or implementation error	Trace intermediate values or lines; preserve the first mismatch and retry that step.
Correct result without a reason	Ask for a trace and a changed case before marking independent understanding.
An unsupported wider claim	Ask which supplied evidence supports the claim and which further observation would be needed.

Offer an oral explanation, drawing, enlarged visual or fewer examples when that removes a reading/writing barrier. Keep the same reasoning goal.

Stretch secure learners by changing a boundary or assumption and asking them to defend the effect, not simply by assigning more of the same questions.

Assess and explain the answers

> Use the Debugging shapes and gradients questions, teacher keys and criteria after the relevant attempts. Previously discussed cases are practice; protect the separately selected independent task.

Guided and exit questions

Guided: correct scores [0, 2, -1], activations [0, 2, 0]. With the third bias omitted, scores become [0, 2, -2], but activations stay [0, 2, 0]. Exit: neither check is sufficient.

Verify the intermediate score, coordinate meanings and expected update, use multiple independent **input**s and retain malformed-dimension checks.

W1 Reject a shape mismatch

Workbook question · W1

The layer expects W **shape** 3 by 2, b length 3 and x length 2. A submitted x has length 3. Should the last feature be silently ignored? State the failed **contract** and repair **process**.

Teacher reasoning · W1

Teacher explanation: No. Each weight row must have the same length as x.

Confirm the intended feature schema, then supply a valid two-feature **input** or deliberately redesign and retrain the layer; do not silently discard a value.

W2 Expose a hidden bias error

Workbook question · W2

Compute scores and activations for x = [3, 1] with the lesson layer, then omit the third bias. Identify the first discrepancy and the resulting activation error.

Teacher reasoning · W2

Teacher explanation: Correct scores and activations are [3, 1, 3]. Omitting the third bias produces [3, 1, 2]. The third score is the first discrepancy and now survives ReLU.

W3 Check an update sign

Workbook question · W3

For the diagnostic model at [1, 0], gradient [-4, -2] and rate 0.05, calculate the correct new parameters and loss. Compare with adding the gradient step.

Teacher reasoning · W3

Teacher explanation: Correct subtraction gives [1.2, 0.1], **prediction** 2.5 and loss 0.25. Addition gives [0.8, -0.1], **prediction** 1.5 and loss 2.25, compared with starting loss 1.

W4 Debug a new gradient independently

Workbook question · W4

Use y = 3a + c, target 2, loss (y - 2) squared, at [a, c] = [0, 1]. A program returns gradient [-2, -6] in order [a, c].

Use symmetric step 0.1 to check each coordinate, then update both with the corrected gradient and rate 0.05. Report new parameters and loss.

Teacher reasoning · W4

Teacher explanation: For a, losses at -0.1 and 0.1 are 1.69 and 0.49, giving -6. For c, losses at 0.9 and 1.1 are 1.21 and 0.81, giving -2. The entries were swapped. Correct update gives [0.3, 1.1], **prediction** 2 and loss 0.

W5 Keep independent regression checks

Workbook question · W5

A program passes only the x = [1, 2] final-activation test. Propose one intermediate-value check, one malformed-**input** check and one additional **input** that exposes the bias omission.

Teacher reasoning · W5

Teacher explanation: Check scores [1, 2, 0] before ReLU; reject a wrong **input** length or bias count; test x = [3, 1], whose third activation must be 3.

These checks address different defects rather than repeating the same final **output**.

Independent assessment and fresh retry

Teacher key · Independent assessment and fresh retry

W4 requires partials [-6, -2], new parameters [0.3, 1.1] and loss 0. Fresh retry: y = 2p + q, target 4, at [1, 1]. With step 0.1, p losses 1.44 and 0.64 give -4; q losses 1.21 and 0.81 give -2.

Rate 0.1 gives [1.4, 1.2], **prediction** 4 and loss 0. Require parameter ordering to remain explicit.

Assess independent transfer

Independent question · withhold the key

Selected case: Use y = 3a + c, target 2, loss (y - 2) squared, at [a, c] = [0, 1]. A program returns gradient [-2, -6] in order [a, c].

Use symmetric step 0.1 to check each coordinate, then update both with the corrected gradient and rate 0.05. Report new parameters and loss.

Selected case answer

> **Teacher key · Selected case answer**
>
> Teacher explanation: For a, losses at -0.1 and 0.1 are 1.69 and 0.49, giving -6. For c, losses at 0.9 and 1.1 are 1.21 and 0.81, giving -2. The entries were swapped. Correct update gives [0.3, 1.1], **prediction** 2 and loss 0.

Dimension	Evidence required
Explanation	Names the applicable idea or procedure and ties it to the supplied facts.
Trace and result	Preserves the given inputs and shows the relevant intermediate steps; distinguishes a prediction from an observed execution.
Limits	States the assumptions, missing evidence or conditions under which the result would change.

> **Teacher key · Selected case answer**
>
> Record each dimension as not yet, with support, or independent. Accept a valid alternative procedure with a defensible trace.
>
> Do not penalise an honestly recorded model failure if the learner correctly explains its **evidence** and limits.

Feedback that the learner uses

Name the earliest unsupported step and give one action to repair it. Have the learner make that repair now and explain why. Then assess the relevant skill on a fresh, fully specified case.

Confirm it was not previously practised with feedback; solve and check the new case before assigning it. A follow-up design prompt is a starting brief, not automatically an equivalent test.

Connect the project, support and next lesson

> Connect Debugging shapes and gradients to Image-pattern Network Investigation, adapt support and plan a later changed-case check.

Add a labelled debugging **shape**s and gradients **evidence** sheet to Image-pattern Network Investigation. Show how you can check dimension **contract**s before computing a layer.

Use the supplied fictional case and keep its **input**s, intermediate steps, calculation or **prediction**, and limitation. Connect this record to last week's record; a matching answer without a trace is insufficient.

Provide labelled columns for **input**s, scores, activations and parameter coordinates; allow calculators.

Extension: test several positive and negative **input**s against an independent explicit formula and explain why a test at a ReLU corner needs different reasoning from a smooth gradient check.

Week 19 explores learned representations and the distinctions hidden activations preserve.

Retain the project ledger and assess a changed case after support. Check the relevant prerequisite before carrying this component forward.

Plan the delayed return

Suggested return points in this level: ai-5/19, ai-5/21, ai-5/24. Use actual classroom dates, adjusting for holidays and gaps. One, three and six teaching weeks are scheduling choices, not a claimed optimal spacing.

At a delayed check, ask for the idea from memory and a changed application. Compare with the earlier independent response and record support used.

For a new level, revisit the previous capstone before checking the new prerequisites.

Record	Teacher evidence
Learner code and date	
Concept and case used; prior exposure	

Record	Teacher evidence
Explanation / trace / limits	
Support and first repair	
Changed case and delayed outcome	
Next teaching action	

Use the **evidence** to choose reteaching or the next step. A completed page, confidence rating or attractive project does not by itself demonstrate understanding.

Project evidence from this case

For your Image-pattern Network Investigation, save the **input**, procedure, observed result and limitation of this check.

Label this worked example as practice; use a different, previously unreviewed case when checking independent understanding.

Prepare, teach and assess

> Use this preparation summary alongside the detailed Debugging shapes and gradients lesson; it is a checklist rather than a replacement for the full sequence.

Teaching target

Teaching target: Check dimension **contract**s before computing a layer

Prepare the labelled worked-case picture, the matching workbook, fictional **input** cards and a place for individual responses. Check a local Python 3 environment before class; have a paper-trace version ready.

Session · Plan · Resources

> **Session:** Session 1 · Understand · 45 min
>
> **Plan:** 0–7: recall and prerequisite; 7–15: inspect the concrete case and predict; 15–30: teacher models the worked trace; 30–40: learners explain a step using the text and visual; 40–45: check the core idea.
>
> **Resources:** Sections 1–6; record the brief recall in the workbook.

> **Session:** Session 2 · Practise · 45 min
>
> **Plan:** 0–5: retrieve the procedure; 5–15: W2 completion practice; 15–23: explain and check with a partner; 23–30: each learner answers the misconception check; 30–40: targeted reteaching or a harder variation; 40–45: prepare the investigation.
>
> **Resources:** Sections 7–10; use the matching workbook W2 and misconception check.

> **Session:** Session 3 · Investigate and transfer · 45 min
>
> **Plan:** 0–5: retrieve the decision rule; 5–20: investigate or trace; 20–30: start the independent case; 30–38: connect the project; 38–43: act on feedback; 43–45: plan the return check.
>
> **Resources:** Sections 9 and 11–14. Give extra time to finish the full task set; use Section 15 when the week includes a coding lab.

Before class, solve the supported practice: Compute scores and activations for x = [3, 1] with the lesson layer, then omit the third bias. Identify the first discrepancy and the resulting activation error.

Supported practice answer

Reasoned practice answer: Teacher explanation: Correct scores and activations are [3, 1, 3]. Omitting the third bias produces [3, 1, 2]. The third score is the first discrepancy and now survives ReLU.

Check every learner before discussion: Use the worked case for Debugging **shape**s and gradients. Proposed explanation: “Matching **output shape** guarantees the computation”. Decide whether this explanation is supported.

Point to the step or supplied fact that decides; explain your repair if needed.

Repair the misconception

Misconception repair: Correct dimensions can hide swapped features, missing biases or wrong axis meanings.

Support without giving away the answer

Support: read the exact case aloud, enlarge the labelled picture, supply **input** cards and model only the first deciding step. Accept a spoken explanation or drawing; retain the reasoning goal.

Extend the reasoning

Extension: The program changes its declared order to [c, a] and returns [-12,-8]. Require a **prediction** and a reason before comparing. Expected result: That vector now matches the declared coordinate order.

Reason: Gradient values are meaningful only when their parameter names and array positions agree.

Protect the independent attempt

Independent assessment: withhold the reserved answer until the learner has attempted the new case. Record support separately from correctness.

Criterion	Not yet	With support	Independent
Explanation	Names an answer without a deciding fact	Uses a hint to link fact and decision	Explains the deciding fact in own words
Trace or test	Cannot connect input and result	Completes steps with prompts	Traces or tests a changed case accurately

Criterion	Not yet	With support	Independent
Limits and revision	Claims more than evidence supports	Names a limit after a prompt	States a defensible limit and useful next test

Project checkpoint

Project checkpoint: Test changed cases. Keep normal, boundary and failure cases; compare expected and observed results.

Use the weekly teacher answer for topic-specific reasoning. A saved progress tick is an activity record; judge mastery from the learner's explanation and **evidence**.

TEACHER GUIDE · 8 OF 9

Use feedback, labs and repair paths

> Use feedback, earlier review and portfolios purposefully. Apply the coding routine only when this lesson has an executable lab.

Use the two formative questions as supported practice, not as independent mastery scores. Discuss the deciding **evidence** rather than accepting a guessed selection.

The feedback comes from the reviewed public worked case. Do not reveal the separately reserved independent teacher answer until the learner has attempted that case.

Ask students to predict before running code. Preserve errors and actual **output**s; collect a changed test and an explanation. The branch-boundary and indexing lessons deliberately include failure cases.

Use the earlier worked-explanation links to address a specific missing building block, then return to the current question. Adapt this suggestion after observing the learner; it is not an automatic diagnosis.

Collect the completed-work portfolio as **evidence**. Record support separately from correctness, and assess explanation, trace/test and limitations. Progress ticks and quiz selections alone do not establish mastery.


TEACHER GUIDE · 9 OF 9

Visual concept journey

> Show one Debugging shapes and gradients graphic at a time, request a prediction and discuss its trace before the independent assessment.

Use one picture at a time. Hide a worked result before asking for a **prediction**, then reveal it for feedback. These are supported teaching cases; retain the separate independent assessment for a fresh first attempt.

01. Debugging shapes and gradients: the case



Follow the labelled picture with the matching explanation. Open the vector diagram

Catch a gradient -order bug before the optimiser changes parameters. Supplied facts: Toy y=2a+3c, target 4, start [a, c]=[1, 0]. Loss $(y-4)^2$. Program claims gradient [-12,-8] in order [a, c].


All **input**s and outcomes in this worked example are invented classroom data; no real model run is claimed.

Point to the given fact that matters most. Explain why it matters.

Discuss while showing the picture

Teacher prompt: Point to the given fact that matters most. Explain why it matters. Ask learners to describe one label or arrow in ordinary words. Use the adjacent transcript if the image is difficult to see.

02. Follow the deciding steps



Follow the labelled picture with the matching explanation. Open the vector diagram


Compute correct gradient: y = 2, residual -2: gradient [-8,-12], not [-12,-8]. → Check coordinates: Step 0.1: a losses 3.24, 4.84 give -8; c losses 2.89, 5.29 give -12. → Apply correct update: At rate 0.01: new [a, c]=[1.08, 0.12]; y = 2.52, loss 2.1904.

Point to each numbered stage and explain which recorded **input** it uses.

Discuss while showing the picture

Teacher prompt: Point to each numbered stage and explain which recorded **input** it uses. Ask learners to describe one label or arrow in ordinary words. Use the adjacent transcript if the image is difficult to see.

03. Repair from the first disagreement



Follow the labelled picture with the matching explanation. Open the vector diagram


Repair from the first disagreement. **Input** and dimensions | x length 2 W 3 by 2 b length 3 | Dimensions match. Scores before ReLU | [1, 2, 0] | [1, 2, -1]. Hidden activations | [1, 2, 0] | [1, 2, 0]

Read the labels and values. Explain the relationship the model shows.

Discuss while showing the picture

Teacher prompt: Read the labels and values. Explain the relationship the model shows. Ask learners to describe one label or arrow in ordinary words. Use the adjacent transcript if the image is difficult to see.

04. Change one thing. Trace what follows.



Follow the labelled picture with the matching explanation. Open the vector diagram

Original case: At rate 0.01: new [a, c]=[1.08, 0.12]; y = 2.52, loss 2.1904. Changed condition: The program changes its declared order to [c, a] and returns [-12,-8].

Expected result: That vector now matches the declared coordinate order. Reason: Gradient values are meaningful only when their parameter names and array positions agree.


Predict before checking the worked changed-case result. Name what changed and what the supplied facts allow you to conclude.

Discuss while showing the picture

Teacher prompt: Predict before checking the worked changed-case result. Name what changed and what the supplied facts allow you to conclude. Ask learners to describe one label or arrow in ordinary words.

Use the adjacent transcript if the image is difficult to see. Changed-case reasoning: Gradient values are meaningful only when their parameter names and array positions agree.

05. Connect the explanation to its limit



Follow the labelled picture with the matching explanation. Open the vector diagram

Array **shape** and coordinate meaning both matter. A vector with two entries can have the right length but assign each derivative to the wrong parameter.

Label the entries a and c, then perturb one coordinate at a time to check their slopes. Repairing the coordinate mapping is necessary before using the gradient to update the network.

Limit: A correct gradient at one point does not establish every batch, **shape** or activation path is implemented correctly.


Explain the case, then point to a limit on the claim.

Discuss while showing the picture

Teacher prompt: Explain the case, then point to a limit on the claim. Ask learners to describe one label or arrow in ordinary words. Use the adjacent transcript if the image is difficult to see.

Keep the stated scope: A correct gradient at one point does not establish every batch, **shape** or activation path is implemented correctly.

06. Make the idea visible in your project



Follow the labelled picture with the matching explanation. Open the vector diagram

For your Image-pattern Network Investigation, save the **input**, procedure, observed result and limitation of this check.

Label this worked example as practice; use a different, previously unreviewed case when checking independent understanding. Draw your **input**, deciding step, result and limit.

Supported question: What should a debugging record pair with every gradient value? Point to the relevant step in the picture, then write the changed result and the rule or **evidence** that supports it.

> Draw your project trace and justify the deciding step using **evidence**.

Discuss while showing the picture

Teacher prompt: Draw your project trace and justify the deciding step using **evidence**. Ask learners to describe one label or arrow in ordinary words. Use the adjacent transcript if the image is difficult to see.

Supported practice key: Parameter name and index, expected **shape**, analytic derivative and numerical check; correct [a, c] gradient is [-8,-12]. Changed-case check: That vector now matches the declared coordinate order.

Gradient values are meaningful only when their parameter names and array positions agree.

Save or print your responses for your portfolio. Progress and drafts on the hosted website stay in the current browser. Use only fictional or teacher-approved data.