Convolution as a local operation

Learn to understand, design, build, test and explain AI systems responsibly.

Project: Image-pattern Network Investigation

TEACHER GUIDE · 1 OF 9

Prepare the purpose, prerequisites and materials

> Prepare Convolution as a local operation: check the target, prerequisites, resources and adaptable teaching schedule.

Teach the learning cycle

Primary target: Compute a local weighted sum at each valid image position

Session · Sequence and minutes · Resources

> **Session:** Session 1 · Understand · 45 min
>
> **Sequence and minutes:** 0–7: recall and prerequisite; 7–15: inspect the concrete case and predict; 15–30: teacher models the worked trace; 30–40: learners explain a step using the text and visual; 40–45: check the core idea.
>
> **Resources:** Sections 1–6; record the brief recall in the workbook.

> **Session:** Session 2 · Practise · 45 min
>
> **Sequence and minutes:** 0–5: retrieve the procedure; 5–15: W2 completion practice; 15–23: explain and check with a partner; 23–30: each learner answers the misconception check; 30–40: targeted reteaching or a harder variation; 40–45: prepare the investigation.
>
> **Resources:** Sections 7–10; use the matching workbook W2 and misconception check.

> **Session:** Session 3 · Investigate and transfer · 45 min

> **Sequence and minutes:** 0–5: retrieve the decision rule; 5–20: investigate or trace; 20–30: start the independent case; 30–38: connect the project; 38–43: act on feedback; 43–45: plan the return check.
>
> **Resources:** Sections 9 and 11–14. Give extra time to finish the full task set; use Section 15 when the week includes a coding lab.

This is a starting allocation of 135 minutes, not a validated duration. Preserve all named topics. Schedule extra time for connected examples, the full investigation, independent cases and project building.

Repeated copies of a case share one recorded attempt; they are not new **evidence**.

Retrieval answer guidance

Image tensors and channels

Without opening the old lesson, explain one key idea from Image tensors and channels. Give an example and a mistake that the idea helps you avoid.

Look for: Read a pixel using declared row column and channel axes

Reference example, not the only acceptable wording: Teacher explanation: The RGB pixel is [0, 0, 255]; its blue value is 255. Shape is 2 by 2 by 3, with four pixels and twelve channel values.

Debugging shapes and gradients

Without opening the old lesson, explain one key idea from Debugging shapes and gradients. Give an example and a mistake that the idea helps you avoid.

Look for: Check dimension contracts before computing a layer

Reference example, not the only acceptable wording: Teacher explanation: No. Each weight row must have the same length as x.

Confirm the intended feature schema, then supply a valid two-feature **input** or deliberately redesign and retrain the layer; do not silently discard a value.

Training and validation curves

Without opening the old lesson, explain one key idea from **Training** and validation curves. Give an example and a mistake that the idea helps you avoid.

Look for: Compute comparable **training** and validation losses at saved checkpoints

Reference example, not the only acceptable wording: Teacher explanation: **Prediction**s [3, 4], residuals [-1.5, -2], squares [2.25, 4], MSE 3.125.

Use two 45-minute sessions. Prepare a 2 by 2 paper window and a labelled 3 by 3 grid. Keep **kernel** orientation fixed and distinguish raw sums, bias and ReLU.

Explain that neural-network convolution commonly uses cross-correlation; the exercise explicitly declares this convention. Technical reference: https://docs.pytorch.org/docs/stable/generated/torch.nn.modules.conv.Conv2d.html .

No library installation is needed.

Outcomes

Compute a local weighted sum at each valid image position

Explain shared weights and predict **output** dimensions

Check how **stride** boundaries and activation affect the result

Preparation

Printed lesson and workbook; paper and pencil

Calculator and optional local Python 3 editor; no packages or AI accounts needed

Use the fictional examples supplied; prepare the fresh retry before class

Prerequisite answer

The same dimensions can describe different coordinate meanings. A correct computation must know which axis is row, column or channel.

End goal for the pictorial case

By the end, I can explain convolution as a local operation using a traced example and a stated limitation.

This added worked case illustrates the week’s main idea. Retain all original and connected topics; schedule its practice within the teaching cycle.

Explain and model the mechanism

> Model Convolution as a local operation using the supplied case, labelled mechanism and reasoning. Make the scope of each conclusion explicit.

Explain Convolution as a local operation · 1

Use a fictional single-channel image with rows [1, 2, 0], [0, 1, 3] and [2, 0, 1]. Coordinates are zero-based row then column. Our **kernel** has rows [1, -1] and [0, 1].

At each position, multiply matching entries of a 2 by 2 window and the **kernel**, then add the four products. Use bias 0, **stride** 1 and no **padding**.

At the top-left window, the sum is 1 times 1 plus 2 times -1 plus 0 times 0 plus 1 times 1 = 0. Slide the same **kernel** right, then down. Only use windows that fit entirely inside the image; this is the valid boundary rule.

Explain Convolution as a local operation · 2

The **feature map** has rows [0, 5] and [-1, -1]. This neural-network convention keeps the **kernel** orientation fixed; mathematically it is cross-correlation. Mathematical convolution reverses the **kernel** along both spatial axes.

We use the fixed-orientation convention throughout, so every hand calculation and program agrees.

The following function assumes nonempty rectangular numeric arrays and a positive integer **stride**. It rejects a **kernel** larger than the image.

It computes one **input** channel, one **output** map, zero bias and no **padding**; no activation is applied inside the function.

Explain Convolution as a local operation · 3

The **kernel** weights are reused at all four positions. There are four **kernel** parameters, not sixteen separate weights. If we add one shared bias for this **output** map, there are five parameters.

The number of multiply operations grows with the number of windows even though the parameter count stays fixed.

Term	Meaning
Kernel	A small array of weights applied to a local input neighbourhood
Feature map	The spatial array of outputs produced by applying a filter
Stride	The distance between successive window starting positions
Padding	Values added around an input boundary under a declared rule

One shared kernel produces four local sums

WINDOW START	KERNEL ROWS	OUTPUT VALUE
Row 0 column 0	[1 -1] and [0 1]	0
Row 0 column 1	[1 -1] and [0 1]	5
Row 1 column 0	[1 -1] and [0 1]	-1
Row 1 column 1	[1 -1] and [0 1]	-1

Read windows in row order. Each output summarizes one neighbourhood. With stride 1, adjacent windows overlap, but their output values occupy separate cells.

Explain Convolution as a local operation · 4

Guided: only the window starting [0, 0] includes **input**[0][0]. Its weight is 1, so adding 3 changes that **output** from 0 to 3. The map becomes [[3, 5], [-1, -1]].

Exit: the declared unpadded **stride**-1 setup gives 2 by 2, not 3 by 3. A different **padding** or **kernel** setup would need documentation. Values are local weighted sums, not probabilities.

Model the reasoning aloud

Use the complete worked example below before asking learners to complete W2. Reveal a small part, invite a **prediction**, then explain the deciding step.

These teacher notes contain solutions; do not reveal the independent case answer during modelling.

One shared kernel produces four local sums

WINDOW START	KERNEL ROWS	OUTPUT VALUE
Row 0 column 0	[1 -1] and [0 1]	0
Row 0 column 1	[1 -1] and [0 1]	5
Row 1 column 0	[1 -1] and [0 1]	-1
Row 1 column 1	[1 -1] and [0 1]	-1

Read windows in row order. Each output summarizes one neighbourhood. With stride 1, adjacent windows overlap, but their output values occupy separate cells.

Change only input[0][0] from 1 to 4. Which valid windows include it? Compute the changed feature map and explain why the other three outputs stay the same.

Thinking move	Teacher prompt
Plan	What is given? What is the question? Which procedure fits these facts?
Do	Point to each input and intermediate step in the worked trace. Name the rule that allows the next step.
Check	Does the output answer the question? Which assumption or limitation prevents a larger claim?

Use the diagram and verbal explanation together. Ask learners to match a sentence to a specific visual step; do not assign learners fixed visual or auditory learning styles.

A pictorial worked case: Convolution as a local operation

Draw the exact patch-by-patch arithmetic of a local image operation.

The facts we will use

Supplied facts

Image rows [1, 2, 3],[4, 5, 6]; **kernel** rows [1, 0],[0,-1]. Use unflipped **kernel**, no **padding**, **stride**1, bias0.

Supplied facts

All **input**s and outcomes in this worked example are invented classroom data; no real model run is claimed.

AI ACADEMY / AI-5/21

Image used by both local kernel windows

	col0	col1	col2
row0	1	2	3
row1	4	5	6

Read a cell using both its row and column labels.

Follow the labelled picture with the matching explanation. Open the vector diagram

AI ACADEMY / AI-5/21

Convolution as a local operation

Start with the supplied facts

Follow each arrow. Ask which fact allows the next step.



1. First patch

1 x 1+2 x 0+4 x 0+5 x (-1)=-4.



2. Second patch

2 x 1+3 x 0+5 x 0+6 x (-1)=-4.



3. Feature map

Output shape1 x 2 and map [[-4,-4]]; the same kernel is reused at each position.

CHANGE ONE THING

Add shared bias2 after each patch sum.

Explain the changed result using the matching lesson.

Follow the labelled picture with the matching explanation. Open the vector diagram

Read the picture one step at a time

STEP	WHAT HAPPENS AND WHY
1. First patch	1×1+2×0+4×0+5×(-1)=-4.
2. Second patch	2×1+3×0+5×0+6×(-1)=-4.
3. Feature map	Output shape1×2 and map [[-4,-4]]; the same kernel is reused at each position.

Match each pictured step to the supplied facts. This is a worked teaching case, not an independent assessment.

Why this result follows

Why the result follows

A local **kernel** combines the values in one small image window with a fixed set of weights. Slide that same **kernel** to the next valid window and repeat the products.

Sharing weights lets the operation look for the same local pattern at different positions. This example declares an unflipped **kernel**; adding bias changes each window result without changing which pixels were used.

What this example does not establish

Keep the stated limit

A local filter detects a numerical pattern; one **feature map** does not establish recognition or learned visual understanding.

Change one thing in the pictured case

Change one thing

Change: Add shared bias2 after each patch sum.

Predicted result

Prediction: **Feature map** becomes [[-2,-2]].

Why the result follows

Reason: Bias adds2 to each **output**; it does not change patch products or **output** shape.

Ask while showing the picture

Ask while showing the picture · 5

Cover the result. Ask learners to name the **input**s and predict the next step. Uncover one step, connect the icon to the actual procedure, and explain its **evidence**. Then change the supplied condition and compare.

The picture is a representation; it does not document execution of a real AI model.

Demonstrate and guide practice

> Demonstrate Convolution as a local operation, reduce support deliberately and check individual reasoning before discussing answers.

Time or stage	Teacher action
Session 1 start to 7 minutes	Retrieve row and column axes, then label the input and fixed-orientation kernel.
7 to 18 minutes	Compute the four products at the top-left position and complete W1 at the next window.
18 to 32 minutes	Trace the remaining windows and run or hand-trace the optional code.
32 to 45 minutes	Use W2 to distinguish shared parameter count from repeated arithmetic work.
Session 2 start to 8 minutes	Complete the guided changed-pixel case and explain its local influence.
8 to 20 minutes	Count stride positions and padded windows, then complete W3.
20 to 35 minutes	Collect W4 independently, requiring separate raw, biased and activated maps.
35 to 45 minutes	Use W5 and the exit response to check conventions and claims, then administer the fresh retry.

Use the worked example in Sections 3 and 6. Collect a **prediction** before revealing its result; ask the learner to point to each intermediate fact.

Provide a four-cell product ledger and move a paper window one position at a time. Use labelled coordinates rather than colour alone.

Extension: compare a numerical implementation with an independent explicit four-term formula across rectangular **input**s, and show how changing **stride** alters the sampled start positions.

Reduce help deliberately

Completion practice

Completion task: How many shared **kernel** weights does the lesson use? How many products are computed over all four valid windows? What changes if one shared bias is added?

Reasoning to listen for

Teacher check: Teacher explanation: There are four shared weights and sixteen products across four windows. One shared bias raises the parameter count to five and adds the same bias once to each **output**.

Start by identifying the given **input**s together. Leave the intermediate steps blank. If needed, model one step, then withdraw that help on the next step. Move to a full trace only when the partial trace is understood.

For partners, alternate explainer and checker; collect a response from every learner before discussion.

Individual reasoning check

Use the worked case for Convolution as a local operation. Proposed explanation: “Each window has its own set of learned weights”. Decide whether this explanation is supported.

Point to the step or supplied fact that decides; explain your repair if needed.

Expected repair

Expected correction: The same **kernel** parameters are reused at every position for this **output** map.

Collect explanations, not only yes/no votes. If a misunderstanding is common, re-model the relevant step for the class.

If it affects a few learners, give a short targeted group explanation while others solve a more demanding variation.

Pictorial practice question

Why is flipping the **kernel** an implementation change here? Point to the relevant step in the picture, then write the changed result and the rule or **evidence** that supports it.

Reasoned teacher answer

The declared operation uses an unflipped **kernel**, often called cross-correlation. Flipping it changes the arithmetic contract and may change results. Changed-case check: **Feature map** becomes [[-2,-2]].

Bias adds2 to each **output**; it does not change patch products or **output** shape.

Changed-case reasoning: **Feature map** becomes [[-2,-2]]. Bias adds2 to each **output**; it does not change patch products or **output** shape.

Collect each learner's explanation before discussion. Use the first missing connection between **input**, deciding step and result to choose support. This question is worked-case practice, not fresh mastery **evidence**.

Run the investigation and diagnose misconceptions

> Run the Convolution as a local operation investigation and use the first unsupported step to choose a teaching response.

Each window has its own set of learned weights: The same **kernel** parameters are reused at every position for this **output** map.

A negative feature-map value means the code failed: Signed weighted sums are valid; an activation may later change them.

A local response proves an object was recognised: The authored filter only computes a local sum; object recognition and probability claims require additional modelling and **evidence**.

Use Section 9 for the **evidence** ledger. Add a boundary or missing-**input** case and record the expected response before checking. More successful repeats of one case do not establish wider coverage.

Match the support to the first error

What the response shows	Next teaching action
Missing or misread facts	Read the case aloud, mark supplied versus unknown facts, and let the learner restate it.
Wrong procedure	Return to the deciding step in the worked case. Contrast it with the proposed incorrect explanation.
Arithmetic or implementation error	Trace intermediate values or lines; preserve the first mismatch and retry that step.
Correct result without a reason	Ask for a trace and a changed case before marking independent understanding.
An unsupported wider claim	Ask which supplied evidence supports the claim and which further observation would be needed.

Offer an oral explanation, drawing, enlarged visual or fewer examples when that removes a reading/writing barrier. Keep the same reasoning goal.

Stretch secure learners by changing a boundary or assumption and asking them to defend the effect, not simply by assigning more of the same questions.

Assess and explain the answers

> Use the Convolution as a local operation questions, teacher keys and criteria after the relevant attempts. Previously discussed cases are practice; protect the separately selected independent task.

Guided and exit questions

Guided: only the window starting [0, 0] includes **input**[0][0]. Its weight is 1, so adding 3 changes that **output** from 0 to 3. The map becomes [[3, 5], [-1, -1]].

Exit: the declared unpadded **stride**-1 setup gives 2 by 2, not 3 by 3. A different **padding** or **kernel** setup would need documentation. Values are local weighted sums, not probabilities.

W1 Trace a local sum

Workbook question · W1

Use the lesson image and **kernel** at window start [0, 1]. List the window rows, four products and **output** before activation.

Teacher reasoning · W1

Teacher explanation: Window rows are [2, 0] and [1, 3]. Products are 2, 0, 0 and 3, giving **output** 5.

W2 Separate parameters and operations

Workbook question · W2

How many shared **kernel** weights does the lesson use? How many products are computed over all four valid windows? What changes if one shared bias is added?

Teacher reasoning · W2

Teacher explanation: There are four shared weights and sixteen products across four windows. One shared bias raises the parameter count to five and adds the same bias once to each **output**.

W3 Check stride and padding

Workbook question · W3

For the lesson image and **kernel**, give the **output** shape with no **padding** and **stride** 2. Then give the shape with one zero border on each side and **stride** 1, and calculate that padded map's top-left **output**.

Teacher reasoning · W3

Teacher explanation: **Stride** 2 without **padding** gives shape 1 by 1. The padded **input** is 5 by 5, giving **output** 4 by 4. Its top-left window [[0, 0], [0, 1]] gives **output** 1.

W4 Filter a new image independently

Workbook question · W4

Use image rows [2, 1, 0], [1, 3, 2] and **kernel** rows [0, 1], [-1, 2]. Use no **padding**, **stride** 1 and bias 0. Give the **output** shape, both four-product sums and the **feature map**. Then add a shared bias of -5 and apply ReLU.

Teacher reasoning · W4

Teacher explanation: Shape is 1 by 2. First products are 0, 1, -1, 6, summing to 6. Second products are 0, 0, -3, 4, summing to 1. Map is [[6, 1]]. Bias gives [[1, -4]]; ReLU gives [[1, 0]].

W5 Test a convention error

Workbook question · W5

A program reverses both axes of the lesson **kernel** to [[1, 0], [-1, 1]]. Compute the top-left **output**. Does it agree with our declared convention? Explain what the test checks.

Teacher reasoning · W5

Teacher explanation: The top-left **output** becomes 1 + 0 + 0 + 1 = 2 instead of 0. It does not follow the declared fixed-orientation convention. The asymmetric **kernel** and known window expose a **kernel**-orientation mismatch.

Independent assessment and fresh retry

Teacher key · Independent assessment and fresh retry

W4 requires shape 1 by 2, raw **output**s 6 and 1, biased **output**s 1 and -4 and ReLU **output**s 1 and 0. Fresh retry: image rows [1, 2, 4], [3, 0, 1]; **kernel** rows [1, 0], [-1, 1].

Products at the two starts are [1, 0, -3, 0] and [2, 0, 0, 1], giving [[-2, 3]]. Add shared bias 1 to get [[-1, 4]], then ReLU gives [[0, 4]].

Assess independent transfer

Independent question · withhold the key

Selected case: Use image rows [2, 1, 0], [1, 3, 2] and **kernel** rows [0, 1], [-1, 2]. Use no **padding**, **stride** 1 and bias 0. Give the **output** shape, both four-product sums and the **feature map**.

Then add a shared bias of -5 and apply ReLU.

Selected case answer

Teacher key · Selected case answer

Teacher explanation: Shape is 1 by 2. First products are 0, 1, -1, 6, summing to 6. Second products are 0, 0, -3, 4, summing to 1. Map is [[6, 1]]. Bias gives [[1, -4]]; ReLU gives [[1, 0]].

Dimension	Evidence required
Explanation	Names the applicable idea or procedure and ties it to the supplied facts.
Trace and result	Preserves the given inputs and shows the relevant intermediate steps; distinguishes a prediction from an observed execution.
Limits	States the assumptions, missing evidence or conditions under which the result would change.

Teacher key · Selected case answer

Record each dimension as not yet, with support, or independent. Accept a valid alternative procedure with a defensible trace.

Do not penalise an honestly recorded model failure if the learner correctly explains its **evidence** and limits.

Feedback that the learner uses

Name the earliest unsupported step and give one action to repair it. Have the learner make that repair now and explain why. Then assess the relevant skill on a fresh, fully specified case.

Confirm it was not previously practised with feedback; solve and check the new case before assigning it. A follow-up design prompt is a starting brief, not automatically an equivalent test.

Connect the project, support and next lesson

> Connect Convolution as a local operation to Image-pattern Network Investigation, adapt support and plan a later changed-case check.

Add a labelled convolution as a local operation **evidence** sheet to Image-pattern Network Investigation. Show how you can compute a local weighted sum at each valid image position.

Use the supplied fictional case and keep its **input**s, intermediate steps, calculation or **prediction**, and limitation. Connect this record to last week's record; a matching answer without a trace is insufficient.

Provide a four-cell product ledger and move a paper window one position at a time. Use labelled coordinates rather than colour alone.

Extension: compare a numerical implementation with an independent explicit four-term formula across rectangular **input**s, and show how changing **stride** alters the sampled start positions.

Week 22 explores pooling and spatial information, including distinct **input**s that share a pooled **output**.

Retain the project ledger and assess a changed case after support. Check the relevant prerequisite before carrying this component forward.

Plan the delayed return

Suggested return points in this level: ai-5/22, ai-5/24, ai-5/27. Use actual classroom dates, adjusting for holidays and gaps. One, three and six teaching weeks are scheduling choices, not a claimed optimal spacing.

At a delayed check, ask for the idea from memory and a changed application. Compare with the earlier independent response and record support used.

For a new level, revisit the previous capstone before checking the new prerequisites.

Record	Teacher evidence
Learner code and date	
Concept and case used; prior exposure	
Explanation / trace / limits	
Support and first repair	
Changed case and delayed outcome	
Next teaching action	

Use the **evidence** to choose reteaching or the next step. A completed page, confidence rating or attractive project does not by itself demonstrate understanding.

Project evidence from this case

For your Image-pattern Network Investigation, save the **input**, procedure, observed result and limitation of this check.

Label this worked example as practice; use a different, previously unreviewed case when checking independent understanding.

Prepare, teach and assess

> Use this preparation summary alongside the detailed Convolution as a local operation lesson; it is a checklist rather than a replacement for the full sequence.

Teaching target

Teaching target: Compute a local weighted sum at each valid image position

Prepare the labelled worked-case picture, the matching workbook, fictional **input** cards and a place for individual responses. Check a local Python 3 environment before class; have a paper-trace version ready.

Session · Plan · Resources

> **Session:** Session 1 · Understand · 45 min
>
> **Plan:** 0–7: recall and prerequisite; 7–15: inspect the concrete case and predict; 15–30: teacher models the worked trace; 30–40: learners explain a step using the text and visual; 40–45: check the core idea.
>
> **Resources:** Sections 1–6; record the brief recall in the workbook.

Session: Session 2 · Practise · 45 min

Plan: 0–5: retrieve the procedure; 5–15: W2 completion practice; 15–23: explain and check with a partner; 23–30: each learner answers the misconception check; 30–40: targeted reteaching or a harder variation; 40–45: prepare the investigation.

Resources: Sections 7–10; use the matching workbook W2 and misconception check.

Session: Session 3 · Investigate and transfer · 45 min

Plan: 0–5: retrieve the decision rule; 5–20: investigate or trace; 20–30: start the independent case; 30–38: connect the project; 38–43: act on feedback; 43–45: plan the return check.

Resources: Sections 9 and 11–14. Give extra time to finish the full task set; use Section 15 when the week includes a coding lab.

Before class, solve the supported practice: How many shared **kernel** weights does the lesson use? How many products are computed over all four valid windows? What changes if one shared bias is added?

Supported practice answer

Reasoned practice answer: Teacher explanation: There are four shared weights and sixteen products across four windows. One shared bias raises the parameter count to five and adds the same bias once to each **output**.

Check every learner before discussion: Use the worked case for Convolution as a local operation. Proposed explanation: “Each window has its own set of learned weights”. Decide whether this explanation is supported.

Point to the step or supplied fact that decides; explain your repair if needed.

Repair the misconception

Misconception repair: The same **kernel** parameters are reused at every position for this

output map.

Support without giving away the answer

Support: read the exact case aloud, enlarge the labelled picture, supply **input** cards and model only the first deciding step. Accept a spoken explanation or drawing; retain the reasoning goal.

Extend the reasoning

Extension: Add shared bias2 after each patch sum. Require a **prediction** and a reason before comparing. Expected result: **Feature map** becomes [[-2,-2]].

Reason: Bias adds2 to each **output**; it does not change patch products or **output** shape.

Protect the independent attempt

Independent assessment: withhold the reserved answer until the learner has attempted the new case. Record support separately from correctness.

Criterion	Not yet	With support	Independent
Explanation	Names an answer without a deciding fact	Uses a hint to link fact and decision	Explains the deciding fact in own words
Trace or test	Cannot connect input and result	Completes steps with prompts	Traces or tests a changed case accurately
Limits and revision	Claims more than evidence supports	Names a limit after a prompt	States a defensible limit and useful next test

Project checkpoint

Project checkpoint: Evaluate and revise. Compare with your starting method, explain errors and record a justified revision.

Use the weekly teacher answer for topic-specific reasoning. A saved progress tick is an activity record; judge mastery from the learner's explanation and **evidence**.

TEACHER GUIDE · 8 OF 9

Use feedback, labs and repair paths

> Use feedback, earlier review and portfolios purposefully. Apply the coding routine only when this lesson has an executable lab.

Use the two formative questions as supported practice, not as independent mastery scores. Discuss the deciding **evidence** rather than accepting a guessed selection.

The feedback comes from the reviewed public worked case. Do not reveal the separately reserved independent teacher answer until the learner has attempted that case.

Ask students to predict before running code. Preserve errors and actual **output**s; collect a changed test and an explanation. The branch-boundary and indexing lessons deliberately include failure cases.

Use the earlier worked-explanation links to address a specific missing building block, then return to the current question. Adapt this suggestion after observing the learner; it is not an automatic diagnosis.


Collect the completed-work portfolio as **evidence**. Record support separately from correctness, and assess explanation, trace/test and limitations. Progress ticks and quiz selections alone do not establish mastery.

Visual concept journey

> Show one Convolution as a local operation graphic at a time, request a prediction and discuss its trace before the independent assessment.

Use one picture at a time. Hide a worked result before asking for a **prediction**, then reveal it for feedback. These are supported teaching cases; retain the separate independent assessment for a fresh first attempt.

01. Convolution as a local operation: the case



Follow the labelled picture with the matching explanation. Open the vector diagram

Draw the exact patch-by-patch arithmetic of a local image operation. Supplied facts: Image rows [1, 2, 3],[4, 5, 6]; **kernel** rows [1, 0],[0,-1]. Use unflipped **kernel**, no **padding**, **stride**1, bias0.


All **input**s and outcomes in this worked example are invented classroom data; no real model run is claimed.

> Point to the given fact that matters most. Explain why it matters.

Discuss while showing the picture

Teacher prompt: Point to the given fact that matters most. Explain why it matters. Ask learners to describe one label or arrow in ordinary words. Use the adjacent transcript if the image is difficult to see.

02. Follow the deciding steps



Follow the labelled picture with the matching explanation. Open the vector diagram


First patch: 1×1+2×0+4×0+5×(-1)=-4. → Second patch: 2×1+3×0+5×0+6×(-1)=-4. → **Feature map**: **Output** shape1×2 and map [[-4,-4]]; the same **kernel** is reused at each position.

Point to each numbered stage and explain which recorded **input** it uses.

Discuss while showing the picture

Teacher prompt: Point to each numbered stage and explain which recorded **input** it uses. Ask learners to describe one label or arrow in ordinary words. Use the adjacent transcript if the image is difficult to see.

03. Image used by both local kernel windows



Follow the labelled picture with the matching explanation. Open the vector diagram

Image used by both local **kernel** windows. row0: col0 = 1, col1 = 2, col2 = 3. row1: col0 = 4, col1 = 5, col2 = 6.


Read the labels and values. Explain the relationship the model shows.

Discuss while showing the picture

Teacher prompt: Read the labels and values. Explain the relationship the model shows. Ask learners to describe one label or arrow in ordinary words. Use the adjacent transcript if the image is difficult to see.

Check row/column meanings, units and denominators before discussing a difference. Supplied toy values are not real class or model results.

04. Change one thing. Trace what follows.



Follow the labelled picture with the matching explanation. Open the vector diagram

Original case: **Output** shape1×2 and map [[-4,-4]]; the same **kernel** is reused at each position. Changed condition: Add shared bias2 after each patch sum. Expected result: **Feature map** becomes [[-2,-2]].

Reason: Bias adds2 to each **output**; it does not change patch products or **output** shape.


Predict before checking the worked changed-case result. Name what changed and what the supplied facts allow you to conclude.

Discuss while showing the picture

Teacher prompt: Predict before checking the worked changed-case result. Name what changed and what the supplied facts allow you to conclude. Ask learners to describe one label or arrow in ordinary words.

Use the adjacent transcript if the image is difficult to see. Changed-case reasoning: Bias adds2 to each **output**; it does not change patch products or **output** shape.

05. Connect the explanation to its limit



Follow the labelled picture with the matching explanation. Open the vector diagram

A local **kernel** combines the values in one small image window with a fixed set of weights. Slide that same **kernel** to the next valid window and repeat the products.

Sharing weights lets the operation look for the same local pattern at different positions. This example declares an unflipped **kernel**; adding bias changes each window result without changing which pixels were used.

Limit: A local filter detects a numerical pattern; one **feature map** does not establish recognition or learned visual understanding.


Explain the case, then point to a limit on the claim.

Discuss while showing the picture

Teacher prompt: Explain the case, then point to a limit on the claim. Ask learners to describe one label or arrow in ordinary words. Use the adjacent transcript if the image is difficult to see.

Keep the stated scope: A local filter detects a numerical pattern; one **feature map** does not establish recognition or learned visual understanding.

06. Make the idea visible in your project



Follow the labelled picture with the matching explanation. Open the vector diagram

For your Image-pattern Network Investigation, save the **input**, procedure, observed result and limitation of this check.

Label this worked example as practice; use a different, previously unreviewed case when checking independent understanding. Draw your **input**, deciding step, result and limit.

Supported question: Why is flipping the **kernel** an implementation change here? Point to the relevant step in the picture, then write the changed result and the rule or **evidence** that supports it.

> Draw your project trace and justify the deciding step using **evidence**.

Discuss while showing the picture

Teacher prompt: Draw your project trace and justify the deciding step using **evidence**. Ask learners to describe one label or arrow in ordinary words. Use the adjacent transcript if the image is difficult to see.

Supported practice key: The declared operation uses an unflipped **kernel**, often called cross-correlation. Flipping it changes the arithmetic contract and may change results. Changed-case check: **Feature map** becomes [[-2,-2]].

Bias adds2 to each **output**; it does not change patch products or **output** shape.

Save or print your responses for your portfolio. Progress and drafts on the hosted website stay in the current browser. Use only fictional or teacher-approved data.