From a paper algorithm to Python

Learn to understand, design, build, test and explain AI systems responsibly.

Project: Python readiness portfolio

TEACHER GUIDE · 1 OF 9

Prepare the purpose, prerequisites and materials

> Prepare From a paper algorithm to Python: check the target, prerequisites, resources and adaptable teaching schedule.

Teach the learning cycle

Primary target: Translate a short paper calculation into a Python script

Session · Sequence and minutes · Resources

> **Session:** Session 1 · Understand · 45 min
>
> **Sequence and minutes:** 0–7: recall and prerequisite; 7–15: inspect the concrete case and predict; 15–30: teacher models the worked trace; 30–40: learners explain a step using the text and visual; 40–45: check the core idea.
>
> **Resources:** Sections 1–6; record the brief recall in the workbook.

> **Session:** Session 2 · Practise · 45 min
>
> **Sequence and minutes:** 0–5: retrieve the procedure; 5–15: W2 completion practice; 15–23: explain and check with a partner; 23–30: each learner answers the misconception check; 30–40: targeted reteaching or a harder variation; 40–45: prepare the investigation.
>
> **Resources:** Sections 7–10; use the matching workbook W2 and misconception check.

> **Session:** Session 3 · Investigate and transfer · 45 min

> **Sequence and minutes:** 0–5: retrieve the decision rule; 5–20: investigate or trace; 20–30: start the independent case; 30–38: connect the project; 38–43: act on feedback; 43–45: plan the return check.
>
> **Resources:** Sections 9 and 11–14. Give extra time to finish the full task set; use Section 15 when the week includes a coding lab.

This is a starting allocation of 135 minutes, not a validated duration. Preserve all named topics. Schedule extra time for connected examples, the full investigation, independent cases and project building.

Repeated copies of a case share one recorded attempt; they are not new **evidence**.

Case exposure check: this source example appears in ai-2/1, ai-3/23, python-bridge/1. Reuse a familiar case for recall or modelling; verify that the case used to assess transfer has not already received feedback.

Retrieval answer guidance

> Four packs contain six counters each. What steps find and show the total?

Record four and six, multiply them to get 24, then display 24. The order must make the required values available before use.

This is a first encounter with saved Python scripts, not a compressed implementation of the Grade 6 adviser. Teach **assignment**, multiplication and print only as needed; values and types follow in Week 2.

Use a fresh run to avoid hidden interactive state. Reference: Python tutorial, An Informal Introduction to Python, https://docs.python.org/3/tutorial/introduction.html (**assignment**, arithmetic and print).

Outcomes

Translate a short paper calculation into a Python script

Predict and explain the order of executed statements

Keep expected and observed **output** separate when checking a **program**

Preparation

Teacher-prepared Python 3 editor with a new saved .py file and a visible **output** area; test Run before class

Paper counters or equal-group sketches and a blank expected/observed record

The printed script and workbook; no logins or personal data required

Prerequisite answer

Record four and six, multiply them to get 24, then display 24. The order must make the required values available before use.

End goal for the pictorial case

Trace from a paper **algorithm** to python and explain the changed **program** before running it.

This added worked case illustrates the week's main idea. Retain all original and connected topics; schedule its practice within the teaching cycle.

Explain and model the mechanism

> Model From a paper algorithm to Python using the supplied case, labelled mechanism and reasoning. Make the scope of each conclusion explicit.

Explain From a paper algorithm to Python · 1

In Grade 6 you traced rules on paper. Now you will write a small Python **program** and check what it actually does. Begin with a counter-packing calculation, not the whole activity adviser.

The requirement is to find the total counters in equal packs and display that total. For this first **program**, the supplied quantities are whole, nonnegative numbers; it does not yet validate typed **input**.

Explain From a paper algorithm to Python · 2

Use a teacher-prepared Python 3 editor that can run a saved .py file. Open a new file called counters.py, type the code exactly as shown in the next section, save it, and use the editor's Run command.

Read the **output** area separately from the source editor. No account, AI tool, package installation or personal data is needed. If a device is unavailable, trace on paper and label the result predicted rather than executed.

Explain From a paper algorithm to Python · 3

Read the script from top to bottom. The equals sign assigns the value on its right to the name on its left. The star means multiplication. print(total) displays the value of total; it does not display the letters in the name.

Type ordinary straight characters and keep the parentheses. The Python prompt symbols >>> are not part of this saved script.

Term	Meaning
Algorithm	An ordered procedure for solving a stated problem
Program	Instructions written in a language a computer can execute
Interpreter	Software that executes Python instructions
Assignment	Binding a name to the value of an expression
Output	Information a program displays or returns

A calculation from paper to output

PAPER STEP	PYTHON INSTRUCTION	EFFECT
Record pack count	packs = 4	Name holds 4
Multiply two quantities	total = packs * per_pack	Name holds product
Show the answer	print(total)	Displays the value

Assign per_pack before the multiplication. This diagram summarises the steps; the complete script below includes that assignment.

Explain From a paper algorithm to Python · 4

The third line assigns total but does not call print, so nothing is displayed. A first-line print(total) raises NameError in a fresh run because total has not been assigned.

Exit: 11 is wrong for five groups of six; addition is a likely cause, and multiplication should give 30. Retain the old result and check the repaired file with both pack counts. Record whether the work was executed or traced.

Model the reasoning aloud

Use the complete worked example below before asking learners to complete W2. Reveal a small part, invite a **prediction**, then explain the deciding step.

These teacher notes contain solutions; do not reveal the independent case answer during modelling.

After line	Names and values	Displayed output
packs = 4	packs is 4	Nothing yet
per_pack = 6	packs is 4; per_pack is 6	Nothing yet

After line	Names and values	Displayed output
total = packs * per_pack	total is 24	Nothing yet
print(total)	Values are unchanged	24

Model the reasoning aloud · 5

Write 24 as the expected **output** before running. Then copy the actual **output** into a separate column. A matching result supports this case, not every possible **input**.

A saved file may contain an old edit: save again and rerun the whole script. Do not type the expected number into the **output** record without running.

> **Why is there no displayed output after the third line? What changes if print(total) is placed first in a fresh run, before any assignment? Explain using which names exist.**

Thinking move	Teacher prompt
Plan	What is given? What is the question? Which procedure fits these facts?
Do	Point to each input and intermediate step in the worked trace. Name the rule that allows the next step.
Check	Does the output answer the question? Which assumption or limitation prevents a larger claim?

Use the diagram and verbal explanation together. Ask learners to match a sentence to a specific visual step; do not assign learners fixed visual or auditory learning styles.

A pictorial worked case: From a paper algorithm to Python

Convert a seed-count **algorithm**. The paper plan counts seeds in identical trays, then adds a labelled spare tray.

The facts we will use

Supplied facts

Python 3: trays=4; per_tray=6; spare=2; total=trays*per_tray+spare; print(total). All quantities count seeds.

AI ACADEMY / PYTHON-BRIDGE/1

From a paper algorithm to Python

Start with the supplied facts

Follow each arrow. Ask which fact allows the next step.

1. Name the inputs

Four trays hold six seeds each; two extra seeds are separate.

2. Translate the plan

Multiply tray count by seeds per tray, then add the spare count.

3. Trace the assignment

4*6+2 is 26; total stores 26 and print displays it.

CHANGE ONE THING

Change spare to 5 while keeping both tray inputs fixed.

Explain the changed result using the matching lesson.

Follow the labelled picture with the matching explanation. Open the vector diagram

Read the picture one step at a time

STEP	WHAT HAPPENS AND WHY
1. Name the inputs	Four trays hold six seeds each; two extra seeds are separate.
2. Translate the plan	Multiply tray count by seeds per tray, then add the spare count.
3. Trace the assignment	4*6+2 is 26; total stores 26 and print displays it.

Match each pictured step to the supplied facts. This is a worked teaching case, not an independent assessment.

Why this result follows

Why the result follows

Python follows the arithmetic instructions. This translation automates a declared counting rule; it does not train a model from examples.

What this example does not establish

Keep the stated limit

The calculation assumes identical tray sizes and measured counts; it cannot detect a miscounted tray.

Change one thing in the pictured case

Change one thing

Change: Change spare to 5 while keeping both tray **input**s fixed.

Predicted result

Prediction: The printed total becomes 29.

Why the result follows

Reason: 4*6 remains 24; adding five gives 29.

Ask while showing the picture

Ask while showing the picture · 6

Cover the result. Ask learners to name the **input**s and predict the next step. Uncover one step, connect the icon to the actual procedure, and explain its **evidence**. Then change the supplied condition and compare.

The picture is a representation; it does not document execution of a real AI model.

Demonstrate and guide practice

> Demonstrate From a paper algorithm to Python, reduce support deliberately and check individual reasoning before discussing answers.

Time or stage	Teacher action
Session 1 start to 7 minutes	Retrieve equal-group multiplication and collect the prerequisite explanation.
7 to 20 minutes	Model source versus output, save counters.py and translate each paper step with the diagram.
20 to 33 minutes	Complete W1 and predict the trace before running the four-line program.
33 to 45 minutes	Start W2 and distinguish observation from the expected answer; record device access.
Session 2 start to 8 minutes	Rerun with five packs and compare the two records.
8 to 20 minutes	Use W3 and the guided question to diagnose a first-line print in a fresh run.
20 to 35 minutes	Collect W4 independently before hints; observe whether each pupil can explain zero trays.
35 to 45 minutes	Complete W5 and the exit. Save source and records; identify pupils needing editor support.

Use the worked example in Sections 3 and 6. Collect a **prediction** before revealing its result; ask the learner to point to each intermediate fact.

Offer four separate line cards, a source/**output** label and a multiplication sketch. Allow a paper trace when devices are unavailable, with execution practice still pending.

Do not supply the independent transfer numbers' answers. Extension: explain why a plus-sign version can accidentally agree with multiplication for two packs of two, and why one passing example is weak **evidence**.

Reduce help deliberately

Completion practice

Completion task: Make records for 4 packs of 6, then 5 packs of 6. Predict before running. Record actual **output**, any error and what changed. If working on paper, label both results as traces.

Reasoning to listen for

Teacher check: Expected 24 then 30. Accept actual errors with an accurate account; do not replace **observation**s. Record the changed pack count, saved file and run or trace status.

Two matching cases do not show all **input**s are handled.

Start by identifying the given **input**s together. Leave the intermediate steps blank. If needed, model one step, then withdraw that help on the next step. Move to a full trace only when the partial trace is understood.

For partners, alternate explainer and checker; collect a response from every learner before discussion.

Individual reasoning check

Use the worked case for From a paper **algorithm** to Python. Proposed explanation: “An equals sign displays the answer”. Decide whether this explanation is supported.

Point to the step or supplied fact that decides; explain your repair if needed.

Expected repair

Expected correction: **Assignment** binds a name; print produces the displayed **output**.

Collect explanations, not only yes/no votes. If a misunderstanding is common, re-model the relevant step for the class.

If it affects a few learners, give a short targeted group explanation while others solve a more demanding variation.

Pictorial practice question

Match each paper quantity to its Python name. Why does the spare count get added once, and what prints when spare is five?

Reasoned teacher answer

The names map trays→4, per_tray→6 and spare→2. The spare count is outside the identical trays, so total is 24+2=26. With spare=5, print displays 29.

Changed-case reasoning: The printed total becomes 29. 4*6 remains 24; adding five gives 29.

Collect each learner's explanation before discussion. Use the first missing connection between **input**, deciding step and result to choose support. This question is worked-case practice, not fresh mastery **evidence**.

Run the investigation and diagnose misconceptions

> Run the From a paper algorithm to Python investigation and use the first unsupported step to choose a teaching response.

An equals sign displays the answer: **Assignment** binds a name; print produces the displayed **output**.

A successful run means the requirement was met: Compare the **output** with the paper rule and expected result.

Python guesses the intended order: A name must be assigned before this script reads it.

Typing a **program** trains an AI model: These statements apply an explicit multiplication rule.

Use Section 9 for the **evidence** ledger. Add a boundary or missing-**input** case and record the expected response before checking. More successful repeats of one case do not establish wider coverage.

Match the support to the first error

What the response shows	Next teaching action
Missing or misread facts	Read the case aloud, mark supplied versus unknown facts, and let the learner restate it.
Wrong procedure	Return to the deciding step in the worked case. Contrast it with the proposed incorrect explanation.
Arithmetic or implementation error	Trace intermediate values or lines; preserve the first mismatch and retry that step.
Correct result without a reason	Ask for a trace and a changed case before marking independent understanding.
An unsupported wider claim	Ask which supplied evidence supports the claim and which further observation would be needed.

Offer an oral explanation, drawing, enlarged visual or fewer examples when that removes a reading/writing barrier. Keep the same reasoning goal.

Stretch secure learners by changing a boundary or assumption and asking them to defend the effect, not simply by assigning more of the same questions.

TEACHER GUIDE · 5 OF 9

Assess and explain the answers

> Use the From a paper algorithm to Python questions, teacher keys and criteria after the relevant attempts. Previously discussed cases are practice; protect the separately selected independent task.

Guided and exit questions

The third line assigns total but does not call print, so nothing is displayed. A first-line print(total) raises NameError in a fresh run because total has not been assigned.

Exit: 11 is wrong for five groups of six; addition is a likely cause, and multiplication should give 30. Retain the old result and check the repaired file with both pack counts. Record whether the work was executed or traced.

W1 Connect the paper steps to Python

Workbook question · W1

Write the complete four-line script for 4 packs of 6. Beside each line explain what it does. Which line displays information?

Teacher reasoning · W1

packs = 4; per_pack = 6; total = packs * per_pack; print(total), each on its own line. The first two bind quantities, the third computes 24 and the fourth displays 24.

Assignment alone produces no displayed **output** in this script.

W2 Predict then observe

Workbook question · W2

Make records for 4 packs of 6, then 5 packs of 6. Predict before running. Record actual **output**, any error and what changed. If working on paper, label both results as traces.

Teacher reasoning · W2

Expected 24 then 30. Accept actual errors with an accurate account; do not replace **observation**s. Record the changed pack count, saved file and run or trace status. Two matching cases do not show all **input**s are handled.

W3 Explain an order error

Workbook question · W3

Move print(total) to the first line of a fresh script. Predict what happens and why. Put the lines back into an order that meets the requirement.

Teacher reasoning · W3

The first line tries to read total before it exists, causing NameError in a fresh run. Assign packs and per_pack, calculate total, then print it.

Earlier values lingering in an interactive session can hide the problem; run the complete saved script afresh.

W4 Transfer the procedure independently

Workbook question · W4

A fictional shelf has 3 trays of 7 tiles each. Write a four-line Python script using trays, per_tray and tiles. Predict its **output**. Then change only trays to 0 and predict again. Explain why adding the two quantities is wrong.

Teacher reasoning · W4

trays = 3; per_tray = 7; tiles = trays * per_tray; print(tiles), on separate lines. **Output**s 21 and then 0. Zero trays contain zero tiles. Addition would give 10 then 7, not the number in equal groups.

W5 Keep an honest conclusion

Workbook question · W5

Explain the difference between a successful run and a correct calculation. State one limit of this **program** and what you would keep so another person can check your work.

Teacher reasoning · W5

A successful run means the execution finished without a reported error; correctness requires matching the stated total-count rule. The script assumes supplied whole nonnegative quantities and does not validate arbitrary **input**.

Keep source, quantities, expected and actual **output** and whether it was run or traced.

Independent assessment and fresh retry

Teacher key · Independent assessment and fresh retry

W4 must give a complete ordered script and explain **output**s 21 and 0 using equal groups. Distinguish an independent paper trace from successful use of the editor; record both skills separately.

After support, retry with 2 boxes of 9 pencils, then 0 boxes: 18 and 0. Ask for the print line and why it follows the calculation.

Assess independent transfer

Independent question · withhold the key

Selected case: Predict the printed value. Change only packs to 5 and predict again. Explain which statements apply a **written rule**.

```
packs = 3
per_pack = 7
total = packs * per_pack
print(total)
```

Selected case answer

> **Teacher key · Selected case answer**
>
> 21, then 35. The multiplication rule is written; changing an **input** is not **fitting** an AI model.

Dimension	Evidence required
Explanation	Names the applicable idea or procedure and ties it to the supplied facts.
Trace and result	Preserves the given inputs and shows the relevant intermediate steps; distinguishes a prediction from an observed execution.
Limits	States the assumptions, missing evidence or conditions under which the result would change.

> **Teacher key · Selected case answer**
>
> Record each dimension as not yet, with support, or independent. Accept a valid alternative procedure with a defensible trace.
>
> Do not penalise an honestly recorded model failure if the learner correctly explains its **evidence** and limits.

Feedback that the learner uses

Name the earliest unsupported step and give one action to repair it. Have the learner make that repair now and explain why. Then assess the relevant skill on a fresh, fully specified case.

Confirm it was not previously practised with feedback; solve and check the new case before assigning it. A follow-up design prompt is a starting brief, not automatically an equivalent test.

Connect the project, support and next lesson

> Connect From a paper algorithm to Python to Python readiness portfolio, adapt support and plan a later changed-case check.

Add a labelled from a paper **algorithm** to python **evidence** sheet to Python readiness portfolio. Show how you can translate a short paper calculation into a python script.

Use the supplied fictional case and keep its **input**s, intermediate steps, calculation or **prediction**, and limitation. Connect this record to last week's record; a matching answer without a trace is insufficient.

Offer four separate line cards, a source/**output** label and a multiplication sketch. Allow a paper trace when devices are unavailable, with execution practice still pending.

Do not supply the independent transfer numbers' answers. Extension: explain why a plus-sign version can accidentally agree with multiplication for two packs of two, and why one passing example is weak **evidence**.

Week 2 studies values, variable names and types, including the difference between numeric data and text.

Retain the project ledger and assess a changed case after support. Check the relevant prerequisite before carrying this component forward.

Plan the delayed return

Suggested return points in this level: python-bridge/2, python-bridge/4, python-bridge/7. Use actual classroom dates, adjusting for holidays and gaps.

One, three and six teaching weeks are scheduling choices, not a claimed optimal spacing.

At a delayed check, ask for the idea from memory and a changed application. Compare with the earlier independent response and record support used.

For a new level, revisit the previous capstone before checking the new prerequisites.

Record	Teacher evidence
Learner code and date	
Concept and case used; prior exposure	
Explanation / trace / limits	
Support and first repair	
Changed case and delayed outcome	
Next teaching action	

Use the **evidence** to choose reteaching or the next step. A completed page, confidence rating or attractive project does not by itself demonstrate understanding.

Project evidence from this case

For Python readiness before the Responsible Plant Classifier, retain a trace of the values, the predicted **output**s and the changed-case explanation. Use actual Python 3 results to check the **prediction** after reasoning first.

Prepare, teach and assess

> Use this preparation summary alongside the detailed From a paper algorithm to Python lesson; it is a checklist rather than a replacement for the full sequence.

Teaching target

Teaching target: Translate a short paper calculation into a Python script

Prepare the labelled worked-case picture, the matching workbook, fictional **input** cards and a place for individual responses. Check a local Python 3 environment before class; have a paper-trace version ready.

Session · Plan · Resources

> **Session:** Session 1 · Understand · 45 min
>
> **Plan:** 0–7: recall and prerequisite; 7–15: inspect the concrete case and predict; 15–30: teacher models the worked trace; 30–40: learners explain a step using the text and visual; 40–45: check the core idea.
>
> **Resources:** Sections 1–6; record the brief recall in the workbook.

> **Session:** Session 2 · Practise · 45 min
>
> **Plan:** 0–5: retrieve the procedure; 5–15: W2 completion practice; 15–23: explain and check with a partner; 23–30: each learner answers the misconception check; 30–40: targeted reteaching or a harder variation; 40–45: prepare the investigation.
>
> **Resources:** Sections 7–10; use the matching workbook W2 and misconception check.

> **Session:** Session 3 · Investigate and transfer · 45 min
>
> **Plan:** 0–5: retrieve the decision rule; 5–20: investigate or trace; 20–30: start the independent case; 30–38: connect the project; 38–43: act on feedback; 43–45: plan the return check.
>
> **Resources:** Sections 9 and 11–14. Give extra time to finish the full task set; use Section 15 when the week includes a coding lab.

Before class, solve the supported practice: Make records for 4 packs of 6, then 5 packs of 6. Predict before running. Record actual **output**, any error and what changed. If working on paper, label both results as traces.

Supported practice answer

Reasoned practice answer: Expected 24 then 30. Accept actual errors with an accurate account; do not replace **observation**s. Record the changed pack count, saved file and run or trace status.

Two matching cases do not show all **input**s are handled.

Check every learner before discussion: Use the worked case for From a paper **algorithm** to Python. Proposed explanation: “An equals sign displays the answer”. Decide whether this explanation is supported.

Point to the step or supplied fact that decides; explain your repair if needed.

Repair the misconception

Misconception repair: **Assignment** binds a name; print produces the displayed **output**.

Support without giving away the answer

Support: read the exact case aloud, enlarge the labelled picture, supply **input** cards and model only the first deciding step. Accept a spoken explanation or drawing; retain the reasoning goal.

Extend the reasoning

Extension: Change spare to 5 while keeping both tray **input**s fixed. Require a **prediction** and a reason before comparing. Expected result: The printed total becomes 29. Reason: 4*6 remains 24; adding five gives 29.

Protect the independent attempt

Independent assessment: withhold the reserved answer until the learner has attempted the new case. Record support separately from correctness.

Criterion	Not yet	With support	Independent
Explanation	Names an answer without a deciding fact	Uses a hint to link fact and decision	Explains the deciding fact in own words
Trace or test	Cannot connect input and result	Completes steps with prompts	Traces or tests a changed case accurately
Limits and revision	Claims more than evidence supports	Names a limit after a prompt	States a defensible limit and useful next test

Project checkpoint

Project checkpoint: Python readiness portfolio. Keep runnable code, **prediction**s, actual **output**s, one repaired error and an explanation of a function on changed **input**s.

Use the weekly teacher answer for topic-specific reasoning. A saved progress tick is an activity record; judge mastery from the learner's explanation and **evidence**.

TEACHER GUIDE · 8 OF 9

Use feedback, labs and repair paths

> Use feedback, earlier review and portfolios purposefully. Apply the coding routine only when this lesson has an executable lab.

Use the two formative questions as supported practice, not as independent mastery scores. Discuss the deciding **evidence** rather than accepting a guessed selection.

The feedback comes from the reviewed public worked case. Do not reveal the separately reserved independent teacher answer until the learner has attempted that case.

Ask students to predict before running code. Preserve errors and actual **output**s; collect a changed test and an explanation. The branch-boundary and indexing lessons deliberately include failure cases.

Use the earlier worked-explanation links to address a specific missing building block, then return to the current question. Adapt this suggestion after observing the learner; it is not an automatic diagnosis.

Collect the completed-work portfolio as **evidence**. Record support separately from correctness, and assess explanation, trace/test and limitations. Progress ticks and quiz selections alone do not establish mastery.


TEACHER GUIDE · 9 OF 9

Visual concept journey

> Show one From a paper algorithm to Python graphic at a time, request a prediction and discuss its trace before the independent assessment.

Use one picture at a time. Hide a worked result before asking for a **prediction**, then reveal it for feedback. These are supported teaching cases; retain the separate independent assessment for a fresh first attempt.

01. From a paper algorithm to Python: the case



Follow the labelled picture with the matching explanation. Open the vector diagram

Convert a seed-count **algorithm**. The paper plan counts seeds in identical trays, then adds a labelled spare tray. Supplied facts: Python 3: trays=4; per_tray=6; spare=2; total=trays*per_tray+spare; print(total).


All quantities count seeds.

> Point to the given fact that matters most. Explain why it matters.

Discuss while showing the picture

Teacher prompt: Point to the given fact that matters most. Explain why it matters. Ask learners to describe one label or arrow in ordinary words. Use the adjacent transcript if the image is difficult to see.

02. Follow the deciding steps



Follow the labelled picture with the matching explanation. Open the vector diagram


Name the **input**s: Four trays hold six seeds each; two extra seeds are separate. → Translate the plan: Multiply tray count by seeds per tray, then add the spare count. → Trace the **assignment**: 4*6+2 is 26; total stores 26 and print displays it.

Point to each numbered stage and explain which recorded **input** it uses.

Discuss while showing the picture

Teacher prompt: Point to each numbered stage and explain which recorded **input** it uses. Ask learners to describe one label or arrow in ordinary words. Use the adjacent transcript if the image is difficult to see.

03. A calculation from paper to output



Follow the labelled picture with the matching explanation. Open the vector diagram


A calculation from paper to **output**. Record pack count | packs = 4 | Name holds 4. Multiply two quantities | total = packs * per_pack | Name holds product. Show the answer | print(total) | Displays the value

Read the labels and values. Explain the relationship the model shows.

Discuss while showing the picture

Teacher prompt: Read the labels and values. Explain the relationship the model shows. Ask learners to describe one label or arrow in ordinary words. Use the adjacent transcript if the image is difficult to see.

04. Change one thing. Trace what follows.



Follow the labelled picture with the matching explanation. Open the vector diagram

Original case: 4*6+2 is 26; total stores 26 and print displays it. Changed condition: Change spare to 5 while keeping both tray **input**s fixed. Expected result: The printed total becomes 29.

Reason: 4*6 remains 24; adding five gives 29.


Predict before checking the worked changed-case result. Name what changed and what the supplied facts allow you to conclude.

Discuss while showing the picture

Teacher prompt: Predict before checking the worked changed-case result. Name what changed and what the supplied facts allow you to conclude. Ask learners to describe one label or arrow in ordinary words.

Use the adjacent transcript if the image is difficult to see. Changed-case reasoning: 4*6 remains 24; adding five gives 29.

05. Connect the explanation to its limit



Follow the labelled picture with the matching explanation. Open the vector diagram

Python follows the arithmetic instructions. This translation automates a declared counting rule; it does not train a model from examples.

Limit: The calculation assumes identical tray sizes and measured counts; it cannot detect a miscounted tray.


Explain the case, then point to a limit on the claim.

Discuss while showing the picture

Teacher prompt: Explain the case, then point to a limit on the claim. Ask learners to describe one label or arrow in ordinary words. Use the adjacent transcript if the image is difficult to see.

Keep the stated scope: The calculation assumes identical tray sizes and measured counts; it cannot detect a miscounted tray.

06. Make the idea visible in your project



Follow the labelled picture with the matching explanation. Open the vector diagram

For Python readiness before the Responsible Plant Classifier, retain a trace of the values, the predicted **output**s and the changed-case explanation. Use actual Python 3 results to check the **prediction** after reasoning first.

Draw your **input**, deciding step, result and limit. Supported question: Match each paper quantity to its Python name. Why does the spare count get added once, and what prints when spare is five?

Draw your project trace and justify the deciding step using **evidence**.

Discuss while showing the picture

Teacher prompt: Draw your project trace and justify the deciding step using **evidence**. Ask learners to describe one label or arrow in ordinary words. Use the adjacent transcript if the image is difficult to see.

Supported practice key: The names map trays→4, per_tray→6 and spare→2. The spare count is outside the identical trays, so total is 24+2=26. With spare=5, print displays 29.

Save or print your responses for your portfolio. Progress and drafts on the hosted website stay in the current browser. Use only fictional or teacher-approved data.