

## Searching for a Specific User and Updating the User Information

source code:

Open pom.xml

```
<?xml version="1.0" encoding="UTF-8"?>
<project xmlns="http://maven.apache.org/POM/4.0.0"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://maven.apache.org/POM/4.0.0
https://maven.apache.org/xsd/maven-4.0.0.xsd">
  <modelVersion>4.0.0</modelVersion>
  <parent>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-starter-parent</artifactId>
    <version>2.4.3</version>
    <relativePath /> <!-- lookup parent from repository -->
  </parent>
  <groupId>com.example</groupId>
  <artifactId>UserManager</artifactId>
  <version>0.0.1-SNAPSHOT</version>
  <name>UserManager</name>
  <description>Searching for a Specific User and Updating the User
Information.</description>
  <properties>
    <java.version>1.8</java.version>
  </properties>
  <dependencies>
    <dependency>
      <groupId>org.springframework.boot</groupId>
      <artifactId>spring-boot-starter-data-jpa</artifactId>
    </dependency>
    <dependency>
      <groupId>org.springframework.boot</groupId>
      <artifactId>spring-boot-starter-web</artifactId>
    </dependency>
    <dependency>
      <groupId>org.projectlombok</groupId>
      <artifactId>lombok</artifactId>
      <optional>true</optional>
    </dependency>
  </dependencies>
</project>
```

```

</dependency>
<dependency>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-starter-test</artifactId>
    <scope>test</scope>
</dependency>
<dependency>
    <groupId>org.apache.tomcat.embed</groupId>
    <artifactId>tomcat-embed-jasper</artifactId>
    <scope>provided</scope>
</dependency>

<dependency>
    <groupId>javax.xml.bind</groupId>
    <artifactId>jaxb-api</artifactId>
</dependency>

<dependency>
    <groupId>org.javassist</groupId>
    <artifactId>javassist</artifactId>
    <version>3.25.0-GA</version>
</dependency>

<dependency>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-devtools</artifactId>
    <scope>runtime</scope>
    <optional>true</optional>
</dependency>
</dependencies>

<build>
    <plugins>
        <plugin>
            <groupId>org.springframework.boot</groupId>
            <artifactId>spring-boot-maven-plugin</artifactId>
            <configuration>
                <excludes>
                    <exclude>

```

```

        <groupId>org.projectlombok</groupId>
            <artifactId>lombok</artifactId>
                <exclude>
                    </exclude>
                </excludes>
            </configuration>
        </plugin>
    </plugins>
</build>

</project>

```

### UserManagerApplication.java

```

package com.example.UserManager;

import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;

@SpringBootApplication
public class UserManagerApplication {

    public static void main(String[] args) {

        SpringApplication.run(UserManagerApplication.class, args);

    }

}

```

### AppErrorController.java

```

package com.example.UserManager.controller;

import org.springframework.boot.web.servlet.error.ErrorController;
import org.springframework.web.bind.annotation.RequestMapping;

public class AppErrorController implements ErrorController {

```

```

@RequestMapping("/error")

public String handleError() {

    //do something like logging

    return "error";

}

@Override

public String getErrorPath() {

    return null;

}

}

```

### MainController.java

```

package com.example.UserManager.controller;

import org.springframework.stereotype.Controller;
import org.springframework.ui.ModelMap;
import org.springframework.web.bind.annotation.GetMapping;
import org.springframework.web.bind.annotation.RequestParam;

@Controller

public class MainController {

    @GetMapping(value = "/")

    public String showIndexPage(ModelMap model,

    @RequestParam(value = "name", required = false, defaultValue = "World")
    String name) {

        model.addAttribute("name", name);
    }
}

```

```
        return "index";
    }
}
```

### **UserController.java**

```
package com.example.UserManager.controller;

import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.stereotype.Controller;
import org.springframework.ui.ModelMap;
import org.springframework.web.bind.annotation.GetMapping;
import org.springframework.web.bind.annotation.ModelAttribute;
import org.springframework.web.bind.annotation.PostMapping;
import org.springframework.web.bind.annotation.RequestMapping;
import org.springframework.web.bind.annotation.RequestMethod;
import org.springframework.web.bind.annotation.RequestParam;
import com.example.UserManager.entities.User;
import com.example.UserManager.services.UserService;

@Controller
public class UserController {

    //controls the functionality of the user entity

    @Autowired
```

```

private UserService userService;

Logger logger = LoggerFactory.getLogger(UserController.class);

@GetMapping("/users")

public String showUsers(ModelMap model) {

    logger.info("Getting all users");

    Iterable<User> users = userService.GetAllUsers();

    logger.info("Passing users to view");

    model.addAttribute("users", users );

    return "users";

}

@RequestMapping(value = "/search/{id}", method =
RequestMethod.POST)

public String searchUser(ModelMap model, @RequestParam("id") int
id) {

    logger.info("Searching for a user");

    User user = userService.GetUserById(id);

    logger.info("Passing Searched User to View");

    model.addAttribute("userSearch", user);

    return "search";

}

@PostMapping("search/update")

public String updateUser(ModelMap model,
@ModelAttribute("update") User user) {

```

```

        logger.info("Updating a User");

        userService.UpdateUser(user);

        model.addAttribute("updatedUser", user);

        return "update";
    }
}

```

### UserExceptionHandler.java

```

package com.example.UserManager.controller;

import org.springframework.http.HttpStatus;
import org.springframework.http.ResponseEntity;
import org.springframework.web.bind.annotation.ControllerAdvice;
import org.springframework.web.bind.annotation.ExceptionHandler;
import com.example.UserManager.exceptions.UserNotFoundException;

@ControllerAdvice
public class UserExceptionHandler {

    @ExceptionHandler(value=UserNotFoundException.class)

    public ResponseEntity<Object> exception(UserNotFoundException ex)
    {

        return new ResponseEntity<>("Product not found",
        HttpStatus.NOT_FOUND);

    }

}

```

### User.java

```
package com.example.UserManager.entities;

import javax.persistence.Entity;
import javax.persistence.GeneratedValue;
import javax.persistence.GenerationType;
import javax.persistence.Id;

@Entity

public class User { //The Entity of a User; What it is.

    @Id

    @GeneratedValue(strategy=GenerationType.AUTO)

    private Integer id;

    private String name;

    private String email;

    private String password;

    public User() {

        super();

    }

    public User(Integer id, String name, String email, String password) {

        super();

        this.id = id;

        this.name = name;

        this.email = email;

        this.password = password;

    }

}
```



```
}  
  
public Integer getId() {  
    return id;  
}  
  
public void setId(Integer id) {  
    this.id = id;  
}  
  
public String getName() {  
    return name;  
}  
  
public void setName(String name) {  
    this.name = name;  
}  
  
public String getEmail() {  
    return email;  
}  
  
public void setEmail(String email) {  
    this.email = email;  
}  
  
public String getPassword() {  
    return password;  
}
```

```

        public void setPassword(String password) {

            this.password = password;

        }

        @Override

        public String toString() {

            return (id.toString() + " " + name + " " + email + " " + password);

        }

    }

```

#### UserNotFoundException.java

```

package com.example.UserManager.exceptions;

public class UserNotFoundException extends RuntimeException {
    private static final long serialVersionUID = 1L;
}

```

#### UserRepository.java

```

package com.example.UserManager.repositories;

import org.springframework.data.repository.CrudRepository;
import org.springframework.stereotype.Repository;

import com.example.UserManager.entities.User;

@Repository

public interface UserRepository extends CrudRepository<User, Integer> {

    public User findByName(String name);

}

```

#### UserService.java

```

package com.example.UserManager.services;

```

```
import java.util.Optional;

import org.springframework.beans.factory.annotation.Autowired;

import org.springframework.stereotype.Service;

import com.example.UserManager.entities.User;

import com.example.UserManager.exceptions.UserNotFoundException;

import com.example.UserManager.repositories.UserRepository;

@Service

public class UserService {

    @Autowired

    private UserRepository userRepository;

    public Iterable<User> GetAllUsers() {

        return userRepository.findAll();

    }

    public User GetUserByName(String name) {

        return userRepository.findByName(name);

    }

    public User GetUserById(Integer id) {

        Optional<User> foundUser = userRepository.findById(id);

        if(!foundUser.isPresent()) throw new UserNotFoundException();

        return foundUser.get();

    }

    public User UpdateUser(User userToUpdate) {
```

```

        return userRepository.save(userToUpdate);
    }
}

```

## application.properties

```

spring.jpa.hibernate.ddl-auto=update
spring.datasource.url=jdbc:mysql://localhost:3306/mywork
spring.datasource.username=root
spring.datasource.password=ramani44
logging.level.org.springframework.web: DEBUG
spring.mvc.view.prefix=/WEB-INF/jsp/
spring.mvc.view.suffix=.jsp
server.port=8080

```

## error.jsp

```

<!DOCTYPE html>
<html>
<body>
<h1>Something went wrong! </h1>
<h2>Our Engineers are on it</h2>
<a href="/">Go Home</a>
</body>
</html>

```

## index.jsp

```

<html>
<body>
<h2>Spring Application</h2>

<h2 class="hello-title">Hello ${name}!</h2>
<a href="/users">List Users</a>
<form action="/search/{id}" method="post">
Enter ID Number: <input name="id" type="text" id="id" placeholder="1"
required/>
<input name="Submit" type="submit"/>

```

```
</form>
```

```
</body>
```

```
</html>
```

search.jsp

```
<%@ page language="java" contentType="text/html; charset=UTF-8"
    pageEncoding="UTF-8"%>
```

```
<%@ taglib prefix="form"
```

```
uri="http://www.springframework.org/tags/form"%>
```

```
<!DOCTYPE html PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
    "http://www.w3.org/TR/html4/loose.dtd">
```

```
<html>
```

```
<style>
```

```
table {
```

```
    float: left;
```

```
}
```

```
th {
```

```
    border-bottom: 1px solid black;
```

```
    text-align: left;
```

```
}
```

```
</style>
```

```
<body>
```

```
<h2>Search for User</h2>
```

```
<table>
```

```
<tr>
```

```
<th>ID</th>
```

```
<th>Name</th>
```

```
<th>Email</th>
```

```
<th>Password</th>
```

```
</tr>
```

```
<tr>
```

```
<td>${userSearch.id}</td>
```

```
<td>${userSearch.name}</td>
```

```
<td>${userSearch.email}</td>
```

```

        <td>${userSearch.password}</td>
    </tr>
</table>

<br />
<br />
<br />
<br />
<br />
<br />
<form:form action="update" method="post"
commandName="update">
    <h3>Update This User?</h3>
    <p>User ID: ${userSearch.id}</p>
    <input type="hidden" name="id" id="id"
value="${userSearch.id}" required/>
    <label for="name">New Name:</label><br/>
    <input type="text" name="name" id="name"
value="${userSearch.name}" required/><br/>
    <label for="email">New Email:</label> <br/>
    <input type="text" name="email" id="email"
value="${userSearch.email}" required/><br/>
    <label for="password">New Password:</label><br/>
    <input type="text" name="password" id="password"
value="${userSearch.password}" required/><br/><br/>
    <input type="submit" value="Submit"/>
</form:form>
<br />
<br />
<a href="/">Return to Menu</a>
</body>
</html>

```

update.jsp

```

<html>
<body>
<h2>Update Successful</h2>
Updated User Credentials: ${updatedUser.toString()}
<br/><br/>

```

```
<a href= "/">Return to Menu</a>
</body>
</html>
```

## users.jsp

```
<%@ taglib uri= "http://java.sun.com/jsp/jstl/core" prefix= "c"%>
<html>
<style>
table {
float: left;
}

table, th, td {
border: 1px solid black;
}
</style>
<head></head>
<body>
    <h2>Users Page</h2>
    <table>
        <tr><th>ID</th><th>Name</th><th>Email</th><th>Password</th></tr>
        <tr>
            <td><div>
                <c:forEach items= "${users}" var= "user" varStatus= "count">
                    <tr id= "${count.index}" >
                        <td>${user.id}</td>
                        <td>${user.name}</td>
                        <td>${user.email}</td>
                        <td>${user.password}</td>
                    </tr>
                </c:forEach>
            </td>
        </tr>
    </table>
</body>
</html>
```

