

MONGODB COMMANDS

```
>_MONGOSH
> show dbs
< admin          108.00 KiB
  bookflow_db    40.00 KiB
  config         72.00 KiB
  local          40.00 KiB
test>
```

```
>_MONGOSH
> show dbs
< admin          108.00 KiB
  bookflow_db    40.00 KiB
  config         72.00 KiB
  local          40.00 KiB
> use myDatabase
< switched to db myDatabase
> db
< myDatabase
> show collections
<
> show collections
<
> db.users.insertOne({ name: "Alice", age: 25 })
< {
  acknowledged: true,
  insertedId: ObjectId('6a8e63388594a503133c51b5')
}
myDatabase> |
```

Insert many :

```
> db.users.insertMany([
  { name: "Bob", age: 30 },
  { name: "Carol", age: 28 }
])
< {
  acknowledged: true,
  insertedIds: {
    '0': ObjectId('6a8e636b8594a503133c51b6'),
    '1': ObjectId('6a8e636b8594a503133c51b7')
  }
}
myDatabase >
```

All Documents:

```

    {
      _id: ObjectId('6a8e636b8594a503133c51b6'),
      name: 'Bob',
      age: 30
    }
  ],
  {
    _id: ObjectId('6a8e636b8594a503133c51b7'),
    name: 'Carol',
    age: 28
  }
]
> db.users.findOne({ name: "Alice" })
< {
  _id: ObjectId('6a8e63388594a503133c51b5'),
  name: 'Alice',
  age: 25
}
> db.users.find(
  { age: { $gte: 25 } },
  { name: 1, _id: 0 }
)
< {
  name: 'Alice'
}
{
  name: 'Bob'
}
{
  name: 'Carol'
}

```

CURD Operations:

Create:

```
> db.users.insertOne({
  name: "Alice",
  age: 25,
  email: "alice@gmail.com"
})
< {
  acknowledged: true,
  insertedId: ObjectId('6a8e643f8594a503133c51b8')
}
myDatabase> |
```

Insert multiple documents:

```
> db.users.insertMany([
  { name: "Bob", age: 30, email: "bob@gmail.com" },
  { name: "Carol", age: 28, email: "carol@gmail.com" }
])
< {
  acknowledged: true,
  insertedIds: {
    '0': ObjectId('6a8e645d8594a503133c51b9'),
    '1': ObjectId('6a8e645d8594a503133c51ba')
  }
}
```

READ

Find all documents

>_MONGOSH

```
> db.users.find()
< {
  _id: ObjectId('6a8e63388594a503133c51b5'),
  name: 'Alice',
  age: 27
}
{
  _id: ObjectId('6a8e636b8594a503133c51b7'),
  name: 'Carol',
  age: 29
}
{
  _id: ObjectId('6a8e643f8594a503133c51b8'),
  name: 'Alice',
  age: 25,
  email: 'alice@gmail.com'
}
{
  _id: ObjectId('6a8e645d8594a503133c51b9'),
  name: 'Bob',
  age: 30,
  email: 'bob@gmail.com'
}
{
  _id: ObjectId('6a8e645d8594a503133c51ba'),
  name: 'Carol',
  age: 28,
  email: 'carol@gmail.com'
}
```

Find specific document:

```
> db.users.findOne({ name: "Alice" })
< {
  _id: ObjectId('6a8e63388594a503133c51b5'),
  name: 'Alice',
  age: 27
}
```

Conditional query:

>_MONGOSH

```
> db.users.find(
  { age: { $gte: 25 } },
  { name: 1, email: 1, _id: 0 }
)
< {
  name: 'Alice'
}
{
  name: 'Carol'
}
{
  name: 'Alice',
  email: 'alice@gmail.com'
}
{
  name: 'Bob',
  email: 'bob@gmail.com'
}
{
  name: 'Carol',
  email: 'carol@gmail.com'
}
```

UPDATE (Modify Data):

>_MONGOSH

```
> db.users.updateOne(  
  { name: "Alice" },  
  { $set: { age: 26 } }  
)
```

```
< {  
  acknowledged: true,  
  insertedId: null,  
  matchedCount: 1,  
  modifiedCount: 1,  
  upsertedCount: 0  
}
```

```
> db.users.updateMany(  
  { age: { $lt: 30 } },  
  { $inc: { age: 1 } }  
)
```

```
< {  
  acknowledged: true,  
  insertedId: null,  
  matchedCount: 4,  
  modifiedCount: 4,  
  upsertedCount: 0  
}
```

```
> db.users.replaceOne(  
  { name: "Bob" },  
  { name: "Bob", age: 31, email: "bob@gmail.com", active: true }  
)
```

```
< {  
  acknowledged: true,
```