

Intermediate Git

Day 4: Collaborating on GitHub

Raman A. Shah

Copyright (c) 2015 by Raman A. Shah.

Creative Commons BY-NC-SA 3.0 Unported.

https://github.com/ramanshah/intermediate_git

Back to the Day 2 repo

Do you have a clean sample repository from last time?

```
cd sample  
git status
```

If not, either clone the course repo or refresh it with `git pull origin master`:

```
git clone https://github.com/\  
ramanshah/intermediate_git.git
```

Then decompress an updated sample repository:

```
cp ../intermediate_git/day4/sample.tgz .  
tar xzvf sample.tgz  
cd sample  
git status
```

Manage GitHub: git remote

Try these on your `intermediate_git` and sample repos. What do you get?

```
git remote
git remote -v
git remote show origin
```

To connect your repository to a server:

```
git remote add [remote_name] [url]
```

To delete the connection:

```
git remote rm [remote_name]
```

Remote branches

`[remote]/[branch]`

A read-only pointer to the state of
[branch] on [remote] the last time you
checked.

Tracking branches

A local branch is sometimes automatically set up to correspond to a remote branch:

- When you `git clone` a repo, master tracks `origin/master`.
- When you `git push` a new branch, that gets set up to track as well.

But to check out someone else's branch from a remote, you have to set up tracking yourself:

```
git checkout -b [branch] \
  [remote]/[branch]
```

Push, fetch, and pull

To put local commits on the remote server:

```
git push [remote] [branch]
```

To download remote objects:


```
git fetch [remote]
```

To download remote objects *and* merge them into your current branch:

```
git pull [remote] [branch]
```

`git pull` = `git fetch` + `git merge`!


Everyone's on master



A standard git clone.

Scott Chacon, *Pro Git*, Fig. 3-22. CC-BY-NC-SA.
<https://progit.org/>


Everyone's on master



Local master has diverged from origin/master.

Scott Chacon, *Pro Git*, Fig. 3-23. CC-BY-NC-SA.
<https://progit.org/>


Everyone's on master



You have to `git fetch`, not `git pull`.

Scott Chacon, *Pro Git*, Fig. 3-24. CC-BY-NC-SA.
<https://progit.org/>


Everyone's on master



You can add a second remote.

Scott Chacon, *Pro Git*, Fig. 3-25. CC-BY-NC-SA.
<https://progit.org/>

Everyone's on master



Again, git fetch, not git pull, is appropriate.

Scott Chacon, *Pro Git*, Fig. 3-26. CC-BY-NC-SA.
<https://progit.org/>

Recommendation

When collaborating,
don't work on master.
If you do, avoid `git
pull`.

Pull requests—can push


Why wouldn't you just push to master?

- Pull requests give a mechanism for peer review of code.
- Others might expect master to be working or stable.
- The master branch might need to be ready to go, e.g., deployable.

Even if you have push access, submit changes as pull requests as a matter of *safety* and *etiquette*.


Pull requests—can push

Their GH
(origin)



Someone has a project.
They give you push access.



Pull requests—can push



`git clone [url]`

Pull requests—can push

Their GH
(origin)





My
computer

```
git checkout -b my_branch  
git commit [...]
```


Pull requests—can push

Their GH
(origin)





My
computer

```
git push origin my_branch
```

Pull requests—can push

Their GH
(origin)





My
computer

They put some new work on master.

Pull requests—can push

Their GH
(origin)





My
computer

```
git checkout master  
git pull origin master
```

Pull requests—can push

Their GH
(origin)





My
computer

```
git checkout my_branch  
git merge master
```

Pull requests—can push

Their GH
(origin)





My
computer

```
git push origin my_branch
```

Pull requests—can push

Their GH
(origin)





My
computer

Click “New Pull Request;” code review

```
git commit [...]
```

Pull requests—can push

Their GH
(origin)





My
computer

```
git push origin my_branch
```

Pull requests—can push

Their GH
(origin)





My
computer

“LGTM” — “Looks Good To Me.”
You click “Merge Pull Request.”

Pull requests—can push

Their GH
(origin)





My
computer

You click “Delete Branch.”

Pull requests—can push

Their GH
(origin)





My
computer

```
git checkout master  
git pull origin master
```

Pull requests—can push

Their GH
(origin)



My
computer

```
git branch -d my_branch
```

Done!

Pull requests—can't push


If you don't have push access, you have to:

- *Fork* the repo on GitHub.
- Curate your fork so that the changes in the fork can be applied to the original repo in a single pull without merge conflicts.
- In some projects, rebase your work so that the commits are “nice” and result in a fast-forward merge.

This is the default case in open source work.


Pull requests—can't push

Their GH
(origin)




Someone has a project.

Pull requests—can't push



`git clone [url]`


Pull requests—can't push





Click "Fork" on GitHub
`git remote add my_fork [url]`

Pull requests—can't push

My GH
(my_fork)




Their GH
(origin)



My
computer


```
git checkout -b my_branch  
git commit [...]
```


Pull requests—can't push





Pull requests—can't push

My GH
(my_fork)




Their GH
(origin)



My
computer


They put some new work on master.

Pull requests—can't push



```
git checkout master  
git pull origin master
```


Pull requests—can't push





```
git push my_fork master
```

Pull requests—can't push

My GH
(my_fork)




Their GH
(origin)



My
computer

```
git checkout my_branch  
git merge master
```


Pull requests—can't push





```
git push my_fork my_branch
```

Pull requests—can't push

My GH
(my_fork)



Their GH
(origin)




My
computer

Click “New Pull Request;” code review


```
git commit [...]
```

Pull requests—can't push



```
git push my_fork my_branch
```



Pull requests—can't push





They're happy. They click "Merge Pull Request."

Pull requests—can't push

My GH
(my_fork)




Their GH
(origin)



My
computer


They click “Delete Branch.”

Pull requests—can't push



```
git checkout master  
git pull origin master
```


Pull requests—can't push





```
git push my_fork master
```

Pull requests—can't push

My GH
(my_fork)



Their GH
(origin)




My
computer



```
git branch -d my_branch
```

Pull requests—can't push

My GH
(my_fork)



Their GH
(origin)



My
computer

```
git push my_fork :my_branch
```

Done!

Keep pull requests small!

Shorter pull requests involve:

- Less *time* to diverge from master—hence fewer merge conflicts
- Less *cognitive load* for the developer and maintainer to comprehend and communicate the reasoning behind the changes

My personal rule of thumb is that a pull request is too big if you exceed:

- Roughly one week of active development time
- Roughly 150 lines of source code

Conclusion

