

Abb Af146-30 Contactor 200A

ABB AF146-30 Contactor - 200A, 100-250V AC/DC Coil, Heavy-Duty Industrial Use

The ABB AF146-30 is a high-performance contactor engineered for demanding industrial applications requiring reliable switching of heavy electrical loads. This contactor supports both AC and DC control voltages from 100V to 250V and is built to handle up to 200A, making it ideal for motor control centers, power distribution systems, and automation panels.

Key Features:


- Rated operational current: 200A, suitable for large-scale power control
- Universal coil voltage range (100-250V AC/DC) ensures flexible application compatibility
- Meets IEC/EN 60947-4-1, IEC 60947-5-1, and GB 14048 standards for global compliance and safety


Specifications:


- Manufacturer: ABB AB Control Products
- Model: AF146-30
- Rated Operational Voltage (Ui): 1000V
- Rated Insulation Voltage: 690V~
- Control Voltage: 100-250V AC/DC, 50/60Hz

- Rated Current: 200A
- Standards: IEC/EN 60947-4-1, IEC/EN 60947-5-1, GB 14048.4, GB 14048.5
- Torque Ratings: 8 Nm (71 lb.in), 9 Nm (80 lb.in), 1 Nm (9 lb.in)
- Product Code: 1SFC100003M0201
- Country of Origin: Made in Sweden
- Weight: 1.960 Kg

Robust and versatile, the ABB AF146-30 is a trusted solution for controlling high-power equipment in industrial and commercial settings, offering dependable performance with global standard compliance.

 **Email:** info@ramautomations.com

 **WhatsApp:** +1 330 294 2744

 **Contact:** +91 78638 05686