

Allen-bradley 592-jov16-500-nx101 Overload Relay With Contactor Ser:B

The Allen-Bradley 592-JOV16/500-NX101 Overload Relay with Contactor Series B is a rugged and reliable motor protection solution designed for industrial control applications. This combination unit includes a NEMA Size 00 contactor and an overload relay, offering dependable protection against overload conditions in motors and connected machinery. Built to meet IEC/EN 60947-4-1/-5-1 standards, the unit supports a wide control voltage range and includes auxiliary contacts rated A600 for enhanced signaling capabilities. With a durable design and international voltage compatibility, this assembly is ideal for use in industrial automation, manufacturing, and motor control centers.

Key Features:

- Includes NEMA Size 00 contactor and overload relay in a compact assembly
- Supports control circuit voltages from 120V to 600V AC with high make/break capacity
- Auxiliary contacts rated A600 for reliable signaling and circuit feedback
- Built to IEC/EN 60947-4-1/-5-1 with 8kV impulse withstand voltage
- Constructed for durability in demanding industrial environments

Specifications:

- Product Name: Allen-Bradley 592-JOV16/500-NX101 Overload Relay with Contactor
- Catalog Numbers: 592-JOV16 (Ser: B), 500-NX101* (Ser: D)

• NEMA Size: 00

• Control Circuit Ratings: 120-600V AC

• Make Capacity: 7200 VA | Break Capacity: 720 VA

Auxiliary Contact Rating: NEMA A600

• Standards: IEC/EN 60947-4-1 / -5-1

• Uimp (Impulse Withstand Voltage): 8 kV

• Max Continuous Current: 9 A

Voltage: 600V AC max

Wire Size: #10 AWG max, 75°C Cu only

Power Terminal Torque: 12 lb-in

Coil Voltage: 110V 50Hz / 120V 60Hz

Origin: Made in Switzerland, Assembled in Mexico

• Weight: 1.760 kg

The **Allen-Bradley 592-JOV16/500-NX101** offers compact, high-performance motor protection with proven reliability. Its versatile voltage range, high-quality construction, and compliance with global standards make it a preferred choice for engineers and technicians in industrial motor control applications.

™ Email: info@ramautomations.com

(Section 2014) WhatsApp: +1 330 294 2744

Contact: +91 78638 05686