

Linux User Management – Complete Hands-on Guide with Practical Examples

Linux User Management: Linux User Management is the process of creating, modifying, and deleting users and groups to control access, manage permissions, and improve server security.

Important Files:

/etc/passwd – Stores user account information.

/etc/shadow – Stores encrypted user passwords.

/etc/group – Stores group details and members.

/etc/gshadow – Stores secure group information and passwords.

User Management Commands

Use the following command to create a new user.

CMD: `sudo adduser <username>`

Description: The adduser command is an interactive utility that creates a new user account, sets a password, creates a home directory, and allows you to enter optional user details.

Alternatively, you can use:

CMD: `useradd` The useradd command creates only the user account. You must manually configure the password and home directory if required.

```
root@ip-172-31-25-7:/home/ubuntu# adduser Ramesh
New password:
Retype new password:
passwd: password updated successfully
Changing the user information for Ramesh
Enter the new value, or press ENTER for the default
  Full Name []: Ramesh Yadav
  Room Number []: 1
  Work Phone []: 28384585869
  Home Phone []: 98325752909
  Other []:
Is the information correct? [Y/n] y
```

To verify whether the user has been created successfully, follow the steps below :
here in the we can see the user (Ramesh)

```

root@ip-172-31-25-7:/home/ubuntu# cat /etc/passwd
root:x:0:0:root:/root:/bin/bash
daemon:x:1:1:daemon:/usr/sbin:/usr/sbin/nologin
bin:x:2:2:bin:/bin:/usr/sbin/nologin
sys:x:3:3:sys:/dev:/usr/sbin/nologin
sync:x:4:65534:sync:/bin:/bin/sync
games:x:5:60:games:/usr/games:/usr/sbin/nologin
man:x:6:12:man:/var/cache/man:/usr/sbin/nologin
lp:x:7:7:lp:/var/spool/lpd:/usr/sbin/nologin
mail:x:8:8:mail:/var/mail:/usr/sbin/nologin
news:x:9:9:news:/var/spool/news:/usr/sbin/nologin
uucp:x:10:10:uucp:/var/spool/uucp:/usr/sbin/nologin
proxy:x:13:13:proxy:/bin:/usr/sbin/nologin
www-data:x:33:33:www-data:/var/www:/usr/sbin/nologin
backup:x:34:34:backup:/var/backups:/usr/sbin/nologin
list:x:38:38:Mailing List Manager:/var/list:/usr/sbin/nologin
irc:x:39:39:ircd:/run/ircd:/usr/sbin/nologin
_apt:x:42:65534::/nonexistent:/usr/sbin/nologin
nobody:x:65534:65534:nobody:/nonexistent:/usr/sbin/nologin
systemd-network:x:998:998:systemd Network Management:/:/usr/sbin/nologin
dhcpcd:x:996:996:DHCP Client Daemon:/usr/lib/dhcpcd:/bin/false
messagebus:x:995:995:System Message Bus:/nonexistent:/usr/sbin/nologin
syslog:x:100:101::/nonexistent:/usr/sbin/nologin
systemd-resolve:x:989:989:systemd Resolver:/:/usr/sbin/nologin
_chrony:x:988:988:Chrony Daemon:/var/lib/chrony:/usr/sbin/nologin
tss:x:987:987:tss user for tpm2:/:/usr/sbin/nologin
uuidd:x:101:103::/run/uuidd:/usr/sbin/nologin
sshd:x:986:65534:sshd user:/run/sshd:/usr/sbin/nologin
pollinate:x:102:1::/var/cache/pollinate:/bin/false
tcpdump:x:985:985:tcpdump:/nonexistent:/usr/sbin/nologin
landscape:x:103:106::/var/lib/landscape:/usr/sbin/nologin
fwupd-refresh:x:984:984:Firmware update daemon:/var/lib/fwupd:/usr/sbin/nologin
polkitd:x:983:983:User for polkitd:/:/usr/sbin/nologin
ec2-instance-connect:x:104:65534:/nonexistent:/usr/sbin/nologin
ubuntu:x:1000:1000:Ubuntu:/home/ubuntu:/bin/bash
devopsuser:x:1001:1001:Devops Engineer,1,3459u395738957734,3874365423:/home/devopsuser:/bin/bash
Ramesh:x:1002:1002:Ramesh Yadav,1,28384585869,98325752909:/home/Ramesh:/bin/bash
root@ip-172-31-25-7:/home/ubuntu#

```

Now the user is created we will check now the user able to login into the server or not.

```

PS C:\Users\ramee\Downloads> ssh Ramesh@51.20.250.128
Ramesh@51.20.250.128: Permission denied (publickey).
PS C:\Users\ramee\Downloads> ssh Ramesh@51.20.250.128
Ramesh@51.20.250.128: Permission denied (publickey).
PS C:\Users\ramee\Downloads> ssh Ramesh@51.20.250.128
Ramesh@51.20.250.128: Permission denied (publickey).
PS C:\Users\ramee\Downloads>

```

After creating the user also I am not able to login into the system.

So will check what happening here the password authentication is enable or not

the main configuration file path /etc/ssh/sshd_config

here I have changed PasswordAuthentication yes then also I am not able to connecting the servers.

```

root@ip-172-31-25-7:/home/ubuntu# grep "PasswordAuthentication" /etc/ssh/sshd_config
PasswordAuthentication yes
# PasswordAuthentication. Depending on your PAM configuration,
# PAM authentication, then enable this but set PasswordAuthentication
root@ip-172-31-25-7:/home/ubuntu#

```

Even after turning on passwords in the main file, login still failed. This is because AWS reads the extra file (60-cloudimg-settings.conf) last, which completely blocks passwords and overrides our changes.

Restarted the sshd service.

```

root@ip-172-31-25-7:/home/ubuntu#
root@ip-172-31-25-7:/home/ubuntu# vim /etc/ssh/sshd_config.d/60-cloudimg-settings.conf
root@ip-172-31-25-7:/home/ubuntu#
root@ip-172-31-25-7:/home/ubuntu# cat /etc/ssh/sshd_config.d/60-cloudimg-settings.conf
PasswordAuthentication yes
root@ip-172-31-25-7:/home/ubuntu#
root@ip-172-31-25-7:/home/ubuntu#
root@ip-172-31-25-7:/home/ubuntu# sudo systemctl restart sshd
root@ip-172-31-25-7:/home/ubuntu#

```

Now I am able to connect the server.

```
PS C:\Users\ramee\Downloads>
PS C:\Users\ramee\Downloads> ssh Ramesh@51.20.250.128
Ramesh@51.20.250.128's password:
Welcome to Ubuntu 26.04 LTS (GNU/Linux 7.0.0-1004-aws x86_64)

 * Documentation:  https://docs.ubuntu.com
 * Management:    https://landscape.canonical.com
 * Support:       https://ubuntu.com/pro

System information as of Tue Jun  9 06:02:57 UTC 2026

System load:  0.08               Temperature:   -273.1 C
Usage of /:   18.5% of 13.40GB    Processes:    150
Memory usage: 17%               Users logged in: 0
Swap usage:   0%                IPv4 address for ens5: 172.31.25.7

 * Ubuntu Pro delivers the most comprehensive open source security and
  compliance features.

  https://ubuntu.com/aws/pro

Expanded Security Maintenance for Applications is not enabled.

49 updates can be applied immediately.
44 of these updates are standard security updates.
To see these additional updates run: apt list --upgradable

Enable ESM Apps to receive additional future security updates.
See https://ubuntu.com/esm or run: sudo pro status

The programs included with the Ubuntu system are free software;
the exact distribution terms for each program are described in the
individual files in /usr/share/doc/*/copyright.

Ubuntu comes with ABSOLUTELY NO WARRANTY, to the extent permitted by
applicable law.

Ramesh@ip-172-31-25-7:~$ |
```

Group Management

=====

Now, I will create groups and add users to those groups.

To create the groups, use the following commands:

CMD: sudo groupadd developer

CMD: sudo groupadd testing

```
root@ip-172-31-25-7:/home/ubuntu# sudo groupadd developer
root@ip-172-31-25-7:/home/ubuntu# sudo groupadd testing
```

Next, I created two users:

- **dev1** (Developer)
- **tester1** (Tester)

```
root@ip-172-31-25-7:/home/ubuntu# adduser Tester1
New password:
Retype new password:
passwd: password updated successfully
Changing the user information for Tester1
Enter the new value, or press ENTER for the default
  Full Name []:
  Room Number []:
  Work Phone []:
  Home Phone []:
  Other []:
Is the information correct? [Y/n] y
root@ip-172-31-25-7:/home/ubuntu# useradd Tester2
root@ip-172-31-25-7:/home/ubuntu# useradd Tester3
root@ip-172-31-25-7:/home/ubuntu# useradd Tester4
root@ip-172-31-25-7:/home/ubuntu# useradd Tester5
root@ip-172-31-25-7:/home/ubuntu# adduser dev1
```

```

root@ip-172-31-25-7:/home/ubuntu# adduser dev1
New password:
Retype new password:
passwd: password updated successfully
Changing the user information for dev1
Enter the new value, or press ENTER for the default
  Full Name []:
  Room Number []:
  Work Phone []:
  Home Phone []:
  Other []:
Is the information correct? [Y/n] y
root@ip-172-31-25-7:/home/ubuntu# useradd dev2
root@ip-172-31-25-7:/home/ubuntu# useradd dev3
root@ip-172-31-25-7:/home/ubuntu# useradd dev4
root@ip-172-31-25-7:/home/ubuntu# useradd dev5

```

After creating the users, I added them to their respective groups using the following command:

CMD: `usermod -aG <group name> (username).`

```

root@ip-172-31-25-7:/home/ubuntu# usermod -aG testing Tester1
root@ip-172-31-25-7:/home/ubuntu# usermod -aG testing Tester2
root@ip-172-31-25-7:/home/ubuntu# usermod -aG testing Tester3
root@ip-172-31-25-7:/home/ubuntu# usermod -aG testing Tester4
root@ip-172-31-25-7:/home/ubuntu# usermod -aG testing Tester5
root@ip-172-31-25-7:/home/ubuntu# usermod -aG developer dev1
root@ip-172-31-25-7:/home/ubuntu# usermod -aG developer dev2
root@ip-172-31-25-7:/home/ubuntu# usermod -aG developer dev3
root@ip-172-31-25-7:/home/ubuntu# usermod -aG developer dev4
root@ip-172-31-25-7:/home/ubuntu# usermod -aG developer dev5

```

To verify whether the user has been added to the group, use:

CMD: `getent group testing`

The **getent** command stands for **Get Entries**. It is used to retrieve user and group information from the Linux system.

```

root@ip-172-31-25-7:/home/ubuntu# getent group testing
testing:x:1014:Tester1,Tester2,Tester3,Tester4,Tester5
root@ip-172-31-25-7:/home/ubuntu# grep testing /etc/group
testing:x:1014:Tester1,Tester2,Tester3,Tester4,Tester5

```

Now we need to create some folders under the root user and we will give the permission to group and check this working properly or not

To Create Directory use the below command.

CMD: `mkdir /dev-Team`

CMD: `mkdir /Testing-Team`

CMD: `touch /dev-Team/dev.txt` --- here we creating the file use touch command.

CMD: `chown root:developer /dev-Team/` -here we are adding the group to this directory

CMD: `chmod 770 /dev-Team/` ---- here we are giving the permissions all members of that group can read, write, and access it.

```

root@ip-172-31-25-7:/home/ubuntu#
root@ip-172-31-25-7:/home/ubuntu# chown root:developer /dev-Team
root@ip-172-31-25-7:/home/ubuntu# chmod 770 /dev-Team
root@ip-172-31-25-7:/home/ubuntu#
root@ip-172-31-25-7:/home/ubuntu#
root@ip-172-31-25-7:/home/ubuntu# ls -ld /dev-Team
drwxrwx--- 2 root developer 4096 Jun  9 12:19 /dev-Team
root@ip-172-31-25-7:/home/ubuntu# |

```

This all things I have done in the root user.

Now I am login to the dev1 user there I will create the file. We will see the Tester1 user able access the file editable or not we will check.

Here i have created the file in the added the content in the file.

```

Enable ESM Apps to receive additional future security updates.
See https://ubuntu.com/esm or run: sudo pro status

```

```

*** System restart required ***
Last login: Tue Jun  9 12:17:13 2026 from 103.160.27.107
dev1@ip-172-31-25-7:~$
dev1@ip-172-31-25-7:~$
dev1@ip-172-31-25-7:~$
dev1@ip-172-31-25-7:~$ whoami
dev1
dev1@ip-172-31-25-7:~$ vim /dev-Team/dev.txt
dev1@ip-172-31-25-7:~$
dev1@ip-172-31-25-7:~$ cat /dev-Team/dev.txt
this file only access dev team only.
dev1@ip-172-31-25-7:~$ ls -lrth /dev-Team/dev.txt
-rw-rw-r-- 1 dev1 dev1 37 Jun  9 12:19 /dev-Team/dev.txt
dev1@ip-172-31-25-7:~$ |

```

Now I will login into the Tester1 user we will see I am able access the file or editable or not. Here I am not able access not editable.

```

*** System restart required ***
Last login: Tue Jun  9 11:52:08 2026 from 103.160.27.107
Tester1@ip-172-31-25-7:~$ ls -lrth /dev-Team/
ls: cannot open directory '/dev-Team/': Permission denied
Tester1@ip-172-31-25-7:~$ vim /dev-Team/dev.txt
Tester1@ip-172-31-25-7:~$
Tester1@ip-172-31-25-7:~$
Tester1@ip-172-31-25-7:~$ |

```

Now we will set the password for user.

Password expiration: Set password expiry days for the specific user.

=====

chage = Change Age (used to manage password aging policies)

-M = Maximum number of days a password can be used

90 = Password will expire after 90 days

dev1 = Username

CMD: chage -M 90 dev1

```
ubuntu@ip-172-31-25-7:~$ sudo su
root@ip-172-31-25-7:/home/ubuntu# chage -l dev1
Last password change                    : Jun 09, 2026
Password expires                        : never
Password inactive                       : never
Account expires                         : never
Minimum number of days between password change : 0
Maximum number of days between password change : 99999
Number of days of warning before password expires : 7
root@ip-172-31-25-7:/home/ubuntu#
root@ip-172-31-25-7:/home/ubuntu#
root@ip-172-31-25-7:/home/ubuntu#
root@ip-172-31-25-7:/home/ubuntu# chage -M 90 dev1
root@ip-172-31-25-7:/home/ubuntu#
root@ip-172-31-25-7:/home/ubuntu#
root@ip-172-31-25-7:/home/ubuntu# chage -l dev1
Last password change                    : Jun 09, 2026
Password expires                        : Sep 07, 2026
Password inactive                       : never
Account expires                         : never
Minimum number of days between password change : 0
Maximum number of days between password change : 90
Number of days of warning before password expires : 7
root@ip-172-31-25-7:/home/ubuntu# |
```

Lock a user account:

=====

To temporarily block a user's login access, lock the user account using the following command:

passwd -l dev1

```
ubuntu@ip-172-31-25-7:~$ sudo su
root@ip-172-31-25-7:/home/ubuntu# passwd -l dev1
passwd: password changed.
root@ip-172-31-25-7:/home/ubuntu# |
```

now I am trying to login into the server. It's not possible.

```
PS C:\Users\ramee\Downloads> ssh dev1@51.20.250.128
dev1@51.20.250.128's password:
Permission denied, please try again.
dev1@51.20.250.128's password:
Permission denied, please try again.
dev1@51.20.250.128's password: |
```

This command locks the user's password and prevents them from logging in to the server.

Once we locked the user in the /etc/shadow file.

Notice the ! added at the beginning of the password hash. This indicates the account password is locked.

```
root@ip-172-31-25-7:/home/ubuntu# grep dev1 /etc/shadow
dev1:!!$y$j9T$I50Tm.2YuSMg25fPAnFw/.$JqIMzWjICfk/QnLHFyjj74gODgqTVdpDByEODCpUqmD:20613:0:90:7:::
root@ip-172-31-25-7:/home/ubuntu# grep dev1 /etc/Tester1
grep: /etc/Tester1: No such file or directory
root@ip-172-31-25-7:/home/ubuntu# grep Tester1 /etc/shadow
Tester1:$y$j9T$GP8pwz3UZGCPTE4z3gQN/$80Me87VyA418P.bv..tGUKds7gt9RABdEtOcbfvVysC:20613:0:99999:7:::
root@ip-172-31-25-7:/home/ubuntu# |
```

The Test use not have ! at the beginning of the password hash.

Unlock a user account

=====

here -u means unlock

here we are unlock the use dev1. **The ! also gone . please**

```
root@ip-172-31-25-7:/home/ubuntu# passwd -u dev1
passwd: password changed.
root@ip-172-31-25-7:/home/ubuntu# grep dev1 /etc/shadow
dev1:$y$j9T$I50Tm.2YuSMg25fPAnFw/.$JqIMzWjICfk/QnLHFyfy74g0DgqTVdpDByEODCpUqmD:20613:0:90:7:::
root@ip-172-31-25-7:/home/ubuntu# |
```

Now I am able to login in to the server.

```
PS C:\Users\Ramesh\Downloads> ssh dev1@51.20.250.128
dev1@51.20.250.128's password:
Welcome to Ubuntu 26.04 LTS (GNU/Linux 7.0.0-1004-aws x86_64)

 * Documentation:  https://docs.ubuntu.com
 * Management:    https://landscape.canonical.com
 * Support:       https://ubuntu.com/pro

System information as of Tue Jun  9 14:33:57 UTC 2026

   System load:  0.0           Temperature:   -273.1 C
   Usage of /:   19.5% of 13.40GB   Processes:    196
   Memory usage: 25%           Users logged in: 0
   Swap usage:  0%             IPv4 address for ens5: 172.31.25.7

 * Ubuntu Pro delivers the most comprehensive open source security and
   compliance features.
   https://ubuntu.com/aws/pro

Expanded Security Maintenance for Applications is not enabled.

3 updates can be applied immediately.
To see these additional updates run: apt list --upgradable
Enable ESM Apps to receive additional future security updates.
See https://ubuntu.com/esm or run: sudo pro status

*** System restart required ***
Last login: Tue Jun  9 12:44:39 2026 from 103.160.27.107
dev1@ip-172-31-25-7:~$ |
```

To Delete the user use the below command.

CMD: userdel <username> --- the command delete the user and keep their home folder.

Now we are able to see the user Ramesh.

```
root@ip-172-31-25-7:/home/ubuntu# cat /etc/passwd
root:x:0:0:root:/root:/bin/bash
daemon:x:1:1:daemon:/usr/sbin:/usr/sbin/nologin
bin:x:2:2:bin:/bin:/usr/sbin/nologin
sys:x:3:3:sys:/dev:/usr/sbin/nologin
sync:x:4:65534:sync:/bin:/bin/sync
games:x:5:60:games:/usr/games:/usr/sbin/nologin
man:x:6:12:man:/var/cache/man:/usr/sbin/nologin
lp:x:7:7:lp:/var/spool/lpd:/usr/sbin/nologin
mail:x:8:8:mail:/var/mail:/usr/sbin/nologin
news:x:9:9:news:/var/spool/news:/usr/sbin/nologin
uucp:x:10:10:uucp:/var/spool/uucp:/usr/sbin/nologin
proxy:x:13:13:proxy:/bin:/usr/sbin/nologin
www-data:x:33:33:www-data:/var/www:/usr/sbin/nologin
backup:x:34:34:backup:/var/backups:/usr/sbin/nologin
list:x:38:38:Mailing List Manager:/var/list:/usr/sbin/nologin
irc:x:39:39:ircd:/run/ircd:/usr/sbin/nologin
_apt:x:42:65534::/nonexistent:/usr/sbin/nologin
nobody:x:65534:65534:nobody:/nonexistent:/usr/sbin/nologin
systemd-network:x:998:998:systemd Network Management:/usr/sbin/nologin
dhcpcd:x:996:996:DHCP Client Daemon:/usr/lib/dhcpcd/bin/false
messagebus:x:995:995:System Message Bus:/nonexistent:/usr/sbin/nologin
syslog:x:100:101::/nonexistent:/usr/sbin/nologin
systemd-resolve:x:989:989:systemd Resolver:/usr/sbin/nologin
_chrony:x:988:988:Chrony Daemon:/var/lib/chrony:/usr/sbin/nologin
tss:x:987:987:tss user for tpm2:/usr/sbin/nologin
uuid:x:101:103:/run/uuid:/usr/sbin/nologin
sshd:x:986:65534:sshd user:/run/sshd:/usr/sbin/nologin
pollinate:x:102:1:/var/cache/pollinate:/bin/false
tcpdump:x:985:985:tcpdump:/nonexistent:/usr/sbin/nologin
landscape:x:103:106:/var/lib/landscape:/usr/sbin/nologin
fwupd-refresh:x:984:984:Firmware update daemon:/var/lib/fwupd:/usr/sbin/nologin
polkitd:x:983:983:User for polkitd:/usr/sbin/nologin
ec2-instance-connect:x:104:65534:/nonexistent:/usr/sbin/nologin
ubuntu:x:1000:1000:Ubuntu:/home/ubuntu:/bin/bash
devopsuser:x:1001:1001:Devops Engineer,1,3459u395738957734,3874365423:/home/devopsuser:/bin/bash
Ramesh:x:1002:1002:Ramesh Yadav,1,28384585869,98325752909:/home/Ramesh:/bin/bash
Tester1:x:1003:1003:::/home/Tester1:/bin/bash
Tester2:x:1004:1004:/home/Tester2:/bin/sh
Tester3:x:1005:1005:/home/Tester3:/bin/sh
Tester4:x:1006:1006:/home/Tester4:/bin/sh
```

After running the command, the user account is removed from the system.

```
root@ip-172-31-25-7:/home/ubuntu# userdel Ramesh
root@ip-172-31-25-7:/home/ubuntu# cat /etc/passwd
root:x:0:0:root:/root:/bin/bash
daemon:x:1:1:daemon:/usr/sbin:/usr/sbin/nologin
bin:x:2:2:bin:/bin:/usr/sbin/nologin
sys:x:3:3:sys:/dev:/usr/sbin/nologin
sync:x:4:65534:sync:/bin:/bin/sync
games:x:5:60:games:/usr/games:/usr/sbin/nologin
man:x:6:12:man:/var/cache/man:/usr/sbin/nologin
lp:x:7:7:lp:/var/spool/lpd:/usr/sbin/nologin
mail:x:8:8:mail:/var/mail:/usr/sbin/nologin
news:x:9:9:news:/var/spool/news:/usr/sbin/nologin
uucp:x:10:10:uucp:/var/spool/uucp:/usr/sbin/nologin
proxy:x:13:13:proxy:/bin:/usr/sbin/nologin
www-data:x:33:33:www-data:/var/www:/usr/sbin/nologin
backup:x:34:34:backup:/var/backups:/usr/sbin/nologin
list:x:38:38:Mailing List Manager:/var/list:/usr/sbin/nologin
irc:x:39:39:ircd:/run/ircd:/usr/sbin/nologin
_apt:x:42:65534:/:nonexistent:/usr/sbin/nologin
nobody:x:65534:65534:nobody:/nonexistent:/usr/sbin/nologin
systemd-network:x:998:998:systemd Network Management:/:/usr/sbin/nologin
dhcpcd:x:996:996:DHCP Client Daemon:/usr/lib/dhcpcd:/bin/false
messagebus:x:995:995:System Message Bus:/nonexistent:/usr/sbin/nologin
syslog:x:100:101:/:nonexistent:/usr/sbin/nologin
systemd-resolve:x:989:989:systemd Resolver:/:/usr/sbin/nologin
_chrony:x:988:988:Chrony Daemon:/var/lib/chrony:/usr/sbin/nologin
tss:x:987:987:tss user for tpm2:/:/usr/sbin/nologin
uidd:x:101:103:/:run/uidd:/usr/sbin/nologin
shd:x:986:65534:shd user:/run/shd:/usr/sbin/nologin
pollinate:x:102:1:/:var/cache/pollinate:/bin/false
tcpdump:x:985:985:tcpdump:/nonexistent:/usr/sbin/nologin
landscape:x:103:106:/:var/lib/landscape:/usr/sbin/nologin
fwupd-refresh:x:984:984:Firmware update daemon:/var/lib/fwupd:/usr/sbin/nologin
polkitd:x:983:983:User for polkitd:/:/usr/sbin/nologin
ec2-instance-connect:x:104:65534:/:nonexistent:/usr/sbin/nologin
ubuntu:x:1000:1000:Ubuntu:/home/ubuntu:/bin/bash
devopsuser:x:1001:1001:Devops Engineer, 1, 3459u395738957734, 3874365423:/home/devopsuser:/bin/bash
Tester1:x:1003:1003:,,,:/home/Tester1:/bin/bash
Tester2:x:1004:1004:/:/home/Tester2:/bin/sh
Tester3:x:1005:1005:/:/home/Tester3:/bin/sh
Tester4:x:1006:1006:/:/home/Tester4:/bin/sh
```

However, the user's home directory is still available.

If you also want to remove the user's home directory, use the following command:

CMD: `userdel -r <username>`

The **-r** option deletes both the user account and the user's home directory.

```
root@ip-172-31-25-7:/home/ubuntu# ls -lrth /home/
total 20K
drwxr-x--- 4 ubuntu      ubuntu      4.0K Jun  8 13:51 ubuntu
drwxr-x--- 3 1002        1002        4.0K Jun  9 07:48 Ramesh
drwxr-x--- 3 devopsuser  devopsuser  4.0K Jun  9 07:53 devopsuser
drwxr-x--- 3 1003        1003        4.0K Jun  9 12:53 Tester1
drwxr-x--- 3 dev1        dev1        4.0K Jun  9 14:00 dev1
root@ip-172-31-25-7:/home/ubuntu# userdel -r dev1
userdel: dev1 mail spool (/var/mail/dev1) not found
root@ip-172-31-25-7:/home/ubuntu# ls -lrth /home/
total 16K
drwxr-x--- 4 ubuntu      ubuntu      4.0K Jun  8 13:51 ubuntu
drwxr-x--- 3 1002        1002        4.0K Jun  9 07:48 Ramesh
drwxr-x--- 3 devopsuser  devopsuser  4.0K Jun  9 07:53 devopsuser
drwxr-x--- 3 1003        1003        4.0K Jun  9 12:53 Tester1
root@ip-172-31-25-7:/home/ubuntu#
```