

Data Schema Reference

Each division's data lives in `data/division-{a..k}.js`. The file declares a set of `const` global variables prefixed with `DIV_X_` (e.g. `DIV_C_PLAYERS`). All globals are loaded into the page via `<script>` tags in `index.html`.

Common structures (all 11 divisions)

DIV_X_TEAMS

Array of team objects.

```
const DIV_C_TEAMS = [
  { short:'SVG-C', full:'SVG TENNIS CLUB - C', captain:'Nagendran K', club:'SVG', players:
    ...
  ];
```

Field	Type	Notes
<code>short</code>	string	Custom short code (see below)
<code>full</code>	string	Full team name as on league.cdta.co.in
<code>captain</code>	string	Captain's display name
<code>club</code>	string	Parent club name
<code>players</code>	number	Roster size

DIV_X_PLAYERS

Array of player objects.

```
{ name:'Nagendran K', team:'SVG-C', gender:'M', age:45, role:'Captain',
  gamesPlayed:null, wins:null, photo:'photos/div-c/svg-c/nagendran-k.jpg' }
```

Field	Type	Notes
<code>name</code>	string	Display name (Title Case)
<code>team</code>	string	Must match a <code>DIV_X_TEAMS[].short</code>
<code>gender</code>	<code>'M' 'F' null</code>	
<code>age</code>	number null	
<code>role</code>	<code>'Captain' 'Player'</code>	
<code>gamesPlayed</code>	number null	Recomputed at runtime for C/F/H/I

Field	Type	Notes
wins	number null	Recomputed at runtime for C/F/H/I
photo	string	Relative path to JPG/PNG

Important: gamesPlayed and wins may be null in the file. The render layer for divisions C/F/H/I calls recomputeDivStats() which derives them from DIV_X_SCHEDULE. Do **not** rely on the file values.

DIV_X_STANDINGS

Pre-computed standings table (one row per team).

```
{ rank:1, short:'PSG-C', full:'PSG SPORTS CLUB - C', pts:24, played:30,
  setsW:48, setsL:18, gamesW:312, gamesL:215 }
```

Field	Type	Notes
rank	number	1-based
short / full	string	
pts	number	League points earned
played	number	Courts played (= max possible pts). Exception: Div K stores matches , not courts
setsW / setsL	number	Set wins / losses
gamesW / gamesL	number	Game wins / losses

DIV_X_SCHEDULE

Week-by-week match data including court-level player pairings — the **authoritative source of truth** for player stats.

```
const DIV_C_SCHEDULE = [
  { week:1, date:'24-25 Jan 2026', done:true, matches:[
    { home:'PROSCHOOL - B', score:'2-1', away:'CMTA - C', venue:'',
      courts:[
        { ct:1, home:'Riyas / Arun Karthik', away:'Manikandan K / NITHISH',
          sets:'6-2, 6-0', win:'home' },
        ...
      ]},
    ...
  ]},
  ...
];
```

Field	Type	Notes
week	number	1-indexed
date	string	Free-text date label
done	boolean	true if results are in
matches[]	array	One per fixture
matches[].home / away	string	Full team name
matches[].score	string	e.g. '2-1' (in courts won)
matches[].courts[]	array	Always 3 entries (3 doubles per match)
courts[].ct	number	Court number (1, 2, or 3)
courts[].home / away	string	Two player names separated by /
courts[].sets	string	e.g. '6-2, 6-0'
courts[].win	'home' 'away'	Which side won the court

Manual-division-only structures (C, F, H, I)

These four divisions started life as hand-curated data and retain extra fields for projections and key analytics.

DIV_X_PROJECTIONS

Projected final standings (synced with actuals once season ends).

```
{ rank:1, short:'PSG-C', full:'PSG SPORTS CLUB - C', currentPts:24, projectedPts:24, ch
```

DIV_X_PROJ_BREAKDOWN

Per-team projection breakdown for upcoming weeks. **Empty** when the season is complete.

```
{ team:'PSG-C', remainingMatches:[ { week:11, opponent:'TIR-C', expected:2 }, ... ] }
```

DIV_X_KEY_PAIRS

"Most active doubles pairs" — top doubles partnerships by court appearances.

```
{ pair:'Gowtham V / V. Yaswanth', team:'FMP-C', apps:7, wins:null }
```

Field	Type	Notes
pair	string	"Player A / Player B"

Field	Type	Notes
<code>team</code>	string	Their team's short code
<code>apps</code>	number	Court appearances together
<code>wins</code>	number null	Recomputed at runtime

`DIV_X_PARTNERS`

Per-player list of partners and counts. Object keyed by player display name.

```
const DIV_C_PARTNERS = {
  'Ganesan S': [['Madhan Kumar P',4],['Shravan Krishnan G',1]],
  'Madhan Kumar P': [['Ganesan S',4],['Keerthan Kumar B',2]],
  ...
};
```

Note: This entire object is **rebuilt at runtime** by `recomputeDivStats()` . The static values in the file are placeholders; only the keys (player names) need to be present so the runtime can match them.

`DIV_X_TEAM_INFO` (some divisions only)

Extra metadata per team — court venues, contact, etc. Free-form.

Custom team short codes (manual divisions)

Manual divisions use opinionated short codes to fit in the standings table. The codes are **NOT** scraped — they are hand-assigned and used everywhere as the join key (`DIV_X_PLAYERS.team` → `DIV_X_TEAMS.short`).

Div C	Div F	Div H	Div I
PSG-C, FMP-C, SNS-A, TIR-C, PRO-C, ANU-C, SVG-C, CMT-C, COS-C, GPT-C, LIF-C	GNEST, ACES, CCTA, ALPHA, SNS, MAP, CSA, CASA, TIR, ALV, CMTA	SNS-D, PSG, ANU-B, RSP, GPTC-C, ANNUR, ACTC-B, TIR-B, KGR-D, FALCON, CSA	SATCH, TTOTS, STARS, RAIL, CBE, TGLO, SNS, GNEST, CHAMPS, SAI, KING

Photo paths

```
photos/div-{a..k}/{team-short-lower}/{player-name-slug}.{jpg|jpeg|png}
```

- `team-short-lower` is the `short` field lowercased (e.g. `svg-c`)
- `player-name-slug` is the player name lowercased with non-alphanumerics replaced by `-`
- Examples:

- `photos/div-c/svg-c/nagendran-k.jpg`
- `photos/div-i/stars/akilan-ramesh.jpeg`

If a photo is missing the row's `<img onerror>` hides it gracefully.

"Courts vs matches" gotcha

Division	What played means in STANDINGS
A, B, C, D, E, F, G, H, I, J	Courts played (matches × 3)
K	Matches played (not courts)

The render functions compensate, so the UI always shows `Played Pts (matches)` correctly. If you ever change a render function, copy the pattern from an existing one.

Adding a new player manually

1. Find the team's short code
2. Append to `DIV_X_PLAYERS` with `gamesPlayed:null`, `wins:null` (the recomputer will fill them)
3. Add the photo file at the correct path
4. Reload — that's it. No other field needs editing.

Adding a new match result manually

1. Find the right `DIV_X_SCHEDULE[wk]` entry
2. Add the match object with all 3 courts and `win` set on each
3. Update `DIV_X_STANDINGS` rows for both teams (rank, pts, played, setsW/L, gamesW/L)
4. Reload — player stats and partners auto-recompute