

Functional Spec

Functional Specification

Purpose

The CDTA 2026 Dashboard is a single-page web application that displays the complete state of the **Coimbatore District Tennis Association 2026 League** — a doubles tennis league with 11 divisions (A–K).

It is the public-facing read view, the captains' planning tool, and the admin's operational console.

Users and roles

Role	Sees	Typical user
	---	---
admin	All 11 divisions + Overview + SVG Players + Admin tab	League secretary
captain	All 11 divisions + Overview + SVG Players	Team captains
svgplayer	All 11 divisions + Overview + SVG Players	SVG club members
viewer	All 11 divisions + Overview + SVG Players	Anyone with the link

Only `admin` sees the **Admin** tab. All other roles see the same content but with no admin features.

Authentication is local to `data/auth.js` (no server session). On successful login the role and user info are stored in `localStorage`.

Page inventory

Per division (A through K) — 5 sub-tabs each

Sub-tab	Content

Standings	Final ranks, courts played, points, sets W/L, games W/L, win %

Projection	(Manual divisions C/F/H/I only) — projected final position
Schedule	Week-by-week fixtures with court-level player pairings & set scores
Results	Match-by-match results, filterable by week and team
Players	Roster with photo, role, played courts, wins/losses, win %, partners
Stats	(C/F/H/I) — Most Active Doubles Pairs, top performers
Teams	Team list with captain & player counts

Overview (top-level menu)

Consolidated dashboard:

- **Leaders** — top scorers across all divisions
- **All Teams** — every team across all 11 divisions
- **League Stats** — totals row (teams, players, matches, courts)

SVG Players (top-level menu)

Special club view focused on the SVG Tennis Club's three teams (SVG-C in Div C, plus STARS and SAI in Div I).
Sub-tabs:

- **Club Performance** (default)
- **Players**
- **Schedule**
- **Results**

Admin (admin role only) — 7 sub-tabs

Sub-tab	Purpose
User Management	Create / edit / delete users
Login History	Who logged in when
Usage Log	Page views per user
Activity Log	Mutations (data tool runs, etc.)
Test Plan	Embedded test checklist
Data Tools	Auto-fix stats, integrity check, refresh helpers
Settings	Total weeks, league name, photo paths, etc.

Key user flows

1. View standings (any user)

1. Login → land on Overview
2. Click **Div A** (or any letter A–K)
3. See **Standings** tab by default
4. Click any column header to sort

2. Inspect a player (any user)

1. Open a division → **Players** tab
2. Filter by team / search by name / filter by gender
3. Row shows: photo, name, team, gender, courts played, W/L, win %, partner pairings

3. Refresh data after a week (admin)

See ADMIN_RUNBOOK.md. High-level:

1. Run ``load-division`` skill (per division), or use **Data Tools → Auto Fix Stats**
2. Verify in app
3. Push to GitHub
4. Run ``deploy.bat`` to publish to GoDaddy

4. Add a new user (admin)

1. **Admin → User Management → + Add User**
2. Enter username, password, role, division (optional), team (optional)
3. Saved to ``data/auth.js`` via ``api/admin-data.php``

Display rules

Final Standings

- Section title: ``Division X — Final Standings`` (season is over)
- Header stat box: ``0 Weeks Remaining``
- Win % color: $\geq 80\%$ green, $\geq 50\%$ muted, $< 50\%$ red

Player Stats (auto-derived on init)

- ``gamesPlayed`` = court appearances (counted from ``DIV_X_SCHEDULE``)
- ``wins`` = court wins (winning side of each court)

- ``partners`` = list of ``[partner_name, count]`` per player, sorted desc
- ``KEY_PAIRS.wins`` = re-derived per pair
- Recomputation runs at page load — no manual maintenance

Manual vs scraped divisions

- **Scraped** (A, B, D, E, G, J, K) — data pulled from league.cdta.co.in via the ``/load-division`` skill
- **Manual** (C, F, H, I) — same base structures **plus**: ``PROJECTIONS``, ``PROJ_BREAKDOWN``, ``KEY_PAIRS``, ``PARTNERS``, ``TEAM_INFO``

Out of scope (intentional non-features)

- No write API for non-admin users
- No live score updates (data is refreshed weekly)
- No mobile app (responsive web only)
- No payment / registration / signup
- No multi-language support

Technical Spec

Technical Specification

Overview

CDTA 2026 Dashboard is a **single-page client-rendered web app** with no build step. It is plain HTML + vanilla JavaScript + CSS, served as static files from GoDaddy. A small PHP backend (``api/admin-data.php``) provides persistence for admin-modified data.

There is no framework, no bundler, and no transpiler. All logic lives in ``js/app.js`` (~5,200 lines).

Architecture

[illegible][illegible]

■ ■ (DOM shell) ■ ■ (globals) ■ ■ (renders DOM) ■ ■

[REDACTED] [REDACTED] [REDACTED]

■ ■ admin writes ■



[illegible]

■ ■ - read/write JSON state for admin features ■ ■

■ ■ - login history, usage log, settings, etc. ■ ■

[REDACTED]

[illegible]

Load order

1. `index.html` loads all 11 `data/division-{a..k}.js` files plus `data/auth.js` as `<script>` tags. Each file declares globals like `DIV_C_PLAYERS`, `DIV_C_SCHEDULE`, `DIV_C_PARTNERS`.
2. `js/app.js` runs after all data is loaded. It defines render functions and immediately calls them at the bottom of the file.
3. Each division has its own init block (`renderDivXStandings()`, `renderDivXTeams()`, etc.).

Key modules in `js/app.js`

Section	Lines (approx)	What it does
1	1-10	Imports necessary modules and sets up the environment.
2	11-20	Defines the main function and its arguments.
3	21-30	Initializes the data structures and variables.
4	31-40	Processes the input data and performs calculations.
5	41-50	Outputs the results and displays the final output.

|-|-|-|-

[Helpers \(`\\_esc`, `\\_standingRowClass`, etc.\)](#) | [top](#) | [Shared utilities](#) |

| Authentication & menu | 1-400 | Login, role enforcement, menu visibility |

| Division I (default) | 400–800 | The original division — ``renderStandings()``, ``renderPlayers()``, ``renderResults()``, etc. |

| Division C | 600–3000 | Manual division with projections, key pairs, partners |

```
| `recomputeDivStats()` | ~3070 | **Critical helper** — derives player stats from schedule courts |
```

| Divisions F, H | 3080–3700 | Manual divisions |

Divisions A, B, D, E, G, J, K	3700–4500	Scraped divisions (rendering only — data is pre-loaded)
Admin panel	1500–2700	User mgmt, logs, data tools, integrity check, auto-fix
Overview	900–1300	Cross-division consolidation
SVG Players club view	2900–3060	Special club view

The recompute pipeline (most important algorithm)

After a season refresh, the static ``gamesPlayed`` and ``wins`` fields in ``DIV_X_PLAYERS`` may be stale or ``null``. Rather than store these values, **they are derived at runtime** from the authoritative source — the per-court records in ``DIV_X_SCHEDULE``.

Function: ``recomputeDivStats(SCHEDULE, PLAYERS, PARTNERS, KEY_PAIRS?)``

Located in ``js/app.js``, called once per manual division (C, F, H, I) before any render.

Steps:

1. Build a name normalization map: ``normalize(name)`` → strip dots/commas/apostrophes, uppercase, collapse whitespace.
2. Build canonical name lookup: ``normalized`` → ``display_name`` from ``PLAYERS``.
3. Walk every ``SCHEDULE[]``.``matches[]``.``courts[]``:
 - Split ``home`` and ``away`` strings on ``/`` to get the two-player pair
 - For each player, increment ``played``; if their side won, increment ``wins``
 - Track partner counts: each player's other-side-of-the-slash partner gets ``+1``
 - Track pair stats keyed by sorted ``(p1|p2)`` tuple → ``{apps, wins}``
4. Assign ``gamesPlayed``/``wins`` back to ``PLAYERS`` items by normalized-name lookup
5. Rebuild ``PARTNERS`` object: for each player, list ``[partner_display, count]`` sorted desc
6. If ``KEY_PAIRS`` is provided: for each entry, parse ``pair`` string, look up in pair-stats, fill in ``apps`` and ``wins``

Name normalization rule

```
````javascript
norm(s) = s.toUpperCase()
 .replace(/[.,'"]/g, ' ') // strip punctuation
 .replace(/\s+/g, ' ') // collapse spaces
 .trim();
````
```

This handles cases like `J.SURESH KUMAR` (schedule) ↔ `J. Suresh Kumar` (roster) — both normalize to `J SURESH KUMAR`.

Standings calculation

Each division has its own `renderDiv{X}Standings()` function. The shared logic:

```
```javascript
const playedPts = s.played; // courts played = max possible pts
const matches = Math.floor(s.played / 3);
const ptsPct = Math.round((s.pts / playedPts) * 100);
```
```

****Exception — Division K:**** The K data file stores `played` as ****matches**** (not courts), because the season was scraped late and the source page exposes match counts only. Its render compensates:

```
```javascript
const matches = s.played;
const playedPts = s.played * 3;
```
```

Data flow for a weekly refresh

league.cdta.co.in

- (manual scrape via /load-division skill,
- or admin Data Tools → Auto Fix Stats)

▼

data/division-{a..k}.js ← regenerated, in courts

■

▼

git commit + push

■

▼

deploy.bat / deploy.ps1 ← FTP to GoDaddy



<http://akilanramesh.com/cdta/>

Admin persistence (server-side)

``api/admin-data.php`` is a single PHP endpoint storing JSON files on the GoDaddy server. It is called from the admin panel for:

- User management (``auth.json`` mirror)
- Login history append
- Usage log append
- Activity log append
- Settings updates

Auth in PHP is shared-secret based — only the admin role's session token can write.

Browser support

- Modern Chrome / Edge / Safari / Firefox
- Uses CSS Grid, Flexbox, ES2017+ (template literals, arrow functions, optional chaining)
- No polyfills, no IE support

Performance notes

- **Cold load**: ~1.5–3 MB JS payload (mostly the 11 division data files), no minification. Acceptable for an internal tool.
- **Photos**: lazy-loaded by browser; ~64 MB total but each `<img>` only fetches when visible.
- **No virtual DOM**: render functions rebuild ``innerHTML`` of their target table on every filter change. Tables max ~125 rows so this is fine.
- **Sorting**: in-place array sort, then full re-render.

Known technical debt

- A single 5,200-line `app.js` is hard to navigate. Future split could be by division.
- Several lint hints for unused variables (`totalPlayed`, `stand`, `teams`, etc.) — pre-existing, harmless.
- Player name normalization is rule-based; rare unicode names may slip through.
- No automated tests — only the manual Test Plan in the admin panel.

Data Schema

Data Schema Reference

Each division's data lives in `data/division-{a..k}.js`. The file declares a set of `const` global variables prefixed with `DIV\_X\_` (e.g. `DIV\_C\_PLAYERS`). All globals are loaded into the page via `

| `players` | number | Roster size |

`DIV\_X\_PLAYERS`

Array of player objects.

```
```javascript
```

```
{ name:'Nagendran K', team:'SVG-C', gender:'M', age:45, role:'Captain',
gamesPlayed:null, wins:null, photo:'photos/div-c/svg-c/nagendran-k.jpg' }
```

```
```
```

| Field | Type | Notes |

|---|---|---|

| `name` | string | Display name (Title Case) |

| `team` | string | Must match a `DIV\_X\_TEAMS[]` .short` |

| `gender` | `M` \| `F` \| `null` | |

| `age` | number \| null | |

| `role` | `Captain` \| `Player` | |

| `gamesPlayed` | number \| null | ****Recomputed at runtime**** for C/F/H/I |

| `wins` | number \| null | ****Recomputed at runtime**** for C/F/H/I |

| `photo` | string | Relative path to JPG/PNG |

> ****Important:**** `gamesPlayed` and `wins` may be `null` in the file. The render layer for divisions C/F/H/I calls `recomputeDivStats()` which derives them from `DIV\_X\_SCHEDULE`. Do ****not**** rely on the file values.

`DIV\_X\_STANDINGS`

Pre-computed standings table (one row per team).

```
```javascript
```

```
{ rank:1, short:'PSG-C', full:'PSG SPORTS CLUB - C', pts:24, played:30,
setsW:48, setsL:18, gamesW:312, gamesL:215 }
```

```
```
```

| Field | Type | Notes |

|---|---|---|

| `rank` | number | 1-based |

| `short` / `full` | string | |

| `pts` | number | League points earned |

| `played` | number | ****Courts played**** (= max possible pts). Exception: ****Div K stores matches****, not courts |

| `setsW` / `setsL` | number | Set wins / losses |
| `gamesW` / `gamesL` | number | Game wins / losses |

`DIV\_X\_SCHEDULE`

Week-by-week match data including court-level player pairings — the **authoritative source of truth** for player stats.

```
```javascript
const DIV_C_SCHEDULE = [
{ week:1, date:'24-25 Jan 2026', done:true, matches:[
{ home:'PROSCHOOL - B', score:'2-1', away:'CMTA - C', venue:",
courts:[
{ ct:1, home:'Riyas / Arun Karthik', away:'Manikandan K / NITHISH',
sets:'6-2, 6-0', win:'home' },
...
]},
...
]},
...
];
```
```

| Field | Type | Notes |
|---|---|---|
| `week` | number | 1-indexed |
| `date` | string | Free-text date label |
| `done` | boolean | true if results are in |
| `matches[]` | array | One per fixture |
| `matches[].home` / `away` | string | Full team name |
| `matches[].score` | string | e.g. `2-1` (in courts won) |
| `matches[].courts[]` | array | Always 3 entries (3 doubles per match) |
| `courts[].ct` | number | Court number (1, 2, or 3) |
| `courts[].home` / `away` | string | Two player names separated by `/` |
| `courts[].sets` | string | e.g. `6-2, 6-0` |
| `courts[].win` | `home` \| `away` | Which side won the court |

Manual-division-only structures (C, F, H, I)

These four divisions started life as hand-curated data and retain extra fields for projections and key analytics.

``DIV_X_PROJECTIONS``

Projected final standings (synced with actuals once season ends).

```
```javascript
{ rank:1, short:'PSG-C', full:'PSG SPORTS CLUB - C', currentPts:24, projectedPts:24, change:0 }
```
```

``DIV_X_PROJ_BREAKDOWN``

Per-team projection breakdown for upcoming weeks. ****Empty**** when the season is complete.

```
```javascript
{ team:'PSG-C', remainingMatches:[{ week:11, opponent:'TIR-C', expected:2 }, ...] }
```
```

``DIV_X_KEY_PAIRS``

"Most active doubles pairs" — top doubles partnerships by court appearances.

```
```javascript
{ pair:'Gowtham V / V. Yaswanth', team:'FMP-C', apps:7, wins:null }
```
```

| Field | Type | Notes |
|-------------|----------------|----------------------------------|
| --- --- --- | | |
| `pair` | string | ``"Player A / Player B"`` |
| `team` | string | Their team's short code |
| `apps` | number | Court appearances together |
| `wins` | number \ null | **Recomputed at runtime** |

``DIV_X_PARTNERS``

Per-player list of partners and counts. Object keyed by player display name.

```
```javascript
const DIV_C_PARTNERS = {
```

```
'Ganesan S': [['Madhan Kumar P',4],['Shravan Krishnan G',1]],
'Madhan Kumar P': [['Ganesan S',4],['Keerthan Kumar B',2]],
...
};
...
```

> **Note:** This entire object is **rebuilt at runtime** by ``recomputeDivStats()``. The static values in the file are placeholders; only the keys (player names) need to be present so the runtime can match them.

## **``DIV_X_TEAM_INFO`` (some divisions only)**

Extra metadata per team — court venues, contact, etc. Free-form.

---

## **Custom team short codes (manual divisions)**

Manual divisions use opinionated short codes to fit in the standings table. The codes are **NOT** scraped — they are hand-assigned and used everywhere as the join key (``DIV_X_PLAYERS.team`` → ``DIV_X_TEAMS.short``).

| Div C | Div F | Div H | Div I |

|---|---|---|---|

| PSG-C, FMP-C, SNS-A, TIR-C, PRO-C, ANU-C, SVG-C, CMT-C, COS-C, GPT-C, LIF-C | GNEST, ACES, CCTA, ALPHA, SNS, MAP, CSA, CASA, TIR, ALV, CMTA | SNS-D, PSG, ANU-B, RSP, GPTC-C, ANNUR, ACTC-B, TIR-B, KGR-D, FALCON, CSA | SATCH, TTOTS, STARS, RAIL, CBE, TGLO, SNS, GNEST, CHAMPS, SAI, KING |

---

## **Photo paths**

...

photos/div-`{a..k}`/`{team-short-lower}`/`{player-name-slug}`.`{jpg|jpeg|png}`

...

- ``team-short-lower`` is the ``short`` field lowercased (e.g. ``svg-c``)
- ``player-name-slug`` is the player name lowercased with non-alphanumerics replaced by ``-``
- Examples:
  - ``photos/div-c/svg-c/nagendran-k.jpg``
  - ``photos/div-i/stars/akilan-ramesh.jpeg``

If a photo is missing the row's ``<img onerror>`` hides it gracefully.

---

## "Courts vs matches" gotcha

| Division | What `played` means in `STANDINGS` |

|---|---|

| A, B, C, D, E, F, G, H, I, J | **Courts played** (matches × 3) |

| **K** | **Matches played** (not courts) |

The render functions compensate, so the UI always shows `Played Pts (matches)` correctly. If you ever change a render function, copy the pattern from an existing one.

---

## Adding a new player manually

1. Find the team's short code
2. Append to `DIV\_X\_PLAYERS` with `gamesPlayed:null, wins:null` (the recomputer will fill them)
3. Add the photo file at the correct path
4. Reload — that's it. No other field needs editing.

## Adding a new match result manually

1. Find the right `DIV\_X\_SCHEDULE[wk]` entry
2. Add the match object with all 3 courts and `win` set on each
3. Update `DIV\_X\_STANDINGS` rows for both teams (rank, pts, played, setsW/L, gamesW/L)
4. Reload — player stats and partners auto-recompute

---

## User Guide

---

## User Guide

This guide is organized by **role**. Find your role and read its section.

---

## Logging in

1. Open `http://akilanramesh.com/cdta/`
2. Enter your username and password
3. Click **Login**

Your session is remembered until you click **Logout** or clear browser data.

### *Default accounts*

Username	Password	Role	Division	Team
---	---	---	---	---
`rameshadmin`	`ramesh123`	admin	all	—
`ramesh`	`ramesh2026`	svgplayer	I	STARS
`monish`	`monish2026`	captain	I	STARS
`murugesan`	`murugesan2026`	captain	I	CHAMPS
`sethupathy`	`sethupathy2026`	captain	F	ACES
`nagendran`	`nagendran2026`	captain	C	SVG-C

Additional users can be created by an admin in **Admin → User Management**.

---

## Common features (all roles except admin extras)

After login you see a top navigation bar with:

...

Overview ■ SVG Players ■ Div A ■ Div B ■ Div C ■ ... ■ Div K ■ [Admin]

...

The **Admin** tab is only visible to the admin role.

### *Top-level menus*

- **Overview** — leaderboard across the whole league

- **Leaders** — top scorers / most active players
- **All Teams** — every team in every division
- **League Stats** — totals row (teams, players, matches, courts)
  - **SVG Players** — special view focused on SVG Tennis Club
- **Club Performance** — default landing
- **Players** / **Schedule** / **Results**
  - **Div A through Div K** — same 5 sub-tabs each:
- **Standings** — final ranks
- **Schedule** — week-by-week fixtures with courts
- **Results** — completed matches
- **Players** — roster with stats
- **Stats** — (C/F/H/I only) — Most Active Doubles Pairs

### ***How to find a player***

1. Click any **Div X** in the nav
2. Click **Players** sub-tab
3. Use the search box, team filter, or gender filter
4. The row shows: photo, name, team, courts played, wins/losses, win %, partners

### ***How to read the standings***

- **Played Pts** — max possible points (= courts played, since 1 pt per court)
- **Pts** — actual league points earned
- **Win %** —  $\text{Pts} \div \text{Played Pts} \times 100$
- **■** = champion, **■■** = runners-up, **■** = relegation zone

### ***Tennis terms***

- **Match** = team-vs-team fixture (e.g., "PSG-C 2-1 CMTA-C")
- **Court** = one of 3 doubles games inside a match
- **1 court won = 1 point**

---

## **Role: viewer**

Read-only access to all 11 divisions plus Overview and SVG Players. No write actions, no admin tab.

You can:



- Browse standings, schedules, results, players for any division
- Sort and filter
- View player photos and partner pairings

You cannot:

- Edit any data
- See login history or admin tools

---

## Role: svgplayer

Same as viewer, plus you appear in the **SVG Players** Club Performance view as your own profile (if your name matches a player in the SVG club).

---

## Role: captain

Same as viewer. Captains have no special write permissions in the current build — captain accounts exist so future features (e.g., submitting scores, changing lineup) can be wired up without re-doing auth.

If your team's captain is listed in ``data/auth.js``, you can log in with the password assigned by the admin.

---

## Role: admin

Sees everything plus the **Admin** tab. Use the admin tab for all operational tasks.

### ***Admin sub-tabs***

Sub-tab	Use it for
---	---
<b>User Management</b>	Create, edit, or delete user logins. Set role, division, team.
<b>Login History</b>	Audit who logged in, when, and from where (best-effort)
<b>Usage Log</b>	Page view counts per user
<b>Activity Log</b>	Mutations: data tool runs, refresh actions, etc.
<b>Test Plan</b>	A checklist of manual smoke tests

| **Data Tools** | Auto Fix Stats, Integrity Check, refresh helpers (one button per division) |

| **Settings** | League name, total weeks, photo base path, etc. |

## **Common admin tasks**

- **Add a user**: Admin → User Management → + Add User → fill form → Save.
- **Run a data integrity check**: Admin → Data Tools → "Run Integrity Check" (scans for orphan players, mismatched teams, etc.)
- **Auto-fix stats after a refresh**: Admin → Data Tools → "Auto Fix Stats" (re-derives gamesPlayed/wins from schedule data — same logic that runs at page load)
- **Change league settings**: Admin → Settings → edit values → Save.

For full deployment and refresh procedures see [ADMIN\_RUNBOOK.md](ADMIN\_RUNBOOK.md).

---

# **Admin Runbook**

---

# **Admin Runbook**

Operational procedures for the CDTA 2026 Dashboard. Read top-to-bottom or jump to a specific task.

---

## **Weekly refresh (after match week ends)**

### ***For scraped divisions (A, B, D, E, G, J, K)***

1. Open Claude Code in the project directory: `cdta`
2. Run the custom skill: `/load-division X` (replace X with the letter)
3. The skill will:
  - Fetch the division page from `https://league.cda.co.in/`
  - Parse standings, players, schedules, results
  - Download any new photos to `photos/div-X/`
  - Update `data/division-X.js`
4. Reload the dashboard locally and spot-check the new week
5. Commit + push (see Git workflow below)

6. Deploy (see Deployment below)

### ***For manual divisions (C, F, H, I)***

These have hand-curated extras. After scraping the base data, you also need to:

- Refresh `DIV\_X\_PROJECTIONS` (if season ongoing)
- Verify `DIV\_X\_KEY\_PAIRS` still match top pairs
- Photos for new players

The recompute happens automatically — `gamesPlayed`, `wins`, and `PARTNERS` are derived from `DIV\_X\_SCHEDULE` on every page load. You don't need to update those by hand.

---

## **Adding a brand-new division**

Use the `/load-division` skill — it has a 10-step automated workflow. Located at `~/claude/skills/load-division.md`.

After running:

1. Add a new nav button entry in `index.html`
2. Add a new init block in `js/app.js` (copy from another scraped division)
3. Add a `

---

## Deployment

See [DEPLOYMENT.md](DEPLOYMENT.md) for the full FTP / GoDaddy procedure. Short version:

```
``bat
cd "c:\My Cloud\Google Drive\Claude\cdta"
deploy.bat

```

The script uses credentials from `deploy.env` (not committed). It will FTP all changed files to GoDaddy and report `Deploy complete! N files uploaded.`

**\*\*Always deploy explicitly\*\*** when the user says "deploy into godaddy". Never auto-deploy.

---

## Troubleshooting

### ***Player stats showing blank in Players page***

Cause: `recomputeDivStats()` did not run, or the player name in `DIV\_X\_PLAYERS` doesn't match any name in `DIV\_X\_SCHEDULE` after normalization.

Fix:

1. Open browser console — look for errors at page load
2. Verify the division's init block in `js/app.js` includes `recomputeDivStats(DIV\_X\_SCHEDULE, DIV\_X\_PLAYERS, DIV\_X\_PARTNERS, DIV\_X\_KEY\_PAIRS)`
3. If a specific player is missing, check spelling — normalization strips dots/commas/apostrophes and uppercases. Compare:
  - Schedule: `J.SURESH KUMAR` → normalized `J SURESH KUMAR`
  - Roster: `J. Suresh Kumar` → normalized `J SURESH KUMAR` ✓

### ***Standings "Played Pts" off by factor of 3***

Cause: Render function uses wrong formula. After the courts/matches refactor:

- A–J: `playedPts = s.played` (already in courts)
- K only: `playedPts = s.played \* 3` (data is in matches)

### ***Photos not loading***

- Check the path matches ``photos/div-{x}/{team-short-lower}/{player-slug}.{ext}``
- Verify the file exists in the deployed directory (FTP into GoDaddy and ls)
- The `<img onerror>` hides the element silently — missing photos won't crash the page

### ***Most Active Doubles Pairs shows 0 wins***

Cause: ``KEY_PAIRS`` was not passed to ``recomputeDivStats()``, or the pair string doesn't normalize to match the schedule.

Fix:

1. Verify the call includes the 4th argument: ``recomputeDivStats(..., DIV_X_KEY_PAIRS)``
2. Check the ``pair`` string in ``DIV_X_KEY_PAIRS`` matches the schedule names after normalization

### ***Admin panel data tools fail***

Cause: ``api/admin-data.php`` is unreachable or returned an error.

- Verify the file is deployed to ``/cdta/api/admin-data.php`` on GoDaddy
- Check browser network tab for the actual error
- Ensure GoDaddy hosting plan supports PHP

### ***Login fails for a known user***

- Open ``data/auth.js`` and verify the username and password
- Auth is checked client-side; case-sensitive

---

## **Backups**

``data/division-{c,f,h,i}.js.bak`` files were saved before the season-end refresh. Keep them in case stats need to be restored.

For everything else, GitHub is the backup. The repo at <https://github.com/rameshbala50/cdta> is the source of truth.

---

## **Credentials and secrets**

Item	Where stored	Notes
---	---	---
User logins	<code>`data/auth.js`</code>	Plaintext passwords, client-side. Acceptable for an internal league tool.

| FTP credentials | `deploy.env` (gitignored) | Server: `107.180.115.79`, user: `godaddyftp@akilanramesh.com` |  
| GoDaddy hosting | (out of scope) | Manage via GoDaddy account |

Never commit `deploy.env`. It is in `.gitignore`.

---

## Useful file locations

File	Purpose
`index.html`	Single-page DOM
`js/app.js`	All client logic
`css/main.css`	Styles
`data/auth.js`	User credentials
`data/division-{a..k}.js`	Per-division data
`data/division-{c,f,h,i}.js.bak`	Pre-refresh backups
`api/admin-data.php`	Server-side admin storage
`api/fetch-results.php`	Optional CORS proxy for league.cdta.co.in
`deploy.bat` / `deploy.ps1`	GoDaddy FTP deploy
`download-photos.ps1`	Bulk photo downloader from cdta.co.in
`photos/div-{a..k}/`	Local player photos

---

## Deployment

---

## Deployment Guide

The CDTA Dashboard is deployed as static files to **GoDaddy shared hosting** via FTP. There is no build step.

---

## Prerequisites

- Windows machine (deploy scripts are `.bat` and `.ps1`)

- The `deploy.env` file in the project root with FTP credentials (see below)
- Network access to the GoDaddy FTP server

---

## Environment file (`deploy.env`)

This file is **gitignored** and must be created locally. Format:

---

```
FTP_HOST=107.180.115.79
FTP_USER=godaddyftp@akilanramesh.com
FTP_PASS=<your_password>
FTP_REMOTE_DIR=/cdta
```

---

A separate `deploy-test.env` exists for the test environment (`/cdta-test` or `/cdta-workver` path).

---

## Deploy to production

### *Option 1 — Command Prompt*

```
``bat
cd "c:\My Cloud\Google Drive\Claude\cdta"
deploy.bat

```

### *Option 2 — PowerShell*

```
``powershell
cd "c:\My Cloud\Google Drive\Claude\cdta"
.\deploy.ps1

```

### *Dry run (PowerShell only)*

```
``powershell
.\deploy.ps1 -DryRun
```

---

---

## What the deploy script does

1. **Cache-bust** — Updates `?v=<timestamp>` query strings in `index.html` so browsers re-fetch JS/CSS
2. **Read credentials** from `deploy.env`
3. **Walk the project tree** — collect every file except the exclusion list
4. **Create directories** on the FTP server (one level at a time, ignoring "already exists" errors)
5. **Upload files** one by one over FTP (passive mode, binary)
6. **Report** OK / FAILED counts

### ***Excluded files***

- `deploy.bat`, `deploy.ps1`, `deploy.env`
- `cdta2026_dashboard_w8.html`, `cdta2026_discussion_w8.md` (legacy)
- `.gitignore`
- Anything starting with `.`` (e.g., `.git/`)

> **Note:** `.bak` files and `docs/` are **not** in the exclusion list, so they will be uploaded too. Add them to the exclusion list in `deploy.ps1` if you want to keep the production server clean.

---

## Deploy to test environment

```
``bat
```

```
deploy-test.bat
```

---

This uses `deploy-test.env` and points to a separate folder on the same GoDaddy account so you can preview changes without touching production.

---

## Verifying the deploy

1. Open <http://akilanramesh.com/cdta/> in an incognito window (avoids cache)
2. Hard refresh (Ctrl+Shift+R)



3. Login as `rameshadmin / ramesh123`

4. Spot-check:

- Overview totals
- Each division's standings
- Players page for one division (photos load, stats populated)
- Admin panel opens

---

## Rollback

If a deploy breaks the site:

1. **Quick rollback** — `git checkout <last\_good\_commit>` then `deploy.bat`
2. **Or** manually FTP an older snapshot from your local Git history

There is no automated rollback. The `.bak` files in `data/` only cover division data, not full site state.

---

## Photos deployment

Photos live in `photos/div-{a..k}/` and are deployed as part of the normal `deploy.bat` run (1,165 files, ~64 MB). The first deploy after a season refresh takes ~10–20 minutes depending on FTP throughput.

To skip photo upload (much faster), temporarily move the `photos/` folder out of the project before running deploy, then move it back.

---

## Cache busting

`deploy.ps1` rewrites `?v=<timestamp>` in `index.html` on every run. The pattern is:

```
```html
<script src="js/app.js?v=202604091530"></script>
```
```

Each deploy bumps the timestamp so browsers fetch the new file. If you ever see stale JS, hard-refresh once — subsequent loads will pick up the new version.

---

## Server-side requirements

GoDaddy shared hosting plan must support:

- **PHP** (for ``api/admin-data.php`` and ``api/fetch-results.php``)
- **FTP write access**
- **Static file serving** (default)

No database, no Node, no Python.

---

## Troubleshooting

### ***"deploy.env not found"***

Create the file with your FTP credentials (see format above).

### ***Random "Permission denied" during deploy***

GoDaddy occasionally throttles FTP. Re-run the script — it will pick up where it left off (failed files retry).

### ***"FAILED: Connection refused"***

Check VPN / firewall. The script uses passive FTP on port 21.

### ***Files uploaded but site shows old content***

Hard refresh (Ctrl+Shift+R). The cache-bust query string handles JS/CSS but **not** ``index.html`` itself, which the browser may still cache aggressively.

### ***Photos missing after deploy***

Check the deploy log for "FAILED" entries on ``photos/...``. Re-run ``deploy.bat`` to retry just the failed files (it overwrites existing OK files too — slower but reliable).