

Data Schema Reference

Each division's data lives in `data/division-{a..k}.js`. The file declares a set of `const` global variables prefixed with `DIV\_X\_` (e.g. `DIV\_C\_PLAYERS`). All globals are loaded into the page via `

| `name` | string | Display name (Title Case) |
 | `team` | string | Must match a `DIV\_X\_TEAMS[].short` |
 | `gender` | `M` \| `F` \| `null` | |
 | `age` | number \| null | |
 | `role` | `Captain` \| `Player` | |
 | `gamesPlayed` | number \| null | **Recomputed at runtime** for C/F/H/I |
 | `wins` | number \| null | **Recomputed at runtime** for C/F/H/I |
 | `photo` | string | Relative path to JPG/PNG |

> **Important:** `gamesPlayed` and `wins` may be `null` in the file. The render layer for divisions C/F/H/I calls `recomputeDivStats()` which derives them from `DIV\_X\_SCHEDULE`. Do **not** rely on the file values.

`DIV\_X\_STANDINGS`

Pre-computed standings table (one row per team).

```
```javascript
{ rank:1, short:'PSG-C', full:'PSG SPORTS CLUB - C', pts:24, played:30,
setsW:48, setsL:18, gamesW:312, gamesL:215 }
...

```

Field	Type	Notes
`rank`	number	1-based
`short` / `full`	string	
`pts`	number	League points earned
`played`	number	<b>Courts played</b> (= max possible pts). Exception: <b>Div K stores matches</b> , not courts
`setsW` / `setsL`	number	Set wins / losses
`gamesW` / `gamesL`	number	Game wins / losses

## ***`DIV\_X\_SCHEDULE`***

Week-by-week match data including court-level player pairings — the **authoritative source of truth** for player stats.

```
```javascript
const DIV_C_SCHEDULE = [
{ week:1, date:'24-25 Jan 2026', done:true, matches:[
{ home:'PROSCHOOL - B', score:'2-1', away:'CMTA - C', venue:"",
courts:[

```

```
{ ct:1, home:'Riyas / Arun Karthik', away:'Manikandan K / NITHISH',
sets:'6-2, 6-0', win:'home' },
...
}},
...
}},
...
];
```

```

```
Field	Type	Notes
`week`	number	1-indexed
`date`	string	Free-text date label
`done`	boolean	true if results are in
`matches[]`	array	One per fixture
`matches[].home` / `away`	string	Full team name
`matches[].score`	string	e.g. `2-1` (in courts won)
`matches[].courts[]`	array	Always 3 entries (3 doubles per match)
`courts[].ct`	number	Court number (1, 2, or 3)
`courts[].home` / `away`	string	Two player names separated by `/`
`courts[].sets`	string	e.g. `6-2, 6-0`
`courts[].win`	`home` \| `away`	Which side won the court

```

## Manual-division-only structures (C, F, H, I)

These four divisions started life as hand-curated data and retain extra fields for projections and key analytics.

### ***`DIV\_X\_PROJECTIONS`***

Projected final standings (syncd with actuals once season ends).

```
```javascript
{ rank:1, short:'PSG-C', full:'PSG SPORTS CLUB - C', currentPts:24, projectedPts:24, change:0 }
```
```

## ***`DIV\_X\_PROJ\_BREAKDOWN`***

Per-team projection breakdown for upcoming weeks. **\*\*Empty\*\*** when the season is complete.

```
```javascript
{ team:'PSG-C', remainingMatches:[ { week:11, opponent:'TIR-C', expected:2 }, ... ] }
```
```

## ***`DIV\_X\_KEY\_PAIRS`***

"Most active doubles pairs" — top doubles partnerships by court appearances.

```
```javascript
{ pair:'Gowtham V / V. Yaswanth', team:'FMP-C', apps:7, wins:null }
```
```

| Field       | Type           | Notes                            |
|-------------|----------------|----------------------------------|
| --- --- --- |                |                                  |
| `pair`      | string         | ``Player A / Player B``          |
| `team`      | string         | Their team's short code          |
| `apps`      | number         | Court appearances together       |
| `wins`      | number \  null | <b>**Recomputed at runtime**</b> |

## ***`DIV\_X\_PARTNERS`***

Per-player list of partners and counts. Object keyed by player display name.

```
```javascript
const DIV_C_PARTNERS = {
  'Ganesan S': [['Madhan Kumar P',4],['Shravan Krishnan G',1]],
  'Madhan Kumar P': [['Ganesan S',4],['Keerthan Kumar B',2]],
  ...
};
```
```

> **\*\*Note:\*\*** This entire object is **\*\*rebuilt at runtime\*\*** by ``recomputeDivStats()``. The static values in the file are placeholders; only the keys (player names) need to be present so the runtime can match them.

## ***`DIV\_X\_TEAM\_INFO` (some divisions only)***

Extra metadata per team — court venues, contact, etc. Free-form.

---

## Custom team short codes (manual divisions)

Manual divisions use opinionated short codes to fit in the standings table. The codes are **\*\*NOT\*\*** scraped — they are hand-assigned and used everywhere as the join key (``DIV_X_PLAYERS.team` → `DIV_X_TEAMS.short``).

| Div C | Div F | Div H | Div I |

|---|---|---|---|

| PSG-C, FMP-C, SNS-A, TIR-C, PRO-C, ANU-C, SVG-C, CMT-C, COS-C, GPT-C, LIF-C | GNEST, ACES, CCTA, ALPHA, SNS, MAP, CSA, CASA, TIR, ALV, CMTA | SNS-D, PSG, ANU-B, RSP, GPTC-C, ANNUR, ACTC-B, TIR-B, KGR-D, FALCON, CSA | SATCH, TTOTS, STARS, RAIL, CBE, TGLO, SNS, GNEST, CHAMPS, SAI, KING |

---

## Photo paths

...

photos/div-`{a..k}`/`{team-short-lower}`/`{player-name-slug}`.`{jpg|jpeg|png}`

...

- ``team-short-lower`` is the ``short`` field lowercased (e.g. ``svg-c``)
- ``player-name-slug`` is the player name lowercased with non-alphanumerics replaced by ``-``
- Examples:
  - ``photos/div-c/svg-c/nagendran-k.jpg``
  - ``photos/div-i/stars/akilan-ramesh.jpeg``

If a photo is missing the row's ``<img onerror>`` hides it gracefully.

---

## "Courts vs matches" gotcha

| Division | What ``played`` means in ``STANDINGS`` |

|---|---|

| A, B, C, D, E, F, G, H, I, J | **\*\*Courts played\*\*** (matches × 3) |

| **\*\*K\*\*** | **\*\*Matches played\*\*** (not courts) |

The render functions compensate, so the UI always shows ``Played Pts (matches)`` correctly. If you ever change a render function, copy the pattern from an existing one.

---

## **Adding a new player manually**

1. Find the team's short code
2. Append to `DIV\_X\_PLAYERS` with `gamesPlayed:null, wins:null` (the recomputer will fill them)
3. Add the photo file at the correct path
4. Reload — that's it. No other field needs editing.

## **Adding a new match result manually**

1. Find the right `DIV\_X\_SCHEDULE[wk]` entry
2. Add the match object with all 3 courts and `win` set on each
3. Update `DIV\_X\_STANDINGS` rows for both teams (rank, pts, played, setsW/L, gamesW/L)
4. Reload — player stats and partners auto-recompute