

```
3
4 int main() {
5     /* Enter your code here. Read input from STDIN. Print output to STDOUT */
6     int N; cin >> N;
7     vector<string> a;
8     while(N!=0){
9         string s; cin >> s;
10        a.push_back(s);
11        // do all operation here itself
12        vector<string> w;
13        string word="";
14        for(int i=0;i<(int)s.size();i++){
15            if(s[i]!=' '){
16                word += s[i];
17            } else {
18
19                w.push_back(word);
20            }
21        }
22        if(w[0]=="hackerrank"){
23            cout << 1 << endl;
24
25        } else if(w[w.size()-1]=="hackerearth"){
26            cout << 2 << endl;
27
28        } else if(w[0]=="hackerrank" and w[w.size()-1]=="hackerearth"){
29            cout << 0 << endl;
30
31        } else {
32            cout << -1 << endl;
33        }
34        N--;
35    }
36    return 0;
37 }
```

```
2 using namespace std;
3
4 int main() {
5     /* Enter your code here. Read input from STDIN. Print output to STDOUT */
6     int N; cin >> N;
7     vector<string> a;
8     while(N!=0){
9         string s; getline(cin >> ws,s);
10        a.push_back(s);
11        // do all operation here itself
12        vector<string> w;
13        string word="";
14        for(int i{};i<(int)s.size();i++){
15            if(s[i]!=' '){
16                word += s[i];
17            } else {
18                w.push_back(word);
19            }
20        }
21
22        if(w.front()=="hackerrank" and w.back()=="hackerrank"){
23            cout << 0 << endl;
24        } else if(w.back()=="hackerrank"){
25            cout << 2 << endl;
26        } else if(w.front()=="hackerrank"){
27            cout << 1 << endl;
28        } else {
29            cout << -1 << endl;
30        }
31        N--;
32    }
33    return 0;
34 }
35
```