

[Support](#)[Dark mode](#)[ON OFF](#)

Legacy mode [ON OFF](#)

press Esc to resume

Programming Language

JavaScript

Users **2**

Ramesh Sore
 Bhartendu


Chat Messages

type here

```
113 // degree (for accuracy)
114
115
116 Amazon customers collect packages from pickup stations containing lockers of different sizes.
117 Each station contains small, medium, and large lockers.
118 Design and implement an in-memory library that assigns packages to lockers and releases lockers after pickup.
119
120 Each package has:
121
122   packageId
123   size
124
125 Each locker has:
126
127   lockerId
128   size
129
130 The supported sizes are:
131
132   SMALL
133   MEDIUM
134   LARGE
135
136 Implement these operations:
137
138   storePackage(package)
139   findPackage(packageId)
140   pickupPackage(packageId)
141
142 #
143 Requirements
144
145   Package IDs and locker IDs are unique, nonempty strings.
146   Each locker holds at most one package.
147   A package cannot be stored more than once.
148   A small package fits in a small, medium, or large locker.
```

[Conditions of Use](#)[Privacy Notice](#)[Need Help?](#)

© 1996



Support

Dark mode

ON OFF

Font



Legacy mode ON OFF

```
137
138 storePackage(package)
139 findPackage(packageId)
140 pickupPackage(packageId)
141
142 #
143 Requirements
144
145 Package IDs and locker IDs are unique, nonempty strings.
146 Each locker holds at most one package.
147 A package cannot be stored more than once.
148 A small package fits in a small, medium, or large locker.
149 A medium package fits in a medium or large locker.
150 A large package fits only in a large locker.
151 Assign the smallest available locker that fits the package.
152 When multiple fitting lockers have the same size, select the locker with the lexicographically smallest ID.
153 storePackage returns the assigned locker ID or a defined failure when no locker is available.
154 findPackage returns the locker ID containing the package without changing state.
155 pickupPackage removes and returns the package, then makes its locker available again.
156 Missing packages, duplicate packages, invalid inputs, and invalid locker configuration must have deliberate behavior.
157 The station and its lockers already exist when the service is constructed.
158 Assume the implementation is single-threaded and keeps all state in memory.
159
160 You may choose the classes, method signatures, return types, internal data structures, and error-handling model.
161
162 Before coding, briefly explain:
163
164 The main classes or data types in your design.
165 The state your library needs to maintain.
166 The public API and error model.
167 The invariants that keep package and locker state consistent.
168
169
170 */
171
```

Programming Language

JavaScript

Users 2

Ramesh Soren
Bhartendu

Chat Messages

type here