

Logging & Monitoring Standard

Asteria Digital Services | LMS-OPS-003 | Version 1.8 | Effective 2026-06-01

Owner: Platform Operations

Synthetic training document - created for the Week 2 RAG project. No real company policy is represented.

1. Purpose

This standard defines minimum application logging, monitoring, alerting, and retention requirements for production services.

2. Required Log Fields

Application and integration logs SHOULD include the following when relevant:

- timestamp in UTC
- service or application name
- environment
- severity
- correlationId or traceId
- event or operation name
- result/status
- safe errorCode where applicable

3. Sensitive Information

- Passwords, access tokens, refresh tokens, API keys, private keys, and client secrets **MUST NEVER** be logged.
- Restricted data **MUST NOT** be written to normal application or integration logs.
- Confidential customer information **MAY** appear only when masked, tokenized, or otherwise reduced to the minimum data required for operational diagnosis.
- Full payment card numbers, security codes, and authentication credentials are prohibited in logs regardless of environment.

4. Correlation

- Services **MUST** preserve an inbound correlationId or traceId when available.
- If none exists, the entry component **MUST** create one.
- The same identifier **SHOULD** be included in downstream logs, messages, and error responses when safe to expose.

5. Retention

Log Type	Default Retention
Production application logs	90 days online/searchable
Security audit logs	365 days minimum
Non-production application logs	30 days unless a team has an approved exception
Debug/trace logging in production	Temporary only; disable after diagnosis and follow sensitive-data rules

6. Monitoring and Alerting

- Production services **MUST** monitor availability, latency, error rate, and resource saturation where applicable.
- A sustained error rate above the service's agreed threshold **SHOULD** generate an operational alert.
- Repeated authentication failures or suspected secret leakage **SHOULD** be routed to security monitoring.
- Alerts **SHOULD** include enough context to identify the affected service without embedding sensitive payload data.

7. Incident Evidence

During a production incident, teams should preserve relevant logs, correlation identifiers, timestamps, deployment versions, and error codes. Evidence collection must not bypass data classification or security rules.

8. Related Documents

- Data Classification Policy - DCP-DATA-002
- Cloud Security Policy - CSP-SEC-004
- Incident Management Guide - IMG-OPS-006