## **RED HAT ENTERPRISE LINUX 5, 6, AND 7**

## Common administrative commands

SYSTEM BASICS TASK		RHEL
	/etc/sysconfig/rhn/systemid	5
View subscription information	/etc/sysconfig/rhn/systemid subscription-manager identity	6
	subscription-manager identity	7
	rhn_register subscription-manager <sup>1</sup>	5
Configure subscription	rhn_register rhnreg_ks subscription-manager	6
	subscription-manager <sup>2</sup> rhn_register <sup>3</sup>	7
	sosreport dmidecode hwbrowser	5
View system profile	sosreport dmidecode lstopo lscpu	67
View RHEL version information	/etc/redhat-release	567

- 1 Be aware of potential issues when using subscription-manager on Red Hat Enterprise Linux 5: https://access.redhat.com/ solutions/129003.
- 2 Subscription-manager is used for Satellite 6, Satellite 5.6 with SAM and newer, and Red Hat's CDN.
- 3 RHN tools are deprecated on Red Hat Enterprise Linux 7.
  rhn\_register should be used for Satellite server 5.6 and newer
  only. For details, see: Satellite 5.6 unable to register RHEL 7
  client system due to rhn-setup package not included in
  Minimal installation (https://access.redhat.com/
  solutions/737373)

BASIC CONFIGURATIO	N	
TASK		RHEL
Graphical configuration tools	system-config-*	56
oraphical configuration tools	gnome-control-center	7
	system-config-network	56
Configure network	nmcli nmtui nm-connection-editor	7
Configure quetom language	system-config-language	56
Configure system language	localectl	7
Configure time and date	system-config-date date	56
Configure time and date	timedatectl date	7
	ntpdate /etc/ntp.conf	56
Synchronize time and date	timedatectl /etc/chrony.conf ntpdate	7
Configure keyboard	system-config-keyboard	56
Configure keyboard	localectl	7
Text-based configuration tools	system-config-*-tui	567
Configure printer	system-config-printer	567
Configure SSH	/etc/ssh/ssh_config /etc/ssh/sshd_config ~/.ssh/config ssh-keygen	367

RESOURCE MANAGEMENT			
TASK		RHEL	
	top ps sar iostat netstat vmstat mpstat numastat	<b>5</b>	
View system usage	top ps sar iostat netstat ss vmstat mpstat numastat tuna  top ps sar iostat ss vmstat mpstat numastat tuna	<b>6</b>	
	df	5	
View disk usage	df iostat	67	
Trace system calls	strace	567	
Trace library calls	ltrace	567	
Change process priority	nice renice	567	
Change process run location	taskset	567	
Kill a process	kill pkill killall	567	

SOFTWARE MANAGEMENT		
TASK		RHEL
Install software	yum install yum groupinstall	56
install software	yum install yum group install	7
View software	yum info yum groupinfo	56
info	yum info yum group info	7
Update software	yum update	567
Upgrade software	yum upgrade	567
Configure software repository	subscription-manager repos /etc/yum.repos.d/*.repo	567
Find file in package	rpm -qf filename yum provides filename-glob	567
View software version	rpm -q <i>packagename</i>	567
View installed software	rpm -qa yum list installed	567

TASK		RHEL
Graphical user management	system-config-users	567
Create user account	useradd	567
Delete user account	userdel	567
View/change user account details	usermod /etc/passwd vipw id	567
Create user group	groupadd	567
Delete user group	groupdel	567
Change group details	groupmod /etc/group	567
Change user password	passwd	567
Change user permissions	usermod visudo	567
Change group permissions	groupmod visudo	567
Change password policy	chage	567
View user sessions	w	567

NETWORK	ING	
TASK		RHEL
	iptables and ip6tables /etc/sysconfig/ip*tables	5
Configure firewall	iptables and ip6tables /etc/sysconfig/ip*tables system-config-firewall	6
	firewall-cmd firewall-config	7
Configure	/etc/hosts /etc/resolv.conf	56
name resolution	/etc/hosts /etc/resolv.conf nmcli con mod	7
	/etc/sysconfig/network	56
Configure hostname	hostnamectl /etc/hostname nmtui	0
	ip addr ifconfig brctl	56
View network interface info	ip addr nmcli dev show teamdctl brctl bridge	7
	/etc/sysconfig/network-scripts/ifcfg-*	56
Configure network interface	/etc/sysconfig/network-scripts/ifcfg-* nmcli con [add mod edit] nmtui nm-connection-editor	7
View ports/	ss lsof netstat	56
Sounces	ss lsof	7
	ip route add system-config-network /etc/sysconfig/route- <i>iface</i>	56
Configure routes	ip route add nmcli nmtui nm-connection-editor /etc/sysconfig/route- <i>iface</i>	7
View routes	ip route	567

SECURITY AND IDENTITY		
TASK		RHEL
Configure system security	/etc/selinux/config chcon restorecon semanage setsebool system-config-selinux	567
Report on system security	sealert	567
LDAP, SSSD, Kerberos	authconfig authconfig-tui authconfig-gtk	567
Network users	getent	567

JOBS AND SERVICES		
TASK RHEL		
TASIC	/etc/syslog.conf	6
Configure logging	/etc/rsyslog.comf	6
	/etc/rsyslog.conf	
	/etc/rsyslog.d/*.conf /var/log/journal	7
	systemd-journald.service	
	chkconfiglist ls /etc/init.d/	56
List all services	systemctl -at service ls /etc/systemd/system/*.service ls /usr/lib/systemd/system/*.service	7
	servicestatus-all	56
List running services	systemctl -t servicestate=active	7
	service name start service name stop	56
Start/stop service	systemctl start <i>name</i> .service systemctl stop <i>name</i> .service	7
En abla /disabla	chkconfig <i>name</i> on chkconfig <i>name</i> off	56
Enable/disable service	systemctl enable <i>name</i> .service systemctl disable <i>name</i> .service	7
View service status	service <i>name</i> status	56
view service status	systemctl status name.service	7
Check if service is enabled	chkconfig namelist	56
	systemctl is-enabled <i>name</i>	7
Create new service file or	chkconfigadd	56
modify configuration	systemctl daemon-reload /etc/systemd/system/*.service	7
	runlevel who -r	56
View run level/target	systemctl get-default who -r	7
Character to the control of the cont	/etc/inittab init run_level	56
Change run level/target	systemctl isolate <i>name</i> .target systemctl set-default	7
	/var/log	56
View logs	/var/log journalctl	7
Configure system audit	add audit=1 to kernel cmdline auditctl /etc/audit/auditd.conf /etc/audit/audit.rules authconfig /etc/pam.d/system-auth pam_tty_audit kernel module	567
View audit output	aureport /var/log/faillog	567
Schedule/batch tasks	cron at batch	567
Find file by name	locate	567
Find file by characteristic	find	567
Tind file by characteristic	tar	
Create archive	cpio zip	567

FILE SYSTEMS, VOLUMES, AND DISKS		
TASK		RHEL
	ext3	5
Default file system	ext4	6
	xfs	7
	copy data to new file system fsck (look for 'non-contiguous inodes')	5
Defragment disk space	copy data to new file system fsck (look for 'non-contiguous inodes') xfs_fsr	67
	fdisk parted	56
Create/modify disk partitions	fdisk gdisk parted ssm create	7
	mkfs.filesystem_type (ext4, xfs) mkswap	56
Format disk partition	mkfs.filesystem_type (ext4, xfs) mkswap ssm create	7
	mount /etc/fstab	56
Mount storage	mount /etc/fstab ssm mount	•
	pvcreate	56
Create physical volume	pvcreate ssm create (if backend is lvm)	7
	vgcreate	56
Create volume group	vgcreate ssm create (if backend is lvm)	7
	lvcreate	56
Create logical volume	lvcreate ssm create (if backend is lvm)	7
Enlarge volumes formatted with default file system	vgextend lvextend resize2fs	56
	vgextend lvextend xfs_growfs ssm resize	7
Shrink volumes formatted	resize2fs lvreduce vgreduce	5 6
with default file system	XFS cannot currently be shrunk; copy desired data to a smaller file system.	7
	fsck	56
Check/repair file system	fsck ssm check	7
Configure NFS share	/etc/exports service nfs reload	56
- configure for 5 shalle	/etc/exports systemctl reload nfs.service	7
Mount and activate swap	/etc/fstab swapon -a	567
Configure static mounts	/etc/fstab	567
View free disk space	df	567
View NFS share	showmount -e	
	mount	

FILE SYSTEMS, VOLUMES, AND DISKS (CONT.)		
TASK		RHEL
View logical volume info	lvdisplay lvs vgdisplay vgs pvdisplay pvs	567
Configure on-demand auto-mounts	/etc/auto.master.d/*.autofs /etc/auto.*	567
Change file permissions	chmod chown chgrp umask (future file creation)	567
Change file attributes	chattr	567
Change access control list	setfacl	567

KERNEL, BOOT, AND HA	ARDWARE	
TASK		RHEL
Cinala usau/nasaua mada	append 1 or s or init=/bin/bash to kernel cmdline	56
Single user/rescue mode	append rd.break or init=/bin/bash to kernel cmdline	7
	shutdown	56
Shut down system	shutdown systemctl shutdown	7
	poweroff	56
Power off system	poweroff systemctl poweroff	7
	halt	56
Halt system	halt systemctl halt	7
	reboot	56
Reboot system	reboot systemctl reboot	7
Configure default run level/target	/etc/inittab	56
Configure default full level/target	systemctl set-default	7
Configure GRUB bootloader	/boot/grub/grub.conf	<b>5 6</b>
	/etc/default/grub grub2-mkconfig grub-set-default	7
View hardware configured	hwbrowser	6
view nardware configured	lshw (in EPEL)	67
Configure kernel module	modprobe	567
Configure hardware device	udev	567
View kernel parameters	sysctl -a cat /proc/cmdline	567
Load kernel module	modprobe	567
Remove kernel module	modprobe -r	567
View kernel version	rpm -q kernel uname -r	567

## 11/14

Copyright © 2014 Red Hat, Inc. Red Hat, Red Hat Enterprise Linux, the Shadowman logo, and JBoss are trademarks of Red Hat, Inc., registered in the U.S. and other countries. Linux $^{\circ}$  is the registered trademark of Linus Torvalds in the U.S. and other countries.

