403 Forbidden on getProductImages

Cause, example, and how to resolve it

Error returned

```
{
  "title": "Forbidden",
  "type": "https://api.commercecloud.salesforce.com/documentation/error/v1/errors/forbidden",
  "detail": "Access to requested resource forbidden"
}
```

Request: `GET https://oatyq2b1.api.commercecloud.salesforce.com/product/shopper-products/v1/organizations/f_ecom_bfgf_dev/products/SAP_1585173/images?siteId=homefragranceus&locale=default`

1. The reason

Salesforce checks the scope inside the access token against the scopes each endpoint accepts. The token is valid (right organization, short code, site, not tampered with), but it carries the wrong scope for this endpoint. A bad or expired token would return 401, not 403.

Token payload (decoded):

```
"scp": "sfcc.shopper-standard"
"ssc": "oatyq2b1"
"iss": "slas/prod/bfgf_dev"
"isb": "...::chid:homefragranceus"
"iat": 2026-10-19 13:54:52 UTC   "exp": 2026-10-19 14:24:52 UTC   (30 minutes)
```

Scopes each endpoint accepts (Shopper Products v1.13.0 spec):

Endpoint	Accepted scopes
getProducts, getProduct	sfcc.shopper-products **or** sfcc.shopper-standard
getProductImages, getProductPrices, getProductPromotions	**sfcc.shopper-products only**
getCategories, getCategory	sfcc.shopper-categories **or** sfcc.shopper-standard

What happens with the token above:

Call	Token scope	Result
GET .../products/SAP_1585173?siteId=homefragranceus	shopper-standard	Allowed
GET .../products/SAP_1585173/images?siteId=homefragranceus	shopper-standard	**403 Forbidden**

2. How to resolve it

Step 1: add the scope to the SLAS client. Open the SLAS client that issued the token. Add `sfcc.shopper-products` to its allowed scopes, and `sfcc.shopper-categories` if you call categories. Use the SLAS Admin UI or the SLAS Admin API; the SLAS guide on the Salesforce developer site has the exact screens for your version. If you lack SLAS admin access, ask whoever set up the client.

Step 2: request the scope when you get the token. A client can only issue scopes it was granted, and the token holds only what you ask for. Add `scope` to the request.

Private client, guest flow:

```
HOST="https://oatyq2b1.api.commercecloud.salesforce.com"
SLAS="$HOST/shopper/auth/v1/organizations/f_ecom_bfgf_dev"

curl -X POST "$SLAS/oauth2/token" \
  -H "Content-Type: application/x-www-form-urlencoded" \
  -H "Authorization: Basic {base64(client_id:client_secret)}" \
  -d "grant_type=client_credentials" \
  -d "channel_id=homefragranceus" \
  -d "scope=sfcc.shopper-products sfcc.shopper-categories"
```

Public client, guest flow: add `scope=sfcc.shopper-products sfcc.shopper-categories` to the authorize request, then exchange the code for a token as usual. Scopes are separated by spaces; URL-encode the spaces if your tool builds the request for you.

Step 3: confirm the new token has the scope. Decode the payload (never post the token itself):

```
echo "{access_token}" | cut -d. -f2 | tr '_-' '/+' | base64 -d 2>/dev/null | python3 -m json.tool
```

Expected: `"scp": "sfcc.shopper-products ..."`

Step 4: call the endpoint again.

```
HOST="https://oatyq2b1.api.commercecloud.salesforce.com"
BASE="$HOST/product/shopper-products/v1/organizations/f_ecom_bfgf_dev"

curl "$BASE/products/SAP_1585173/images?siteId=homefragranceus" \
  -H "Authorization: Bearer {new_token}"
```

Expected: **200** with `{ "id": "SAP_1585173", "imageGroups": [ ... ] }`

If it still returns 403

• The scope is on the token but the 403 remains: the /images endpoint is new in the 1.13 spec and may not be enabled on your instance yet. Compare against the plain product call below, and check your B2C Commerce release.
• The token expired. Guest tokens last about 30 minutes. This one expired at 14:24 UTC.

3. Workaround while the scope is being added

GET .../products/{id} accepts your current scope, and `expand=images` returns the same imageGroups:

```
HOST="https://oatyq2b1.api.commercecloud.salesforce.com"
BASE="$HOST/product/shopper-products/v1/organizations/f_ecom_bfgf_dev"

curl "$BASE/products/SAP_1585173?siteId=homefragranceus&expand=images" \
  -H "Authorization: Bearer {token}"
```

The response is larger because it includes the whole product. Add `select=(id,imageGroups.(**))` to trim it. The same fix applies to prices and promotions, which also need sfcc.shopper-products.

Cleanups to your curl

• Remove `--request GET` and `--data '{}'`. A GET should not carry a body, and curl switches to POST if --data is left without --request.
• Remove the `Content-Type: application/json` header; it is unnecessary on a GET.
• `locale=default` is accepted by the spec.