

SecurityContextConstraints

Last Updated: 2026-05-01

Red Hat® OpenShift® SecurityContextConstraints requirement controls pod permissions. These permissions include pod actions and resources 1

You do not have to set any of these constraints as all non-default constraints are automatically set by the product installer. To view the set of Security

```
oc get scc
```

For more information about SecurityContextConstraints, see <https://docs.openshift.com/container-platform/4.18/authentication/managing-sec>

The IBM Storage Scale specific constraints are as follows:

Note: IBM Fusion 2.12.2 supports IBM Storage Scale 5.2.3.6.

NAME	PRIV	CAPS	SELINUX	RUNASUSER	FSGROUP	SUPGROUP	PRIORITY	READONLYR
ibm-spectrum-scale-privileged	true	["*"]	RunAsAny	RunAsAny	RunAsAny	RunAsAny	<no value>	false
restricted-ibm-spectrum-protect-plus-ns	false	<no value>	MustRunAs	MustRunAsRange	MustRunAs	RunAsAny	<no value>	false
spectrum-scale-csiaccess	true	[]	RunAsAny	RunAsAny	MustRunAs	RunAsAny	<no value>	false
data-protection-scc-ibm-backup-restore	true	<no value>	RunAsAny	RunAsAny	RunAsAny	RunAsAny	<no value>	false
data-protection-scc-ibm-dataprotection	true	<no value>	RunAsAny	RunAsAny	RunAsAny	RunAsAny	<no value>	false
data-protection-scc-ibm-dp	true	<no value>	RunAsAny	RunAsAny	RunAsAny	RunAsAny	<no value>	false
guardian-dm-datamover-scc	true	["SYS_ADMIN"]	RunAsAny	RunAsAny	RunAsAny	RunAsAny	<no value>	false
velero-privileged	true	["*"]	RunAsAny	RunAsAny	RunAsAny	RunAsAny	<no value>	false

Parent topic:

→ Prerequisites

